

Product Data



BLAKES HARD RACING

7142H

HSE Number 7385

Description: BLAKES HARD RACING antifouling is a high strength burnishable antifouling especially for power boats, racing yachts and vessels moored in a mud berth and may be used on vessels that are dry sailed. For use below the waterline.

Recommended use: Suitable for all substrates except aluminium. Risk of corrosion in the case of direct contact.

Availability: Subject to confirmation.

PHYSICAL CONSTANTS:

Colours/Shade nos: True Blue/30390 - Black/19990 - Red/51170
Finish: Flat
Volume solids, %: 54 ± 1
Theoretical spreading rate: 13.5 m²/litre - 40 micron
Flash point: 35°C/95°F
Specific gravity: 1.6 kg/litre - 13.4 lbs/US gallon
Dry to touch: 4 (app) hours at 20°C/68°F
8 (app) hours at 10°C/50°F
V.O.C.: 425 g/litre - 3.5 lbs/US gallon

The physical constants stated are nominal data according to the BLAKES Group's approved formulas. They are subject to normal manufacturing tolerances and where stated, being standard deviation according to ISO 3534-1. Further reference is made to "Explanatory Notes" in the BLAKES PAINT MANUAL.

APPLICATION DETAILS:

Application method: Airless Spray Air Spray Brush/Roller/Paint pad
Thinner (max.vol.): BLAKES THINNERS No 3 (5%) BLAKES THINNERS No 3 (5%) BLAKES THINNERS No 3 (5%)
Nozzle orifice: .018" - .023"
Nozzle pressure: 150 bar/2175 psi
(Airless spray data are indicative and subject to adjustment)
Cleaning of tools: BLAKES THINNERS No 3
Indicated film thickness, dry: 40 micron/1.6 mils
Indicated film thickness, wet: 75 micron/3 mils
Recoat interval, min. 5 hours (20°C/68°F)
9 hours (10°C/50°F)
Recoat interval, max. None (See REMARKS overleaf)

Safety: Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult BLAKES PAINTS Material Safety Data Sheets and follow all local or national safety regulations. Avoid inhalation, avoid contact with skin and eyes, and do not swallow. Take precautions against possible risks of fire or explosions as well as protection of the environment. Apply only in well ventilated areas.

Always read the label. Use pesticides safely

Issued: NOVEMBER 2002