



# Product Data

## HEMPEL'S RENEW RUBBING LIQUID 69021

- Description:** HEMPEL'S RENEW RUBBING LIQUID 69021 is a fine abrasive rubbing compound.
- Recommended use:** Restores and renews the gloss and colour to gelcoat and painted surfaces. For removal of light scratches, stains, oxidation and other irregularities from most surfaces including aluminium. Can be used for both manual and machine polishing.
- Availability:** Subject to confirmation.
- PHYSICAL CONSTANTS:**  
Trade nos: 99980  
Flash point: 75°C/167°F  
Specific gravity: 1.3 kg/litre– 10.8 lbs/US gallon  
*The physical constants stated are nominal data according to the HEMPEL Group's approved formulas. They are subject to normal manufacturing tolerances and where stated, being standard deviation according to ISO 3534-1*
- Surface preparation:** Clean and degrease the surface with HEMPEL'S PSE-CLEAN 67602 or HEMPEL'S THAMPOO 67284 to remove dirt and other contaminants, rinse with fresh water. Allow surface to dry.
- Application method:**  
**By hand:** Spread HEMPEL'S RENEW RUBBING LIQUID 69021 uniformly on to the surface, rub with circular movements until almost dry. Wipe off with a clean cloth. Apply more HEMPEL'S RENEW RUBBING LIQUID 69021 until the required finish has been obtained.  
**By rotating polishing machine** (It is the most effective method for large areas): Spread HEMPEL'S RENEW RUBBING LIQUID 69021 uniformly on to the surface and polish with the polishing machine. Work on small areas to avoid the compound drying. Dry compound can burn gelcoat. Use only clean compound pads as dirty or contaminated pads can cause scratches and swirl marks. Clean the compound pad regularly while in use. Keep compound wet, adding some droplets of water onto the compound and the surface can help this process. Keep compound pad flat or at a minimum angle, the use of the edge of the pad may cause burning or swirl marks. Recommended use with a polishing machine rated at 1500-2500 SPM.
- Subsequent treatment:** Finish with HEMPEL'S CLEAN & POLISH 69032 or HEMPEL'S CUTROM MASINE POLISH 67445. If a high performance wax finish is required, follow with HEMPEL'S WAX & PSORECR<sup>RecCel</sup> 69034 or HEMPEL'S WAX & PSORECR 69033.
- Remarks:** Shake well before use. Silicone and ammonia free. It is not recommended to apply in direct sunlight. The surface temperature should be above 5°C/41°F. Painted surfaces should dry for at least 30 days before using HEMPEL'S RENEW RUBBING LIQUID 69021.
- Note:** **The information given in the Product Data Sheet is intended for commercial use.**
- Safety:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult HEMPEL Material Safety Data Sheets and follow all local or national safety regulations. Avoid inhalation, avoid contact with skin and eyes, and do not swallow. Take precautions against possible risks of fire or explosions as well as protection of the environment. Apply only in well ventilated areas.

ISSUED BY: HEMPEL A/T - 6902199980

***This Product Data Sheet supersedes those previously issued.***

***For explanations, definitions and scope, see "Explanatory Notes" in the HEMPEL Book.***

***Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User.***

***The Products are supplied and all technical assistance is given subject to HEMPEL's GENERAL CONDITIONS OF SALES, DELIVERY AND SERVICE, unless otherwise expressly agreed in writing. The Manufacturer and Seller disclaim, and Buyer and/or User waive all claims involving, any liability, including but not limited to negligence, except as expressed in said GENERAL CONDITIONS for all results, injury or direct or consequential losses or damages arising from the use of the Products as recommended above, on the overleaf or otherwise.***

***Product data are subject to change without notice and become void five years from the date of issue.***

**HEMPEL**  
**Product Data Sheet**