New for 2022!



Pages 290 - 291



Page 271

Happy browsing!



Page 249



Page 58



Page 183



We're continuing to increase our product offering and, as you can see, we've lots of new lines again, some of which are illustrated below.


Welcome to our latest Seaware catalogue, edition J.



Page 99



Page 297






Page 148



Page 153





Page 23



Page 212



Page 227 Page 292



Page 162



Page 239





Contents

Anodes

Pages 4 - 22



Boat Cleaning

Pages 23 - 29



Deck Hardware

Pages 30 - 45



Electrical

Pages 46 - 94





Engine Systems Pages 95 - 114



Fastenings

Pages 115 - 139





Fillers, Epoxy & Resins

Pages 140 - 147



Glue, Sealants & Adhesives Pages 148 - 157



Grease, Oil & Lubricants Pages 158 - 164



Hinges, Catches & Vents Pages 165 - 175



Lighting

Pages 176 - 191





Paint

Pages 192 - 219





Paint Brushes, Rollers & Scrapers



Pages 220 - 224

Plumbing

Pages 225 - 259



Pumps Pages 260 - 283



PPE & Workwear Pages 284 - 288



Rigging & Mooring Pages 289 - 323



Safety & Security Pages 324 - 335



Seats

Pages 336 - 346



Sanding, Abrasives & Compounding



Pages 347 - 355

Steering Systems Pages 356 - 363



Tapes

Pages 364 - 374



Terms

Page 375

Useful Information

Pages 376 - 377

Index

Pages 378 - 384

Anodes



They look the same, which is better?

Salt & Brackish Water Use	Salt Water Use Only
Made in the UK	Made in the UK
Used by leading UK Boat Builders	Traditionally used for Over 60 Years
20% Longer Life	Widely Available
3x Lighter	
Higher Output	
Environmentally Friendly	
It even costs less than Zinc!	

Time for a rethink on ZINC!

MEDUFF

Backing Pads



to fit ZD77 8"

Pear Anode.

Part No 11050



B76B Backing Pad to fit ZD76B Mini Euro Anode.

Part No 11062

B78B Backing Pad to fit 12" ZD78B Hull Anode.

Part No 11055



B56B Backing Pad to fit 4" ZD56 Disc Anode.

Part No 11076



Part No 11060

to fit 18" ZD72B

Hull Anode.



B58B Backing Pad to fit 6" ZD58 Disc Anode.

Part No 11078



B77B Backing Pad to fit ZD77 Euro Anode.

Part No 11061

Reduces the back of the anode corroding.

Cushions the hull.

Prevents rubbing and damage.

Fixing Studs



M10 Fixing Studs Sold Individually

A4 Marine Grade Stainless Steel

Part No 11046



M16 Fixing Studs Sold Individually

A4 Marine Grade Stainless Steel

Part No 11048



M16 Fixing Studs Sold Individually Zinc Plated Steel

Part No 11047



M10C Weld-on Stud

Sold Individually

Part No 11080



M16C Weld-on Stud

Sold Individually



Anodes

Hull Anodes Bolt On





ZD78B Zinc Hull Anode		ZD72B Zinc Hull Anode		
Part No	11035	Part No	11040	
Length	305mm (12")	Length	457mm (18")	
Width	76mm	Width	102mm	
Depth	32mm	Depth	64mm	
Centres	200mm (8")	Centres	229mm (9")	
Weight	4KG	Weight	12.2KG	
Stud Size	M10	Stud Size	M16	



ZD72BM Zinc Hull Anode		
Part No	11039	
Length	457mm (18")	
Width	102mm	
Depth	38mm	
Centres	200- 229mm	
Weight	6.5KG	
Stud Size	M10 / M16	



ZD78BMLP Zinc Hull Anode		
Part No	11038	
Length	457mm (18")	
Width	95mm	
Depth	25mm	
Centres	200 - 229mm	
Weight	7.25KG	
Stud Size	M10 / M16	




ZD76	Mini	Euro	Zinc	Hull Anode

Part No	11090
Length	200mm (8")
Width	65mm
Depth	32mm
Centres	0 - 110mm (0" - 4")
Weight	1.4KG
Stud Size	M10



ZD77 Large Euro Zinc Hull Anode

Part No	11092
Length	318mm (12.5")
Width	65mm
Depth	32mm
Centres	110 - 210mm (4" - 8")
Weight	2.4KG
Stud Size	M10



305mm Metec 2.8kg Bolt On Hull Anode (MH28ZS-2) Part No 11484









Vetus ZINK15C Zinc
Hull Anode

Hull Anode		
Part No	57849	
Length	150mm (6")	
Width	70mm	
Depth	25mm	
Centres	150mm	
Weight	1.1KG	
Stud Size	M10	

Vetus ZINK25C Zinc
Hull Anode


Hull Anode		
Part No	57851	
Length	250mm (10"	
Width	75mm	
Depth	30mm	
Centres	140mm	
Weight	2.5KG	
Stud Size	M10	

All the second	
Vetus ZINK	35C Zinc
Hull Anode	


Hull Anode	
Part No	57853
Length	300mm (12")
Width	80mm
Depth	35mm
Centres	200mm
Weight	4.7KG
Stud Size	M10




Part No 11485



457mm Metec 11.5kg Bolt On Hull Anode (MH115ZS-2)







Hull Anodes Bolt On & Weld On



CM500Z Zinc Hull Anode	
Part No	11063
Length	116mm
Width	43mm
Depth	24mm
Centres	113 - 150mm
Weight	0.5KG
Stud Size	M6



ZD77 Pear 8" Hull Anode		
Part No	11030	
Length	229mm	
Width	83mm	
Depth	41mm	
Centres	200mm (8")	
Weight	2.1KG	
Stud Size	M10	



ARNSMALL Small Teardrop Hull Anode	
Part No	11169
Length	154mm
Width	32mm
Depth	30mm
Centres	89mm
Weight	0.27KG
Stud Size	M7



ARNLARGE Large Teardrop Hull Anode	
Part No	11170
Length	190mm
Width	45mm
Depth	44mm
Centres	127mm
Weight	0.74KG
Stud Size	M7





Ribbon Type Anodes

Low profile zinc anode with a non reactive aluminium insert ideally suited for fitting to high speed vessels.

Part No	MG Duff Part No	Length	Centres
11082	ZD42/5" -2H	5" (127mm)	76mm
11083	ZD42/6" - 1H	6" (152mm)	centre
11084	ZD42/12" -2H	12" (305mm)	203mm
11085	ZD42/15" -2H	15" (381mm)	229mm
11086	ZD42/18" -2H	18" (457mm)	305mm
11087	ZD42/24" -2H	24" (610mm)	406mm
11088	ZD42/36" -3H	36" (914mm)	305mm
11089	ZD42/54" - 3H	54" (1372mm)	457mm



Vetus Zinc Bolt On Anode


Zinc anode 23kgf for BOW2312 mounted in tunnel. ZINK02C. 0.54kg.

140mm hole centres

Part No 57847



ZD76 6" Weld On Pear Hull Anode		
Part No	11025	
Length	160mm	
Width	76mm	
Depth	32mm	
Weight 1KG		



200mm 8" Pear Metec 2.1kg Bolt On Hull Anode (MH20ZS) Part No 11483



ZD78 Weld On Hull Anode		
Part No	11036	
Length	385mm	
Width	76mm	
Depth	32mm	
Weight	4.5KG	



ZD80 Weld On Hull Anode		
Part No	11037	
Length	405mm	
Width	152mm	
Depth	32mm	
Weight	8.5KG	



ZD72 Weld On Hull Anode	
Part No	11041
Length	563mm
Width	102mm
Depth	64mm
Weight	14.5KG

Anodes

Disc & Trim Tab Anodes



ZD51 Button Anode		
Part No	11042	
Width	70mm	
Depth	30mm	
Weight	0.5KG	
Stud Size	M10	



ZD56 Disc Anode		
Part No	11070	
Width	100mm	
Depth	25mm	
Weight	1KG	
Stud Size	M10	



ZD58 Disc Anode			
Part No	11075		
Width	150mm		
Depth	35mm		
Weight	2.2KG		
Stud Size	M10		



ZINK8C Disc Anode			
Part No	57848		
Width	90mm		
Depth	45mm		
Weight	1KG		
Stud Size	M10		



ZD27 Transom Anode				
Part No 11376				
Width	125mm			
Depth	28mm			
Weight	2.7KG			
Stud Size M10				



ZD45 Transom Anode			
Part No	11377		
Width	135mm		
Depth	50mm		
Weight	4.5KG		
Stud Size	M10		



ZD52 Bolt Anode (Pa	011 2100
Part No	11043
Width	50mm
Depth	15mm
Weight	0.12KG



ZD59 Bolt On Disc Anode (Pair)		CMR03 Bolt On Disc Anode (Pair)		
Part No	art No 11044		11020	
Width	75mm	Width	95mm	
Depth	25mm	Depth	24mm	
Weight	0.43KG	Weight	0.73KG	



CMR04 Bolt On Disc Anode (Pair)			
Part No 11021			
Width	127mm		
Depth	32mm		
Weight	1.46KG		



CMR05 Bolt On Disc Anode (Pair)

Part No	11022
Width	130mm
Depth	44mm
Weight	2.14KG



70mm Metec 0.4kg Disc Anode (MD4Z) Part No 11480

Ø100 Ø35

100mm Metec 1kg Disc Anode (MD9Z) Part No 11481



140mm Metec 2.5kg Disc Anode (MD23Z) Part No 11482

Whether your boat is steel or GRP, to provide the best protection to the stern gear the shaft should be fitted with an MGDUFF Electro Eliminator Brush assembly. The MGDUFF Electro-Eliminators offer the most effective shaft bonding solution. Running directly onto the propeller shaft the electro eliminator puts the anode in constant low resistance contact with the propeller shaft. The copper graphite brushes will give at least 2000 running hours under normal conditions. The electro eliminators will also remove the interference to electronic equipment caused by the rotating shaft.








11094









EE2/208

Shaft earthing assembly for propeller shafts between 40mm to 100mm diameter. Does not include mounting bar.

EE2/208

Standard Zinc Shaft Anodes



Part No	MG Duff Part No	Shaft Diameter	Length	Outer Diameter
11000	ZSA 75	3/4"	2"	2.04"
11001	ZSA 88	7/8"	2.08"	2.12"
11002	ZSA 98	25mm	55mm	56mm
11003	ZSA 100	1"	2.15"	2.16"
11004	ZSA 112	1 1/8"	2 1/4"	2.36"
11006	ZSA 120	30mm	60mm	58mm
11007	ZSA 125	1 1/4"	2.35"	2.42"
11008	ZSA 138	1 3/8"	2.35"	2.66"
11009	ZSA 150	1 1/2"	2 1/2"	2.78"

Part No	MG Duff Part No	Shaft Diameter	Length	Outer Diameter
11010	ZSA 178	45mm	73mm	82mm
11011	ZSA 155	40mm	73mm	82mm
11012	ZSA 175	1 3/4"	2 3/4"	3 1/4"
11013	ZSA 200	2"	2.9"	3.6"
11014	ZSA 236	60mm	90mm	110mm
11015	ZSA 225	2 1/4"	3 3/4"	4 1/4"
11016	ZSA 250	2 1/2"	3 3/4"	4 1/4"



Zinc Shaft Anodes With Insert



Part No	MG Duff Part No	Shaft Diameter	Length	Outer Diameter
11100	MGD3/4"	3/4"	2 1/2"	2 1/8"
11101	MGD7/8"	7/8"	2 1/2"	2 1/8"
11102	MGD25mm	25mm	65mm	55mm
11103	MGD1"	1"	2 1/2"	2 1/8"
11104	MGD1 1/8"	1 1/8"	2 1/2"	2 1/8"
11105	MGD30mm	30mm	65mm	55mm
11106	MGD1 1/4"	1 1/4"	3"	2 5/8"

	~			
Part No	MG Duff Part No	Shaft Diameter	Length	Outer Diameter
11107	MGD1 3/8"	1 3/8"	3"	2 5/8"
11108	MGD1 1/2"	1 1/2"	3"	2 5/8"
11109	MGD40mm	40mm	78mm	68mm
11110	MGD1 3/4"	1 3/4"	4"	3 1/4"
11111	MGD2"	2"	4"	3 1/4"
11112	MGD60mm	60mm	100mm	85mm
11113	MGD70mm	70mm	95mm	110mm

Zinc Shaft Collar Anodes



Part No	MG Duff Part No	To Fit Shaft	Wall Thickness	Outer Diameter
11120	ZSC20	20mm	25mm	54mm
11121	ZSC22	22mm	25mm	54mm
11122	ZSC25	25mm	32mm	54mm
11129	ZSC27	1 1/8"	1 1/4"	2 1/2"
11123	ZSC30	30mm	32mm	63mm
11130	ZSC32	1 1/4"	1 1/4"	2 1/2"

Part No	MG Duff Part No	To Fit Shaft	Wall Thickness	Outer Diameter
11124	ZSC35	35mm	32mm	76mm
11128	ZSC38	1 1/2"	1 1/4"	2 1/2"
11125	ZSC40	40mm	32mm	76mm
11126	ZSC45	45mm	35mm	89mm
11127	ZSC50	50mm	35mm	89mm

Zinc Shaft Collar Anodes Thin Wall



Part No	MG Duff Part No	To Fit Shaft	Wall Thickness	Outer Diameter
11131	ZSC20T	20mm	15mm	60mm
11132	ZSC25T	25mm	15mm	60mm
11133	ZSC30T	30mm	18mm	60mm
11134	ZSC35T	35mm	18mm	74mm
11135	ZSC40T	40mm	18mm	74mm
11136	ZSC45T	45mm	18mm	82mm
11137	ZSC50T	50mm	18mm	82mm



Vetus Shaft Anode ZINKA25C 25mm x 65mm x 30mm Part No **57858**

Zinc Propeller Anodes









M G Duff Beneteau / Jeanneau Propeller Anodes					
Part No	M G Duff	Inner Dia	Outer Dia	Length	
11311	CMAN225	22/25mm	34mm	40mm	
11312	CMAN230	30mm	41mm	54mm	
11313	CMAN235	35mm	46mm	58mm	
11314	CMAN240	40mm	51mm	67mm	
11315	CMAN245	45mm	61mm	76mm	
11316	CMAN250	50mm	-	-	



Vetus Type Beneteau / Jeanneau Propeller Anodes				
57645	SN25B	25mm Shaft		
57646	SN30B	30mm Shaft		
57647	SN35B	35mm Shaft		
57648	SN40B	40mm Shaft		
57649	SN45B	45mm Shaft		
57650	SN50B	50mm Shaft		







Part No	MG Duff	Thread	Length	Outer
	Part No	Size		Diameter
11355	RAD22/25 CPT	16 X 1.5	60mm	37mm
11356	RAD30 CPT	20 X 1.5	75mm	45mm
11357	RAD35 CPT	24 X 2.0	77mm	48mm
11358	RAD40 CPT	2.4 X 2.0	92mm	54mm
11359	RAD45 CPT	33 X 2.0	100mm	64mm
11360	RAD50 CPT	36 X 2.0	118mm	75mm
11361	RAD55 CPT	40 X 3.0	120mm	78mm
11362	RAD60 CPT	45 X 3.0	135mm	88mm

Part No	MG Duff Part No	Length	Outer Diameter	Hex Size
11363	RAD22/25Z	39mm	32mm	23mm
11364	RAD30Z	57mm	41mm	27mm
11365	RAD35Z	58mm	44mm	32mm
11366	RAD40Z	65mm	50mm	36mm
11367	RAD45Z	73mm	59mm	41mm
11368	RAD50Z	83mm	72mm	46mm
11369	RAD55Z	83mm	72mm	50mm
11370	RAD60Z	95mm	82mm	55mm

Zinc Propeller Anodes

Popular on Spanish and French built boats.






Part No	MG Duff Part No	Length	Outer Dia	Inner Dia
11371	SOLE32	39mm	32mm	24mm
11372	SOLE37	45mm	37mm	26mm
11373	SOLE45	60mm	46mm	36mm
11374	SOLE55	70mm	55mm	45mm

To suit Flex-O-Fold 3 blade folding propeller.





Part No	MG Duff	Width	Depth	
	Part No			
11375	FLX-01	68mm	37mm	







Hanging Anodes



Zinc Hanging Anode for connecting to hanging cable. For salt water use.



Zinc Hanging Anode. Kit includes 4 metres of cable with an M10 terminal, 1x mounting bracket and 2x re-useable rubber tie wraps. For use in Salt water.

Part No	MG Duff Part No	Weight	Length (Min/Max)	Width (Min/Max)	Depth	Stud Size	Fixing Details
11430	ZD57L	1.8KG	120mm / 120mm	75mm / 75mm	75mm	M10	M10 Terminal for fixing to wire
11431	ZD57L KIT	1.96KG	120mm / 120mm	75mm / 75mm	75mm	M10	M10 Terminal for connection to wire

Zinc Bow Thruster Anodes





SET0148

Zinc anode for bow thrusters 25 kgf.

Part No 55137



SET0149

Zinc anode for bow thruster 35. 45, 55 kgf.

Part No 55138



SET0150

Zinc anode for bow thruster 60, 75, 80, 95 kgf.

Part No 55139



SET0151

Zinc anode for bow thruster 130, 160 kaf.

Part No 55140



SET0152

Zinc anode for bow thrusters 220 kaf.

Part No 55141



SET0153

Zinc anode for bow thruster 23, 50, 80 kgf and for all stern thruster sets.

Part No 55142

Aluminium Bow Thruster Anodes



SIDE-POWER



SP101180A

Aluminium Side Power anode for 250mm & 300mm diameter thrusters with bronze propellers. For salt and brackish water use only.

Weight (kg): 0.06kg

Outside Diameter: 41mm

Height: 35mm Part No 11440



SP201180A

Aluminium Side Power SP125T - 285TC / SE120 / SE150 / SP220 / 300 HYD & SH160 Thruster Anode. For salt and brackish water use only.

Weight (kg): 0.10kg

Outside Diameter: 48mm

Height: 42mm

Part No 11441



SP31180A

Aluminium Side Power SP30 / SP35 / SP40 & SE30 / SE40 Thruster Anode. For salt and brackish water use only.

Weight (kg): 0.006kg

Outside Diameter: 24mm

Height: 14mm

Part No 11442



SP501180A

Aluminium Side Power SP550 HYD Thruster Anode. For salt and brackish water use only.

Weight (kg): 0.35kg

Outside Diameter: 72mm

Height: 52mm

Part No 11443



SP71180A

Aluminium Side Power 7HP Model Thruster Anode (3 Bladed Props). For salt and brackish water use only.

Weight (kg): 0.018kg

Outside Diameter: 36mm

Width: 21mm

Height: 13mm

Part No 11446



SP71190A

Aluminium Side Power SP55S / SE60 / SP75T / SE80 / SP95T / SE100 Thruster Anode. For salt and brackish water use only.

Weight (kg): 0.05kg

Outside Diameter: 43mm

Height: 20mm

Part No 11447



SP61180A

Aluminium Side Power thruster anode for older 4 / 6HP models with 3 blade propellers. For salt and brackish water use only.

Weight (kg): 0.016kg

Outside Diameter: 24mm

Height: 20mm

Part No 11444



SP701180A

Aluminium Side Power Thruster Anode. For salt and brackish water use only.

Weight (kg): 1.15kg

Outside Diameter:135mm

Height: 52mm Part No 11445







CMALPHAKITZ



Zinc Mercury / Mercruiser Alpha 1 Generation 2 engine anode kit. For salt water use only.

Kit Includes:

CM76214Z: x1 CM806105Z: x1

CM806189Z: x2


CM821629CZ: x1

CM821631Z: x1

Fixing Kit: x1

Part No MG Duff Part No **CMALPHAKITZ**

CMBRAVO1KITZ



Zinc Mercury / Mercruiser Bravo 1 engine anode kit. For salt water use only.

Kit Includes:

11383


CM76214Z: x2 CM806188Z: x1

CM806190Z: x1

CM81630C2Z: x1 Fixing Kit: x1

Part No MG Duff Part No CMBRAVO1KITZ 11388

CMBRAVO3KITZ



Zinc Mercury / Mercruiser Bravo 3 (2004+) engine anode kit. For salt water use only.

x1

Kit Includes: CM7621447:

CM76215Z: x1 CM806190Z: x2 CM821630C2Z: x1 CM865182Z: x1

Fixing Kit: x1

Part No MG Duff Part No 11390 CMBRAVO3KITZ

CMALPHAKITZ1



Zinc Mercury / Mercruiser Alpha 1 Generation 1 engine anode kit. For salt water use only.

Kit Includes:


CM31640Z: x1 CM55989Z: x2 CM821631Z: x1

Fixing Kit:

Part No MG Duff Part No 11384 CMALPHAKITZ1

x1

CMBRAVO23KITZ



Zinc Mercury / Mercruiser Bravo 2 & 3 engine anode kit. For salt water use only.

Kit Includes:

CM76214Z: x1 CM806190Z: x2

CM821630C2Z: x1 Fixing Kit: x1

Part MG Duff Part No No

11389 CMBRAVO23KITZ

VOLVO

CMSXKITZ



salt water use only. Direct OEM replacement.

Zinc Volvo SX anode kit. For

Kit Includes:

11378

CM3854130Z: CM3855411Z: x1 Fixing Kit: x1

Part No MG Duff Part No

CMSXKITZ

CMV280DP



Zinc Volvo 280 DP Drive anode kit. For salt water use only. Direct OEM replacement.

Kit Includes:

11380

CM832598Z: x1 CM875821Z: x1 Fixing Kit: x1 Part No MG Duff Part No

CMV280DPKIT

CMV280KIT



Zinc Volvo 280 Drive anode kit. For salt water use only. Direct OEM replacement.

Kit Includes:

CM832598Z: x1 CMV18: x1 Fixing Kit: **x**1

Part No MG Duff Part No 11379 CMV280KIT

CMV290DPKIT



Zinc Volvo 290 DP Drive anode kit. For salt water use only.

Kit Includes:

CM852835Z: x1 CM875821Z: x1 Fixing Kit: x1

Part No MG Duff Part No 11382 CMV290DPKIT

Outboard & Outdrive Anodes



ZBU1 Engine Pencil Anode Bukh 000E0450

The pencil anode is 12mm X 35mm with 5mm stud. Original part number 000E0450. See also 02050

This anode fits in a brass plug located at the rear of the Bukh DV10-20-24-32 engine just above the gearbox.

On the Bukh DV36 & 48 the anode is on the starboard side of the engine.

Dimensions 12 × 12 × 35 mm

Weight 0.03kg

Part No 11328







CM123009Z - Martyr Zinc Anode for Bombardier Johnson, Evinrude

Fits a wide range of Johnson and Evinrude outboards and outdrive legs, 1981 - 2011.

Dimensions 60 × 22 × 12 mm

Weight 0.09 kg

Part No 11250



EVINRUDE {= *





CM327606Z - Martyr Zinc Anode for Bombardier Johnson, Evinrude

Fits 1983-1990 2HP Johnson and Evinrude outboards.

Dimensions 60 × 22 × 12 mm

Weight 0.08 kg









EVINRUDE = EVINRUDE =









CM398331Z - Martyr Zinc Midsection Block Anode for Bombardier Johnson, Evinrude

For use in Salt water. Original part number 398331.

Fits outboard tail Johnson-Evinrude 160-280HP (V4-V6).

Dimensions 44 × 57 × 22 mm

Weight 0.32 kg

Part No 11253



CM392123Z OMC Zinc Anode

Martyr Zinc Anode for Bombardier Johnson, Evinrude. Martyr crescent shape Zinc Anode for Bombardier Johnson/Evinrude. Half Moon -Transom. For use in Salt water. Part number 392123. Fits outboard engine OMC 90-140 HP Series, Johnson 90-140 HP Series, Evinrude 90-140 HP Series.

Dimensions 118 × 80 × 23 mm

Weight 0.76kg

Part No 11265



CM431708Z - Martyr Zinc Anode for Bombardier Johnson. Evinrude

Original part number 431708

Fits outboard engine Johnson/Evinrude 45-300 HP Series (1988-90), Diabolo 70/120 HP Series.

Dimensions 76 × 50 × 21 mm

Weight 0.27kg

Part No 11254

CM433580Z - Martyr Zinc Anode for Bombardier Johnson, Evinrude

Transom for Power Trim and Tilt Models. For use in Salt water. Original part number 433580 5007089/433580.

Fits outboard engine Johnson 60/300 HP Series, Evinrude 60/300 HP Series

Dimensions 175 × 34 × 21 mm

Weight 0.77kg

Part No 11268







lamilton let



CMHJ102185Z

203123



CMHJ1126646Z CMHJ111593Z

203131

Part No

11391

203133

Part No 11392

Part No

Part No 11394

CMHJ103359Z 203124

> Part No 11395

CMHJ104634Z

11393

Hamilton Jet bolt on bar anode.

82mm centres.

Dimensions: 101 × 22 × 23mm

Weight 0.285kg







CM31640Z - Martyr Zinc Anode for Honda, Mercury Outboard & Mercruiser Sterndrive and engines

Standard Skeg Trim Tab. For use in Salt water. Mercury Equivalent Part: 31640T4, 31640Q4 (fits Alpha 1, 120, 140, 470, 485 R, MR) Mercruiser No: 679-45251-00

Fits HONDA BF75AT/AW, BF90AT/AW, MERCURY 50HP, MARI-NER 40/60 HP <1991 Honda P/N: 41107-ZW1-003-ZA.

Dimensions: 90 × 90 × 105 mm

Weight 0.55kg Part No 11200



CM826134Z – Martyr Zinc Anode for Honda 75, Mercury Outboard & Mercruiser Sterndrive and engines

Wedge anode located on the side of the gearhousing just above the cavitation plate. For use in salt water. Honda part number 41109-ZW1-003

Dimensions: 77 × 29 × 22 mm

Weight 0.26kg

Part No 11220



CM06411ZW1Z

Zinc Honda 75 / 130 / 225 HP large bar anode. For salt water use only.

Anode Body Length: 226mm

Width: 50mm Height: 16mm

Stud Size: 6mm

Fixing Hole Details: 202mm Centres

Weight 0.36kg Part No 11344





CM806105Z - Martyr Zinc Anode for Mercury Outboard & Mercruiser Sterndrive and engines.

Bearing carrier behind propeller. Mercury Part: 806105A2, 806105Q1. Fits: Alpha 1 Gen II. For use in Salt water

Dimensions: 72 × 85 × 25 mm

Weight 0.23kg

Part No 11223





CM762145Z – Martyr Zinc Anode for Mercury Outboard & Mercruiser Sterndrive and engines.

New Generation – Circular Plate Flat Trim Tab. Fits all high performance Mercury outboards, Alpha 1 Gen II. Mercury Part no: 76214-5 Threaded Hole. For use in Salt water.

Dimensions: 92 × 92 × 24mm

Weight 0.33kg

Part No 11224





CM76214Z – Martyr Zinc Anode for Mercury Outboard & Mercruiser Sterndrive and engines

New Generation – Circular Plate Flat Trim Tab. Mercury Part no: 76214Q5, 76214A6. Fits Alpha 1 Gen II, Bravo 1, 2, 3. For use in Salt water.

Dimensions: 90 × 90 × 24 mm

Weight 0.28kg









CM55989Z - Martyr Zinc Anode for Mercury Outboard & Mercruiser Sterndrive and engines.

Gimbal Bolt Head anode. Mercury Part: 55989T3, 55989Q9. Fits: Alpha 1, Bravo 1, 120, 140, 470, 485. Also used by Keypower KP08 and KP10 bow thrusters. For use in Salt water.

Dimensions: 33 × 33 × 29 mm

Weight 0.11kg

Part No 11201

CM34762Z – Martyr Zinc Anode for Mercury Outboard & Mercruiser Sterndrive and engines.

Gimbal Plate. Fits Mercruiser TR and TRS outdrives. For use in Salt water. Mercury part no: 34762A1

Dimensions: 62 × 62 × 10 mm

Weight 0.24kg

Part No 11204



Gimbal Plate Block. Fits: Mercury F.BB, Mercruiser E.B ALPHA ONE GEN I and ALPHA ONE GEN II and Bravo. Mercury part number 43994. For use in Salt water.

Dimensions: 95 × 77 × 39 mm

Weight 0.95kg

Part No 11205





CM822157Z - Martyr Zinc Anode for Mercury Outboard & Mercruiser Sterndrive and engines.

Trim Tab. Fits Mercury 30-50 Hp F25, F30, F40 and F50 outboards (1998 and later). Mercury Part no: 822157c2. For use in Salt water.

Dimensions: 116 × 93 × 83mm

Weight 0.42kg

Part No 11208







CM821631Z - Martyr Zinc Anode for Mercury Outboard, Mercruiser Sterndrive and engines.

Gimbal Housing Plate Block. Fits Alpha I and Alpha I Gen II. Mercury Part no: 821631Q1, 821631A1. For use in Salt

Dimensions: 95 × 77 × 39 mm

Weight 0.89kg

Part No 11209





CM984325Z Zinc Mercury / Mercruiser 25 HP outboard anodic plate bar anode. For salt water use only.

Outside Diameter: 91mm

Height: 100mm

Thread Size: M8

Weight 0.42kg

Part No 11210





CM821630C2Z - Martyr Zinc Anode for Mercury Outboard & Mercruiser Sterndrive and engines.

Forward Cavitation Plate. Fits Bravo I, II, III, X, XR and XZ. Mercury Part no: 821630A2, 821630Q1. For use in Salt water.

Dimensions: 175 × 110 × 16 mm

Weight 1kg

Part No 11214





CM821629CZ - Martyr Zinc Anode for Mercury Outboard; Mercruiser Sterndrive and engines.

Forward Cavitiation Plate. Fits Alpha I Gen II. Mercury Part no: 821629A2, 821629Q1. For use in Salt water. CM821629Z.

Dimensions: 188 × 72 × 18 mm

Weight 0.78kg

Part No 11215



CM818298Z - Martyr Zinc Anode for Mercury Outboard & Mercruiser Sterndrive and engines.

Plate Bar for engine trim. Fits Mercury/Mariner 30/40 Four Stroke, 40 (4 cylinder), 50 (3 cylinder 1987-1997), 55 (3 cylinder), 60-90 (3 cylinder 1987 & newer), 75 (4 cylinder), 75/90 Four-Stroke, 100-125 (4 cylinder), 115 (6 cylinder 1984-1988) and all V-6 and OptiMax. Mercury Part no: 818298T3 For use in Fresh water.

Dimensions: 191 × 50 × 11 mm

Weight 0.68kg











Transom mounted 'Waffle Bar'. For use in Salt water. Mercury part number 43396. Fits Mercury 25HP, 50, 60, 75 Mercruiser E.B90, 100 SINO 91, 115,

Dimensions: 194 × 52 × 20 mm

Weight 0.66kg

Part No 11217

CM806190Z - Martyr Zinc Anode for Mercury Outboard & Mercruiser Sterndrive and engines.

Lift-Trim Cylinder Ram End Horseshoe. Fits Bravo I, II, III, X, XR, XZ and Blackhawk drives. Mercury Part no: 806190A2, 806190Q1. 2 Required. For use in Salt water.

Dimensions: 49 × 49 × 51 mm

Weight 0.35kg

Part No 11221



CM806189Z – Martyr Zinc Anode for Mercury Outboard & Mercruiser Sterndrive and engines.

Lift-Trim Cylinder Ram End Horseshoe. Fits Alpha 1 Gen II. Mercury part no: 806189A2, 806189Q1. 2 required. For use in Salt water.

Dimensions: 49 × 49 × 16 mm

Weight 0.1kg

Part No 11222









CM3C7602181A0Z Nissan / Tohatsu transom bar in zinc.

Part No 11353



CM5532095310Z

Zinc Suzuki block anode. For salt water use only.

Anode Body Length: 40mm

Width: 30mm Height: 12mm

Stud Size: 6mm Weight 0.24kg

Part No 11350



CMS551259630Z

Zinc Suzuki - Cutdown Skeg

Dimensions: 69mm x 69mm x 49mm

Weight 0.13kg

Part No 11351



CMS5512587D00Z

Suzuki - standard skeg

Part No 11352





CM832598Z - Martyr Zinc Anode for Volvo Penta Sterndrive Outdrive 832598

Martyr Zinc Anode for Volvo Penta Sterndrive outdrive. Transom Shield Bar Anode. Fits 200, 250, 270, 275, 280, 285. Aquamatic sterndrive single prop drive anode. Volvo Part no: 832598. For use in Salt water.

Dimensions: 187 × 41 × 22 mm

Weight 0.95kg Part No 11150



CM838929Z - Martyr Zinc Pencil Anode for Volvo Penta Cooler 838929

Martyr Zinc Pencil Anode for Volvo Penta engines. Cooling system anode. Fits MD40A, TMD40 A/B/C, D4 D6, TAMD63, TAMD74 / TAMD75, TAMD122P, D12C, TAMD163P-A, 2001 / 2002 / 2003, TAMD103, TAMD122A, TAMD162C, TAMD163A-A. Volvo replacement part for 838929, 804107, 800476, 858501. For use in Salt water

Dimensions: 43 × 17 × 43mm

Weight 0.05kg

VOLVO PENTA



CMV15 - Martyr Zinc Anode for Volvo Penta 100 Drive Sterndrive 875810

Small Prop Ring. Fits 100A and 100B. Aquamatic sterndrive single prop drive anode. Volvo Part no: 875810. For use in Salt water.

Dimensions:

100 × 100 × 12 mm

Weight 0.2kg

Part No 11153

Anodes



CMV16 - Martyr Zinc Anode for Volvo Penta 200 Drive Sterndrive 875809

Small Prop Ring, Fits 200, 200A, 200B. Volvo Part no: 875809. For use in Salt water

Dimensions: 108 × 108 × 11 mm

Weight 0.21kg

Part No 11154

VOLVO



CMV17 – Martyr Zinc Anode for Volvo Penta 270 Drive Sterndrive 875805

Medium Prop Ring. Fits 270 B,C,D, SP, T, 275, A, SP-A/MT, 250, C,D. Volvo Part no: 875805. For use in Salt water.

Dimensions: 116 × 116 × 10 mm

Weight 0.32kg

Part No 11155

VOLVO PENTA



CMV18 - Martyr Zinc Anode for Volvo Penta 200-290 Sterndrives 875815

Large Prop Ring. Fits 280, B, C, D, E, SP, T, 290, A, B, D, SP, SP-A, SP-C, SP-E, SP-A1, SP-A2, 280PT. Aquamatic sterndrive single prop drive anode. Volvo Part no: 875815. For use in Salt water.

Dimensions: 120 × 154 × 35 mm

Weight 0.73kg

Part No 11156

VOLVO



CM823661Z - Martyr Zinc Pencil Anode for Volvo Penta Diesel engines 823661

Fits TAMD60 A,B,C, MD70B, TAMD70 B, C, D, E, D12 500, 700, 715, 800, TAMD122 A, C, D, P, P-A, P-B, P-C, MD70C. For use in Salt water. Original part number 823661.

Dimensions: 25 × 25 × 54 mm

Weight 0.15kg

Part No 11158

VOLVO



CM875821Z – Martyr Zinc Anode for Volvo Penta Duo DP 280 290 Outdrive 875821

Duo Prop Ring Anode. Fits: 280DP, 280T-DP, 280A-DP, DPA, A1, A2, B, G, C, D, D1, D2, E, B1, C1. Volvo Part no: 875821 lower gear anode. For use in Salt water.

Dimensions: 111 × 144 × 30 mm

Weight 0.58kg

Part No 11160

CM852835Z - Martyr Zinc Bar Anode for Volvo Penta Sterndrive and engines 852835/873178

Fits transom shield Aquamatic sterndrive single prop drive 280 and 290 and SP ranges. Fits 290, A, A-DP, B, D, DP, DP-A, DP-A1, DP-A2, DP-B, DP-B1, DP-C, DP-C1, DP-D, DP-D1, DP-D2, DP-E, DP-G, SP, SP-A, SP-A1, SP-A2, SP-C, SP-E. Volvo part number 852835 or 873178. For use in Salt water

Dimensions: 129 × 44 × 27 mm

Weight 0.76kg

Part No 11161

VOLVO PENTA



CM851983Z - Martyr Zinc Anode for Volvo Penta 120 Saildrive 876286/851983

Fits 120, B, C, D, E, MS25S, MS25S-A, MS25S-R, S120C. Volvo Part no: 876286. For use in Salt water. Split ring version also available.

120S, 120SB, 120C-D, 120S-D, 120-E, S120C.

Dimensions: 123 × 96 × 28 mm

Weight 0.6kg

Part No 11162

VOLVO

CM875812Z – Martyr Zinc Anode for Volvo Penta 110 120 Saildrive 875812

Sail Drive Prop Ring Anode. Fits 110S, 120S, MS25S. Volvo Part no: 875812 lower gear anode. For use in Salt water.

Dimensions: 106 × 138 × 43 mm

Weight 0.92kg





VOLVO PENTA



CM872793Z - Martyr Zinc Anode for Volvo Penta SX and DPX Outdrive 872793/3861583

Hook-up Fork Triangle Anode. Fits SP, DP, SX, DPX, XDP-B Sterndrives. Volvo Part: Volvo Part no: 3861583. For use in Salt water.

Dimensions: 65 × 38 × 13 mm

Weight 0.11kg Part No 11165

VOLVO



CM3854130Z - Martyr Zinc Anode for Volvo Penta Outdrive 3854130

Gimbal Plate or transom shield Anode. Fits DP-SM, DP-SMTD1, DP-SMTD1, DP-SMTD2, DP-SMTD3, SX-M, SX-MTD, SX-MTD3, SX-M, SX-M1, SX-MLT, SX-MDA, SX-MDB, SX-MHP, SX-MACLT, SX-MDC, SX-MBAC, SX-MACLT, SX-MBAC, SX-MHP, SX-C, SX-C1, SX-C2, SX-CT, SX-CT1, SX-R, SX-RT1, SX-RT2, DP-S, DP-S1, SX-C1AC, SX-C2AC, SX-R1, SX-R2, SX-CLT, SX-CLT1 and Aquamatic sterndrive single prop drives. Volvo Part no: 3854130. For use in Salt water.

Dimensions: 90 × 80 × 48 mm

Weight 1.05kg Part No 11327



CMBNT1AZ

Martyr Zinc Trim Tab Anode for Bennett or similar. For use in Salt water. Anode only. Designed to mount on Bennett Trim Tabs where the actuator mounts to the plane.

Dimensions: 55 × 27 × 14 mm

Weight 0.2kg

Part No 11325



CM872139Z - Martyr Zinc Anode for Volvo Penta DPX Outdrive 872139

DPX Outdrive or Aquamatic sterndrive Duoprop range. Transform Bar Anode. Fits DPX, DPX-C, DPX-R, DPX-S, DPX-A. Volvo Part no: 872139. For use in Salt water.

Dimensions: 130 × 45 × 26 mm

Weight 0.66kg

Part No 11151

VOLVO



CM3858399Z

Volvo 3 piece propeller anode

Part No 11387

VOLVO PENTA



CM3855411Z - Martyr Zinc Anode for Volvo Penta Outdrives

Forward Spray Plate/Cavitation Plate/ Transom Plate Anode. Fits DP-SM, DP-SMTD, DP-SMTD1, DP-SMTD3, SX-M, SX-MTD, SX-MTD3, SX-MTD, SX-MTD3, SX-M1, SX-MLT, SX-MDA, SX-MDB, SX-MHP, SX-MACLT, SX-MDC, SX-MBAC, SX-MACLT, SX-MBAC, SX-MHP, SX-C, SX-C1, SX-C2, SX-CT, SX-CT1, SX-R, SX-RT1, SX-RT2, DP-S, DP-S1, SX-C1AC, SX-C2AC, SX-R1, SX-R2, SX-CLT, SX-CLT1. Volvo Part no: 3855411. Aquamatic sterndrive single prop drive. For use in Salt water.

Dimensions: 62 × 62 × 10 mm

Weight 0.24kg Part No 11326

≤ YANMAR



CM19642002652Z - Martyr Zinc Anode for Yanmar Saildrive Engines

Martyr Zinc Anode for Yanmar Saildrive Engines without adaptor ring. Fits SD20, SD30, SD31, SD40, SD50. For use in Salt water. Yanmar part number: 196420-02652. Like Tecnoseal part number 01305.

Dimensions: 147 × 107 × 26 mm

Weight 0.85kg

Part No 11180



CM272100200300Z

Pencil Anode

Yanmar plug anode

Part No 11181



CM19644002660

For drives with adaptor ring











Martyr CM6H14525102Z Yamaha Outboard Transom Bar Zinc Anode. Replaces Yamaha 6H1-45251-02Z.

Part No 11296



CM6884537102Z - Martyr Zinc Fin Anode for Yamaha Engines

Skeg / Trim Tab. For use in Salt water. Original part no: 688-45371-02

Fits outboard engine 70-90 ETLN/ETXN/ETLK, CV75-85ELF/TLR, P60TJHR, F50TLH Series. Yamaha 50-60-70-75-80-85-90 HP series.

Dimensions: 134 × 93 × 80mm

Weight 0.48kg Part No 11298 CM6E54525100Z

Zinc Yamaha small block anode. For salt water use only.

Anode Body Length: 47mm

Width: 23mm Height: 23mm Weight 0.14kg

Part No 11300









CM6J94537100Z - Martyr Zinc Skeg Anode for Yamaha 150-225HP Engines

Skeg / Trim Tab. For use in Salt water. Standard rotation.

Original part: 6J9-45371-00.

Dimensions: 129 × 99 × 90 mm

Weight 0.5kg Part No 11303



CM6884525101Z - Martyr Zinc Button Anode for Yamaha Engines

Button for use in Salt water. Original part number 688-45251-01

Fits Mariner/Yamaha 40-50-70-90 HP up to 1987.

Dimensions: 20 × 20 × 8 mm

Weight 0.04kg

Part No 11304



CM61N4525101Z - Martyr Zinc Anode for Yamaha 8-25HP Engines

Trim Tab. For use in Salt water. Original part number 61N-45251-01.

Dimensions: 80 × 59 × 27 mm

Weight 0.26kg

Part No 11305

Zingard Zinga Spray



Zingaspray (500ml aerosol) has all the advantages of the original Zinga in an easy-to-use spray can.

One coat of Zingaspray will dry at approximately 20-25 microns. Therefore a minimum of two coats is recommended.

Zingaspray can be used for repairing galvanised steel or products previously treated with Zinga.

Part No

Zinc Pencil Anodes



Part No	MG Duff	Desciption	Part No	MG Duff	Description
	Part No			Part No	
11401	P10502	1.05" X 2"	11411	P5004	1/2" X 4"
11402	P10502 8MM	1.05" X 2" with 8mm	11412	P5006	1/2" X 6"
11403	P10503	1.05" X 3"	11413	P6252	5/8" X 2"
11404	P10504	1.05" X 4"	11414	P6253	5/8" X 3"
11405	P10506	1.05" X 6"	11415	P6254	5/8" X 4"
11406	P3752	3/8" X 2"	11416	P6256	5/8" X 6"
11407	P3753	3/8" X 3"	11417	P7502	3/4" X 2"
11408	P3754	3/8" X 4"	11418	P7503	3/4" X 3"
11409	P3758MM	3/8" X 35mm	11419	P7504	3/4" X 4"
11410	P5002	1/2" X 2"	11420	P7506	3/4" X 6"

Brass Pencil Anode Plug



Part No	MG Duff	Description
	Part No	
11421	PP1000B	Brass Plug for P1050 - 1" NPT Thread
11422	PP250B	Brass Plug for P375 - 1/4" NPT Thread
11423	PP375B	Brass Plug for P500 - 3/8" NPT Thread
11424	PP500B	Brass Plug for P625 - 1/2" NPT Thread
11425	PP750B	Brass Plug for P750 - 3/4" NPT Thread



For bolt on hull anodes see page 6.

Aluminium Anodes

For use in Salt & Brackish Water only.

Aluminium anodes have been on the market for the last 30 years or more, but since the price of zinc has doubled in the last two years, aluminium is now cheaper," says MG Duff commercial director James Beale. "And it's the better anode material: it has a higher driving voltage so, unlike zinc, it works in salt water and brackish – and has a higher amp-hour per kg rate meaning it lasts longer too. Another plus is that aluminium anodes are more environmentally friendly as, unlike zincs, they don't contain cadmium.



AD59 Button Anode		
Part No	11450	
Width	70	
Depth	25	
Weight	0.16KG	



AD56 Disc	Anode	AD58 Disc	Anode
Part No	11451	Part No	11449
Length	100mm	Length	150mm
Width	80mm	Width	125mm
Depth	25mm	Depth	35mm
Weight	0.42KG	Weight	0.9KG
Stud Size	M10	Stud Size	M10



AD77 Pear	r Anode
Part No	11452
Length	229mm
Width	83mm
Depth	41mm
Weight	1KG
Stud Size	M10
Centres	200mm



AD77 Large Euro Anode		
Part No	11453	
Length	318mm	
Width	65mm	
Depth	32mm	
Weight	1KG	
Stud Size	M10	
Centres	110 - 210mm	



AD78BX H	AD78BX Hull Anode	
Part No	11454	
Length	305mm	
Width	76mm	
Depth	32mm	
Weight	1.85KG	
Stud Size	M10	
Centres	200mm	



The ASA range of shaft anodes are well known for their quality, and classic golf ball shape. This range of shaft anodes are an excellent way to protect your shaft from corrosion.

Part No	Shaft Dia
11455	25mm
11456	1"



MGDA Shaft Anodes

The MGDA range of shaft anodes are known for their superior quality, and are particularly suited to vessels with high shaft speeds.

Building on the integral core bar design that controls wastage, ensuring the shaft anode remains secure, the MGD range now incorporates socket head (allen bolt) stainless steel fixings with captive nuts to ensure maximum reliability. Available in a wide range of metric and imperial sizes, offering a direct fit for your propeller shaft.

Part No	Shaft Dia
11457	25mm
11458	1"
11459	30mm
11460	1 1/4"

NESSE

Boat Cleaning



Part No Description 61130 Fibreblast 1 Litre 61131 Fibreblast 3.25 Litre

Fibreblast removes stubborn stains on the waterline as well as rust and exhaust stains and the usual dirt and grime found on boats. Fibreblast is suitable for fibreglass, gelcoat and most two pack polyurethane paints and single pack yacht enamels.

Directions

- Unscrew the lid and apply generously to the surface with a paintbrush.
- Leave for about 30 minutes on the surface to gently "blast" away and absorb the stains.
- Rinse with a sponge and clean water.
- Leave on longer or repeat the application process for tough stains and in colder weather.
- When using for the first time on a surface it is advisable to apply Fibreblast on a small area first to test.





3M™ Perfect-it™ Boat Wash

3M's best product solution to clean a variety of boat surfaces. The product is a professional strength concentrate, making up to 16 gallons. It works safely on surfaces from stem to stern. And it works without stripping wax.

Part No	Description
63680	3M Perfect - It Boat Wash 473ml
63681	3M Perfect - It Boat Wash 946ml



Wessex Propeller Cleaner

This professional-grade propeller cleaner has been designed to remove calcium deposits, algae and soften and help remove barnacles from all boat and yacht propellers.

It delivers superb propeller cleaning results on a range of metals including stainless steel, bronze and aluminium propeller blades, shafts and casings.

Part No

61566





Wessex Proflush Engine Descaler

Proflush Marine Engine Descaler removes unwanted marine deposits from waterways including: scale and light rust crustaceans Salt deposits Magnetite With a colour indicator you can clearly see when all scale and deposits are neutralised as the liquid will remain a constant colour once it's work is completed. Proflush will remove 1.09Kg of calcium/scale equivalent per litre of product used.

Part No	Description
61567	Wessex Proflush 1 Litre
61568	Wessex Proflush 5 Litre





Jabsco Toilet Cleaner 1 Litre Part No 61109





Jabsco Odourless Holding Tank Treatment 1 Litre

A blend of enzymes, friendly bacteria and surfactants, to break down waste in marine holding tanks.



Wessex Boat Wash

Boat Wash is the perfect solution for cleaning fibreglass hulls on boats and yachts. It effectively removes dirt, grime and grease leaving your hull clean and shining.

Great for use on non-slip decks, metal parts and railings, and teak decks, Boat Wash is highly concentrated, as little as 20 ml into a bucket of water will do an excellent job of cleaning down hulls and leaving them shiny and streak-free.

Boat Wash can also be used as a spoton spray for quickly removing marks, stains and even birdlime.

Part No	Description
61550	Wessex Boat Cleaner 1litre



Sail Cleaner

This sail cleaner is quick and effective at cleaning boat, yacht and dinghy sails. It removes general dirt, grime, grease, traffic/pollution film and mould from sail material and is safe on sail stitching and other sail materials. It also smells pretty good too! It is biodegradable, so is environmentally safe, and can be used for cleaning your boat in and out of the water. It also works brilliantly for cleaning caravan and boat awnings too.

Part No	Description
61558	Wessex Sail Cleaner 750ml





Wessex Canopy Cleaner & Protector

This Canopy Cleaner & Protector effectively cleans off mould, dirt, grime, grease and oil from boat and yacht canopies and other marine craft covers.

After cleaning, the spray leaves a special protective film to combat against regrowth and prevent UV fading. This ready-to-use formula means you can just spray onto the canopy then simply wipe clean with a non-scratch cloth.

The water based mixture is fully biodegradable and so can be used for cleaning your boat in and out of the water.

Part No	Description
61552	Wessex Canopy Cleaner





Wessex Oxalic Acid

Industrial grade, high purity oxalic acid crystals / granules suitable for a range of purposes. Suitable for various uses including stain removal from hardwoods to rust removal from stainless steel and other metals.

Frequently used on boats and yachts for GRP fibreglass cleaning, salt corrosion removal from engine waterways and cleaning/stain removal on teak boat decks. Helps clean and remove problematic areas on boats including rust, algae, dirt and grime.

Should be used with caution around delicate metals, for example, aluminium.

Part No	Description
61556	Wessex Oxalic Acid 1KG









Teak Cleaner Part One

Wessex Teak Cleaner. (part 1) is designed to take away the natural silver colour teak turns over time, and bring it back to the colour it was when new (a straw colour). When using the Wessex Teak Cleaner for the first time, you will notice it making the teak wood go dark brown in colour. As you apply it with a sponge or brush you will also notice the dirt and muck coming off. When you have finished applying Teak Cleaner and begin to rinse off with water, you will see dirty brown water running off the teak. You will literally see the dirt being removed!


Part No	Description
61560	Wessex Teak Deck Cleaner Part 1 - 1 Litre
61561	Wessex Teak Deck Cleaner Part 1 - 5 Litre

Teak Renovator Part Two

Wessex Teak Renovator (part 2), sometimes referred to as a teak brightener, is designed to restore the colour so it looks like new teak again. As soon as you apply Teak Renovator, the teak will lighten to a lovely uniform amber colour and eventually dry to a straw colour, just like new teak. No patchy areas, just some teak to be proud of again!

Part No	Description
61562	Wessex Teak Renovator Part 2 - 1 Litre
61563	Wessex Teak Renovator Part 2 - 5 Litre





Wessex Bilge Cleaner lifts off dirt, grime, grease, oil and scale from bilges, pipes and lockers in boats and yachts.

It helps combat the growth of limescale, mould and mildew commonly found in boat bilges. Wessex Bilge Cleaner also controls bad odours caused by stagnant water in bilges, holding tanks and traps under showers and sinks.

Ideal for over-wintering to keep tanks free from odour build-up. Safe for use on a variety of hard surfaces including metals, plastics, laminates and ceramics. Avoid spillages on fabrics, including carpets.100% environmentally friendly and biodegradable.

Part No	Description
61132	Wessex Bilge Cleaner 1 Litre
61133	Wessex Bilge Cleaner 5 Litre



Glass Cleaner

Powerful formulation contains a high alcohol and ammonia content for superior cleaning performance.

Part No	Description
61564	Wessex Glass Cleaner
	750ml



Epifanes Inflatable Boat Cleaner

This product is specially designed for safely cleaning and maintaining all butyl, hypalon, rubber and vinyl boats and surfaces. It slows down the ageing process considerably, prevents drying out and cracking and removes ingrained dirt, tar, diesel oil, scuff marks etc. Seapower Inflatable Boat Cleaner is also excellent for cleaning fenders. After treatment, they will not become sticky when exposed to sunlight, like other cleaners. It also reduces fender squeaks, familiar to all who lie alongside.

Part No	Description
69330	Seapower Inflatable Boat cleaner 500ml



(O) HEMPEL

Pre-Clean - 1 Litre

High strength cleaner and degreaser for pre-cleaning gelcoat and painted surfaces to remove fuel, oil, grease, wax and silicone.

Part No 67130



Wax TecCel - 500ml

High performance liquid wax with TecCel technology, for a long lasting, deep gloss, tough protective finish on gelcoat, painted and varnished surfaces.

(O) HEMPEL

Part No 67247



Alu Protect - 500ml

A silicone-free oil, for cleaning and protecting metal rigging and fittings. For cleaning and protecting aluminium masts and booms, steel and stainless steel rigging and fittings. Penetrates into wire ropes and under fittings, ensuring long-term protection.

Part No 67245



Treadcote

TREADCOTE is designed to rejuvenate the appearance of heavily weathered or stained TREADMASTER Original. This paint is easy to apply, with full surface preparation and application details shown on the can.

Part No	Description
91883	White Sand
91884	Grey
91885	Blue
91886	Fawn

International



Super Cleaner - 500ml

A highly concentrated cleaner. Removes wax, oil and contamination effectively. Suitable for hand and high pressure machine washing. Degreases and cleans with no damage to gelcoat or paint work. Always use before waxing diluted or undiluted.

Part No

68480



Stain Remover - 500ml

A high strength penetrating gel that quickly and easily removes stains, such as light rusting and yellowing, on GRP and painted surfaces.

Part No

68482



Marine Polish - 500ml

An ultrafine grade polish with wax, for use on gelcoat and paintwork. Gives lasting protection and high gloss. For manual and machine polishing (800 -1000 rpm). Free from silicon oils.

Part No

68484



Polish and Wax- 500ml

A cleaner, polish and wax in one product. Used for quick and easy cleaning, polishing and waxing of oxidised gelcoat and painted surfaces. Free from silicon oils. For manual or machine use (800 - 1000 rpm)

Part No

68486



Teak Oil - 500ml

A special penetrating oil for protection of teak decks and teak interiors. It produces a protective and easy-clean surface.

Part No

68489



Boat shampoo - 500ml

A universal cleaner for fibreglass, wood, metals and painted surfaces. It does not remove wax and can be used regularly without affecting your wax protection.

Part No

68481



Liquid Rubbing - 500ml

A liquid polishing product that restores the former shine on gelcoat and painted surfaces. Does not contain wax or silicone. For both manual and machine polishing (800 - 1000 rpm).

Part No

68483



Marine Wax - 500ml

Gives lasting protection without abrasives or silicone. Easy to work with and an ideal product for larger surfaces. This product offers a hard, long lasting, full gloss surface and gives protection against saltwater and sunlight. For manual and machine use (800 - 1000 rpm)

Part No

68485



Teak Restorer - 500ml

Cleans and restores teak and other hardwoods.

Part No

68488



Teak Cleaner - 750ml

A powder for cleaning all teak areas. Especially good for large areas such as decks, and for wood that's turned dark grey. Removes dirt and marks giving a clean surface ready for you to apply Teak Oil.

Part No







3M Marine Vinyl Cleaner 250ml

3M Marine Vinyl Cleaner is a one-step product that conditions and protects vinyl, plastic and rubber surfaces as it cleans - creating a long-lasting protective barrier that withstands repeated cleaning and prevents damage from sunlight.

Part No

63691





3M Clear Plastic Restorer 250ml

Safely cleans and removes fine scratches and haziness from most marine plastics. Can also be used on most tinted plastics.

Part No

63696





3M Metal Restorer & Polish 500ml

Designed to restore and polish stainless steel, bronze, copper, chrome, aluminium, and other marine metals by removing surface oxidisation, corrosion and tarnish.

Part No

63689





3M General Purpose

Adhesive Cleaner 1ltr

Mild solvent for surface preparation prior to adhesive use. Also use for cleaning up adhesives/sealants and for the removal of silicone polish, wax, grease and oil.

Part No

63807



Brillo Washing Up Liquid

Specially formulated washing up liquid for use in professional kitchens. Contains a concentrated blend of high active grease cutting ingredients that leaves tableware clean and smear free. 5 litres makes up to 7,500L of ready to use dish washing detergent

Part No

5 Litre

61620





3M Professional Panel Wipes

Have our strong and highly absorbent 3M™ Professional Panel Wipes to hand to clean and degrease auto panels and other surfaces quickly and effectively. You can use our wipes for other heavy duty cleaning tasks. You'll find them safe and suitable for use on stainless steel, chrome, aluminium, plastics, enamel and glass. Use them wet or dry. Our strong and highly absorbent wipes are low linting and anti static. 400 sheets per box.

Part No Description

64048 3M Professional Panel Wipes

Pack of 400



Prep - Heavy Duty Trade Wipes

Safe Guard wipes are tough, fast, safe and convenient wipes designed to remove a wide range of soils such as paint, silicones, mastics, inks, adhesives, oils, greases and general dirt. They are ideal for cleaning the hands, work tools and hard surfaces.

Part No Description

Heavy Duty Trade Wipes 60292

Tub of 80



White Spirit

White Spirit is a highly refined solvent meeting the requirements of BS245. Suitable for general cleaning purposes, brush cleaning and paint thinning. It is more suitable for paint thinning than other solvents as it will not affect the drying time of oil based paints.

750ml	2 Ltr
61505	61500



Acetone

Solvent for cleaning up polyester, polyurethane and epoxy resins. Use for cleaning brushes, equipment, blocked spray guns etc.

Part No

1 Ltr 2.5 Ltr 63000 63001



Turpentine Substitute

A high quality turps substitute which is commonly used for thinning oil based paints and cleaning brushes, or as an organic solvent in other applications.

25 Ltr



Standard Bucket - 10 Litres

2 Gallon (10 Litre) quality general purpose bucket calibrated in gallons and litres. With gripper handle.

Colours may vary.

Part No

91704



Invincible Bucket - 15 Litres

3 Gallon (15 Litre) quality tough heavy duty 'Invincible' Bucket calibrated in gallons and litres. With gripper handle and pourer.

Colours may vary.

Part No

91705



PVC Stow-Away 10 Litre Nylon Bucket

Reinforced Plastic and Stainless handle. Comes in Yellow, with side pocket.

Part No

76156



1 Litre Jug

Clear, rigid general purpose jug. Calibrated to 1 litre.

Part No

91712





Suction Pad Handle

Ideal to hang to the boat sides during cleaning operations and external maintenance activities. Also fit for lifting hatches. It hangs to any surface within seconds. Fitted with suction pads and flip-up fastening flaps.

Part No

96220



Synthetic Sponge

Individually wrapped.

Part No

90557



Hand Scrub Brush

Suitable for removing stubborn stains from hard surfaces and hard floor areas, 220mm

Part No

90545



Professional Microfibre Wash Mitt

Made of soft microfibre. It absorbs large quantities of water for optimal and effortless cleaning of wide surfaces. Elastic wrist band for a better cleaning performance. Universal fit.

Part No

96332



Microfibre Cloths

40 x 40cm

Pack of 10. Colours may vary.

Part No

60360



10kg Bag of White Rags

Mixture of rags for cleaning.

Part No

60291



Mutton Cloth

(Stockinette)

High quality cotton stockinette cloth for general cleaning and polishing tasks.

400gm

60298



Tack Cloths

Cloths for wiping down surfaces prior to painting to ensure a smooth finish. They are slightly tacky and will pick up and hold dust, dirt and sanding residue. Sold singly or in packs of 10.

Part No





Draper syphon pump

Manufactured from plastic, the pump is a useful item for transferring a wide variety of inert liquids. Inlet pipe 390mm long; outlet pipe 400mm long. Display packed.

Part No

90558



9" Complete Deck scrub & Broom Handle set

1.2m Long broom handle

Synthetic Bristles.

Part No

90546



Hand Bailer

Strong thermoplastic

- · Length 20 cm.
- Resistant down to -30°
- Suitable for life rafts.
- · White.

Part No

90560



Standard Funnel

Clear 4.5"

Part No

91706



Standard Funnel

Clear 6.5"

Part No

91707



Large Funnel 10"

Robust, rigid funnel with a 10" (254mm) mouth.

Part No

91708





The telescopic broom handle is simply set in four different lengths.

Blue brush head = 8" wide Soft Bristles

Yellow brush head = 8" wide Medium Bristles

Part No

Blue Brush	Yellow Brush	Telescopic Broom
Soft	Medium	106-180cm
90552	90554	90550



Flexible Funnel

Versatile plastic funnel with detachable long reach spout, splash lip and filter mesh.

Part No

91709



MultiSolve 500ml Aerosol

It is a complete new multi-purpose solvent; for the safe removal of adhesives and sealants.

Removes adhesives, sealants, oil, grease, silicon, wax, tar, paraffin, printing ink etc. Leaves no oil film.

Fast, thorough and safe degreasing and cleaning.

Can be used on painted surfaces, vinyl, glass,rubber and plastics.

Fast drying.

Part No

60516



Mould Stain Remover 500ml

Cleans and bleaches stains caused by mould spores, fungus and algae from most surfaces including grout and the surface of silicone seals and other damp areas. Once cleaned and with regular use it will help prevent re-growth and the reappearance of fungal stains. It has a 360 degrees head for ease of use and gives accurate spray action for interior or exterior use.

For interior and exterior use.

Part No

Bollards / Sampson Posts




Horn Bollards Cast 316 Stainless Steel Horn Bollards.

Militor Polistied.					
Part No	Description				
76218	Horn Bollard 200mm SS 316				
76220	Horn Bollard 240mm SS 316				








316 Stainless Steel Sampson Post. Cast in one piece and hand polished to give a brilliant shine with no joins or unsightly welds to be seen.

Part No	Description
76208	(A) 60 (B) 90 (C) 60 (D) 90 (E) 105mm - M6 Screw
76210	(A) 65 (B) 96 (C) 95 (D) 120 (E) 120mm - M8 Screw
76212	(A) 80 (B) 120 (C) 116 (D) 150 (E) 150mm - M10 Screw




Made of mirror-polished AISI316 stainless steel.

Part No	Description	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	Stud Ø mm
96113	100mm AISI316 Stainless Steel Bollard Ercol	100	Ø 50	55	90	80	130	66	57	6.5
96114	120mm AISI316 Stainless Steel Bollard Ercol	120	Ø 60	70	120	95	180	95	70	6.5
96115	142mm AISI316 Stainless Steel Bollard Ercol	142	Ø 70	82	140	118	180	105	80	8.5

Made of high-gloss polished stainless steel (AISI 316). Bollards type ACHILZ are for direct welding to the deck. Dimensions are similar to ACHIL.


Bollard wit	Bollard with baseplate							
Part No	Vetus	Safe Working Load	Α	В	Ø	С	D	E
58223	ACHIL080	620 kgf	120	90	40	80 x 65	52	4 x Ø6.5
58224	ACHIL090	620 kgf	130	95	50	92 x 92	52	4 x Ø6.5
58225	ACHIL110	1150 kgf	160	120	60	122 x 97	70	4 x Ø8.5
58226	ACHIL130	1150 kgf	180	142	70	140 x 118	82	4 x Ø8.5
58227	ACHIL150	1800 kgf	200	172	80	153 x 122	100	4 x Ø10.5
58228	ACHIL160	2620 kgf	225	195	90	165 x 135	120	4 x Ø10.5
58232	ACHIL080Z	620 kgf	120	90	40		52	
58233	ACHIL090Z	620 kgf	130	95	50		52	
58234	ACHIL110Z	1150 kgf	160	120	60		70	
58235	ACHIL130Z	1150 kgf	180	142	70		82	
58236	ACHIL150Z	1800 kgf	200	172	80		100	
58237	ACHIL160Z	2620 kgf	255	195	90		120	
58239	ACHIL090B	620 kgf	50	92	50			8mm







Cleats




All models are tapped on the underside so that no fastenings are visible. Made of high-gloss polished stainless steel (AISI 316).

Bollard v	Bollard with baseplate						
Part No	Vetus	Safe Working Load	Α	В	С	D	E
58214	TAURUS01	575 kgf	140	50	89.5 x 30	47	2 x M8
58215	TAURUS02	900 kgf	195	60	120.5 x 35	69	2 x M10
58216	TAURUS03	1310 kgf	255	75	150 x 40	83	2 x M12

Precision-cast push-up cleat Made of mirror-polished AISI316 stainless steel. Fitted with mounting studs and retainer plate.





Part No	Description	Α	A1	В	D	С	Е	Stud
96090	6" Pop Up Cleat	164	150	38	12	60	23	10
96091	8" Pop Up Cleat	217	203	50	15	83	36	10

Manufactured from 316 Stainless steel



Stainless Flat Top Cleats		
Part No	Length	
23000	4" (102mm)	
23005	6" (152mm)	
23010	8" (203mm)	
23015	10" (254mm)	



Olouto	
Part No	Length
23200	3" (76mm)
23201	4.5" (102mm)
23202	5.5" (127mm)
23203	6.5" (165mm)

Black Nylon Flat Top

Cleats





Made from 316 S/S these folding cleats require nothing but two holes to fit screws or studs. Where most pop-up cleats need substantial space below deck, these require nothing but a suitable surface to attach them to. Stud mounted with hidden Fastenings.

· ·	
Part No	Length
96556	6" (152mm)



Only Right/Left Terminal for Fairlead Mirror-polished finish.

AISI 316 Stainless Steel

Part No Description 96466 Only Right/Left Terminal

Stainless Steel Fairleads

Manufactured from 316 stainless steel

Stainless Steel Fairleads Rounded

Manufactured from 316 stainless steel





Handed (Pairs)			
Part No	Length	Max Rope Size	
23020	4 1/2" (114mm)	10mm	
23025	6" (152mm)	18mm	



Handed (Pairs)				
Part No	Length	Centre Distance		
96092	4 1/2" (112mm)	84mm		
96093	6" (150mm)	122mm		




Straight (Each) fairleads				
Part No	Length	Height	Width	
23027	4"	24mm	20mm	
23028	5"	24mm	20mm	
23029	6"	36mm	24mm	

Cowl Ventilators

DON316R








DON316WR

Part No	Description	A mm	B mm	C mm	D mm	Free Flow Area (cm²)	Material
56824	DON316WR White Cowl Ventilator SS 316	111	75	123	22	44.2	Stainless Steel (AISI 316)
56825	DON316R Red Cowl Ven- tilator SS 316	111	75	123	22	44.2	Stainless Steel (AISI 316)

YOG316R TOM316R JER316R







YOG316WR TOM316WR JER316WR


Part No	Vetus	Description	A mm	B mm	C mm	D mm	Free Flow Area (cm²)
56833	YOG316WR	125mm White Interior	296	125	181	22	122.8
56834	YOG316R	125mm Red Interior	296	125	181	22	122.8
56835	TOM316WR	100mm White Interior	250	100	153	22	78.6
56836	TOM316R	100mm Red Interior	250	100	153	22	78.6
56837	JER316WR	75mm White Interior	205	75	123	22	44.2
56838	JER316R	75mm Red Interior	205	75	123	22	44.2



Vetus				
Cover & Mosquito Screen				
Part No	Vetus	Description		
56822	SET75	Cover & mosquito screen		
56823	SET100	Cover & mosquito screen		

SAMOENS CHINOOK LIBEC







TRAMON

Part No	Description	A mm	B mm	C mm	D mm	Free Flow Area (cm²)	Material	Replaces
56850	TRAMONS Silicone Cowl Ventilator	100	75	127	11	44.2	Silicone	DONALDS
56851	LIBECS Silicone Cowl Ventilator	192	75	127	11	44.2	Silicone	JERRYS
56852	CHINOOKS Silicone Cowl Ventilator	230	100	152	11	78.6	Silicone	TOMS
56853	SAMOENS Silicone Cowl Ventilator	282	125	179	11	122.8	Silicone	YOGIS

Inspection Hatches

Available in black, white or clear plastic.







Part No	Opening Size mm	Cut Out Size	Overall Deck Plate Size	Colour	Part No	Opening Size mm	Cut Out Size	Overall Deck Plate Size	Colour
25100	4" (102mm)	113mm	147mm	White	25106	6" (152mm)	168mm	205mm	White
25101	4" (102mm)	113mm	147mm	Black	25107	6" (152mm)	168mm	205mm	Black
25102	4" (102mm)	113mm	147mm	Clear	25108	6" (152mm)	168mm	205mm	Clear
25103	5" (127mm)	138mm	172mm	White	25109	8" (203mm)	216mm	260mm	White
25104	5" (127mm)	138mm	172mm	Black	25110	8" (203mm)	216mm	260mm	Black
25105	5" (127mm)	138mm	172mm	Clear	25111	8" (203mm)	216mm	260mm	Clear







Quick Twist Deck Plate (Deck Watertight Stainless Steel Inspection Hatch

> Made of AISI 316 stainless steel, 1/4 turn opening with winch handle. The cover remains attached to the winch handle on removal for ease of use.

Part No	Description
96060	120mm SS 316 Hatch





UV Resistant Inspection Hatch

Anti-Skid watertight surface, recessed hole with swivelling hollow flat.

Max external 315mm Ø

Passage 240mm

Recess 270mm Ø

Centre distance 290mm

Part No	Description
96061	240mm White UV Inspection Hatch
96062	240mm Black UV Inspection Hatch

Key Opening)

Polished 316 Stainless Steel.

Overall Diameter - 247mm

Cut Out - 222mm

Part No Description

96059 247mm Deck Plate

Henderson Locker Doors



TCL2 - Robust aluminium construction. Complete with locking lever. Nitrile rubber seal. 179mm inside diameter, 236mm outside diameter.

Part No: 73200



TCL4 - Available with clear or black cover. Approved for use in lifeboats, with reliable watertight seal. All plastic. 179mm inside diameter, 236mm outside diameter.

Black Cover: 73202 Clear Cover: 73203





Service Kits			
Part No To fit			
73204	TCL2 & TCL4		
73205	TCL3		




Very sturdy anti-skid surface; splash-proof lid closure with neoprene seal; flush mounting; they can be used as hatches for lockers, fishing containers or as boxroom hatches or bayonet front bulkheads; removable front for easy access. Ideal for installation on dashboard with nearby steering bench.

Part No	Description	External Dimensions	Cut - out Dimensions	Inside Dimensions
25145	Black Inspection Hatch (removable lid)	305 X 355	-	225 X 275
25146	Black Inspection Hatch (removable lid)	375 X 375	-	295 X 295
25147	Black Flush Inspection Hatch	373 X 375	300 X 300	285 X 285
25148	White Flush Inspection Hatch	373 X 375	300 X 300	285 X 285
96422	White Flush Inspection Hatch	520 X 465	445 X 390	430 X 375
25149	White Flush Inspection Hatch	600 X 250	530 X 180	515 X 165
25140	Hatch Lock Kit			



Hatch Lock Kit







Stainless steel AISI 316
Hatch Handle

Part No	Description
48052	Hatch Handle 55 x 77mm

Part No	Description	External Dimensions A x B (mm)	Cut - out Dimensions C x D (mm)
25150	White Plastic Waterproof Hatch	270 x 375	183 x 289
25151	White Plastic Waterproof Hatch	370 x 375	283 x 289
25152	White Plastic Waterproof Hatch	606 x 353	353 x 606
25153	Hatch Lock		









Nickel Plated Cylinder Lock

90° rotation of the back latch by turning a knurled ring nut under the flange (loose rotation). Press the side button to lock the latch. Insert the key to release the latch. The advantage is that the lock can always be used without a key. Supplied with 3 latches (16/20/25 mm) for different thickness. Made of nickel-plated brass (springs included).

Part No	Description
96302	Cylinder Lock Bore Ø 16mm thread length 16mm



Vinyl Foam Hatch Tape

Self-adhesive plasticised vinyl foam tape for bedding in windows, deck fittings and engine hatch covers.

Size	Black	Grey	White
19mm X 3mm X 3m	93094	93095	93096
25mm X 6mm X 3m	93097	93098	93099
25mm x 3mm x 3m	93100	-	-

Spring Hatch Stay 222mm




Part No Description

48054 Stainless steel spring useful

for holding locker lids, hatches and doors. Length: 222 mm.


Gas struts



Gas Strut 90° plate Ø 10mm-ball internal					
Part No	Description	Α	_	С	
		(mm)	(mm)	(mm)	
96260	90° gas strut plate	30	50	30	



Flat Fastening Plate Ø 10mm-ball				
Part No	Description	A (mm)	B (mm)	
96259	Flat Gas Strut Plate	60	50	



	_!		
	<u> </u>	Ø 60 Ø 50	(D)
H	37-97		B.

Compression Lift and turn flush latch

External Ø 60mm

Bulkhead hole Ø 50mm

Bulkhead thickness 8-30mm Stop stroke 37-97mm

Part No	
76350	50mm Non Locking
76352	50mm Locking

Compression Lift and turn flush latch

External Ø 90mm

Bulkhead hole Ø 76mm

Bulkhead thickness 10-34mm Stop stroke 39-100mm

Part No	
76358	76mm Non Locking
76360	76mm Locking

Spring Hatch Stay 350mm



Part No Description

96063 Made of stainless steel, fitted with spring hatch opening system, supports heavy loads, suitable for hatches and locker lids. 2 fixing plates size 47x47 mm



_					
Gas Strut with Ball Head Stainless Steel AISI 316					
Part No	Open mm	Closed mm	Stroke mm	Response kg	
96261	254	178	76	14	
96262	380	241	140	18	
96263	500	295	205	20	



Vetus Gas Strut AISI 316

There are many applications on board where the assistance of a gas strut will reduce the effort required.

Part No	Vetus	Force (N)	Stroke S (mm)	Length L (mm)	Length L + S (mm)
55667	GASSP25	180	74	180	254
55668	GASSP30	135	85	220	305
55669	GASSP38	135	140	240	380
55670	GASSP44	180	160	280	440
55666	GASSP51	270	205	305	510







Standard Flush Pull Latch Standard Flush Pull Latch

AISI 316

For thickness 7-19mm External Ø 75mm recess Ø 63mm

	Part No	
ıg	76354	63mm Non Locking
	76356	63mm Locking

AISI 316

Part No 76344

76346

For thickness 5-12mm

50mm Non Lockin


50mm Locking

External Ø 62mm

recess Ø 50mm

Hatches





Type PLANUS (All)

Stylish budget model



These hatches have a satin sheen anodised aluminium frame with a 75 mm corner radius and a 10 mm 'dark smoke' coloured acrylic lid. A friction hinge allows the hatches to remain open at any angle up to 180°. Type PLANUS is suitable for design category A, Area II.


Part No	Vetus	Туре	External Dimensions A x B (mm)	Cut - out Dimensions C x D (mm)
58500	PLA23L	Ventilation Hatch	280 x 280	230 x 230
58501	PLA30L	Ventilation Hatch	350 x 280	300 x 230
58502	PLA34L	Ventilation Hatch	390 x 260	340 x 210
58503	PLA32L	Deck Hatch	474 x 344	424 x 294
58504	PLA40L	Deck Hatch	424 x 424	374 x 374
58505	PLA45L	Escape Hatch	474 x 474	424 x 424
58506	PLA50L	Escape Hatch	521 x 521	471 x 471




Type ALTUS (All)

Best midrange hatch in the business









Part No	Vetus	Туре	External Dimensions A x B (mm)	Cut - out Dimensions C x D (mm)
58522	ALT6363SL	1 ESCAPE	701 x 701	627 x 627
58523	ALT5151SL	1 ESCAPE	581x 581	507 x 507
58524	ALT4747SL	1 ESCAPE	544 x 544	470 x 470
58525	ALTD520SL	2 ESCAPE	592 x 524	518 x 450
58526	ALTR520SL	3 ESCAPE	Ø 592	Ø 518
58527	ALT4242SL	1 DECK	495 x 495	421 x 421
58528	ALT5038SL	1 DECK	581 x 451	507 x 377
58529	ALT4633SL	1 DECK	531 x 401	457 x 327
58530	ALTR420SL	3 DECK	Ø 491	Ø 417
58531	ALT2626SL	1 VENTILATION	334 x 334	260 x 260
58532	ALTD420SL	2 VENTILATION	491 x 326	417 x 252

Model 1



Model 2



Model 3



Type LIBERO (All)

Still going strong



These hatches have a hand polished and anodised aluminium frame with a 32 or 55 mm corner radius and a 10 mm 'dark smoke' coloured acrylic lid. The escape and deck hatches come with adjusters allowing the lid to be held open at almost any angle up to 90°.





Type LIBERO is suitable for design category A, Area II.

Part No	Vetus	Туре	External Dimensions A x B (mm)	Cut - out Dimensions C x D (mm)	Cut - out Radius R (mm)
58533	LIB6232L	ESCAPE	680 x 680	620 x 620	32
58534	LIB6255L	ESCAPE	680 x 680	620 x 620	55
58535	LIB5032L	ESCAPE	560 x 560	500 x 500	32
58536	LIB5055L	ESCAPE	560 x 560	500 x 500	55
56879	LIB4155L	ESCAPE	470 x 470	410 x 410	55
56877	LIB3732L	DECK	560 x 430	500 x 370	32
56878	LIB3755L	DECK	510 x 380	500 x 370	55
56875	LIB3232L	DECK	400 x 255	450 x 320	32
56876	LIB3255L	DECK	510 x 380	450 x 320	55
56874	LIB3432L	VENTILATION	400 x 255	340 x 195	32
56873	LIB2032L	VENTILATION	260 x 260	200 x 200	32

Type MAGNUS (AI)

Heavy duty ocean hatch



MAGNUS hatches have a satin sheen anodised frame profile with a 10 mm thick 'dark smoke' coloured acrylic and are designed for ocean use, design category A, Area I. These hatches can be opened from the inside or outside through 180° with almost no obstructions in the opening. They have a ventilation position and can be locked completely watertight. The cut-out sizes of this type match the market-based dimensions.





Part No	Vetus	Туре	External Dimensions A x B (mm)	Cut - out Dimensions C x D (mm)
58540	MAG6363SL	Escape	679 x 679	627 x 627
58541	MAG5151SL	Escape	559 x 559	507 x 507
58542	MAG4747SL	Escape	522 x 522	470 x 470
58543	MAG4242SL	Deck	473 x 473	421 x 421
58544	MAG5038SL	Deck	559 x 429	507 x 377
58545	MAG4633SL	Deck	509 x 379	457 x 327
58546	MAG2626SL	Ventilation	312 x 312	260 x 260

VETUS handles

Specifications

- The hatch can be opened from the inside or outside
- Can be locked or secured with an air gap for permanent ventilation
- An internal locking mechanism prevents opening from the outside when the boat is unattended
- The low external profiles ensures that ropes cannot get caught under the handles.



Deck Hardware

Type FGH (All)








The FGH is specifically designed for new boats. The flush hatches are most suitable for new builds because the deck must be recessed to receive the hatch. After fitting, the hatches are completely recessed into the deck, leaving the deck smooth without visible lines. Type FGH is available in four sizes and is made of 12 mm thick 'dark smoke' acrylic with a polished and anodised aluminium frame. Type FGH is suitable for design category A, Area II.

Part No	Vetus	Туре	External Dimensions A x B (mm)	Cut - out Dimensions C x D (mm)
58514	FGH2626	Deck Hatch	330 x 330	260 x 260
58515	FGH4444	Deck Hatch	515 x 515	442 x 442
58516	FGH5151	Escape Hatch	580 x 580	507 x 507
58517	FGH6363	Escape Hatch	700 x 700	627 x 627





Portholes Area Al

Heavy duty portholes





These portholes are suitable for use in the hull side. The 10 mm 'smoke' coloured opening pane is set in satin anodisedaluminium frame. Black and white powder coated frames are optional. The clamp fixing ensures that no fasteners are visible from either inside or outside. The portholes can be held open in any position due to the friction type hinges. In closed position knobs ensure water resistance. The porthole can be fitted in a surface with a minimum thickness of 2 mm and a maximum thickness of 18 mm. As standard a mosquito screen is supplied. A fixed version of each opening porthole




Porthole					
Part No	Vetus	External dimensions A x B (mm)	Cut-out dimensions C x D (mm)	Cut-out radius R (mm)	Type mosquito screen
58550	PM111	244 X 146	220 X 122	61	HOR11
58551	PM121	294 X 172	270 X 148	74	HOR12
58552	PM131	344 X 198	320 X 174	87	HOR13
58553	PM141	362 X 146	338 X 122	61	HOR14
58554	PM151	390 X 220	366 X 196	98	HOR15
58555	PM161	399 X 199	375 X 175	87	HOR16

Type PZ (AI)











Porthole					
Part No	Vetus	External dimensions A x B (mm)	Cut-out dimensions C x D (mm)	Cut-out radius R (mm)	Type mosquito screen
58556	PZ611	301 X 164	277 X 140	54	HOR61
58557	PZ621	368 X 179	344 X 155	61	HOR62
58558	PZ631	622 X 197	598 X 173	61	HOR63
58559	PZ641	397 X 197	373 X 173	61	HOR64
58560	PZ651	399 X 190	375 X 166	54	HOR65
58561	PZ661	399 X 234	375 X 210	54	HOR66
58562	PZ671	451 X 274	427 X 250	54	HOR67

Type PW (AI)





Porthole				
Part No	Vetus	External dimensions A (mm) Ø	Cut-out dimensions B (mm) Ø	Type mosquito screen
58563	PW201	198	174	HOR2013
58564	PW211	220	196	HOR2113
58565	PW221	260	236	HOR2213



Portholes Area Alli


Medium duty portholes

These portholes are suitable for use in the coachroof side. They come with a 10 mm 'smoke' coloured -unframed- opening pane. The clamp type installation ensures that no fasteners are visible from either inside or outside. The portholes can be held open in any position due to the friction type hinges. In the closed position 2 knobs ensure water resistance. They are supplied as standard with a mosquito screen. The porthole can be fitted in a surface with a minimum thickness of 2 mm and a maximum thickness of 18 mm.












Porthole					
Part No	Vetus	External dimensions A x B (mm)	Cut-out dimensions C x D (mm)	Cut-out radius R (mm)	Type mosquito screen
58566	PM113	244 X 146	220 X 122	61	HOR11
58567	PM123	294 X 172	270 X 148	74	HOR12
58569	PM143	362 X 146	338 X 122	61	HOR14
58570	PM153	390 X 200	366 X 196	98	HOR15

Type PZ (AIII)












Porthole					
Part No	Vetus	External dimensions A x B (mm)	Cut-out dimensions C x D (mm)	Cut-out radius R (mm)	Type mosquito screen
58572	PZ613	301 X 164	277 X 140	54	HOR61
58573	PZ623	368 X 179	344 X 155	61	HOR62
58574	PZ633	622 X 197	598 X 173	61	HOR63
58575	PZ643	397 X 197	373 X 173	61	HOR64
58576	PZ653	399 X 190	375 X 166	54	HOR65
58577	PZ663	399 X 234	375 X 210	54	HOR66
58578	PZ673	451 X 274	427 X 250	54	HOR67

Type PW (AIII)








Type PX (AIII)

Porthole				
Part No	Vetus	External dimensions A (mm) Ø	Cut-out dimensions B (mm) Ø	Type mosquito screen
58582	PX45	441 X 179	417 X 155	HOR45
58583	PX46	492 X 196	468 X 172	HOR46
58584	PX47	544 X 217	520 X 193	HOR47
58585	PXF	480 X 239	456 X 215	HORPXF













Porthole - PWS = Stainless steel portholes (Al and AIII)					
Part No	Vetus	External dimensions A (mm) Ø	Cut-out dimensions B (mm) Ø	Type mosquito screen	
58586	PWS31A2	220	198	HOR31S	
58587	PWS31A1	220	198	HOR31S	
58588	PWS32A1	260	238	HOR32S	

Type PMS















Porthole				
Part No	Vetus	External dimensions A (mm) Ø	Cut-out dimensions B (mm) Ø	Type mosquito screen
58590	PMS23A2	346 X 199	322 X 177	HOR23S
58591	PMS23A1	346 X 199	322 X 177	HOR23S
58592	PMS24A2	390 X 199	366 X 177	HOR24S
58593	PMS24A1	390 X 199	366 X 177	HOR24S



Recommended screw size for VETUS portholes

Screws available for PWS and PMS portholes in packs of 50.



Porthole			
Part No	Vetus	Panel Thickness	Screw
58594	SET0092	3 - 5MM	M5 X 12
58595	SET0093	5 - 9MM	M5 X 16
58596	SET0094	9 -14MM	M5 X 20
58597	SET0095	14 - 18MM	M5 X 25

Portholes type PQ

CE marking All

VETUS PQ portholes are made of stainless steel and include a counter flange.

They have an 8 mm thick acrylic 'smoke' coloured pane and come with a mosquito screen.









Porthole				
Part No	Vetus	External dimensions A (mm) Ø	Cut-out dimensions B (mm) Ø	Type mosquito screen
58598	PQ51	158	126	HORPQ51
58599	PQ52	184	151	HORPQ52
58600	PQ53	210	176	HORPQ53








Stainless Steel Handrails



Part No	Tube Diameter	Length
23037	1" (25mm)	12" (305mm)
23038	1" (25mm)	24" (610mm)



Made of mirror-polished AISI 316 stainless steel. 19x25-mm section, screw external mounting.



Grab Handles

Polished Stainless Steel 25mm diameter. Grab Rails for under deck fastening with an M6 stud or bolt. Stainless Steel Adaptor Plates can be purchased to convert these Grab Rails to above deck fastening (2 needed per rail).

Part No	Description
76096	SS Grab Rail Adaptor Plate
76102	9" SS Grab Rail
76098	12" SS Grab Rail
76100	18" SS Grab Rail



Grab Handle

Bolted underneath via fixing plates.

Made of mirror-polished AISI316 stainless steel, elliptical section.

Part No	Description	
96462	Handrail SS 610mm	
96461	Handrail Fixing Kit (2 plates + 2 screws)	

Rail Mounts



Wire Rail Mount Life Buoy Holder

Rail Mount Ring Buoy Holder Kit with Stainless Steel wireform holder with nylon strap. This Rail Mount accessory is designed for easy attachment to tube 22mm - 25mm dia, without having to drill holes in your boat.

Part No	Description
76068	Wire Rail Mount Life Buoy Holder



Rail Mount Nylon Rope Hook Kit

This Rail Mount Rope Hook Kit is very useful for keeping ropes/hooks/life jackets tidy and handy.

This Rail Mount accessory is designed for easy attachment to tube 22mm - 25mm dia, without having to drill holes in your boat.

Part No	Description	
76082	Rail Mount Nylon Rope Hook Kit	

Deck Hardware



Rail Mount Bracket

Complete Rail Mount Bracket with SS Fixing Screws. This Rail Mount accessory is designed for easy attachment to tube 22mm - 25mm dia, without having to drill holes in your boat.

Part No	Description
76084	Rail Mount Bracket

Flags & Flag Poles



Part No	Description
76374	Teak Flag Pole 600mm x 25mm
76376	Teak Flag Pole 750mm x 25mm



Stainless steel terminal ball, stainless steel ends and eyelets, suitable for flags.

Part No	Description	
96413	Flagstaff SS 900 X 25mm	
96557	Flagstaff SS 1020 X 25mm	
96331	Flagstaff SS 1200 X 25mm	



Rail Mount Nylon Cleat

This Rail Mount accessory is designed for easy attachment to tube 22mm - 25mm dia, without having to drill holes in your boat. 114mm long, black nylon cleat set

Part No	Description
76086	Rail Mount Cleat

Red Ensign Flags



Made of polyester, indelible colours.

Part No	Description
96270	UK Red Ensign 30cm x 45cm
96271	UK Red Ensign 40cm x 60cm
96272	UK Red Ensign 50cm x 75cm





Flagstaff Base

Made of mirror polished AISI 316 stainless steel; clip-on base fitting.

Base mm		60x45
Depth mm		40
Part No Descri		otion
96412	Flush F	lagstaff Base



Rail Mount Nylon Fairlead

This Rail Mount accessory is designed for easy attachment to tube 22mm - 25mm dia, without having to drill holes in your boat. Kit with 17mm Fairlead Eye

Part No	Description
76088	Rail Mount Nylon Fairlead

Stanchions



Tapered Stanchions Heavy Duty 304 Tube Cast 316 Stainless Steel Tops.

Part No	Description
76138	Stanchion 520mm
76150	Stanchion 620mm



Stanchion Base

Cast 316 Stainless Steel To fit 25mm Diameter Stanchion.

Part No	Description
76348	Stanchion Base 90 Degree
76347	Stanchion Base 84 Degree



Stainless Steel (316) Stanchion Mounting Eyes

Part No	Description
23048	Clip for 1" Stanchion (25mm)

23049 Backing Plate for Clip





Deck Hardware



Part No


20272

20285

Part No	Shaft Dia
20270	3/8" (10mm)
20280	1/2" (13mm)







Part No	To fit shaft		
20278	3/8" (10mm)		



Captive Rowlocks (Single)

Part No	Jaw Size
20271	2" (51mm)





A strong lightweight corrosion free white Rowlock for rowing boats up to 3.5m (11ft). Also available in black, for use with both top mount(R5050) and side mount (R5040)

Part No	Colour
25000	White (R5030)
25010	Black (R5032)



To fit shaft

3/8" (10mm)

1/2" (13mm)

RWO Rowlock Socket (Single)

Top mount white bracket for use with R5030 rowlock also available in black

Part No	Colour	
25020	White (R5050)	
25030	Black (R5052)	



RWO Rowlock BSide mount white bracket for use with R5030 rowlock also available in black racket (Single)

Part No	Colour
25040	White
	(R5040)



Foldable Chromed Brass Rowlock 12 x 50mm (Single)

Foldable captive rowlock, suitable for all types of boats, convenient, trouble-proof.

Part No 96120



Seagrade Lahna Oars - Made in Finland

A very high-class oar laminated from clean timber for demanding conditions such as sea. Beautifullyshaped handle and blade reinforced with a wedge. Finished with water-proof special varnish. The oar sleeve is already fitted on this oar. (Sold Each)

Part No	Length	Blade Width	Blade Length	Shaft Diameter Ø
90430	180cm 5ft 11"	112mm	540mm	44mm
90435	195cm 6ft 5"	112mm	540mm	44mm
90440	210cm 6ft 10"	112mm	580mm	44mm
90445	225cm 7ft 4"	112mm	580mm	44mm
90450	240cm 8ft	115mm	600mm	44mm
90460	270cm 9ft	115mm	600mm	44mm



Chromed Brass Rowlock Blind Socket (Single)

Includes blind socket, specially suited for plastic boats with interspace; the rowlock has a bayonet fitting; this product is a perfect alternative to most plastic rowlocks that break easily; the socket has a wide area for covering any pre-existing plastic socket holes.

Stem Ø mm 12

A mm 42

B mm 52

Part No

96121

Gull 'Custom' Paddles (Sold Singly)

Light weight paddles with an excellent finish. Constructed from Tasman Fir with Beech palm grip.

Part No	Size
90400	3' 6" (1.07m)
90405	4' (1.22m)
90410	4' 6" (1.37m)
90415	5' (1.52m)



Aluminium 2 Part Oars Sold complete as a pair.

Part No	Size
90498	1.64M Long Oars
90499	1.34M Short Oars

Ladders & Steps



Folding Mast Step SS 304

Stamped 304 Stainless Steel, Mast

Length 108mm - Base Size 85mm x 60mm

Part No Description

76148 Folding Mast Step SS 304



Folding Step


Cast 316 Stainless Steel folding step, which only projects 24mm above the surface when folded. Folding Step - base size - 111mm x 47mm

Part No Description

76214 Folding Mast Step SS 316







3 Step Emergency Ladder + Holder

Watertight thermopolymer housing. Ladder with nylon braid structure and highly resistant thermopolymer steps. To be installed above the waterline. Very simple to use: in a man-overboard situation, the crew member in the water pulls the locking cap ring to let the ladder out of its housing. Sold in display package. Length 1100mm Width 135mm

Part No	Description
96467	3 Step Emergency Ladder + Housing
96469	3 Step Emergency Ladder + Housing (Screw Mounted)




Inflatable Stair Fenders								
Part No	Description	Width	Diameter	Height				
34376	Stair Fender White 2 Stairs	25CM	12CM	55CM				
34379	Stair Fender Blue 2 Stairs	25CM	12CM	55CM				
34377	Stair Fender White 3 Stairs	25CM	12CM	75CM				
34378	Stair Fender Blue 3 Stairs	25CM	12CM	75CM				



Made of mirror polished stainless steel; oval steps with white plastic coating, fitted with fall safe front lock. Ladder folds away inside itself for maximum convenience. AISI 316.

Part No	Steps	Length mm - Open	Length mm - Closed	Max Width (mm)	Tube Ø
96468	3	880	373	300	19/25/32
96411	4	1155	405	300	19/25/32/38



Folding Ladders 316SS

Folding ladder, transom mounted. Stainless steel (AISI 316). Available with 3 or 4 steps. With synthetic black grips.

Part No	Vetus	Steps		L (Retracted)		Tube Ø	Weight (Kg)
58359	SLF3	3	600	315	228	22	1.7
58360	SLF4	4	875	450	228	22	2

CABLES (OCEANFLEX® TINNED COPPER CABLES)

Single Core Tinned 1.0mm², 1.5mm², 2.5mm², 4mm², 6mm² & 10mm²



ROSS SECTION



OCEANFLEX® TINNED COPPER SINGLE CORE CABLES

High temperature, thin wall, low voltage, wiring cables, suitable for use in automotive, marine, and other harsh environments. The tinned copper conductors make this cable more resistant to corrosion.

SPECIFICATIONS

- Cores manufactured to ISO 6722-1:2011 (class B) 105°C.
- Tinned Copper Conductors, PVC Insulated.
- Suitable for use at temperatures from -40°C to 105°C with excursions up to 120°C.
- Twins and multicores PVC sheathed at 70°C.
- Suitable for 12v and 24v systems (maximum 60v).
- Good resistance to petrol, diesel, lubricating oils and diluted acid.
- Very good resistance to moisture.
- PVC insulation saves weight and offers good resistance to abrasion and cut through.
- Cables are printed with the specification on the insulation.

Description		Black Tinned	Conductor Cross Sec-	oss Sec- Specification Overall Current	Overall	Current	Maximum Loading (Watts)		Resistance Per Metre at
	Part No	Part No	tion (mm ²)		12 Volts	24 Volts	20°C (Ohms)		
1mm Single Core	70900	70906	1.0	32/0.20	2.1	16.5	198	396	0.0191
1.5mm Single Core	70901	70907	1.5	21/0.30	2.4	21.0	252	504	0.0130
2.5mm Single Core	70902	70908	2.5	35/0.30	3.0	29.0	348	696	0.00782
4mm Single Core	70903	70909	4.0	56/0.30	3.7	39.0	468	936	0.00485
6mm Single Core	70904	70910	6.0	84/0.30	4.3	50.0	600	1200	0.00323
10mm Single Core	70905	70911	10.0	80/0.40	6.0	70.0	840	1680	0.00185

Part No	Colour	Size mm ²	Part No	Colour	Size mm ²	Part No	Colour	Size mm ²
70970	Blue	1.5	70981	Brown	2.5	70995	Green	6.0
70971	Yellow	1.5	70982	Blue	2.5	70996	Yellow	6.0
70972	Green	1.5	70983	Yellow	2.5	70998	Green	10.0
70973	Brown	1.5	70990	Green	4.0	70999	Yellow	10.0
70980	Green	2.5	70991	Brown	4.0			
			70992	Yellow	4.0			

CABLES (OCEANFLEX® TINNED COPPER CABLES)

OCEANFLEX® 2 CORE CABLES (ROUND & FLAT TWINS)

High temperature, thin wall, low voltage, wiring cables, suitable for use in automotive, marine, and other harsh environments. The tinned copper conductors make this cable more resistant to corrosion.

SPECIFICATIONS

- Cores manufactured to ISO 6722-1:2011 (class B) 105°C.
- Tinned Copper Conductors, PVC Insulated.
- Suitable for use at temperatures from -40°C to 105°C with excursions up to 120°C.
- Twins and multicores PVC sheathed at 70°C.
- Suitable for 12v and 24v systems (maximum 60v).
- Good resistance to petrol, diesel, lubricating oils and diluted acid.
- Very good resistance to moisture.
- PVC insulation saves weight and offers good resistance to abrasion and cut through.
- Cables are printed with the specification on the insulation.

Two Core Round Tinned 1.5mm² & 2.5mm²



Description	Part No	Conductor Specification (mm)	Conductor Cross Section (mm²)	Maximum Overall Diameter (mm)	Nominal Current Rating (Amps)	Sheath Colour	Core Colours
2 Core Round 1.5mm	70930	2 x 21/0.30	2 x 1.5	6.4	21.0	Black	Black,
2 Core Round 2.5mm	70932	2 x 35/0.30	2 x 2.5	6.7	29.0	Black	Red

Two Core Flat Tinned 1.5mm² & 2.5mm²



Description	Part No	Conductor Specification (mm)	Conductor Cross Section (mm²)	Maximum Overall Diameter (mm)	Nominal Current Rating (Amps)	Sheath Colour	Core Colours
2 Core Flat 1.5mm - White	70919	2 x 21/0.30	2 x 1.5	3.5 x 5.8	21.0	White	
2 Core Flat 1.5mm - Black	70920	2 x 21/0.30	2 x 1.5	3.5 x 5.8	21.0	Black	Black, Red
2 Core Flat 2.5mm - Black	70922	2 x 35/0.30	2 x 2.5	3.9 x 6.7	29.0	Black	1100

OCEANFLEX® 3, 5 & 7 CORE CABLES

High temperature, thin wall, low voltage, wiring cables, suitable for use in automotive, marine, and other harsh environments. The tinned copper conductors make this cable more resistant to corrosion.

SPECIFICATIONS


- Cores manufactured to ISO 6722-1:2011 (class B) 105°C.
- Tinned Copper Conductors, PVC Insulated.
- Suitable for use at temperatures from -40°C to 105°C with excursions up to 120°C.
- Twins and multicores PVC sheathed at 70°C.
- Suitable for 12v and 24v systems (maximum 60v).
- Good resistance to petrol, diesel, lubricating oils and diluted acid.
- Very good resistance to moisture.
- PVC insulation saves weight and offers good resistance to abrasion and cut through.
- Cables are printed with the specification on the insulation.

Three Core Round Tinned 1.5mm² & 2.5mm²




Description	Part No	Conductor Specification (mm)	Conductor Cross Section (mm²)	Maximum Overall Diameter (mm)	Nominal Current Rating (Amps)	Sheath Colour	Core Colours
3 Core 1.5mm - White	70959	3 x 21/0.30	3 x 1.5	6.1	21.0	White	Black,
3 Core 1.5mm - Black	70960	3 x 21/0.30	3 x 1.5	6.1	21.0	Black	Green,
3 Core 2.5mm - Black	70961	3 x 35/0.30	3 x 2.5	7.4	29.0	Black	Red

Five Core Round Tinned 1.5mm²



Description	Part No	Conductor Specification (mm)	Conductor Cross Section (mm²)	Maximum Overall Diameter	Sheath Colour	Core Colours
5 Core 1.5mm	70963	5 x 21/0.30	5 x 1.5	8	Black	Black, Green, Red,

Seven Core Round Tinned 1.5mm²



Arctic Blue Cable



Flexible annealed copper conductor. PVC insulated. PVC sheathed flexible cords. Sold by the metre. Maximum length 100m.


Description	Part No	Conductor Cross Section (mm²)	Maximum Overall Diameter (mm)	Voltage Rating	Sheath Colour	Core Colours
Arctic Cable 3 Core 1.5mm	72168	1.5mm²	9.2mm	300V 500V	Blue	Blue, Brown,
Arctic Cable 3 Core 2.5mm	72170	2.5mm²	9.2mm	300V 500V	Blue	and Green/
Arctic Cable 3 Core 4mm	72171	4mm²	9.2mm	300V 500V	Blue	Yellow

OCEANFLEX® PVC BATTERY / EXTRA FLEXIBLE CABLES

Single insulated extra flexible battery cables designed for use in tough working environments. SPECIFICATIONS

- Cores manufactured to ISO 6722-1:2011 (class B) 105°C.
- Tinned Copper Conductors, PVC Insulated.
- Suitable for use at temperatures from -40°C to 105°C with excursions up to 120°C.
- Twins and multicores PVC sheathed at 70°C.
- Suitable for 12v and 24v systems (maximum 60v).
- Good resistance to petrol, diesel, lubricating oils and diluted acid.
- Very good resistance to moisture.
- PVC insulation saves weight and offers good resistance to abrasion and cut through.

Flexible Tinned Battery Cables 16mm², 25mm², 35mm², 50mm², 70mm² & 95mm²



Description	Red Part No	Black Part No	Conductor Specification (mm)	Conductor Cross Section (mm²)	Maximum Overall Diameter (mm)	Nominal Current Rating (Amps)	Resistence Per Metre at 20°C(Ohms)
16mm Battery Cable	70940	70946	203/0.30	16	8.3	110.0	0.001240
25mm Battery Cable	70941	70947	322/0.30	25	10.1	170.0	0.000794
35mm Battery Cable	70942	70948	455/0.30	35	11.8	240.0	0.000565
50mm Battery Cable	70943	70949	637/0.30	50	13.3	345.0	0.000393
70mm Battery Cable	70944	70950	912/0.30	70	15.5	485.0	0.000277
95mm Battery Cable	70945	70951	684/0.40	95	17.9	500.0	0.000210

Copper Tube Terminals (Lugs)



Suitable for o	crimping o	or solderi	ng. Mate	rial – tin	ned copper	

Suitable for	6mm Ring	8mm Ring	10mm Ring	12mm Ring	Suitable For Cables	
Cables	Part No	Part No	Part No	Part No	(mm²)	
6mm²	70890	70880	N/A	-	6mm²	
10mm²	70891	70952	70881	70896	10mm²	
16mm²	70892	70953	70882	70897	16mm²	
25mm²	70893	70954	70883	70898	25mm²	
35mm²	70894	70955	70884	70899	35mm²	
50mm ²	70895	70956	70885	70888	40-50mm ²	
70mm²	N/A	70957	70886	70889	60-70mm ²	
95mm²	N/A	70958	70887	-	95mm²	

Butt Splices





Description	Cable Entry C (mm)	Length L (mm)	Part No
6mm Cable Butt Splice	4.0	20	70790
10mm Cable Butt Splice	4.5	23	70791
16mm Cable Butt Splice	5.5	30	70792
25mm Cable Butt Splice	6.7	35	70793
35mm Cable Butt Splice	8.6	40	70794
40-50mm Cable Butt Splice	9.5	40	70795
60-70mm Cable Butt Splice	12	45	70796

2 Way 0.2-4mm² Compact Splicing Connector

Includes an operating lever. Maximum continuous service temperature: 85°C. Nominal voltage 450v. Nominal current 32 A.

Part No Description

> 72160 2-Way 0.2-4mm² Compact Splicing Connector 13.1 x 8.3 x 18.6mm

3 Way 0.2-4mm² Compact Splicing Connector

Includes an operating lever. Maximum continuous service temperature: 85°C. Nominal voltage 450v. Nominal current 32 A.

Part No Description

72161 3-Way 0.2-4mm² Compact Splicing Connector 18.7 x 8.3 x 18.6mm

Easier, faster, safer: These three attributes characterize WAGO's 221 Series Splicing Connectors. WAGO's 221 Series now offers a model for conductors up to 6 mm2 (10 AWG)

Part No Description

72162 2 Way 41amp Compact 2 Port Lever Connector for 6mm² wire

Easier, faster, safer: These three attributes characterize WAGO's 221 Series Splicing Connectors. WAGO's 221 Series now offers a model for conductors up to 6 mm2 (10 AWG)

Part No Description

3 Way 41amp Compact 2 Port Lever Connector for 6mm² wire 72163

A compact splicing connector with cage clamp connection. 5-conductor terminal block. Comes with operating lever. Maximum continuous service temperature 85°C. Nominal current 32 A.

Part No Description

72164 5-Way 32amp Compact 2 Port Lever Connector 0.08-4mm²











HEAT SHRINK PRE-INSULATED TERMINALS (EASY ENTRY)

Heat shrink pre-insulated terminals provide a long lasting environmental seal.

Pack sizes: 10 or 100.



RED TERMINALS

Suitable for cables 0.5mm² - 1.5mm² 16/0.20mm - 21/0.30mm

Description	Pack of 10	Pack of 100
	Part No	Part No
Red 4.3mm Ring Terminal	70805	70806
Red 5.3mm Ring Terminal	70807	70808
Red 6.4mm Ring Terminal	70809	70810
Red Butt Connector	70811	70812
Red 6.3mm Female Spade	69500	69501
Red 6.3mm Male Spade	69506	69507
Red 4.0mm Male Bullet	69512	69513
Red 4.0mm Female Bullet	69518	69519

BLUE TERMINALS

Suitable for cables 1.5mm² - 2.5mm² 21/0.30mm - 35/0.30mm

Description	Pack Of 10	Pack Of 100
	Part No	Part No
Blue 4.3mm Ring Terminal	70813	70814
Blue 5.3mm Ring Terminal	70815	70816
Blue 6.4mm Ring Terminal	70817	70818
Blue Butt Connector	70819	70820
Blue 6.3mm Female Spade	69502	69503
Blue 6.3mm Male Spade	69508	69509
Blue 5.0mm Male Bullet	69514	69515
Blue 5.0mm Female Bullet	69520	69521

HEAT SHRINK PRE-INSULATED TERMINALS (EASY ENTRY)

Heat shrink pre-insulated terminals provide a long lasting environmental Pack sizes: 10 or 100. seal.



5.3mm Ring Terminal



6.4mm Ring Terminal



8.4mm Ring Terminal



Butt Connector



6.3mm Female Spade



6.3mm Male Spade



5.0mm Male Bullet




5.0mm Female Bullet


YELLOW TERMINALS

Suitable for cables 3.0mm² - 6.0mm² 44/0.30mm - 84/0.30mm


Description	Pack Of 10	Pack Of 100
	Part No	Part No
Yellow 5.3mm Ring Terminal	70821	70822
Yellow 6.3mm Ring Terminal	70823	70824
Yellow 8.4mm Ring Terminal	70825	70826
Yellow Butt Connector	70827	70828
Yellow 6.3mm Female Spade	69504	69505
Yellow 6.3mm Male Spade	69510	69511
Yellow 5.0mm Male Bullet	69516	69517
Yellow 5.0mm Female Bullet	69522	69523



Red Terminals				
Suitable for Cables 0.5mm² - 1.5mm² 16/0.20mm - 21/0.30mm				
Description	Part No			
Red 6.4mm Female Covered Terminal	70600			
Red 6.4mm Ring Terminal	70624			
Red 10mm Ring Terminal	70637			
Red 6.3mm Piggy Back Terminal	70620			



Blue Terminals					
Suitable for Cables 1.5mm² - 2.5mm² 21/0.30mm - 35/0.30mm					
Description	Part No				
Blue 6.4mm Female Covered Terminal	70602				
Blue 6.4mm Male Spade Terminal	70608				
Blue 6.4mm Ring Terminal	70630				
Blue 10mm Ring Terminal	70634				
Blue 6.3mm Piggy Back Terminal	70621				



	Suitable for Cables 4.0mm² - 6.0mm² 56/0.30mm - 84/0.30mm				
	Description	Part No			
	Yellow 6.4mm Female Covered Terminal	70604			
	Yellow 6.4mm Ring Terminal	70632			
	Yellow 10mm Ring Terminal	70636			
	Yellow 13mm Ring Terminal	70635			
	Yellow 6.3mm Piggy Back Terminal	70622			

Yellow Terminals





Commoning Posts

Power distribution posts for distributing power around a vehicle or boat.

Material - glass fibre reinforced nylon base, stainless steel stud, nickel plated brass nut

Part No	Rating (Amps)	Polarity	Base Colour	Stud Size (mm)
70870	150	- VE	Red	8
70871	150	+ VE	Black	8

VTE 8 Point Power Distribution Posts

Used to connect several wires/cables to a central location. These devices can be used to deliver power to a control panel, feed multiple low-current devices, or when grounding wires/cables.

Material: Glass-filled nylon base, stainless steel post, nickelplated copper alloy conductive disc and tin-plated copper alloy conductive nuts.

Part No	Description	Stud Size	Max Rating (Amps) @12V	Polarity	Colour
70865	Red 8 Point Power Post	3/8" (9.5mm)	160	+ VE	Red
70866	Black 8 Point Power Post	3/8" (9.5mm)	160	- VE	Black
70867 Power Post Insulating Polypropylene Disc					

Crocodile Clips



Part	Description	Continuous	Length
No		Rating	(mm)
70797	75mm Crocodile Clip	25	75

Waterproof Plugs & Sockets



Waterproof In-Line Socket

2 pin Technical:

Poles 2 Max A 10

Cable section mm2 0,25-1,5 Cable Ø mm 1x(3-8) / 2x(1,9-2,5)

external mm Ø14 x 90

2/3/4pin Technical:

Poles 2/3/4

Max A 17,5


Cable section mm2 0,5 - 43x(2-4) / 4x(2-4) Cable Ø mm

external mm Ø 23 x 113

Part No	Description
70681	2 pin IP68 Waterproof In Line Connector
70682	2/3/4 pin IP68 Waterproof In Line Connector

Bulgin Waterproof Connectors

A range of quality plugs and sockets, manufactured in glass filled nylon to military specification and waterproofed to IP68 thus ensuring trouble-free cable connections on deck. Blanking cap supplied which doubles an assembly tool. Suitable for AC/DC. Cable Diameter 5-9mm.









Cable	Mounted	Plug
-------	---------	------

Bulkhead Mount Socket

Flange Mount Socket

Cable Mount In-line Socket

`	•	90		
Part No	Description	No of Pins	Rating	Terminations
71754	Cable mount plug	2	10A/250V AC/DC	Screw
71755	Cable mount plug	3	10A/250V AC/DC	Screw
71780	Cable mount plug	6	3A/250V AC/DC	Screw
71762	Flange mount socket	2	10A/250V AC/DC	Screw
71763	Flange mount socket	3	10A/250V AC/DC	Screw
71781	Flange mount socket	6	3A/250V AC/DC	Screw
71778	Bulkhead mount socket	2	10A/250V AC/DC	Screw
71779	Bulkhead mount socket	3	10A/250V AC/DC	Screw
71784	Bulkhead mount socket	6	3A/250V AC/DC	Screw
71785	Mini Bulgin Plug & Cap	2		
71786	Mini Bulgin Inline Socket & Cap	2		
71981	Inline cable mount socket	2	10A/250V AC/DC	Screw
71980	Inline cable mount socket	3	10A/250V AC/DC	Screw
71986	7 Pin plug	7	3A/250V AC/DC	Screw

Chrome Plated Traditional Plug & Sockets



Manufactured in high quality chrome plated brass with solid non-reversible pins and sprung sockets. Complete with captive screw-on cap and rubber mounting gasket.

Rating	2 Pin	3 Pin
2/3 Amp	70700	70701
5/7 Amp	70702	70703



F-2241 6 Way Screw **Terminal** 1 x 5mm hole + 6 x 4mm holes. Current rating: 100A

Length: 75mm Height: 20mm

Part No: 71633



F-2242 12 Way Screw **Terminal** 1 x 5mm hole + 12 x 4mm holes. Current rating: 100A

Length: 116mm Height: 20mm

Part No: 71634



F-2243 6 Way For Crimp / Solder Terminals

For cables terminating in crimp/solder ring terminals. c/w 4mm retaining screws, 6 x 4.3mm ring terminals (cable entry: 1.5-3mm.), and 1 x 6.4mm ring terminal (cable entry: 3-6mm.) Current Rating: 100amps.

Length: 95mm Width: 17mm

Part No: 71635

Electrical



Part No	Description	No. of Studs	Rating (Amps)	Overall Dimensions H x W x D (mm)	
69650	4 way 100amp Stud Busbar	4 x 5mm	100	36 x 104 x 23	
69651	4 way 150amp Stud Busbar	4 x 6mm	150	36 x 150 x 30	
69652	4 way 250amp Stud Busbar	4 x 8mm	250	42 x 200 x 38	
69653	6 way 150amp Stud Busbar	6 x 6mm	150	36 x 230 x 32	
Busbars, available in a variety of amp ratings.					

Material - tin plated copper bar, stainless steel studs and screws.



Part No	Description	No. of Studs	No. of Screws	Rating (Amps)	Overall Dimensions H x W x D (mm)
69654	5 way 100amp Busbar	2 x 4mm	5 x 4mm	100	36 x 104 x 23
69655	10 way 150amp Busbar	2 x 6mm	10 x 4mm	150	36 x 150 x 30
69656	12 way 250amp Busbar	2 x 8mm	12 x 4mm	250	42 x 200 x 38
69657	20 way 150amp Busbar	2 x 8mm	20 x 4mm	150	36 x 230 x 32



Part No	Description	Overall Dimensions H x W x D (mm)
69658	Busbar Cover Fits 69650 + 69654	38 x 143 x 54
69659	Busbar Cover Fits 69651 + 69655	40 x 190 x 64
69660	Busbar Cover Fits 69652 + 69656	45 x 235 x 70
69661	Busbar Cover Fits 69653 + 69657	40 x 270 x 64

		_		-
Ch	-	0	loc	\mathbf{L}
				M 🤝



Part No	Description	Current Rating (Amps)	To Fit Cables (mm²)
70697	2.5mm Flexible Cable Connector Strip	3	Up To 2.5
70698	4mm Flexible Cable Connector Strip	5	Up To 4.0
70699	10mm Flexible Cable Connector Strip	15	Up To 10.0

Cable Sleeving Flexible Ducting Conduit Available in 25m, 30m & 100m rolls



Halogen-free nylon convoluted sleeving suitable for bundling of wires and protection against abrasion. Continuous operating temperature - 40 degrees to 105 degrees with short excursions up to 150 degrees Celsius. Self extinguishing. Resistant to petrol, oil and water. Flammability to UL94.

Description	Internal Diameter (mm)	External Diameter (mm)	Part No	Part No
Description			Roll of 25M	Roll of 100M
6.6mm Black Cable Conduit	6.6mm	10.20mm	70550	70551
10.0mm Black Cable Conduit	10.00mm	13.25mm	-	70556
11.0mm Black Cable Conduit	11.0mm	16.10mm	70552	70553
14.2mm Black Cable Conduit	14.2mm	18.5mm	-	70557
16.9mm Black Cable Conduit	16.1mm	21.35	-	70558
20.1mm Black Cable Conduit	20.1mm	24.50mm	70554	70555
32mm Black Cable Conduit	32mm		70545 - 30M	-
51mm Black Cable Conduit	51mm		70559 - 30M	-

HEAT SHRINK SLEEVING

Halogen-free flexible polyolefin heat shrink sleeving. Suitable for a wide range of applications which include marking, colour coding, insulating, bundling of wires and protection against abrasion. Continuous operating temperature -55°C to 125°C. Flame retardant to UL224. Shrink temperature 100°C. Shrink ratio 2 to 1. Supplied in a variety of sizes, lengths and colours.



Part No	Internal Diameter Before Heating (mm)	Internal Di- ameter After Heating (mm)	Wall Thick- ness After Heating (mm)	Colour	Lengths Available (Metres)
70850	2.4	1.2	0.5	Black	5
70851	3.2	1.6	0.5	Black	5
70852	3.2	1.6	0.5	Red	5
70853	4.8	2.4	0.5	Black	5
70854	4.8	2.4	0.5	Red	5
70855	6.4	3.2	0.65	Black	5
70856	6.4	3.2	0.65	Red	5
70857	9.5	4.8	0.65	Black	5
70858	9.5	4.8	0.65	Red	5
70859	12.7	6.4	0.75	Black	5
70860	12.7	6.4	0.75	Red	5
70861	19.1	9.5	0.75	Black	5
70862	19.1	9.5	0.75	Red	5
70863	25.4	12.7	0.9	Black	5
70864	38.1	19.0	1.0	Black	5



Part No	Description
70651	Heat Shrink Black 6.4mm X 150mm (15 Pack)
70652	Heat Shrink Red 6.4mm X 150mm (15 Pack)
70653	Heat Shrink Black 12.7mm X 150mm (10 Pack)
70654	Heat Shrink Red 12.7mm X 150mm (10 Pack)
70655	Heat Shrink Black 19.1mm X 150mm (7 Pack)
70656	Heat Shrink Red 19.1mm X 150mm (7 Pack)



Blue Sea 7601 M-Series Automatic Charging Relay 12/24V DC 65A.

12V / 24V DC / 65A Continuous 115A Intermittent.

Part No

69908



Blue Sea 7610 Automatic Charging Relay 12/24V DC 120A.

Automatically combines batteries during charging, isolates batteries when discharging and when starting engines Features Protects sensitive electronics by temporary isolation of house loads from engine circuit during engine cranking Designed for 12 or 24 volt systems 12/24 volt auto ranging voltage input Hermetically sealed contacts/vaporproof Ignition protected—safe for installation aboard gasoline powered boats Supports high-output alternators up to 120 Amperes **Dual sensing**

Part No

69909



Voltage Sensitive Relay 125amp (VSR)

Nominal Voltage | DC 12V. Combine / Open Voltage | DC 13.3V / 12.8V. Continuous Current Rating | 125A. Intermittent Current Rating | 140A. Power Consumption | 10mA (Standby) / 330mA (Engage) / 0mA (Storage Mode).IP67 / ISO8846 (SAE J1171) Ignition Protected.

Part No

69910

Shore Power









32A Socket

32A Plug

Wall mounting, 105 x 105 mm. Built-in sizes: D 83 x H 90 x W 83 mm		
Part No	Description	
70763	Outdoor Plug Male - 230V (Shore Power)	
70764	Outdoor Plug Female - 230V (Shore Power)	
70766	Wall Mounting Socket White (shore power)	



30 Amp Shore power plug or socket. Max 30Amp.

Part No	Description
96056	30 Amp Plug & Cap 220V
96055	30 Amp 220V Socket AISI 316



Cigarette Lighter Style Socket

100% water resistant, either with Input 12-24v DC protection cap closed or with lockable plug, equipped with a special watertight collar and a "lock-in" system that locks the plug by turning; designed for plug mounting with back screw nuts or two screw boards; suitable for lighters and cellular phones.

Part No	Description
70762	12V DC Socket



Dual USB Charger Socket

Output 5v/2.1A DC Easy Install Corrosion Resistant materials with protective cap Overheat Protected FCC and CE

Part No	Description
76094	Dual USB Charger Socke



8/32V digital voltmeter. 0/10A digital ammeter.

Part No	Description
76092	Digital Voltmeter + Ammeter





ROKK 2 USB Charger

Charge up to 2 devices at a time. Easy install. Click & lock lid. Output current 4.2A (total). Up to 3x faster than standard USB sockets. Waterproof with 1, 2 and even no cables plugged in. Anticorrosion coating on circuit board. UV resistant. 316 stainless hinge and spring. Ultra low profile: only 29mm high, 94mm long.

Part No	Description
72213	ROKK USB Charger



USB 12V Adaptor



Input 12-24V. Output 5V Max Load 2,1A Overload Protection on 6.8V Part No Description



Made of nylon and fit with protection cap to make them waterproof. 12/24V input, 5V USB output.

Part No	Description
76089	Lighter Socket + Double USB Charger 12/24V

5 (1) 5 ...



8/32V digital voltmeter + Lighter Socket.

Part No Description

76090 Lighter Socket and Voltmeter



8/32V digital voltmeter. Dual USB plug. 2.4 + 2.4A.

Part No Description

76091 Digital Voltmeter & Dual USB Port 4.8A



Weatherproof Switch

15A single pole. 2 Terminals. Panel aperture: 12mm. Flexible splash proof rubber cover.

Part No

70674



Carling Toggle Switches

High tension thermosetting body, silver plated contacts, nickel plated brass lever and sleeve. Capacity of 15 Amp; very sturdy and functional model; "Faston" terminals, pin size 12x10 mm; can be connected to 2 separate circuits.

Part No	Description
70678	2 Position
70679	3 Position



Voltmeter + Dual USB Socket

3/30V. 54 x 100mm

Part No Description

76018 3/30V Voltmeter + Dual USB socket





Momentary Push Button Switch

Marine plastic with rubber button and silver contacts. For 9mm plate.

12V - 5A

Part No

70680



Waterproof Rocker Switch

Mounted switch 12V, waterproof IP65. On/off.

Part No Description

70765 Rocker Switch On/Off



On/Off Switch

Plastic switch for plate thickness 11mm. 12V - 10A

Part No

70676

Stainless Steel Switch 24V

CNC-machined AISI316 stainless steel case. Amperage: 20A at 12V. IP67 watertight (temporary submersion). LED light crown. Life: 20,000 cycles. A scheme wiring: LED light crown always on. B scheme wiring: LED light crown switched when in ON position.

Part No Description

96475 On/Off Switch White 24V

On/Off Switch Red 24V 96476



When the on or off is in brackets it indicates that it is a spring loaded momentary switch.



Sealed Rocker Switch

IP67: Waterproof Non Illuminated 12V 24V

Comes with actuator.

Part No Description

70511 Rocker Switch (on)-off 70512 Rocker Switch (on)-off-(on)



Sealed Single Rocker Switch

IP67: Waterproof Illuminated 12V 24V

Comes with actuator.

Part No Description 70513 Rocker Switch on-off 70514 Rocker Switch (on)-off



Sealed Double Rocker Switch

IP67: Waterproof Illuminated 12V 24V

Comes with actuator.

Part No	Description	
70515	Rocker Switch on-off-on	
70516	Rocker Switch (on)-off-on	



Electrical



Sealed Single Square Rocker Switch

IP67: Waterproof Illuminated 12V 24V

Comes with actuator.

Part No Description

70518 Rocker Switch (on)-off



Actuator Removal Tool

Part No 70521



Label Stickers For Rocker Switches Part No

70522



Part No Description 69906 Carling Switch Contura II Single Pole Off - On Red LED 12/24V

Switch Panels



Blue Sea 6 Way Waterproof Switch Panel

Maximum Amperage 15A @ 12V DC (per circuit).

Panel Cumulative Rating 90A.

Height: 152.4mm x Width 98.55 mm x Depth 63.5 mm

IP67 – protected against immersion up to 1 metre for 30 minutes

Part No Description

69900 6 Position IP67 Waterproof Panel



Waterproof Switch Panel

Black Injection Moulded Waterproof Switch Panel. IP65 with LED indication.

6 Way, Pre-wired, max 15amps

108mm x 95mm

Part Description No

76006 Waterproof 6 Way Switch Panel



Wave 4 Way Electric Switch Panel

110 x 100mm

Fuses included 4Ax1 + 6Ax1 + 8Ax1 + 10Ax1.

Made of black plastic, equipped with toggle switches and resettable thermal automatic fuses. Equipped with sticking labels to identify the different uses.

Part Description No 76015 4 Way Panel



Wave 6 Way Electric Switch Panel

160 x 100mm

Fuses included 5Ax2 + 6Ax2 + 8Ax1 + 10Ax1.

Made of black plastic, equipped with toggle switches and resettable thermal automatic fuses. Equipped with sticking labels to identify the different uses.

Part No Description 76016 6 Way Panel



Wave 8 Way Electric Switch Panel

210 x 100mm

Fuses included 4Ax1 + 5Ax2 + 6Ax2 + 8Ax2 + 10Ax1

Made of black plastic, equipped with toggle switches and resettable thermal automatic fuses. Equipped with sticking labels to identify the different uses.

Part No	Description	
76017	8 Way Panel	



Aluminium Vertical Rocker Switch Panel

Aluminum Vertical Rocker Switch Panel features four 15A 12 VDC illuminated SPST On/Off rocker switches and four 10A 12 VDC fuse holders. Individual circuit 10A max. 37A total. Includes a sheet of 20 preprinted decals to customize to your specific applications. Constructed of stamped anodized aluminium.

Part No	Description
76004	Alu Switch Panel Vertical 4 Gang (127mm x 114mm)



Nylon Vertical 6 Gang Rocker Switch Panel

The Vertical 6-Gang Rocker Switch Panel features six 15A 12 VDC illuminated SPST On/Off rocker switches and six fuse holders for use with standard AGC 1/4" x 1-1/4" glass style fuses. Individual circuit 10A max. 37A total. These fire resistant panels are suitable for use in engine room compartments. Includes a sheet of 20 preprinted decals to customize to your specific application. Constructed of injection molded nylon. CE compliant. 12 VDC.

Part No	Description
76008	Moulded Switch Panel Vertical 6 Way 165mm x 114mm



Aluminium Vertical Rocker Switch Panel

Aluminium Vertical Rocker Switch Panel features six 15A 12 VDC illuminated SPST On/Off rocker switches and six 10A 12 VDC fuse holders. Individual circuit 10A max. 37A total. Includes a sheet of 20 preprinted decals to customize to your specific applications. Constructed of stamped anodized aluminium.

Description		
Alu Switch Panel Vertical 6 Gang (165mm x 114mm)		



Nylon Horizontal 6 Gang Rocker Switch Panel

The Horizontal 6-Gang Rocker Switch Panel features six 15A 12 VDC illuminated SPST On/Off rocker switches and six fuse holders for use with standard AGC 1/4" x 1-1/4" glass style fuses. Individual circuit 10A max. 37A total. These fire resistant panels are suitable for use in engine room compartments. Includes a sheet of 20 preprinted decals to customize to your specific application. Constructed of injection molded nylon. CE compliant. 12 VDC.

Part No	Description
76010	Moulded Switch Panel Horizontal 6 Way 114mm x 165mm



Aluminium Horizontal Rocker Switch Panel

Aluminium Horizontal Rocker Switch Panel features six 15A 12 VDC illuminated SPST On/Off rocker switches and six 10A 12 VDC fuse holders. Individual circuit 10A max. 37A total. Includes a sheet of 20 preprinted decals to customize to your specific applications. Constructed of stamped anodized aluminium.

Part No	Description	
76002	Alu Switch Panel Horizontal 6 Gang (114 x 165mm)	



Nylon Horizontal 4 Gang Rocker Switch Panel

The Vertical 4-Gang Rocker Switch Panel features four 15A 12 VDC illuminated SPST On/Off rocker switches and four fuse holders for use with standard AGC 1/4" x 1-1/4" glass style fuses. Individual circuit 10A max. 37A total. These fire resistant panels are suitable for use in engine room compartments. Includes a sheet of 20 preprinted decals to customize to your specific application. Constructed of injection molded nylon. CE compliant. 12 VDC.

Part No	Description
76012	Moulded Switch Panel Vertical 4 Way 127mm x 114mm



Switch Panel 12/24V

This panel is splash proof according to IP 64. It has 8 separate circuits, each provided with a switch, indicator LED and fuse holder and it is suitable for both 12 and 24 Volt D.C. circuits. The panel can be used with conventional automotive (ATO) fuses or with automatic fuses.

- Dimensions 99 x 161 mm
- Built-in depth 45 mm

Part No	Vetus
55946	P8FA



Switch Panel + Circuit Breakers

This panel features 6 on/off switches, 6 monitoring L.E.D.'s and a choice of either 6 automatic fuses, or 6 tubular glass fuses of 10 A.

Specifications:

Available for 12 or 24 Volt D.C. circuits.

Sixty self-adhesive name/symbol plates for different functions are supplied.

Dimensions 94 x 156 mm

Built-in depth 50 mm

Part No	Description	Vetus
55957	P6 12V	P6CB12
55958	P6 24V	P6CB24



Switch Panel Fuses

This panel features 6 on/off switches, 6 monitoring L.E.D.'s and a choice of either 6 automatic fuses, or 6 tubular glass fuses of 10 A.

Specifications:

Available for 12 or 24 Volt D.C. circuits.

Sixty self-adhesive name/symbol plates for different functions are supplied.

Dimensions 94 x 156 mm

Built-in depth 50 mm

Part No	Description	Vetus
55952	P6 12V	P6F12
55953	P6 24V	P6F24



Switch Panel + Circuit Breakers

This panel features 12 on/off switches, 12 monitoring L.E.D.'s and a choice of either 12 automatic fuses or 12 tubular glass fuses of 10 A.

Available for 12 or 24 Volt D.C. circuits. Sixty selfadhesive name/symbol plates for different functions are supplied.

VETUS switch panels are supplied pre-wired. The only work required is to connect the positive and negative feeds of the various services (lights, pumps etc.). These panels are made of synthetic and noncorrosive materials, but are not waterproof.

Specifications

- Dimensions 188 x 156 mm
- Built-in depth 50 mm

Part No	Description	Vetus
55959	P12 12V	P12CB12
55960	P12 24V	P12CB24



Switch Panel Fuses

This panel features 12 on/off switches, 12 monitoring L.E.D.'s and a choice of either 12 automatic fuses or 12 tubular glass fuses of 10 A.

Available for 12 or 24 Volt D.C. circuits. Sixty self-adhesive name/ symbol plates for different functions are supplied.

VETUS switch panels are supplied pre-wired. The only work required is to connect the positive and negative feeds of the various services (lights, pumps etc.). These panels are made of synthetic and noncorrosive materials, but are not waterproof.

Specifications

- Dimensions 188 x 156 mm
- Built-in depth 50 mm

Part No	Description	Vetus
55954	P12 12V	P12F12
55955	P12 24V	P12F24

Electrical

Switchable Surface Mount



Circuit Breakers				
Part No	Rating (Amps)	Stud Size		
69630	50	1/4"		
69631	60	1/4"		
69632	80	1/4"		
69633	100	1/4"		
69634	150	1/4"		
69635	200	3/8"		

	Typically used in auxiliary and accessory circuits in trucks, buses, RV's and marine
9	systems. Sealed for engine compartment and bilge area applications.
	Protective stud insulators included.
	Compliances: SAE J1171 (ignition protected),
	SAE J1625.
	Ingress Protection: IP67.
	Voltage: 48Vdc.
	Interrupt Rating: 3000A @ 30Vdc.
	Operating Temp: -32°C to 82°C.
	Storage Temp: -34°C to 149°C.
	Material: Black UL-rated 94V0 thermoset
	plastic.



Switchable Panel Mount
Circuit Breakers

Part No	Rating (Amps)	Stud Size
69636	50	1/4"
69637	80	1/4"
69638	100	1/4"

Typically used in auxiliary and accessory circuits in trucks, buses, RV's and marine systems. Sealed for engine compartment and bilge area applications.

Protective stud insulators included.

(Gasket included)

Compliances: SAE J1171 (ignition protected),

SAE J1625.

Ingress Protection: IP67.

Voltage: 48Vdc.

Interrupt Rating: 3000A @ 30Vdc. Operating Temp: -32°C to 82°C. Storage Temp: -34°C to 149°C.

Material: Black UL-rated 94V0 thermoset plastic .



ETA Circuit Breakers

This neat design combines a thermal circuit breaker and switch all in one unit. Push button on-off and breaker reset. The two colour button provides clear on / off indication. Single hole mounting.

Part No	Description
71790	2.5 Amp
71791	5 Amp
71792	10 Amp
71793	15 Amp







Carling Circuit Breaker Switches

Compact size and well known for its proven reliability the A-series utilises the hydraulic magnetic principle which provides precise operation and performance even when exposed to extremely hot or cold application environments. A-series circuit breakers will trip on overload even when the actuator is manually held on the ON position.

Part No	Description
69903	Carling A Series Circuit Breaker 15amp
69904	Carling A Series Circuit Breaker 25amp
69905	Carling A Series Circuit Breaker 50amp

Vetus Watertight Foot Switch Black or White

New Maxwell Compact up and down Windlass Footswitch with Black cover. Designed for use with a solenoid on 12 or 24v systems. Grey activation button is reversible to denote direction and can be operated by hand with the cover in place, or by foot with the cover flipped open.

Part No	Description
55364	Foot Switch Black P104810
55361	Foot Switch White P104809



Blade Fuses			
Rating	Part No	Rating	Part No
2 Amp (Grey)	70580	10 Amp (Red)	70585
3 Amp (Violet)	70581	15 Amp (Blue)	70586
4 Amp (Pink)	70582	20 Amp (Yellow)	70587
5 Amp (Tan)	70583	25 Amp (White)	70588
7.5 Amp (Brown)	70584	30 Amp (Green)	70589





Blade Fuse Holders

Individual fuse holders which accepts blade fuses. The built-in LED glows when the fuse has blown, also fitted with a lid to prevent water ingress.

Part No	Description
70575	20 Amp Blade Fuse Holder for 2mm ²
70576	30 Amp Blade Fuse Holder for 2mm ²



Mega Fuse Holder

An individual fuse holder which accepts mega fuses. The cable connections are made using the 2 x 8mm studs. The fuse holder is fixed onto a firm surface using fixing points located at the ends of the unit. Multiple fuse holders can be clipped together to form a fuse block. Mega fuses for protecting circuits up to 500 amps.

Rating	Part No	Rating	Part No
MEGA Fuse Holder	69600		
100 Amp (Yellow)	69601	225 Amp (Light Brown)	69606
125 Amp (Green)	69602	250 Amp (Pink)	69607
150 Amp (Orange)	69603	300 Amp (Grey)	69608
175 Amp (White)	69604	400 Amp (Violet)	69609
200 Amp (Blue)	69605	500Amp (Brown)	69610



Glass i uses
Flat-ended glass fuses 30mm x 6.3mr

Rating	Part No	Rating	Part No
1 Amp	70663	20 Amp	70669
2 Amp	70664	25 Amp	70670
3 Amp	70665	30 Amp	70671
5 Amp	70666	35 Amp	70672
10 Amp	70667	50 Amp	70673
15 Amp	70668		



Glass Fuse Holders

Glass fuse holders which accept 30mm fuses

Glass fuse floiders which accept somilificases.		
Part No	Description	
70660	Red 10 Amp Glass Fuse Holder 1.0 mm² (cable cross section)	
70661	Green 20 Amp Glass Fuse Holder 2.0 mm² (cable cross section)	



Vetus Fuses & Holders

"Slow blow" type fuse, suitable for Thrusters, Windlasses etc. Encapsulated in glass to prevent fire.

Part No	Description	Part No	Description
55837	40 amp	55844	200 amp
55838	50 amp	55845	250 amp
55839	63 amp	55846	300 amp
55840	80 amp	55847	355 amp
55841	100 amp	55848	425 amp
55842	125 amp	55849	500 amp
55843	160 amp	55850	Fuse Holder

Electrical



Midi Fuse Holder & Fuses

An individual fuse holder which accepts midi fuses. The cable connections are made using the 2 x 5mm studs. Multiple fuse holders can be clipped together to form a fuse block. Midi fuses used for protecting the larger circuits up to 150 amps.

Rating	Part No	Rating	Part No
30 Amp (Orange)	69620	80 Amp (White)	69625
40 Amp (Green)	69621	100 Amp (Blue)	69626
50 Amp (Red)	69622	125 Amp (Pink)	69627
60 Amp (Yellow)	69623	150 Amp (Black)	69628
70 Amp (Brown)	69624	MIDI Fuse Holder	69615



130 Assorted Blade Fuses Refill Box

4amp x 10

5amp x 10

7.5 amp x 20

10 amp x 20

15 amp x 20

20amp x 20

25 amp x 20

30amp x 10

Part No

70590



120 Assorted Pre Insulated Terminals Refill Box

6.4mm Blue ring terminals x 15

Red Butt Connector x 15

Blue Butt Connector x 15

6.3mm Red Female Covered Spade x 15

6.3mm Blue Female Covered Spade x 15

6.3mm Blue Female Spade x 15

6.3mm Red Male Spade

6.3mm Blue Male Spade

Part No

70619



Standard Blade Fuse Box

Blade fuse boxes complete with transparent cover and gasket. The cable connections are made using the 6.3mm male blade terminals which are fitted on the sides

Part No	Description		Male Blade Terminals Fitted	Dimensions H x W x D (mm)
70577	4 Way Blade Fuse Box	4	8 x 6.3mm	36 x 80 x 29
70578	6 Way Blade Fuse Box	6	12 x 6.3mm	36 x 100 x 29
70579	8 Way Blade Fuse Box	8	16 x 6.3mm	36 x 120 x 29



LED Blade Fuse Box

LED blade fuse box complete with transparent cover. Consists of 1 x 5mm positive input stud which feeds each of the blade fuses. Each fuse has a 6.3mm male blade terminal and a red LED indicator light next to it that glows when the fuse has blown.

Part No	Description		Male Blade Terminals Fitted	Dimensions H x W x D (mm)
70560	4 Way LED Blade Fuse Box	4	4 x 6.3mm	35 x 45 x 85
70561	6 Way LED Blade Fuse Box	6	6 x 6.3mm	35 x 65 x 85
70562	10 Way LED Blade Fuse Box	10	10 x 6.3mm	35 x 95 x 85



YUASA Leisure Battery HA08

Brand: Yuasa Volts: 12V Ah: 80A

CCA: 450

Dimensions: L:260mm

W:174mm H:225mm

Part No Description

70800 YUASA Leisure Battery 80AH









YUASA Leisure Battery 100AH

Brand: Yuasa Volts: 12V Ah: 100A CCA: 600

Dimensions: L: 330mm W: 173mm

H: 240mm

Part No Description 70801 YUASA Leisure

Battery 100AH

Vetus Black Battery Boxes

New style injection moulded polypropylene box

Thanks to the correct dimensions and strong mounting straps, your battery will be held securely even in rough

waters.

55857

Part No Description Battery Box BATBOXS VESMF60 VEAGM60 55851 Internal Dimensions:255 x 180 x 195mm (LWH) 55852 Battery Box BATBOXM VESMF70 VEAGM70 Internal Dimensions: 350 x 180 x 195mm (LWH) 55853 Battery Box BATBOXL VESMF/AGM 85/105 Internal Dimensions:360 x 175 x 230mm (LWH)

BATBOXSET Battery Box Spare Strap Set



Trem Battery Box





Osulati Battery Box

Suitable for 100 AH batteries. Inside 320 x 177 x 190h. Outside 370 x 210 x 250h. With fastening strap and buckle.

Part No Size

370 x 210 x 250 high 96416



Vetus Battery Terminal M10 Bolt

Sold as a pair

For cables with cross section between 16 and 35mm². Saddle clamp type cable connection.

BATT150

Part No

55871

Small: Manufactured in resistant plastic material.

Complete with carrying strap and nylon buckle for fastening.

Large: With adjustable partition & belt Can hold 1 big or 2 small batteries Suitable also as onboard equipment holder Manufactured in polypropylene

Part No Size 70715 Small 190 X 270 X 200H mm 70716 Large 200 X 410 X 250H mm



Quick release terminals

Designed to be fitted onto or removed from a battery without tools. Material - Passivated steel. Suitable for cables up to 25mm²

Sold as a pair (blue & red)

Part No

70876



Battery Terminals

Sold Individually

Material - Tin plated brass

M10 Stud size

17mm Stud Length				
Part No	Polarity	Cover		
70873	Positive	70877		
70872	Negative	70878		



Polarity	For Cable up to 40mm ²	For Cable up to 60mm^2
Positive	70638	70642
Negative	70640	70644



Battery Terminal Covers
Positive or Negative
Loft or Dight

Left of Right				
Polarity	Left	Right		
Positive	70647	70649		
Negative	70648	70650		

Electrical

















Part No 55797 96050 70692 55798 70689 70690 Description Battery Switch 75 Amp (BATSW075) 100 Amp Switch 100 Amp (BATSW100) 100 Amp High 75mm Fixed or Removable Key Single Circuit or Single 70689 70690 7	
75 Amp (BATSW075) Battery Switch 100 Amp 100 Amp 100 Amp (BATSW100) Dual Circuit 100 Amp 175 A	
Fixed or Removable Removable Removable Removable Fixed Fixed Fixed Fixed Single Circuit or Single Single Single Single Dual Dual	Switch
Removable Key Single Circuit or Single Single Single Dual Dual	
Dual	
Continuous 75 Amps 100 Amps 100 Amps 100 Amps 100 Amps 175 Amp Rating	nps
5 Seconds Amp 350 Amps 150 Amps 500 Amps 300 Amps Rating	
3 Minutes Amp Rating	
Stud Size 10mm 6mm 9.4mm 10mm 10mm 10mm	
Max Voltage 24V DC 32V DC 24V DC 50V DC 24V DC)













		•				
Part No	55795	55799	70694	35998	69907	69901
Description	3 Way Battery Switch 175 Amp ACCUSCH	Battery Switch 250 Amp (BATSW250)	Heavy Duty Battery Switch 280 Amp	Battery Switch Mini 275Amp	Blue Sea M Series Battery Switch 300amp	Blue Sea M Series Dual Circuit Plus Battery Switch 300Amp
Dimensions	135 x 135 x 75mm High		66mm Flange	69 x 69 x 75mm		
Fixed or Removable Key	Removable	Removable	Removable	Fixed		
Single Circuit or Dual	Dual	Single	Single	Single	Single	Dual
Continuous Amp Rating	175 Amps	250 Amps	280 Amps	275 Amps	300 Amps	300 Amps
5 Seconds Amp Rating	300 Amps	2500 Amps	2500 Amps	10 Seconds = 1250 Amps	30 Seconds = 900 Amps	30 Seconds = 675 Amps Per Circuit
3 Minutes Amp Rating				5 Minutes = 455 Amps	5 Minutes = 500 Amps	5 Minutes = 450 Amps
Stud Size	10mm	10mm	10mm	10mm		
Max Voltage	32V DC	24V DC				

Electrical

BLUE SEA





		•
Part No	69902	55800
Description	Blue Sea E Series Dual Circuit Plus Battery Switch 350amp	Battery Switch 600Amp (BATSW600)
Dimensions		
Fixed or Removable Key		
Single Circuit or Dual	Dual	Single
Continuous Amp Rating	350 Amps	600 Amps
5 Seconds Amp Rating	30 Seconds = 700 Amps Per Circuit	4500 Amps
3 Minutes Amp Rating	5 Minutes = 525 Amps	
Stud Size		
Max Voltage	32V DC	24V DC



Cable Tie Fixing

2 way and 4 way cable tie mounts with a self adhesive base. Alternatively the mount can be fixed by using a self tapping screw (not inc) through the hole in the centre.

Sold Each or in bags of 100

Part No	Maximum	Base Size	Fixing
	Cable Tie	(mm)	Hole
	Size		Size
	(mm)		(mm)
69570	4.8mm	19.0 x 19.0mm	3.5mm
69571	4.8mm	28.0 x 28.0mm	5.7mm



Sold each or in bags of 100

Part No	Width	Length
69550	2.5mm	80mm
69551	2.5mm	100mm
69552	3.6mm	140mm
69553	3.6mm	200mm
69554	3.6mm	300mm
69555	4.8mm	120mm
69556	4.8mm	160mm
69557	4.8mm	200mm
69558	4.8mm	300mm
69559	4.8mm	370mm
69560	7.6mm	200mm
69561	7.6mm	300mm
69562	7.6mm	368mm
69563	9mm	430mm
69564	9mm	526mm
69565	9mm	780mm

Cable Tie Cradle

Cable tie cradle suitable for the larger ties. The cradle is fixed to a firm surface using a self tapping screw (not inc)

Sold Each or in bags of 100

Part No	Maximum Cable Tie	Base Size (mm)	Fixing Hole
NO	Size (mm)	(111111)	Size
			(mm)
69572	9.0mm	21.9 x 15.9mm	5.0mm



Cable Tie Eyelet

Cable tie eyelet suitable for fixing cable ties securely to a firm surface. This can be fixed using a self tapping screw (not inc).

Sold Each or in bags of 100

Part No	Maximum Cable Tie Size (mm)	Base Size (mm)	Fixing Hole Size (mm)
69573	5.0mm	20.0 x 10.0mm	4.3mm





Battery Charger - BC12051

VETUS introduces a new 12 Volt, 5 Ampere battery charger. This new microprocessor controlled 'switch mode' charger will charge a battery in five separate stages. Thanks to the switch mode technology batteries are charged 1.5 times faster compared with a conventional battery charger. It is also capable of 'refreshing' and maintaining your battery.



55794



Nylon P clips for fixing cables, conduits etc.			
Part No	A (height)	B (hole size)	C (width)
70740	3.2mm	5.2mm	13.2mm
70741	4.5mm	5.2mm	9.7mm
70742	6.4mm	5.2mm	9.7mm
70743	7.6mm	4.8mm	9.7mm
70744	9.3mm	4.8mm	9.7mm
70745	12.6mm	5.2mm	12.8mm
70755	15.8mm	4.6mm	12.0mm
70756	19.4mm	5.3mm	12.0mm
70757	25.4mm	4.6mm	12.0mm
70758	28.6mm	4.6mm	12.7mm





Part	Description	Width	Height	Lengt
No		mm	mm	h mm
72150	Combi 206 Grey Junction Box IP66	49	51	85



Part	Description	Width	Height	Length
No		mm	mm	mm
72151	Combi 9 Inlet Grey 4mm²Junction Box IP66	95mm	60	95



Ratchet crimping tool suitable for crimping copper tube terminals from 1.5 - 10mm². The ratchet ensures that the correct crimping pressure is applied before release.

Tool length 260mm.

Part No

70798



Part	Description	Width	Height	Length
No		mm	mm	mm
72152	Combi 8 Inlet Grey 4mm²Junction Box IP66	85	51	85



Part No	Description
72155	20mm Cable Compression Gland IP68
72156	25mm Cable Compression Gland IP68



Economy crimping tool suitable for the full range of pre insulated terminals and heatshrink pre insulated terminals. Also features a cable cutter and wire stripper.

Part No

70829

Waterproof Cable Glands



Manufactured in high quality chrome plated brass. Three hole flange fixing.

Part No	Cable Diameter
70710	6mm
70711	8mm
70712	12mm
70713	19mm

Split Seal Single Cable Glands

Index Marine Equipment Ltd










DG21A

DG21P

DG22A

DG22P

Part No	Туре	Cable Size	Max Connector Diameter	Dimensions
71600	DG21A Aluminium	4.5-9mm	21mm	45 x 21mm
71601	DG21P Plastic	4.5-9mm	21mm	45 x 21mm
71602	DG22A Aluminium	9-14mm	21mm	45 x 21mm
71603	DG22P Plastic	9-14mm	21mm	45 x 21mm
71604	DG45A Aluminium	12-15mm	40mm	66 x 21mm
71605	DG45P Plastic	12-15mm	40mm	66 x 21mm



The DR1 cable gland can be drilled in the same way as the M Series glands, to accept a variety of cables. Following the instructions provided, simply drill holes of appropriate diameter through the 12.5mm thick diaphragm. However, the diaphragm should not be slit as it is not tapered, (as in the M Series glands) and a perfect seal would therefore not be guaranteed. Stainless steel top. Plastic base.

Dimensions: Height 21mm, Length 94mm, width 44mm

Aperture: 65 X 18.5mm

Part No: 71613

DG Series Deck Glands





DG20A

DG20P

DG30A



DG30P





DG40A

DG40P



DG50A

The DG series of plastic cable glands are made from UV stable nylon. They are available in an aperture range of 8mm to 40mm and have an attractive, low profile shape. The range has passed independent rigorous dust and waterproof testing to IP 68. Each unit is supplied with clear fitting instructions and A4 stainless steel fixings. DG Deck Glands are easy to fit and do not require the removal of fitted connectors when installing. The DG Series aluminium cable glands are made from marine grade anodised aluminium.

Part No	Туре	Max Connector Diameter	Dimensions (mm)
71606	DG20A Aluminium	21mm	45 x 21
71607	DG20P Plastic	21mm	45 x 21
71608	DG30A Aluminium	30mm	54 x 21
71609	DG30P Plastic	30mm	54 x 21
71610	DG40A Aluminium	40mm	66 x 21
71611	DG40P Plastic	40mm	66 x 21
71612	DG50A Aluminium	51mm	80 x 25



V12 Series Glands

A gland for a single cable, with no connector attached. Three different diameter seals are supplied. Choose the seal whose diameter most closely matches the diameter of the cable to be passed through. The seal sits between the top and the base of the gland and when the two are screwed together, a neat and watertight seal is created.

Dimensions: Width 35mm, Height 12mm

To fit cables from 2-8mm.

Part No	Туре
71614	V12F Aluminium
71615	DG8P Plastic





DG Coax Kits

Two kits for the installation of VHF radios supplied with either a BNC or PL259 coax connection. Each combines the DG gland (plastic, aluminium or stainless) with a 4.5mm split seal which does not require the removal of fitted connectors during installation (suitable for RG58 type coax cable). Full assembly instructions included.

Part No	Туре
71617	A2 KIT 1
71618	A2 KIT 4

Cables Glands & Accessories




The only guaranteed and proven watertight installation for your antenna and navlight cables.

The range provides waterproof cable routing and is produced in high impact plastic and 316 stainless steel with options for 16mm to 40mm connectors, making it ideal for almost every installation.

Part No	Description
72212	DS6-Plastic (2 - 6mm)
72200	DS16-Plastic (2 - 8mm)
72201	DS21A-Plastic (4 - 9mm)
72202	DS21B-Plastic (9 -14mm)
72203	DS30-Plastic (9 -14mm)
72204	DS40-Plastic (12 - 15mm)
72205	DS16-Stainless 316 (2 - 8mm)
72206	DS21A-Stainless 316 (4 - 9mm)
72207	DS21B-Stainless 316 (9 -14mm)
72208	DS30-Stainless 316 (9 -14mm)
72209	DS40-Stainless 316 (12 - 15mm)




	A mm (inches)	B mm (inches)	C mm (inches)	D mm (inches)	E mm (inches)
DS6	30 (1.18)	N/A	27.0 (1.06)	17 (0.67)	2-6 (0.08-0.24)
DS16	39 (1.53)	16 (0.63)	36.5 (1.44)	19 (0.75)	2-8 (0.08-0.31)
DS21A	49 (1.93)	21 (0.83)	45.7 (1.8)	20.5 (0.81)	4-8 (0.17-0.31)
DS21B	49 (1.93)	21 (0.83)	45.7 (1.8)	20.5 (0.81)	9-14 (0.35-0.55)
DS30	59 (2.32)	30 (1.18)	56 (2.2)	20.5 (0.81)	9-14 (0.35-0.55)
DS40	69 (2.72)	40 (1.57)	66 (2.6)	21.7 (0.85)	12-15 (0.4-0.59




ØB


DS-HD6



The DS-HD6-BLK double horizontal cable seal was designed to eliminate time-consuming and sub-standard routing of solar panel cables. Our seal helps you achieve a sleek, easy-to-fit, and 100% watertight installation every time. Perfect for routing two solar panel cables externally to internally on the roof of









waterproof wireless charging range.

WIRELESS.

ROKK Wireless Surface - SC-CW-02E

ROKK Wireless Hidden Charger

Sub-surface, hidden from view but always ready to charge. Engineered to be installed under the surface and leave the top surface un-cluttered and looking perfect. Simply etch in your logo to identify the charge location. Ideal for GRP or wood, the unit can be installed under tables, cabinets, consoles or worktops. The installation system is simple to install and works with a variety of panel depths and materials.

Part No Description

ROKK Wireless Hidden 72220

ROKK Wireless Surface Flush Mounted Charger

Low-profile, flush-mounted charge pad with an ultra grippy, non-slip surface. Contemporary look with two-tone colour, designed to complement modern interiors and exteriors. Designed to fit to any smooth surface, indoors or out.

Part No Description

ROKK Wireless Surface 72221








The world's first waterproof wireless charging range.

ROKK Wireless Bezel - SC-CW-03E




ROKK Wireless Surface Mounted Charger

The easiest to install, this option includes the non-slip surface pad but simplifies installation even further. Simply drill a 10mm cable access hole and fit to your chosen location Qi wireless charging is ready to go.

Part No Description

72222 **ROKK Wireless Bezel**



ROKK Wireless Phone Charging Mount

One-handed dock/charge operation. Instant charging. No connection needed. 12/24V input compatible. IPX6 Waterproof. Self-aligning grips securely hold your phone. Qi-certified wireless charging. Compatible with wide range of device sizes from Apple,

Samsung and many more. Quick and simple waterproof install on any flat surface. Charges through non-metallic waterproof cases up to 3mm thick (0.11")

Part No Description

72225 **ROKK Wireless Active**

Designed and engineered by the outdoor technologies experts Scanstrut, the new ROKK wireless charging receiver patches are wireless charge ready! Simply plug the Mirco USB or Lightning charge patch into your phones charging port, place on the back of the phone and then clip on your phone case over the top. Your phone is now ready to be charged by any of the 12/24V ROKK wireless charger range or any other Qi-certified charging product.



SC-CW-PATCH-MU

Universal Micro USB wireless charge receiver patch

SC-CW-PATCH-LU

Universal Lightning wireless charge receiver patch for iPhone

Part No	Description
72223	Universal Micro USB Wireless Patch
72224	Lightning IPHONE Wireless Patch

Horns





Electric Horns Compact Type

Compact shell horn, stainless steel (AISI316), low pitch, available in 12 Volt, 110 db. Double horn is high & low pitch.

Part No	Description
58273	C12L Single 12Volt (L X H X W) : 83 x 56 x 85 mm
58272	C12D Double 12 Volt (L X H X W): 205 x 56 x 85 mm



Eco Friendly Compressed Air

Hand-operated via the plunger on the bottom of the cylinder. Fitted with double nozzle to be also used as inflator for fenders and balls.

Part No	Description	
96333	Eco Compressed Air	
	Horn	



Flush Mount Electric Horn

Flush mounted electric horn. Plastic housing, stainless steel (AISI 316) diaphragm. Including white, black and chrome plated ABS cover.

Voltage (V): 12 V

Decibel (dB): 110 dB (A)

Dimensions (height x width) (inches): 2,44 x

5,04

Build-in depth (inches): 3,74

Dimensions (height x width) (mm): 62 x 128

Build-in depth (mm): 95

Part No Description

58289 12V SS 316 110db (T12)



AFI Horn Compact Dual Trumpet 16" SS 110db

Description Part No

AFI Horn Dual Trumpet 96433







Electric Horns Long Trumpet Type

Deluxe 12v electric single trumpet horn with an elegant shape. The horn is made of chromium plated brass, mounting bracket and top cover are stainless steel, mechanism base is chromium plated ABS.

	'
Part No	Description
58275	Single 12Volt Low Pitch (H12L)
58276	Single 24Volt Low Pitch (H24L)
58277	Single 12Volt High Pitch (H12H)
58278	Single 24 Volt High Pitch (H24H)
58279	Double 12 Volt High & Low (H12D)
58280	Double 24 Volt High & Low (H24D)
	, ,

Electric Horns Short Type

Deluxe compact electric horn, made of chromium plated ABS stainless steel. Supplied with relay.

	,
Part No	Description
58283	Single 12Volt Low Pitch (TNA12L)
58284	Single 24Volt Low Pitch (TNA24L)
58285	Single 12Volt High Pitch (TNA12H)
58286	Single 24Volt High Pitch (TNA24H)
58287	Double 12 Volt High & Low (TNA12D)
58288	Double 24 Volt High & Low (TNA24D)
58290	Horn Push Button (HORNPB)



Momentary Push Button Switch

Marine plastic with rubber button and silver contacts. Can be used as a horn push button. For 9mm plate. 12V - 5A

Part No

70680

Dashboard instruments with cream, black or white dials.

Tachometer (revolution counter)

Available in 114mm diameter as 0-4000 r.p.m. version (for most diesel engines) or a 0-5000 r.p.m. version (to suit high speed engines). Dual voltage 12/24V gauges running on DC current are now the new standard. Cut out size 100mm. Overall Diameter 114mm.

Supplied with black and chrome finish bezels.

Part No	Vetus	Description
56092	TACHB4000	Black 4000 rpm tachometer
56093	TACHW4000	White 4000 rpm tachometer
56094	TACHN4000	Cream 4000 rpm tachometer
56095	TACHB5000	Black 5000 rpm tachometer
56096	TACHW5000	White 5000 rpm tachometer
56097	TACHN5000	Cream 5000 rpm tachometer



Exhaust / Gas Temperature Alarm

52mm Cut out size.

63mm Overall Diameter.

Designed for water injected engine systems. Provides a visual and an audible alarm when the temperature inside the exhaust hose or the waterlock exceeds an acceptable level.

A temperature sensor, to be fitted into the exhaust hose or the waterlock must be ordered separately. In case of a twin engine installation two sensors may be connected to one unit if required. One sensor will also operate two alarm units in the case of a second steering position.

Part No	Vetus	Description
56071	XHI12B	Black 12V Audible Alarm
56072	XHI24B	Black 24V Audible Alarm
56073	XHI12W	White 12V Audible Alarm
56074	XHI24W	White 24V Audible Alarm
56075	XHSH	Sensor to fit exhaust hose.
56076	XHSM	Sensor to fit waterlocks: MF/MV/LSG/LSS/MGS/MGL/MGP



Trim Gauge

52mm Cut out size

63mm Overall Diameter

For connection to the trim sensor of a stern drive or a set of trim tabs. Sensor resistance range: Trim down: 10 Ohm. Trim up: 180 Ohm. Dual voltage 12/24V

Part No	Vetus	Description
56098	TRIMB	Black Trim Gauge.
56099	TRIMN	Cream Trim Gauge.
56100	TRIMW	White Trim Gauge
56101	TRIMWR	Connection Cable



Temperature Gauge

52mm Cut out size


63mm Overall Diameter

Scale calibration: 40-120°C. and 105-250°F.

Temperature sensors are available as optional equipment.

Dual Voltage 12/24V.

Part No	Vetus	Description
56102	TEMPB	Black Temperature Gauge
56103	TEMPN	Cream Temperature Gauge
56104	TEMPW	White Temperature Gauge
56062	TEMPSR120	Single Pole Sender M14 x 1.5
56063	TEMPSR122	Double Pole Sender M14 x 1.5



52mm Cut out size

63mm Overall Diameter

Analogue engine hour counter which connects to the ignition switch. Dual Voltage 12/24V.

Part No	Vetus	Description
56105	HOURCB	Black Hour Counter
56106	HOURCN	Cream Hour Counter
56107	HOURCW	White Hour Counter

Voltmeter Gauge

52mm Cut out size

63mm Overall Diameter Dual Voltage 12/24V.

12V = 8-16 VDC

24V = 16-32 VDC

Part No	Vetus	Description
56108	VLT12B	Black 12V Voltmeter
56109	VLT24B	Black 24V Voltmeter
56110	VLT12N	Cream 12V Voltmeter
56111	VLT24N	Cream 24V Voltmeter
56112	VLT12W	White 12V Voltmeter
56113	VLT24W	White 24V Voltmeter

Waste Water Gauge

52mm Cut out size

63mm Overall Diameter

Dual Voltage 12/24V.

The waste water can be provided with an interface (EP412326). A warning light can be connected to this interface, which will indicate when the holding tank is full

Part No	Vetus	Description
56123	WASTB	Black Waste Water Gauge
56124	WASTN	Cream Waste Water Gauge
56125	WASTW	White Waste Water Gauge
56126	EP412326	Interface







WASTE

Electrical

Amp Meter Gauge

52mm Cut out size

63mm Overall Diameter

Dual Voltage 12/24V.

Scale Calibration +/- 50A, 80A or 150A

Part No	Vetus	Description
56114	AMP050B	Black 50A Amp Meter
56115	AMP050N	Cream 50A Amp Meter
56116	AMP050W	White 50A Amp Meter
56117	AMP080B	Black 80A Amp Meter
56118	AMP080N	Cream 80A Amp Meter
56119	AMP080W	White 80A Amp Meter
56120	AMP150B	Black 150A Amp Meter
56121	AMP150N	Cream 150A Amp Meter
56122	AMP150W	White 150A Amp Meter



Oil Pressure Gauge

52mm Cut out size

63mm Overall Diameter

Dual Voltage 12/24V.

Scale calibration 0-8kg/cm² and 0-110 p.s.i. Oil pressure sensors are available as optional equipment.

Part No	Vetus	Description	
56127	OILB	Black Oil Pressure Gauge.	
56128	OILN	Cream Oil Pressure Gauge.	
56129	OILW	White Oil Pressure Guague	
56064	OILS	Single Pole M10 x 1K Oil Pressure Sender	
56065	OILS2	Double Pole M10 x 1K Oil Pressure Sender	







OILSR08 OILS

OILSR082 OILS2

Fuel Gauge

52mm Cut out size

63mm Overall Diameter

Dual Voltage 12/24V.

Part No	Vetus	Description
56130	FUELB	Black Fuel Gauge
56131	FUELN	Cream Fuel Gauge
56132	FUELW	White Fuel Gauge







Fresh Water Gauge

52mm Cut out size

63mm Overall Diameter

Dual Voltage 12/24V.

Part No	Vetus	Description
56133	WATERB	Black Fresh Water Gauge
56134	WATERN	Cream Fresh Water Gauge
56135	WATERW	White Fresh Water Gauge







Rudder 63mm Indicator & Sending Unit

52mm Cut out size

63mm Overall Diameter

Dual Voltage 12/24V.

Part No	Vetus	Description
56136	RUDDB	Black Rudder Indicator
56137	RUDDN	Cream Rudder Indicator
56138	RUDDW	White Rudder Indicator
56146	RUDDS	Rudder position sending unit



Rudder 114mm Indicator & Sending Unit

100mm Cut out size

114mm Overall Diameter

Dual Voltage 12/24V.

Part No	Vetus	Description
56139	RUDDB40	114mm Black Rudder Indicator
56140	RUDDN40	114mm Cream Rudder Indicator
56141	RUDDW40	114mm White Rudder Indicator
56142	RUDDSHD	Heavy Duty Rudder position sending unit

Energy consumption gauge / battery monitor

Type BATMONB

The monitor shows you the exact state of change of a battery or battery bank. The BATMONB has several functions such as voltage, charge or discharge current, scale range of the nominal battery capacity and the time to complete discharge at the present discharge rate.

85mm Cut out size

97mm Overall Diameter

Dual Voltage 12/24V.

Part No	Vetus	Description
56143	BATMONB	Energy Consumption Gauge





Water/Fuel Float Sensor

Universal sender for fresh water, petrol/gasoline and diesel fuel. The Vetus universal tank sender indicates the difference in fluid level in steps of 2.5cm.

Empty 300Ω Full 10Ω

Full 10Ω	
12/24V	
Part No	Length
56080	280mm
56081	320mm
56082	380mm
56083	480mm
56084	580mm
56085	680mm
56086	780mm

Electrical



Waste Water Sensor

Easy measurement.

Simple to fit, reliable waste water tank sensor. The arm length is adjustable between 200mm and 412mm.

Empty 300Ω Full 0Ω 12/24V

WWSENSORA

Part No

56088

Fuel Tank Float 140/660mm

Sender for fuel tanks.

Sender for all rigid petrol and diesel fuel tanks with a depth between 140 and 660mm.

Both the vertical strip and the horizontal float arm are completely adjustable.

Empty 280Ω Full 40Ω 12/24V

FSENSOR

Part No

56087



The ultrasonic level sensors, SENSORA and SENSORB are contactless and will measure the fluid level in any shape of tank. They are suitable for use with: petrol, diesel fuel, fresh water, black and grey waste water. After installation, the sensor can be calibrated very easily with the aid of a LED and a calibration; no other equipment is required. The sensor may be installed in any shape of tank, regardless of its dimensions, but with a maximum depth of 120cm. Max. tank capacity 5000 litre. Model SENSORA may be connected to all standard VETUS analogue level indicators and also to the VETUS waste water control panel (WWCP). Model SENSORB has a CANbus output and may be connected to the VETUS ultrasonic level display SENSORD. SENSORA and SENSORB are not recommended for use with metal tanks.



Ultrasonic Level Sensor SENSORA

- Can be used with all standard VETUS analogue level indicators.
- 12/24V
- Current consumption: 35 mA
- Tank depth: 120mm
- Accuracy: +/- 5%
- Temperature range: -20°C 70°C
- Flange: SAE, 5 holes
- Dimensions: ø 77 x 23mm

Part No

56090



Ultrasonic Level Sensor SENSORB

- Only works with SENSORD
- Uses a Bus interface (RS485 bus)
- 12/24V
- Current consumption: 35 mA
- Tank depth: 120mm
- Accuracy: +/- 5%
- Temperature range: -20°C 70°C
- Flange: SAE, 5 holes
- Dimensions: ø 77 x 23mm

Part No

56091



Ultrasonic Level Display Unit **SENSORD**

The graphic display instrument model SENSORD can be used to show the contents of up to four different tanks on one screen. A maximum of eight tanks can be monitored with the system.

- Uses a Bus interface (RS485 bus)
- 8 32V
- Instrument: 125mA at 12 VDC / 63mA at 24 VDC.
- Current consumption sensor: 35mA
- Max 8 Sensors
- Number of display instruments: max
- Operating Temperature range: -0°C - 70°C
- IP66
- Dimensions: 110 x 110mm

Part No

56089





Vetus Gas & Carbon Monoxide Detector 12/24V

The gas detector model GD1000 offers a gas detection system for a range of combustible gases including propane, butane, methane and hydrogen. In addition it will also detect poisonous carbon monoxide.

Maximum relay contact ratings for extractor fan, gas solenoid valve and external alarm: 1A for each function

Control panel dimensions: 85 x 85mm

Built in depth: 40mm

Sensor 35 x 26 x 62mm

Part No	Vetus	Description
55935	GD1000	12V/24V Detector + Sensor
55936	GSENSOR	Extra Sensor



Waste Water Control Panel 12/24V

This easy to use control panel with security lock can be used manually or automatically to control the full tank pump out and manage the complete waste water system. The WWCP panel is connected to a VETUS level sensor (type WSENSORA or SEN-SORA) and indicates the content level in the tank using LED's. It will ignore brief maximum level peaks caused by boat movements.

Panel Dimensions: 85 x 85mm

Built in depth 40mm

12/24V

Usage in standby mode 4mA, electric pump 10A max, remotely controlled ball valve 5 A max and external alarm 1A max.

Valve and level sensor are not included

Part No	Vetus	Description
56215	WWCP	Waste Water Control Panel





Vetus Petrol & Carbon Monoxide Detector 12/24V

The gas detector PD1000 detects petrol vapour to prevent the risk of explosion in the engine room, as well as poisonous carbon monoxide (CO).

Maximum relay contact ratings for extractor fan, gas solenoid valve and external alarm: 1A for each function.

Control panel dimensions: 85 x 85mm

Built in depth: 40mm Sensor 35 x 26 x 62mm

Part No	Vetus	Description
55937	PD1000	12V/24V Detector + Sensor
55938	PSENSOR	Extra Sensor



Windscreen Wiper Control Panel 12/24V

Control panel for up to three windscreen wipers.

This panel will control up to three switched windscreen wipers synchronously and also activate a screen wash system. The wipers can be set to run at high or low speed at one of five interval wipes and will self park when they are switched off. It is possible to connect up to three rain sensors (type MARBO2) for automatic operation of the wipers.

Dual voltage 12/24V

Dimensions control panel 85 x 85mm

Control unit 159 x 90 x 58mm

Built in depth 40mm

Part No	Vetus	Description
55743	RWPANEL2	Windscreen Wiper Control Panel



12V Screen Washer Kit

Suitable for all VETUS wiper types.

The screen washer is fed by a pressurised, portable water system. The screen washer comes with a hose, solenoid valve and switch, hose pillars, spray nozzles and skin fittings and is easy to install.

Part No	Vetus	Description
55739	HDS12B	12V Screen Washer Kit



Automatic Rain Sensor.

Activates wipers.

Dual voltage 12/24V.

Part No	Vetus	Description
55741	MARBO	Rain Sensor + Switch
55742	MARBO2	Additional Rain Sensor



WPANEL Windscreen Wiper Control Panel

This panel can control up to five wiper motors to run synchronously at high or low speed. Each wiper is individually switched, so you can select which wipers are operational. They also feature a combination switch for screen wash/wipe activation, speed selection and interval wipe delay. The wiper motors to be connected must have a two speed motor and an automatic parking position. It is optional to connect up to three MARBO rain sensors to the control unit. The rain sensor function can be activated by the supplied switch panel and can activate all two wipers simultaneously.

Type WPANEL is supplied with:

One control unit with electronic overload protection (can be DIN rail mounted).

Five wiper motor switches.

One combined switch for wash/wipe and speed selection.

One mounting plate with room for six switches and two blind plates.

Specifications:

Dual voltage 12/24V

Power consumption in stand by mode approx. 10 mA

Maximum power per wiper motor 120W.

Internal fuses 10 A each motor, 5 A for screen wash pump or solenoid valve.

Dimensions control panel 49 x 24 x 37.5mm

Control unit 159 x 90 x 58mm

Part No	Vetus	Description
55740	WPANEL	Windscreen Wiper Control Panel







HDMSW2

Three Position Switch


For two speed wiper motors.

Available as rotary or rocker type switch. Suitable for two-speed wiper motors RWS, DIN and HDM. Not suitable for type ORW.

Part No	Vetus	Description
55682	HDMSW	Rotary Type 7mm max panel thickness 20Amp Max switch current
55683	HDMSW2	Rocker Type 6mm max panel thickness 20Amp Max switch current

Wiper Motors Din Tapered Type + Blades





Wiper Motor with Din Tapered Ends

These high quality marine windscreen wipers feature a powerful electric motor and separate worm wheel transmission. The wiping angle may be adjusted to 8 different settings, which means that the ideal wiping pattern can be found for almost any shape and size of window. This new version is supplied with a tapered and knurled shaft end. This feature provides a stronger connection between the wiper arm and the motor drive shaft, resulting in a longer life span for both parts.

Part No	Description	Vetus
55680	Wiper Motor Cover	RWCG
55671	12V Short Spindle 25mm End	DIN1250
55672	24V Short Spindle 25mm End	DIN2425
55673	12V Long Spindle 50mm End	DIN1225
55674	24V Long Spindle 50mm End	DIN2450



RWCG



High Gloss Polished Type

Wiper Blades

Wiper blades with length of 305mm. The metal parts of the blades are made of stainless steel, either high-gloss polished or coated black. These blades will fit almost all makes and types of wiper arms with a tang of 7.2 x 2.5 mm.

	-	
Part No	Description	Vetus
55684	305mm SS Black Coated	WBB30
55685	410mm SS Black Coated	WBB41
55686	508mm SS Black Coated	WBB51
55688	305mm SS High Gloss Polished	WBS30
55689	410mm SS High Gloss Polished	WBS41
55690	508mm SS High Gloss Polished	WBS51



Black Single Arm DIN

The metal parts of this wiper arm are made of high-gloss polished stainless steel (AISI 316), and the black components are made of top-grade synthetic materials.

Part No	Description	Vetus
55708	280 - 366mm	DINPS
55709	395 - 481mm	DINPL
55710	473 - 559mm	DINPX



Black Dual Wiper Arm

Adjustable dual wiper arm. The metal parts of are made of high-gloss polished stainless steel (AISI 316) and the black components are made of top-grade synthetic materials

Part No	Description	Vetus
55697	308mm - 393mm & Taper	DINPD



Stainless 316 Single Wiper Arm Set

This very strong and durable arm is made entirely from high-gloss polished stainless steel (AISI 316). The spade connector is 7.2 x 2.5 mm.

Part No	Description	Vetus
55705	280 - 366mm	DINSS
55706	395 - 481mm	DINSL
55707	473 - 559mm	DINSX




Stainless 316 Parallel Wiper Arm Set

These arms are made entirely from highgloss polished stainless steel (AISI 316). Not only are they very strong and durable, but in combination with VETUS polished wiper blades, they will enhance the appearance of any boat.

Part No	Description	Vetus
55703	386 with Din Taper	DINSDX
55704	308 with Din Taper	DINSD

Wiper Motors RW Parallel Type





Wiper Motor with Long or Short Spindles

These high quality marine windscreen wipers feature a powerful electric motor and separate worm wheel transmission. The wiping angle may be adjusted to 8 different settings, which means that the ideal wiping pattern can be found for almost any shape and size of window. Features industry standard straight knurled shaft end (Ø16 mm, 72 teeth) for arm attachment. Can be used with single or pantograph arms.

Part No	Description	Vetus
55680	Wiper Motor Cover	RWCG
55675	12V Long Spindle 50mm	RW01A
55676	24V Long Spindle 50mm	RW02A
55677	12V Short Spindle 25mm	RW08A
55678	24V Short Spindle 25mm	RW09A



RWCG



RWASET

Connection set for Vetus parallel wiper arms.

Part No	Description	Vetus
55679	Connection Set	RWASET



Black Single Wiper Arm

Adjustable single wiper arm. The metal parts are made of high-gloss polished stainless steel (AISI 316) and the black components are made of topgrade synthetic materials.

Part No	Description	Vetus
55692	280 - 366mm	RWAS
55693	395 - 481mm	RWAL
55694	473 - 559mm	RWAX



Black Dual Wiper Arm

Adjustable dual wiper arm. The metal parts of are made of highgloss polished stainless steel (AISI 316) and the black components are made of top-grade synthetic materials.

Part No	Description	Vetus
55695	308 - 393mm	RWAD
55696	386 - 471mm	RWADX



Stainless 316 Single Wiper Arm

These arms are made entirely from high-gloss polished stainless steel (AISI 316). Not only are they very strong and durable, but in combination with VETUS polished wiper blades, they will enhance the appearance of any boat.

Part No	Description	Vetus
55698	280 - 366mm	SSAS
55699	395 - 481mm	SSAL
55700	473 - 559mm	SSAX



Stainless 316 Parallel Wiper Arm Set

These arms are made entirely from high-gloss polished stainless steel (AISI 316). Not only are they very strong and durable, but in combination with VETUS polished wiper blades, they will enhance the appearance of any boat.

Part No	Description	Vetus
55701	308 - 393mm	SSAD
55702	386 - 471mm	SSADX



Wiper Blades

Wiper blades with length of 305mm. The metal parts of the blades are made of stainless steel, either high-gloss polished or coated black. These blades will fit almost all makes and types of wiper arms with a tang of 7.2 x 2.5 mm.

	• • • • •	
Part No	Description	Vetus
55684	305mm SS Black Coated	WBB30
55685	410mm SS Black Coated	WBB41
55686	508mm SS Black Coated	WBB51
55688	305mm SS High Gloss Polished	WBS30
55689	410mm SS High Gloss Polished	WBS41
55690	508mm SS High Gloss Polished	WBS51





Heavy Duty Motor Wiper Blades

Wiper blades with length of 660mm. The metal parts of the blades are made of stainless steel, either highgloss polished or coated black. These blades will fit the HDMC series heavy duty motors.

Part No	Description	Vetus
55731	SS 316 Black	WBB66H
55732	SS 316 High Gloss	WBS66H



Heavy Duty Motor Wiper Arms

316 SS Wiper Arm

High quality, high gloss polished stainless steel parallel arm system for the HDM series Heavy Duty Vetus Wiper Motor. Suitable for Vetus blade type WBB66 or WBS66.

Part No	Description	Vetus
55734	508mm	SHDA500
55735	762mm	SHDA760

Wiper type ORW12SET

Supplied as a complete set comprising motor, arm and blade.

The arm is adjustable from 280 to 366mm. The motor is self parking, has a single speed and a wiping angle of 80° or 110°. The wiper blade is made of black synthetic and fits also other makes of wiper arms with a 7,2 x 2,5mm bayonet. Type ORW12SET meets all the EMC requirements.

12V

Max current consumption 2A

Max panel thickness 20mm

Blade length 305mm

Part No	Description	Vetus
55714	Wiper Motor Set 12V	ORW12SET
55175	Spare Blade	ORW12BL



Heating Element type WHEL

Adjustable thermostat (40-80°C.) Male thread size, ISO 228/1 G1 1/4. Screw in length of the element is 300mm.

500 Watt 230 VDC

1000 Watt 120 VDC

1000 Watt 230 VDC

1500 Watt 230 VDC

VETUS heating elements type WHEL meet the low voltage requirements.

Part No	Description	Vetus
56295	500watt 230VDC	WHEL22500
56293	1000watt 230VDC	WHEL220
56296	1000watt 120VDC	WHEL110
56294	1500watt 230VDC	WHEL1500

SHAKESPEARE HELICAL VHF ANTENNAS



HA156C HELIFLEX

Lightweight, low windage, compact helical VHF antenna for short range communications.

A favourite for racing yachts and sports

Integral aluminium masthead mounting bracket.

Part	NIa.	71	Λ1	^
Part	I∕I∪.	71	(11)	

Boats

1 41110: 7 1010		
Cable Included	20m RG58	
Connector Included	PL-259 Connector	
Antenna Length	0.15m (0.5ft)	
Gain	1 dB	
Suitable for: Sailing Boat, Ribs & Motor		



5912 RUBBER DUCK

Lightweight, low windage, compact helical VHF antenna for short range communications.

Ideal for emergency or temporary installations and particularly suitable for cabin or console tops.

Attaches and detaches with ease using supplied flush mounting kit.

Part No: 71451

Х Cable Included

Gold Plated Connector Included

Antenna Length 0.18m (0.6ft)

Gain

Suitable for: Sailing Boat, Ribs & Motor **Boats**

Connectors

1 dB



MD23 SHORT HELICAL ANTENNA

Low profile

Low windage

Unobtrusive

Does not require ground plane

Over-moulded helical

150mm aluminium bracket

Fitted with integral 'N' jack to allow detachable cable

Part No: 71035

Cable Included Χ Connector Included Χ


Antenna Length 0.3m (1ft)


Suitable for: Sailing Boat, Ribs & Motor

Gain 1 dB

Boats

SHAKESPEARE STAINLESS STEEL VHF ANTENNAS





YWX WHIPFLEX™


Stainless steel whip VHF antenna for sail

Unique solderless watertight masthead connector system for easy installation and dismounting.

Lightweight - 0.15 kilo with bracket

Includes 180mm cranked masthead nylon mounting bracket

Cable Included 20m RG58 Connector Included PL-259 Connector Antenna Length 0.9m (3ft) 3 dB Suitable for: Sailing Boat & Ribs



With reflecting material on the vanes. Consists of one moving part and two fixed vanes of stainless steel. With mounting instructions.

Part No	Description
71449	Windex Dinghy 10"
71450	Windex 15"
71448	Windex XL 22"

SHAKESPEARE STAINLESS STEEL VHF ANTENNAS







5215 SQUATTY BODY®

Stainless steel whip VHF antenna for sail boats.

Lightweight and low profile.

Removable whip.

Sealed, tin-plated copper wire coil.

Part No: 71452		
Cable Included	Χ	
Connector Included	SO-239 (UHF) ir Base	
Antenna Length	0.9m (3ft)	
Gain	3 dB	
Suitable for: Sailing Boat		

5247-A LIFT 'N' LAY

Heavy-duty stainless steel whip 'lift and lay' VHF antenna.

Ideal for sports fishing boats and smaller power boats.

Simple to set up and lay down, ensuring the antenna does not obstruct when fishing or storing the boat.

Sealed, tin-plated copper wire coil.

Part No: 71453	
Cable Included	X
Connector Included	SO-239 (UHF) in Base
Antenna Length	0.9m (3ft)
Gain	3 dB
Suitable for: Ribs, Motor Boats & Fishing Boats	

5216

Lightweight, black stainless steel VHF antenna for short range communications

Ideal for sports sailing boats

Gold plated connector

'L' bracket for mast top mounting

Part No: 71454	
Cable Included	Χ
Connector Included	Gold Plated Connector
Antenna Length	0.3m (1ft)
Gain	1 dB
Suitable for: Sailing B	oats

SHAKESPEARE STAINLESS STEEL VHF ANTENNAS



5250 SKINNY MINI ™

Compact, lightweight, stainless steel whip VHF antenna.

Ideal for small power boats.

Sealed, tin-plated copper wire coil.

Requires a mount with centre hole for cable.

Suggested mounts: 4187, 5187, 4188-S or 4190

Chromed brass ferrule.

Part No: 71455	
Cable Included	4.5m RG58
Connector Included	PL-259 PLUG
Antenna Length	0.9m (3ft)
Gain	3 dB
Suitable for: Ribs & Motor Boats	



5241-R

Heavy duty stainless steel whip VHF antenna.

Ideal for fast sports boats, RIBs and small fishing boats.

Whip is user replaceable.

Requires a mount with centre hole for

Chromed brass ferrule.

Part No: 71456	
Cable Included	4.5m RG58
Connector Included	PL-259 PLUG
Antenna Length	0.9m (3ft)
Gain	3 dB
Suitable for: Ribs & Motor Boats	



YRR RIB RAIDER ™

Designed specifically for RIBs.

Short helical design to avoid snagging and excessive whip action.

Solderless connector system.

Integral black bracket with mounting holes.

Part No: 71145	
Cable Included	6m RG58
Connector Included	PL-259 PLUG
Antenna Length	0.48m (1.6ft)
Gain	3 dB



5911 THE STOWAWAY ™

Short VHF whip antenna with flexible outer covering.

Ideal as a temporary, spare or emergency antenna.

Rubber suction cup for easy mounting.

Velcro storage strips included.

Packed in a 50cm, weather resistant, retail plastic tube.

Part No: 71457

Cable Included	3.6m RG58
Connector Included	PL-259 PLUG
Antenna Length	0.25m (0.8ft)
Gain	1 dB
Cuitable for Cailing D	ooto Dibo 9 Mot

Suitable for: Sailing Boats, Ribs & Motor **Boats**

SL 156 SHORELINK ™

Emergency VHF antenna for instant set up if your main antenna becomes broken or disabled.

Suitable for: Ribs

Sealed in a waterproof 24cm weather resistant plastic tube.

Stored easily on bulkhead or in flare pack.

6m of miniature coaxial cable (RG-174) with PL-259 connector fitted.

Compulsory for R.O.R.C. racing.

Part No: 71020

Cable Included	6m RG-174
Connector Included	PL-259 PLUG
Antenna Length	0.4m (1.3ft)
Gain	1 dB

Suitable for: Sailing Boats, Ribs & Motor



SHAKESPEARE STAINLESS STEEL VHF ANTENNAS

MD20 Rugged Stainless Steel Whip Antenna. Stainless steel whip. Lightweight (0.2kg). Low windage. 180mm cranked nylon bracket for masthead mounting. Watertight, strong construction. Part No: 71025 Cable Included 20m RG58 Connector Included PL-259 PLUG Antenna Length 0.9m (3ft) Gain 3 dB Suitable for: Sailing Boats, Ribs, Motor

MD20N	
Rugged Stainless Steel Whip Antenna.	
Stainless steel whip.	
Lightweight.	
Low windage.	
200mm braced alumin masthead mounting.	nium bracket for
Watertight, strong cor	nstruction.
Fitted with integral 'N' jack to allow detachable cable.	
Part No: 71030	
Cable Included	X
Connector Included	N Type Jack
Antenna Length	0.9m (3ft)
Gain	3 dB
Suitable for: Sailing Boats, Ribs, Motor Boats & Fishing Boats	

SHAKESPEARE FIBREGLASS VHF ANTENNAS

Boats & Fishing Boats



426-N

White fibreglass VHF antenna.

Designed for high speed sports boats and RIBs working in rough conditions.

Quality copper cable elements for good range and efficiency.

Nylon ferrule.

Part No: 71458

Cable Included	4.5m RG58
Connector Included	PL-259 PLUG
Antenna Length	1.2m (4ft)
Gain	3 dB

Suitable for: Sailing Boats, Ribs, Motor Boats & Fishing Boats



5104 CENTENNIAL ®

Durable, smooth, white fibreglass VHF antenna with polyurethane finish that will not yellow in the sun. A good looking and superb value antenna, ideal for power and work boats.

Brass and copper elements for extra performance.

Chromed brass ferrule.

Part No: 71459

Cable Included	4.5m RG58
Connector Included	PL-259 PLUG
Antenna Length	1.2m (4ft)
Gain	3 dB
Suitable for: Sailing Boats, Ribs, Motor Boats & Fishing Boats	

SHAKESPEARE FIBREGLASS VHF ANTENNAS



5400-XT LITTLE GIANT™

Heavy-duty, high gloss, smooth Galaxy White fibreglass VHF antenna with polyurethane finish that will not yellow in the sun.

Centre-fed 1/2 wave coaxial sleeve.

An outstanding, heavy-duty antenna, ideal for power boats, work and fishing boats operating in all types of conditions.

Brass and copper elements to maximise range and performance.

Matches 5420-XT / 5421-XT AM/FM antennas

Stainless steel ferrule.

Part No: 71460 WHITE Part No: 71461 BLACK

Cable Included	6m RG-8x Ultra Loss
Connector Included	PL-259 PLUG
Antenna Length	1.2m (4ft)
Gain	3 dB

Suitable for: Sailing Boats, Ribs, Motor **Boats & Fishing Boats**

5400-XP

Heavy-duty, high gloss, smooth Galaxy white fibreglass VHF antenna with polyurethane finish that will not yellow in the sun.

"Silver Series" (extends transmit/ receive performance).

Centre-fed 1/2 wave coaxial sleeve.

Exceptionally efficient performing heavy-duty antenna, ideal for serious power boat, work and fishing boat operators in all types of conditions. Stranded high quality tinned copper inner conductor maximises signal strength, combined with the copper and silver plated brass elements that will extend performance and life.

Stainless steel ferrule.

Part No: 71462 WHITE

Cable Included	6m RG-8x Ultra Loss
Connector In- cluded	PL-259 PLUG
Antenna Length	1.2m (4ft)
Gain	3 dB

Suitable for: Sailing Boats, Ribs, Motor **Boats & Fishing Boats**

427-N & 427-N KIT

Durable smooth gloss finished white fibreglass VHF antenna.

Very good value, this antenna is ideal for power and work boats.

Brass and copper elements for extra performance.

Matches 5350-N AM/FM antenna.

Nylon ferrule.

N Kit comes with 4186 nylon ratchet mount supplied and packaged in a box.

Part No: 71040 (427-N)

Part No: 71050 (427-N Kit)

,	•
Cable Included	6m RG58
Connector Included	PL-259 PLUG
Antenna Length	1.5m (5ft)
Gain	3 dB

Suitable for: Ribs, Motor Boats & Fishing



427-S

Durable smooth gloss finished white fibreglass VHF antenna.

A very good looking antenna, ideal for power and work boats.

Brass and copper elements for extra performance.

Matches 5350-S AM/FM antenna.

Stainless steel ferrule.

Part No: 71045

Cable Included 6m RG58 Connector Included PL-259 PLUG Antenna Length 1.5m (5ft) 3 dB Gain

Suitable for: Ribs, Motor Boats & Fishing Boats

SHAKESPEARE FIBREGLASS VHF ANTENNAS



5101-S

Durable, smooth, white gloss fibreglass VHF antenna.

Good looking and excellent value, ideal for power and work boats.

Brass and copper elements for extra performance.

Twin to 5120-S AM/FM antennas.

Stainless steel ferrule.

Part	No:	71	055
------	-----	----	-----

Cable Included	6m RG58
Connector Included	PL-259 PLUG
Antenna Length	2.4m (8ft)
Gain	6 dB

Suitable for: Ribs, Motor Boats & Fish-

ing Boats

SHAKESPEARE AIS ANTENNAS



1 AIS-MAST

Stainless Steel AIS Masthead Antenna.

Stainless steel whip.

Lightweight.

Low windage.

180mm nylon cranked bracket for masthead mounting.

Watertight strong construction.

Part No: 71175

Cable Included	20m RG58
Connector Included	PL-259 PLUG
Antenna Length	0.9m (3ft)
Gain	3 dB

Suitable for: Sailing Boats, Ribs & Motor Boats

SHAKESPEARE AIS ANTENNAS



HA 156C-AIS

Lightweight, low windage, compact helical AIS antenna.

A favourite for racing yachts and sports

Integral aluminium mounting bracket.

Part No: 71463

Cable Included	20m RG58	
Connector Included	PL-259 PLUG	
Antenna Length	0.15m (1ft)	
Gain	1 dB	
Cuitable fam Cailing Danta Diba 9		

Suitable for: Sailing Boats, Ribs & **Motor Boats**



MD 23-AIS (MD23N)

Extra heavy-duty helical AIS antenna for short range communications.

Ideal for sail and power boats to withstand the most rugged conditions.

Watertight, strong, lightweight (0.3kg) construction.

Electronics are sealed in epoxy for additional protection.

Supplied with 180mm aluminium bracket.

Part No: 71464

Falt No. 7 1404	
Cable Included	20m RG58
Connector Included	PL-259 PLUG
Antenna Length	0.3m (1ft)
Gain	1 dB
0 11 11 6 0 11 1	D (D') 0 M (

Suitable for: Sailing Boats, Ribs & Motor **Boats**

SHAKESPEARE AM / FM ANTENNA & SPEAKERS

5350-N

AM/FM fibreglass antenna with polycarbonate ferrule.

White tapered fibreglass tube.

White polycarbonate ferrule.

1" X 14 TPI thread.

Part No: 71070

Cable Included	4.6m RG-62
Connector Included	Motorola PLUG
Antenna Length	1.5m (5ft)
Gain	X

Suitable for: Sailing Boats, Ribs & Motor **Boats**



WS200-P

Weatherproof Deck Watch Loud Speaker.

Can be surface or flush mounted.

UV Resistant ABS construction.

Can be used on 4 or 8 ohm systems.

Overall diameter 14cm depth 5cm.

Hole diameter of 11.6cm for flush mounting.

Output 5 watts Impedance 8 ohms.

Weight 0.3 kilo

Blister packed

Part No: 71185



HS-5

External Horn Speaker.

12.7cm white plastic horn speaker.

4 ohm speaker, 15 watts (RMS) input.

Part No: 71478



ES-2

6cm external speaker with Mylar cone in a compact white housing.

4 ohm speaker, 5 watts (RMS) input.

Rachet action mounting bracket.

1.8m cable and 3.5mm phono plug.

Part No: 71479



ES-4

10cm deluxe speaker with Mylar cone in white plastic case for protection against moisture.

4 ohm speaker, 8 watts (RMS) input.

Swivel mounting bracket.

1.8m cable with 3.5mm phono plug.

Part No: 71480



4357-S

VHF to AM/FM converter.

For use with VHF antennas where a separate AM/FM antenna is not practical.

Ideal for sail boat applications.

Does not affect or interfere with the VHF performance.

3m RG-62 cable with Motorola plug (attached) plus 0.9m RG-58 cable for connection to VHF.

Part No: 71080

SHAKESPEARE AM / FM ANTENNA & ACCESSORIES



ART 2 VHF TEST METER

Test receiver function

Output power and VSWR (antenna efficiency)

Internal battery or 12 DC

PL259 (UHF) type connectors

Part No: 71443



AS-2 VHF AUTOMATIC SWITCH

This automatic switch toggles two radios to one antenna. When you key the microphone on one of the radios, it switches the antenna to it... automatically. The radio stays locked onto the antenna until the automatic switch detects a transmit from the other radio. Easy!

Specifications:

Frequency Range: up to 600 MHz

VSWR: Below 1.2:1 Power Rating: 30 W Impedance: 50 ohms Connections: SO-239 type Power Supply: 12 vDC @ 200 ma Sensing/Switching Time: Less than 100

ms

Part No: 71468



MAST EXTENSIONS

Heavy-duty stainless steel extension mast with standard 1"-14 thread male and female fittings.

Part No	Description	
71469	6" (15cm) 4700	
71470	12" (30cm) 4700-1	
71471	24" (60cm) 4700-2	



4716 STAND OFF BRACKET

80mm black nylon with 1" X 14 TPI adaptor. 16mm hole.

Part No: 71191



4717 MAST TOP BRACKET

180mm to hole centre.

16mm dia hole.

Part No: 71192



YBR Right Angled Bracket

Black Aluminium. 16mm mounting hole.

Part No: 71193



ADAPT1

M16 Thread to 1" X 14 TPI

Part No: 71441



ADAPT2

1" X 14 TPI to M16 Thread

Part No: 71442



ADAPT3: Adapts SO-239 (UHF) male to 1" x 14 TPI female thread (chrome plated brass) - (converts 5215 & 5247 antennas to 1" x 14 TPI)

Part No: 71466




ADAPT4: Adapts M16 male to 1" x 14bTPI female thread - (converts YRR, YWX, YHK antennas to 1" x 14 TPI)

Part No: 71467



DECK PLUG & SOCKET

Deck plug and socket with 'N' type connector, shroud and screws. Available to suit RG58 (ACC105) or RG213 (ACC106) cable.





ACC156 BNC JACK AND PLUG & RG-58 SHROUD KIT

Contains: 1x BNC Plug 1x BNC Jack 2x RG-58 Shrouds

Part No Shakespeare 71250 ACC156

SHAKESPEARE ACCESSORIES & MOUNTS





Cable Splicer for RG58

The easy way to join or splice RG58 cable. No measuring, no stripping, no soldering!

Part No	Shakespeare
71265	PL-258-CP-G

CENTERPIN PL-259-CP-G SERIES

For RG-58 A/U, and RG-8/X coaxial cable. For installing a PL-259 connector. No soldering or pairing back

Part No	Shakespeare
71472	PL-259-CP-G







Solderless Cable **Termination Kit**

All the spare parts used for solderless terminations on the Hawk, Whipflex and Raider

Part No	Shakespeare
71270	ACC158



N Type Plug

RG58

ACC140

Part No 71225



N Type Jack

RG58

ACC142

Part No 71230



N Type Plug

RG213

ACC144

Part No 71235



UHF Plug

RG58

ACC148

PL259-58-G

Part No 71240



UHF Plug

RG213

PL-259-G

Part No 71245



BNC PLUG

RG58

ACC154

Part No 71255



BNC JACK

RG58

ACC155

Part No 71260



BNC Kit

A6 -100

Part No 71637



PL259/5 Plug

A6 -104

Part No 71638



UHF (PL259) Inline Adaptor

Accepts two male PL259 plugs

A6-109

Part No 71639



Deck Connectors

Available with either 'N' type or UHF type connectors to suit RG58 or RG213 cable. Complete with rubber gasket and protection caps.

Connector	Cable	Part No	Shakespeare
N type	RG58	71210	ACC130
N type	RG213	71215	ACC133
UHF	RG58 / RG213	71220	ACC135



ACC108 Thru Deck Gland

Thru deck gland for RG-58 and RG-213 cable complete with stainless steel screws.

Blister packed

Part No 71200



RG58 COAXIAL CABLE

8 and 20m packs include solderless cable termination and UHF (PL259) plug.

Description	Part No
8m RG58 with connectors	71430
20m RG58 with connectors	71435
100m RG58 only	71440



4187 S/STEEL RATCHET MOUNT

4 way swivel mount.

For deck or side mounting.

Quick release lever allows antenna fold-down.

Suitable for all powerboat antennas.

Part No: 71085



4710 S/STEEL 25MM FLANGE **MOUNT**

Heavy duty 25mm (1") high mount.

70mm (2 3/4") diameter base.

Ideal for GPS, marine TV and fibreglass antennas up to 1.5m long

Part No: 71125



4186 NYLON RATCHET MOUNT

4 way swivel mount.

For deck or side mounting.

Quick release lever allows antenna fold-down.

Made from UV resistant white nylon.

Not for use with antennas longer than 2.4m.

Part No: 71090



5187 S/STEEL RATCHET MOUNT

Nutless, streamlined design.

4 way swivel mounting.

Quick release lever allows antenna fold-down.

Highly polished finish.

Suitable for all powerboat antennas.

Part No: 71095



4711 NYLON 25MM FLANGE MOUNT

White nylon 25mm (1") high mount.

70mm (2 3/4") diameter base.

Suitable for moderate duty applications.

Part No: 71130



4365 S/STEEL 110MM FLANGE MOUNT

Sturdy, 100mm (4") high mount.

75mm (3") base.

Ideal for fitting to radar arches.

Excellent for GPS and marine TV antennas.

71120 Part No:



4190 RAIL RATCHET MOUNT

Ratchet action for antenna fold down.

Easy installation on 22mm (7/8") and 25mm (1") vertical or horizontal rails.

Not for use with antennas longer than 2.4m.

Part No: 71100

4722 PLASTIC RAIL MOUNT

Incorporates slot for cable.

Complete with adaptor, rubber gasket and hexagon key.

Ideal for GPS antennas.

Made from durable white nylon.

Part No:



4721 NYLON RAIL MOUNT

Ratchet action for antenna fold down.

Easy installation on 22mm (7/8") and 25mm (1") vertical or horizontal

Complete with rubber gasket.

Made from durable, white nylon.

Part No: 71105

Fits 22mm (7/8") and 25mm (1") horizontal rails.

71115



Clever design allows a neat fit to 22mm (7/8"), 25mm (1") and 32mm (1 1/4") square or round rails.

For vertical or horizontal rails.

Can also be mounted on flat surfaces.

Complete with nylon adaptors.

Part No: 71110







SHAKESPEARE TV & CELLUAR ANTENNAS



SA-HDTV-MAR8 AnyWhere Marine HDTV 8"

203H x 110W mm (8" x 4.3") Omni Directional HDTV antenna (with built-in LTE filter).

Newly designed using the latest TV technologies.

Compact, lightweight, weatherproof HDTV antenna. Comes with built in high gain, low noise amplifier and LTE filter. Ideal for small power boats and sail boats.

Includes amplifier gain control unit.

10m 75 Ohm RG59 cable with 2 x F connectors + IEC to F connector.

1.5m adapt cable fitted with F plug to IEC •Power 12/24V DC - AC/DC power adaptor (UK/EURO) included.

Receiving range FM/VHF/UHF (VHF:87-230MHz UHF: 470-862).

Gain: 30dB / Noise figure: 3dB.

Max. output level: 110 dB μ V / Impedance: 75 Ω .

Outputs: x 2 TV's.

Fits to standard 1"-14 threaded mount.

Part No 71474



Omni Directional HDTV antenna (with built-in LTE filter)

Newly designed using the latest TV technologies.

Compact, lightweight, white ASA, weatherproof HDTV antenna. Comes with built in high gain, low noise amplifier and LTE filter. Ideal for small power boats and sail boats.

Includes amplifier gain control unit.

25m 75 Ohm RG59 cable with 2 x F connectors + IEC to F connect-

1.5m adapt cable fitted with F plug to IEC.

Power 12/24V DC - AC/DC power adaptor (UK/EURO) included.

Receiving range FM/VHF/UHF (VHF:87-230MHz UHF: 470-862).

Gain: 30dB / Noise figure: 3dB.

Max. output level: 110 dB μ V / Impedance: 75 Ω .

Outputs: x 2 TV's.

Fits to 1"-14 threaded mount.

Part No	Description
71475	SA-HDTV-MAR10 AnyWhere Marine HDTV 10'
71476	SA-HDTV-MAR14 AnyWhere Marine HDTV 14'



9.25" (.23m) World Band Cellular Antenna

The Galaxy 5239 antenna is our smallest Galaxy antenna, but don't let the size fool you. This World-band antenna provides coverage for 2G/3G/4G and WLAN systems for Cellular, PCS, AWS and LTE frequencies, as well as 802.11n Wi-Fi. This compact, feature rich antenna is at home on virtually any watercraft, and is fitted with a stainless steel ferrule and N-connector that are compatible with nearly all Shakespeare 1" -14 threaded mounts.

Full Band (698 - 2700 MHz) Broadband

2G/3G/4G and WLAN systems

Wi-Fi 802.11n compatible

Designed for marine use

Omni-directional antenna 3-4 dB Gain

Easy to install

Part No: 71477

Cutlass Bearings

Precision ground inside and outside. Large range of sizes kept in stock. Nitrile Liner. Outstanding abrasion resistance. Excellent for water lubrication. Good noise damping. More tolerant of misalignment. Allow greater deflection Shell- Brass Shell (standard naval brass)- tough and durable



Imperial Shaft - Imperial Outer Diameter - Imperial length

Part No	Description	Inner Diameter Inches	Outer Diameter Inches	Length Inches	Part No	Description	Inner Diameter Inches	Outer Diameter Inches	Length Inches
96600	Brass Shell Bearing	3/4"	1 1/4"	3"	96613	Brass Shell Bearing	1 1/4"	1 3/4"	5"
96601	Brass Shell Bearing	7/8"	1 3/8"	3 1/2"	96614	Brass Shell Bearing	1 1/4 "	1 5/8"	5"
96602	Brass Shell Bearing	7/8"	1 1/4"	3 1/2"	96615	Brass Shell Bearing	1 1/4"	2"	5"
96603	Brass Shell Bearing	7/8"	1 1/2"	3 1/2"	96616	Brass Shell Bearing	1 1/4"	2 1/8"	5"
96604	Brass Shell Bearing	1"	1 1/2"	4"	96617	Brass Shell Bearing	1 3/8"	1 7/8"	5 1/2"
96605	Brass Shell Bearing	1"	1 1/4"	4"	96618	Brass Shell Bearing	1 1/2"	2"	6"
96606	Brass Shell Bearing	1"	1 3/8"	4"	96619	Brass Shell Bearing	1 3/4"	2 3/8"	7"
96607	Brass Shell Bearing	1"	1 5/8"	4"	96620	Brass Shell Bearing	2"	2 5/8"	8"
96608	Brass Shell Bearing	1"	2"	4"	96621	Brass Shell Bearing	2"	2 3/4"	8"
96609	Brass Shell Bearing	1 1/8"	1 5/8"	4 1/2"	96622	Brass Shell Bearing	2 1/4"	2 15/16"	9"
96610	Brass Shell Bearing	1 1/8"	1 1/2"	4 1/2"	96623	Brass Shell Bearing	2 1/2"	3"	10"
96611	Brass Shell Bearing	1 1/8"	1 3/4"	4 1/2"	96624	Brass Shell Bearing	3 1/4"	4"	13"
96612	Brass Shell Bearing	1 1/8"	2"	4 1/2"					

Metric Shaft - Imperial Outer Diameter - Metric Length


Part No	Description	Inner Diameter mm	Outer Diameter Inches	Length mm
96625	Brass Shell Bearing	25mm	1 1/2"	100mm
96626	Brass Shell Bearing	25mm	1 3/8"	100mm
96627	Brass Shell Bearing	28mm	1 5/8"	112mm
96628	Brass Shell Bearing	30mm	1 3/4"	120mm
96629	Brass Shell Bearing	35mm	1 7/8"	140mm
96630	Brass Shell Bearing	40mm	2 1/8"	160mm
96631	Brass Shell Bearing	50mm	2 5/8"	200mm

Metric Shaft - Metric Outer Diameter - Metric Length

Part No	Description	Inner Diameter	Outer Diameter	Length
		mm	mm	111111
96632	Brass Shell Bearing	20mm	35mm	80mm
96633	Brass Shell Bearing	22mm	35mm	88mm
96634	Brass Shell Bearing	25mm	40mm	100mm
96635	Brass Shell Bearing	30mm	45mm	120mm
96636	Brass Shell Bearing	32mm	45mm	128mm
96637	Brass Shell Bearing	35mm	50mm	140mm
96638	Brass Shell Bearing	40mm	55mm	160mm
96639	Brass Shell Bearing	45mm	65mm	180mm
96640	Brass Shell Bearing	50mm	70mm	200mm

Vetus cutlass bearings with brass outer bushing and polyurethane-rubber lining.

Part No	Vetus Code	Inner Diameter	Outer Diameter	Length
57804	RULAG1	1"	1 1/2"	4"
57805	RULAG11/8	1 1/8"	1 5/8"	4 1/2"
57806	RULAG11/4	1 1/4"	1 3/4"	5"
57807	RULAG13/8	1 3/8"	1 7/8"	5 1/2"
57808	RULAG11/2	1 1/2"	2"	6"
57809	RULAGER25	25mm	1 1/2"	100mm
57810	RL2540	25mm	40mm	100mm



Metric Shaft - Imperial Outer Diameter - Metric length

Part No	Description	Inner Diameter mm	Outer Diameter Inches	Length mm
96641	Phenolic Shell	25mm	1 1/2"	100mm
96642	Phenolic Shell	35mm	1 7/8"	140mm

Metric Shaft - Metric Outer Diameter - Metric length

Part No	Description	Inner Diameter mm	Outer Diameter mm	Length mm
96643	Phenolic Shell	25mm	40mm	100mm
96644	Phenolic Shell	30mm	45mm	120mm
96645	Phenolic Shell	35mm	50mm	140mm

A lightweight paper wound Phenolic resin shell avoids the problem of galvanic corrosion and is suitable for metal stern tubes. These bearings do not possess the structural stability of metals and have a shorter operational life. They swell slightly when immersed in water and are therefore machined to tolerances to accommodate this.



Propprotector Install some PEACE OF MIND, FIT A PROP PROTECTOR

Suitable for commercial
and leisure vessels.

Part No	Description
91590	Slide On 25mm
91591	Clamp On 25mm
91592	Slide On 30mm
91593	Clamp On 30mm
91594	Slide On 40mm
91595	Clamp On 40mm
91596	Slide On 1"
91597	Clamp On 1"
91598	Slide On 1 1/4"
91599	Slide On 1 1/2"






The Prop Protector is a simple shaft driven rope cutter, rotating with the shaft and instantly cutting any rope, weed or debris picked up or snagged by the propeller. Manufactured from high grade (316) Stainless Steel, the Prop Protector is easy to install fully installed in minutes - with your boat out of the water or between tides. The clamp-on version can even be fitted by a diver if underwater installation is required. The Prop Protector sits on the shaft, between the propeller hub and the stern bearing, waiting to cut anything that threatens to entangle it. There are no moving parts to fail - just a razor sharp marine grade stainless steel blade - ready to slice through most marine debris. Available to suit shaft sizes 20mm (3/4 in) to 130mm (5 in). Prop Protectors can be fitted to a wide range of boats (yachts, motor cruisers, fishing vessels, barges etc), and are available in two models, the Clamp-On & the Slide-On.

Manufactured from high grade (BS970-316) Stainless Steel.







Rope Cutter

Designed to stop ropes jamming between the cutlass bearing and the propeller. The Vetus rope cutter (VRC) is a circular AISI Type 316 stainless steel saw blade positioned behind the propeller. It is made up 2 parts and is suitable for 25mm or 30mm propeller shafts. Includes both halves of the disc and nuts and bolts.

Part No	Vetus	Description
57660	VRC25	25mm Shaft (115 x 25mm Main Dimensions)
57661	VRC30	30mm Shaft (115 x 30mm Main Dimensions)

Stern Gland Packing



Quality yarn impregnated with petroleum jelly and coated with flake graphite.

Sold in 1m cut lengths. The maximum complete length of any one size 8m.

length of any one size offi.		
	Part No	
Size	1 Metre	
1/4" (6mm)	91740	
5/16" (8mm)	91741	
3/8" (10mm)	91742	

Stern Gland Lubricator



Brass lubricator for stern tubes, rudder bearings etc. Bulkhead or floor mounted.

Capacity: 150ml, Outlet 1/8" BSP.

An accessory kit is also available which contains 2 X 1/8" BSP connectors, 1 X 1/4" BSP connector and 3m of nylon hose.

Part No	Description
91745	Brass Lubricator
91746	Accessory Kit

Grease





Aqua Slip - 500grams

Carlube Aqua Slip Grease provides

high resistance to salt water

corrosion and water washout in

addition to allowing good shear

stability over a wide temperature

including, trailer wheel bearings,

stern tubes/propeller shafts, cables

range. It is suitable for a wide

range of marine applications







Morris K99 Stern Tube Grease -500grams

This grease has outstanding water resistant qualities and is designed to form a special seal at the water interface. This grade is a high quality lead-free calcium hydroxide stearate grease with special additives to provide extreme pressure properties, improve oxidation resistance and protect against rust and corrosion. Recommended for grease filled stern tubes. Also suitable for plain and antifriction bearings operating in very wet conditions.

Part No 91730

Part No

63076

and pulleys etc.

MPG - 500grams

Universal Marine Grease

MPG is a multi-purpose lithium based grease containing zinc oxide additive to repel moisture making it particularly suitable for use in marine outboard and inboard engines. Also ideal for use in boat trailer hubs and stern tubes.


Part No	Description
91761	MPG Grease 500grm

Mechanical engine remote controls

All remote controls (except type AFST) have a neutral safety switch as standard, which prevents the engine from being started when the gearbox is engaged. Controls which are shown with a red knob are also supplied with a black knob as standard.

With stainless steel (AISI 316) handle and housing. Vetus single lever remote control for side mounting. The push-pull cables can be installed horizontally or vertically.

Part No	Vetus	J	Width (mm)	J	Handle length from centre (mm)	Mechanism depth from centre (mm)
57098	SISCO	142	122	85	200	243
57090	SISCOG	142	122	85	200	243



Vetus single lever remote control for side mounting.

Part No	Vetus	Length (mm)		J	Handle length from centre (mm)	Mechanism depth from centre (mm)
57105	SICO	147	127	85	200	243
57091	SICOG	147	127	85	200	243

With high-gloss polished stainless steel (AISI316) handle and housing.

Vetus single lever remote control for top mounting.

	-			-		
Part No	Vetus	Length (mm)		0	Handle length from centre (mm)	Mechanism depth from centre (mm)
57102	RCTOPS	162	104	237	200	208
57092	RCTOPSG	162	104	237	200	208

With high-gloss polished stainless steel (AISI316) handles and housing.

Vetus twin lever remote control for top mounting.

Part No	Vetus	0		U	Handle length from centre (mm)	Mechanism depth from centre (mm)
57103	RCTOPTS	162	200	237	200	208
57093	RCTOPTSG	162	200	237	200	208

With cast aluminum housing and stainless steel (AISI 316) handles.

VETUS twin lever remote control for top mounting.

Part No	Vetus	J		J	Mechanism depth from centre (mm)
57108	RCTOPTB	162	200	237	208
57094	RCTOPTBG	162	200	237	208

With cast aluminum housing and stainless steel (AISI 316) handles.

VETUS single lever remote control for top mounting.

Part No	Vetus	•		•	Mechanism depth from centre (mm)
57107	RCTOPB	162	104	237	208
57095	RCTOPBG	162	104	237	208







RCTOPS RCTOPSG



RCTOPTS RCTOPTSG



RCTOPTB RCTOPTBG



RCTOPB RCTOPBG



Type AFSTTOPT

Vetus twin lever control for top mounting with synthetic housing and handle. Top mounting for twin engines.

Type AFSTTOP

Vetus single lever control for top mounting with synthetic housing and handle. Top mounting for single engine.

Part No	Vetus	Length (mm)	Width (mm)	•
57114	AFSTTOPT	154	208	238
57113	AFSTTOP	154	118	238



Type AFSTZIJ

This side mount engine control can be used with mechanically controlled engines from 12 - 110 hp. The AFSTZIJ should be mounted in reach of the vessel's helm on either port or starboard side.

The mechanical part of the lever is made of painted zinc, finished with a synthetic housing and an ergonomically shaped rubber grip. The AFSTZIJ works with 33c Edge Control Cables and features an integrated safety mechanism to protect the transmission. The gearbox can only be shifted at idling speed. The AFTZIJ is the ideal engine control for sailing boats.

Part No	Vetus	Length (mm)		J
57112	AFSTZIJ	138	110	78



AFSTZIJ

Ultraflex B183 Single Lever Control Box

Single lever / dual action control to operate both throttle and shift.


Suitable for any type of boats with outboard-inboard or I/O power plants.


The lever assembly is made of painted marine aluminium.

Compatible with 33c cables.

Part No	Description
49020	Ultraflex B183 Single Lever Control







Ultraflex B85 Single Lever Control Box

The Ultraflex B85 is a single lever / dual action control to operate both throttle and shift. Suitable for any type of boat with outboard, inboard or I/O engines.

Features on the B85 enable easy and safe shifting by preventing accidental gear engagement unless engine is idling and can be installed horizontally or vertically, on either the starboard or port side of the boat.


The lever assembly is made of painted marine aluminium.


Compatible with 33c cables.

Part No Description

49021 Ultraflex B85 Single Lever Control











DS-Kit Throttle

Combines the action of the single lever control from either of two command stations and provides a single output to the engine throttle lever. (Only suitable for throttle control by pulling).

Part No	Vetus	Description
57121	DSKITF	Dual Station Kit
		for Throttle



DS-Unit Gearbox

Combines the action of the single lever control from either of two command stations and provides a single output to the gearbox lever.

Part No	Vetus	Description
57120	DS	Dual Station Kit for Gearbox



Type DC

Type DC is corrosion resistant and easy to install (horizontally or vertically) and can be pushed with 33c control cables. Comes with a 30° mounting bracket.

Part No	Vetus	Description
57122	DC	Cable pull handle type DC



Twin Station Control		
Part No	Multiflex	Description
49159	LM-K-13	Twin Station Control



Throttle mechanism for Vetus engine controls type SICO, SISCO and RC-series (RCSIDE, RCTOP, RCTOPT & variants). Comprises complete throttle mechanism with neutral stop switch.

Part No Description

57081 RC01A



Handle attachment kit for side remote control handles.

Part No Description

57115 RC01C



Spare Black Knob 40mm

Part No Description

57096 RC08B



Spare Red Knob 40mm

Part No Description

57097 RC08



Cable fitting kit for Vetus Sico & Sisco

Part No Description

RC01B 57080



Topmount Lever T BAR

Part Description No

RC06RG

57083



Sidemount SS Lever Spare Lever

Part No Description 57084 RC03R



Sidemount SS Lever Spare Lever

Part No Description



33C Cable Ball Joint

Stud 6mm

Material = Zinc Plated Steel

Part No Description

91785 6mm 33c Ball Joint



33C Cable Ball Joint.

Part No Vetus Description 57178 KOGELGEWR 33C Cable



33C Cable Ball Joint.

Part No Multiflex Description

Ball Joint 33C 49156 LM-K-9



Brass Pivot + Split Pin Spindle Dia. 6.4mm. Thread 10-32 UNF. CO/C2/C8 cables.

Lever thickness 3mm Part No Description

Brass Pivot + Split Pin 91786



Ball Joint

SS Pivot 33C

Part No Multiflex Description 49157 LM-K-10 Stainless Steel Pivot + Split Pin



Clevis End Connector

Plated Steel.

7.1mm jaw width with 6.4mm diameter pin .

Part No Description 91789 Clevis End



33C End Eye Metal

Part No Multiflex Description

49154 LM-K-7 End Eye Metal



33C Plastic Pivot

Part No Multiflex Description 49158 LM-K-11 Plastic Pivot



Ball Joint 33C RJ

Part No Multiflex Description

LM-K-14 BALL JOINT 33C RJ 49160



33C End Eye Plastic

Part No Multiflex Description 49155 End Eye Plastic



Cable clamp

33C Cable Clamp.

Part No Vetus Description KABELKL 33C Cable Clamp 57177



Clevis 33C

Part No Multiflex Description 49153 LM-K-5 Clevis End



Clamp & Shim 33C Cable

LM-K-3

49151

Part No Multiflex Description

Clamp & Shim

Saddle Clamp Kit

Saddle shim screws washers nuts included.

Description Part No

91787 33C Cable Clamp



Quick clamp for control cables. Multi hole fixing. Base size 40x 25mm

Part No Description 91788 Quick Clamp



Red Plastic T Handle

Screws onto the end of 33c cables.

Part No Multiflex Description
49161 THANDLE Plastic T Handle



Metal Swivel Connector

Part No Multiflex Description
49165 LM-K-2 Swivel Connector



005 To 014 Connector

Part No Multiflex Description
49150 LM-K-1 Connector





Part No	Multiflex	Description
10162	LM ₋ C ₋ 1	Transom Clamp



Swivel Transom Clamp

Swiver Harisoni Clamp		
Part No	Multiflex	Description
49163	LM-C-3	Swivel Transom Clamp



Splashwell Clamp

Part No	Multiflex	Description
49164	LM-S-1	Splashwell Clamp



Stainless Steel Link Arm

Part No	Multiflex	Description
49172	LM-L-1	SS Link Arm



Stainless Steel Adjustable Link Arm

Part No	Multiflex	Description
49173	LM-L-4	SS Adjustable Link Arm



Steering Grommet Black

J		
Part No	Multiflex	Description
49175	GR1605B	Steering Grommet



Cable Grommet Single

Part No	Multiflex	Description
49166	GR-1601	Cable Grommet Single



Cable Grommet 4"

Part No	Multiflex	Description
49167	GR-1602	Cable Grommet 4"



Cable Grommet 6"

Part No	Multiflex	Description
49168	GR-1603	Cable Grommet 6"



Cable Grommet Lo Profile

Part No	Multiflex	Description
49169	GR-1608	Cable Grommet
		Lo Profile



Cable Grommet Twin

Part No	Multiflex	Description
49170	GR-1609	Cable Grommet
		Twin



Multi Cable Grommet

Part No	Multiflex	Description
49171	GR-1606	Multi Cable Grommet





33C EDGE Series Throttle Control Cable

Premium Quality - Ultra flexible Spiral Construction

The Ultimate High Performance 33c type cable.

Capable of extremely tight radius bends and complex cable runs, with no loss of performance or increased friction. Ideal for RIB and dual station cable installations - time-saving and guaranteed smooth performance. Suitable for inboard.outdrive and outboard installations.

Spiral Conduit - enables repeated tight bends.

Unique cable length ID tag for easy reference.

Comparable to - Teleflex Xtreme and Ultra-Flex Mach Zero.

Direct replacement for any 33c type cable.

Conduit: 8.6mm Blue Ribbed design

Inner: 2.75mm Coated Inner End Thread: 10-32 UNF

Cable bend radius (4" Minimum)



Part No	Description	Part No	Description
49024	Edge Engine Control Cable (Flexi) 6 Feet (1.82M)	49037	Edge Engine Control Cable (Flexi) 19 Feet (5.79M)
49025	Edge Engine Control Cable (Flexi) 7 Feet (2.13M)	49038	Edge Engine Control Cable (Flexi) 20 Feet (6.09M)
49026	Edge Engine Control Cable (Flexi) 8 Feet (2.43M)	49040	Edge Engine Control Cable (Flexi) 22 Feet (6.70M)
49027	Edge Engine Control Cable (Flexi) 9 Feet (2.74M)	49042	Edge Engine Control Cable (Flexi) 24 Feet (7.31M)
49028	Edge Engine Control Cable (Flexi) 10 Feet (3.04M)	49044	Edge Engine Control Cable (Flexi) 26 Feet (7.92M)
49029	Edge Engine Control Cable (Flexi) 11 Feet (3.35M)	49045	Edge Engine Control Cable (Flexi) 28 Feet (8.53M)
49030	Edge Engine Control Cable (Flexi) 12 Feet (3.65M)	49046	Edge Engine Control Cable (Flexi) 30 Feet (9.14M)
49031	Edge Engine Control Cable (Flexi) 13 Feet (3.96M)	49047	Edge Engine Control Cable (Flexi) 32 Feet (9.75M)
49032	Edge Engine Control Cable (Flexi) 14 Feet (4.26M)	49048	Edge Engine Control Cable (Flexi) 34 Feet (10.36M)
49033	Edge Engine Control Cable (Flexi) 15 Feet (4.57M)	49049	Edge Engine Control Cable (Flexi) 36 Feet (10.97M)
49034	Edge Engine Control Cable (Flexi) 16 Feet (4.87M)	49050	Edge Engine Control Cable (Flexi) 38 Feet (11.58M)
49035	Edge Engine Control Cable (Flexi) 17 Feet (5.18M)	49051	Edge Engine Control Cable (Flexi) 40 Feet (12.19M)
49036	Edge Engine Control Cable (Flexi) 18 Feet (5.48M)		



EDGE GEN 1 Mercury / Mercruiser

Part No	Description
49064	Merc Edge Engine Control Cable 10 Feet (3.04M)
49065	Merc Edge Engine Control Cable 11 Feet (3.35M)
49066	Merc Edge Engine Control Cable 12 Feet (3.65M)
49067	Merc Edge Engine Control Cable 13 Feet (3.96M)
49068	Merc Edge Engine Control Cable 14 Feet (4.26M)
49069	Merc Edge Engine Control Cable 15 Feet (4.57M)
49070	Merc Edge Engine Control Cable 16 Feet (4.87M)
49071	Merc Edge Engine Control Cable 17 Feet (5.18M)
49072	Merc Edge Engine Control Cable 18 Feet (5.48M)
49073	Merc Edge Engine Control Cable 19 Feet (5.79M)
49074	Merc Edge Engine Control Cable 20 Feet (6.09M)

Mercury EDGE Series Control Cable

Premium Quality - Ultra flexible Spiral Construction

The Ultimate High Performance Mercury/Mercruiser Gen1 & Gen 2 cable.

9.5mm conduit.

Inner: 3.2mm Flexible Core

End Thread 1/4" x 28 UNF

Specifically, for Mercury + Mercruiser Applications.

Unique cable length ID tag for easy reference.

Comparable to - Teleflex Xtreme and Ultra-Flex Mach Zero.



EDGE GEN 2 Mercury / Mercruiser

Part No	Description
49200	Merc Edge Gen 2 Engine Control Cable 10 Feet (3.04M)
49201	Merc Edge Gen 2 Engine Control Cable 11 Feet (3.35M)
49202	Merc Edge Gen 2 Engine Control Cable 12 Feet (3.65M)
49203	Merc Edge Gen 2 Engine Control Cable 13 Feet (3.96M)
49204	Merc Edge Gen 2 Engine Control Cable 14 Feet (4.26M)
49205	Merc Edge Gen 2 Engine Control Cable 15 Feet (4.57M)
49206	Merc Edge Gen 2 Engine Control Cable 16 Feet (4.87M)
49207	Merc Edge Gen 2 Engine Control Cable 17 Feet (5.18M)
49208	Merc Edge Gen 2 Engine Control Cable 18 Feet (5.48M)
49209	Merc Edge Gen 2 Engine Control Cable 19 Feet (5.79M)
49210	Merc Edge Gen 2 Engine Control Cable 20 Feet (6.09M)



Kill Cord for Outboards Circuit breaker cord with connections for almost all brands. Mercury/Mariner/Tohatsu Suzuki/Johnson/Evinrude Yamaha/Selva OMC Honda Part No 35999



Bow Thrusters

Vetus Bow Thrusters



12 or 24V						
Part No	Vetus No	Description	Thrust at 12/24VDC (KGF)	Power (kw-hp)	Tunnel Diameter (mm)	Main Fuse Required
55001	BOW2512E	Bow Thruster 25 KGF 12V	25	1.5 - 2	110	125 amp
55002	BOW3512E	Bow Thruster 35 KGF 12V	35	1.5 - 2	150	160 amp
55003	BOW5512D	Bow Thruster 55 KGF 12V	55	3 - 4	150	250 amp
55004	BOW5524D	Bow Thruster 55 KGF 24V	60	3 - 4	150	200 amp
55005	BOW6012D	Bow Thruster 60 KGF 12V	65	3 - 4	185	200 amp
55006	BOW6024D	Bow Thruster 60 KGF 24V	70	3 - 4	185	100 amp
55007	BOW7512D	Bow Thruster 75 KGF 12V	80	4.4 - 6	185	355 amp
55008	BOW7524D	Bow Thruster 75 KGF 24V	85	4.4 - 6	185	200 amp
55009	BOW9512D	Bow Thruster 95 KGF 12V	85	5.7 - 8	185	425 amp
55010	BOW9524D	Bow Thruster 95 KGF 24V	95	5.7 - 8	185	200 amp








The state of the s
Bow Thruster Cables
Panel connections with multi- plugs fitted. Suitable for all Vetus Electric and Single Stage Hydrau- lic Thrusters and controls.

Part No	Vetus	Description
55066	BP29	6m Cable
55067	BP2910	10m Cable
55068	BP2916	16m Cable
55069	BP2918	18m Cable
55070	BP2920	20m Cable

6 Blade Prop					
Part No	Vetus No	Description			
55030	SET0086	6 Blade Prop 110mm for BOW2512			
55031	SET0087	6 Blade Prop 150mm for BOW35/55			
55032	SET0088	6 Blade Prop 185mm for BOW50/60/75/80/95			
55033	SET0089	6 Blade Prop 185mm for Bow45/80 until 1998.			
55034	SET0090	6 Blade Prop 250mm for Bow125/130/160			







SET0148 Zinc anode for bow thrusters 25 kgf. Part No 55137



SET0149 Zinc anode for bow thruster 35, 45, 55 kgf. Part No 55138



SET0150 Zinc anode for bow thruster 60, 75, 80, 95 kgf. Part No 55139



SET0151 Zinc anode for bow thruster 130, 160 kgf. Part No 55140



SET0152 Zinc anode for bow thrusters 220 kgf. Part No 55141



SET0153 Zinc anode for bow thruster 23, 50, 80, kgf and for all stern thruster sets.

Part No 55142



Complete packages available for new build, refit and repowering

- Quality engineering
- Innovative design
- Competitive pricing
- Guaranteed compatibility
- Unrivalled warranties





Creators of boat systems. To make boating easy and carefree all over the world. More info: www.vetus.com


*Warranty terms and conditions can be found at www.vetus.com



Vetus Control Panels								
Part No	Vetus No	Description	Voltage	Front panel (mm)	Bezel	IP Rating	Built in depth (mm)	Cut Out Size
55045	BPSR	Thruster touch panel with time delay.	12/24V	Ø 63	White/Black /Chrome	IP65	90	Ø 52
55046	BPJR	Thruster panel with joystick and time delay.	12/24V	Ø 63	White/Black /Chrome	IP65	90	Ø 52
55047	BPAS	Thruster touch panel with time delay.	12/24V	97 x 95	Aluminium	IP65	90	Ø 52
55048	BPAJ	Joystick with time delay.	12/24V	97 x 95	Aluminium	IP65	90	Ø 52
55043	BPJSTA	Joystick with time delay device (excl. Connection cable)	12/24V	N/A	N/A	IP65	50	Ø 22
55036	EZDOCK2	Easy docking system for thrusters with time delay.	12/24V	85 x 138	Synthetic	IP65	90	130 x 75
55037	BPSE2	Thruster touch panel with time delay.	12/24V	85 x 85	Synthetic	IP65	90	Ø 75
55038	BPJE2	Thruster panel with joystick and time delay.	12/24V	85 x 85	Synthetic	IP65	90	Ø 75
55039	BPJDE2	Thruster panel with two joysticks and time delay.	12/24V	85 x 85	Synthetic	IP65	50	130 x 75
55044 BPA Adapter plate to replace the old BPS/BPJ panels with the new BPSE2/BPJE2 panels.			5.					

Engine Mounts








KSTEUN25V KSTEUN35V

Flexible I	Flexible Engine Mounting Type				
Part No	Vetus No	Description			
57337	KSTEUN25V	Max Load 25KG			
57338	KSTEUN35V	Max Load 30KG			


Type K25V and K35V

For small engines and generator sets with 1 or 2 cylinders


These flexible mountings contain a special rubber compound with excellent vibration damping properties. They are suitable for marine engines in the power range between 4 and 15 kW (6-20 hp).



Flexible Engine Mounting Type Part No Vetus Description 57339 KSTEUN40A Max Load 40KG




KSTEUN50V KSTEUN75V KSTEUN100V



MITSTEUN

Hydraulic Engine Mounting Type				
Part No	Vetus	Description		
57345	MITSTEUN	Max Load 67KG		





LMX500

Flexible Engine Mounting Type				
Part No	Vetus	Description		
57347	LMX140	Max Load 140KG		
57348	LMX210	Max Load 210KG		
57349	LMX340	Max Load 340KG		
57350	LMX500	Max Load 500KG		

Type K40A

For 3-cylinder marine diesel engines

Type K40 has a relatively soft, rubber compound which fulfils the requirements of light-weight vessels with a modern 3-cylinder marine diesel engine. The rubber elements create an optimum in vibration dampening. Type KSTEUN40 features internal buffers which limit the engine movements when started or stopped. It is also secured against overload and shearing off.

Type K50V K75V K100V

For smaller engines up to ± 60 kW (80 hp)

This type is suitable for smaller engines up to approximately 60 kW (80 hp).

Flexible Engine Mounting Type				
Part No	Vetus	Description		
57341	KSTEUN50V	Max Load 50KG		
57342	KSTEUN75V	Max Load 75KG		
57343	KSTEUN100V	Max Load 100KG		

Type MITSTEUN

For marine diesel engines from 18 up to 26 kW (25-35 hp)

This hydro-damper is a combination of a conventional rubber-metal damper and a hydraulic shock absorber. Its reduction of vibration and noise is truly amazing. The maximum static load per support is 60 kg and the maximum thrust is 50kg.

Type HY

For heavy-weight engines with 4 or more cylinders

This type is extremely suitable for application with marine diesel engines in the power range between 30 and 125 kW (40-170 hp), by virtue of a low stiffness combined with high stiffness in the longitudinal direction.

Flexible Engine Mounting Type				
Part No	Vetus	Description		
57352	HY100	Max Load 100KG		
57353	HY150	Max Load 150KG		
57354	HY230	Max Load 230KG		

Type LMX

For marine diesel engines with 70 up to 350 kW (95-480 hp)

This type has been designed with particular regard to the power to weight ratio of modern diesel engines. The weight of an engine, in comparison to its thrust, has become lower and lower. Type LMX guarantees optimum damping of vibrations, even at idling revs. It has a very high horizontal and aft stiffness which allows the acceptance of considerable thrust. The cushioning of vibrations in horizontal direction athwart-ships is of equal excellence.

LMX210

Sound Insulation



V Glass Sound Insulation

High quality, professional standard sound insulation with a layer of sound deadening.

Premium quality insulation at a great price. Available in 2 sizes.

Part No	Thickness
59900	50mm V Glass Silver
59901	32mm V Glass Silver



Maritex Sound Insulation Tape

Suitable for use with V Glass Sound Insulation, a tough fibreglass cloth, with a sealed metallised skin, so it cannot absorb oil. Heavy duty in appearance and fire zero rated, the insulation will not tear or fray.

Part No	Description
59902	50mm x 20M



Sound Deadening Sheet PU130S

Sound deadening sheets type PU130S are ideal for smaller engine installations and have excellent noise and vibration reducing qualities.

Part No	
57880	



Sonitech Light

Efficient Sound Insulation. A flexible, cost effective 20mm fire retardant sound insulation sheet with a

reinforced aluminium foil facing and self adhesive backing. Use when cost or space is the prime concern.

Part No	Vetus	Face + Thickness
58335	ST020A	Aluminium 20mm
58336	ST040A	Aluminium 40mm



Prometech Single

Excellent Sound Insulation & Safety. Vetus Prometech Sound Insulation Sheet - full 35mm version for high performance with both high and low frequency engine noise. Fibre reinforced aluminium facing, for durability and radiant heat reflection. Self adhesive backing for simple fitting.

Sheet Size: 1000 x 600mm

Part No	Vetus	Face + Thickness
58341	PT112A	Aluminium 12mm
58342	PT135A	Aluminium 35mm
58343	PT145A	Aluminium 45mm
58344	PT112W	White 12mm
58345	PT135W	White 35mm
58346	PT145W	White 45mm



Sound Insulation Tape

Self-adhesive tape three colours.

50mm x 30m

Part No	Description
57887	Aluminium (TAPEA30)
57888	Grey (TAPEG30)
57889	White (TAPEW30)



Sonitech Single

Good Sound Insulation.

A step up from the light version, which includes a single damping layer resulting in better sound insulation capabilities. Available in 35 or 45 mm thick sheets and with reinforced aluminium foil or white glass cloth facing. With self-adhesive backing.

Sheet Size: 1000 x 600mm

Part No	Vetus	Face + Thickness
58337	ST135A	Aluminium 35mm
58338	ST145A	Aluminium 45mm
58339	ST135W	White 35mm
58340	ST145W	White 45mm



Prometech Double

Ultimate Sound Insulation & Safety Vetus Prometech Sound Insulation Sheet - ultimate 45mm version for high performance with both high and low frequency engine noise. Flexible Silver glass cloth facing, for extreme strength, durability and a high tech appearance to your engine room. Self adhesive backing for simple fitting.

Sheet Size: 1000 x 600mm

Part No	Vetus	Thickness
58347	PT225S	25mm Silver
58348	PT245S	45mm Silver
58349	PT260S	60mm Silver
58350	PT225W	25mm White
58351	PT245W	45mm White
58352	PT260W	60mm White




Sound Insulation Fixing Plates Diameter: 50mm.

Pack of 15, screws not supplied.

Part No	Description
57890	Pack of 15 (FIXP)


Ventilation





9200 8, 000 0







Type UFO

High gloss polished S/S UFO can't be closed, which ensures permanent ventilation. Incl. mosquito screen and interior finishing ring. Rain/splash proof.

31,8 FREE FLOW AREA CM²

AISI 316

Part No	Description

56785 200mm UFO Vent

Type UFOTR

High gloss polished S/S UFOTR can't be closed, which ensures permanent ventilation. Incl. mosquito screen and interior finishing ring. Rain/splash proof. Transparent centre.

31,8 FREE FLOW AREA CM²

AISI 316

Part No	Description
56786	200mm Transparent
	UFOTR


Type UFO2

UFO2 high gloss polished deck ventilator with integral mushroom ventilator can be made watertight. When opened it ensures ventilation.
Rain/splash proof.


30 FREE FLOW AREA CM²

AISI 316


Part No	Description
56788	200mm Closable UFO2















Type PORTOS1

Stainless steel (AISI 316) mushroom ventilator, polished high-gloss, including mosquito screen and synthetic counterflange. Free flow area 30 cm².

Part No	Description
56797	PORTOS1 117mm

Type ATHOS1

Stainless steel (AISI 316) mushroom ventilator, polished high-gloss, including mosquito screen and synthetic counterflange. Free flow area 45 cm².


Part No	Description
56798	ATHOS1 152MM

Type DARTAGNAN1

Stainless steel (AISI 316) mushroom ventilator, polished high-gloss, including mosquito screen and synthetic counterflange. Free flow area 76 cm².

Part No	Description
56799	DARTAGNAN1 185MM





Electric Ventilators.

Designed especially for boats. Suitable for installation to ceiling or wall. With long-life computer motor. Very low energy consumption and noise level.

CAPACITY	70 m³/hoi	ur
STATIC PRE	5 mm H2O	
Part No	Description	Vetus
56792	12 Volt	FAN12
56793	24 Volt	FAN24





Shell Ve	Shell Vents						
Stamped stainless steel shell (midget) vent							
304 ss							
Part No	Description						
76196	41mm x 41mm						
76198	57mm x 54mm						
76200	25mm height x 9	00mm width x 93mm length					



SolarVent

The latest venting system using solar power. Fitted with mirror polished stainless steel vent diffuser. ON-OFF switch. Equipped with NiMH rechargeable batteries which store energy during the day, ensuring 30 hours of operation without solar light. Equipped with 2 RIGHT/LEFT fans to let air in or out.

Cap Ø mm 217

Practice hole mm 119

External/internal overhang mm 71

Air circulation m3/hour 20

Part No Description

96326 Automatic Solar Vent 217mm



UFO Style Roof Vent

Highly polished Stainless Steel (304).

Mounting ring and nipple supplied.

Stainless Steel top - height above deck 30mm - cutout 73mm

Part No	Description
96553	UFO Style Roof Vent





Type TYP75 Shell Ventilator


The outer cover is made of high-gloss polished stainless steel (AISI 316), all other parts of synthetic materials. The unit is suitable for horizontal or vertical use.

Free Flow Area CM² 30

Hose Connection Diameter 75MM

Part No	Description
56817	TYP75







Type TYP100 Shell Ventilator


The outer cover is made of high-gloss polished stainless steel (AISI 316), all other parts of synthetic materials. The unit is suitable for horizontal or vertical use.

Free Flow Area CM²

Hose Connection Diameter 100MM

Part No Description 56818 **TYP100**








Type SCIROCCO

The SCIROCCO can be screwed directly on to hull or superstructure horizontally/vertically. Incl. plastic base plate, water guard, 76 mm hose connection.

Free Flow Area CM²

Hose Connection Diameter 76mm

Part No Description 56820 **SCIROCCO**










SAMOENS CHINOOKS LIBECS



Vetus Silicone Cowl Ventilators								
Part No	Vetus	Replaces	A (mm)	B (mm)	C (mm)	D (mm)	Free flow area (cm²)	Material
56850	TRAMONS	DONALDS	100	75	127	11	44.2	Silicone
56851	LIBECS	JERRYS	192	75	127	11	44.2	Silicone
56852	CHINOOKS	TOMS	230	100	152	11	78.6	Silicone
56853	SAMOENS	YOGIS	282	125	179	11	122.8	Silicone





YOG316R TOM316R JER316R



YOG316WR TOM316WR JER316WR



Removable and rotatable



DON316R



DON316WR

Cowl Ventilator						
Cover & Mosquito Screen						
Part No	Vetus	Size				
56822	SET75	75mm				
56823 SET100 100mm						

Vetus Stainless Steel (AISI 316) Cowl Ventilators							
Part No	Vetus	A (mm)	B (mm)	C (mm)	D (mm)	Free flow area(cm²)	Material
56824	DON316WR White	111	75	123	22	44.2	Stainless Steel AISI 316
56825	DON316R Red	111	75	123	22	44.2	Stainless Steel AISI 316
56833	YOG316WR White	296	125	181	22	122.8	Stainless Steel AISI 316
56834	YOG316R Red	296	125	181	22	122.8	Stainless Steel AISI 316
56835	TOM316WR White	250	100	153	22	78.6	Stainless Steel AISI 316
56836	TOM316R Red	250	100	153	22	78.6	Stainless Steel AISI 316
56837	JER316WR White	205	75	123	22	44.2	Stainless Steel AISI 316
56838	JER316R Red	205	75	123	22	44.2	Stainless Steel AISI 316





Rule In-Line Blowers

Designed for efficient, high output operation, these blowers feature our exclusive front and rear shaft seals and corrosion resistant motor housings for long life. Compact and easily installed on any flat surface, Rule® in-line blowers provide higher air flow, lower amp draw, and quieter operation than standard blowers.

Part No	Description	Dimensions	Fuse Size	Output
75140	12V - 75mm	130 L x 95 H x 125mm Wide	4 Amp	3.8 cu.m/minute
75141	24V - 75mm	130 L x 95 H x 125mm Wide	2.5 Amp	3.8 cu.m/minute
75142	12V - 100mm	130 L x 120 H x 150mm Wide	7 Amp	6.7 cu.m/minute
75143	24V - 100mm	130 L x 120 H x 150mm Wide	4 Amp	6.7 cu.m/minute





Vetus In-Line Blowers

The purpose of these ignition protected (IP67) extraction ventilators is to extract the heat from the engine room when the engine is not running or, when a petrol/gasoline engine is installed, to extract any possible petrol/gasoline fumes prior to starting the engine(s).

Part No	Description	Dimensions	Voltage (DC) AMP	Capacity (m³ /min)
57332	TWINLINEA 76mm 12V	128 L x 88.5 H x 76mm Wide	2.8Amp	5
57333	TWINLINEB 102mm 12V	180 L x 116 H x 101.6mm Wide	8 Amp	7








Vetus Extraction Ventilators - Ideal for Galley, Toilet & Engine Room.

This extraction ventilator with Delrin Impeller is ignition protected IP67 and complies with ISO 9097 Marine Standard. It includes a mounting bracket and connection flange for in-line installation.

Part No	Vetus	ID Hose	Α	В	С	D	Voltage (DC) AMP	Capacity (m³/min)
57334	VENT7612A	76	186	168	88	157	12v - 8 Amps	4
57335	VENT7624A	76	186	168	88	157	24v - 4 Amps	4
57325	VENT10212	102	215	237	113	209	12v - 8 Amps	8
57326	VENT10224	102	215	237	113	209	24v - 4.5 Amps	8







Extraction Ventilators

Suitable for bulkhead mounting and receiving air ducting hose. This extraction ventilator is ignition protected (IP67) and complies with the ISO 9097 Marine Standard.

 $12V = 6 \text{ Amps} / 12,2m^3$

 $24V = 3 \text{ Amps} / 12.5 \text{m}^3$


Part No	Vetus	Description	Voltage	ID Hose mm
57330	VENT17812A	Extraction ventilator	12V	178
57331	VENT17824A	Extraction ventilator	24V	178



Connection Flange

Spare in-line hose connection flanges for VENT76A and VENT102.

F	Part No	Vetus	Α	В	С	D	Е	ØF	ØG
5	7336	VENTKITA	120	115	106.5	46.5	106	83.3	76
5	7327	VENTKITB	150	141	136.5	46.5	136	109.7	102







Ventilation Hose

For shell and extraction ventilators.

Type BLHOSE is made from PVC coated glassfibre with a steel spiral. Temperature resistant between –20° and + 100°C. Sold in 10m lengths.

Part No	Vetus	Internal Ø mm	External Ø mm	Bending Radius	Roll Length
56399	BLHOSE310A	79	85	47	10M
56400	BLHOSE410A	102	108	61	10M



Flexible Ventilation Hose

Very flexible suction or pressure hose.

Flexible TPE ducting hose with steel spiral. Temperature resistant between -30° and + 140° C. Sold in 10m lengths.

Part No	Vetus	Internal Ø mm	External Ø mm	Bending Radius	Roll Length
56401	VHOSE152	152	158	150	10M
56402	VHOSE178	180	186	180	10M



Ventilation Hose

Ducting blower hose sold in 6m lengths

Baoung blower necessarin em lengule								
Part No	Description							
89940	76mm x 6M							
89941	102mm x 6M							









Stainless Steel Breather Nipple

The breathing capacity fulfils the CE requirements. Provided with an easily cleaned stainless steel (AISI 316) gauze, which functions as a flame arrester.

Part No	Size	Part No	Size
56448	16mm straight (AB16S)	56452	19mm angled (AB19B)
56449	16mm angled (AB16B)	56453	25mm angled (AB25B)
56450	19mm straight (AB19S)	56454	38mm angled (AB38B)



Suitable for \emptyset 16 mm internal diameter hose. In stainless steel (AISI 316).

Part No	Description
56457	Stainless Straight 16mm (ST04S)
56458	Stainless Angled 16mm (ST04HS)



Fuel Breather Vents

Mirror polished AISI 316 stainless steel.

Fitted with flame-proof screen, detachable for easy maintenance. Designed in compliance with the requirements of the UNI EN ISO 21487 regulation.

Part No	Description
96463	19mm Fuel Breather Vent 90 degree bend.
96464	16mm Fuel Breather Vent 90 degree bend.





Tank Vents

Chrome plated brass tank vents with fitted gauze and back nut.

Part No	Hose Dia	Aperture	Туре
10260	5/8" (16mm)	3/4" (19mm)	Straight
10265	5/8" (16mm)	3/4" (19mm)	90°
10270	3/4" (19mm)	1" (25mm)	Straight

Brass Page 116







Silicon Bronze Pages 117 - 120









Copper Page 121







Galvanised Pages 122 - 123









Stainless Steel Pages 124 - 138









Accessories Page 139







Fastenings Brass

Brass Countersunk Slotted Woodscrews



Part No	Imperial Size	Metric Size (mm)	Part No	Imperial Size	Metric Size (mm)	Part No	Imperial Size	Metric Size (mm)	Part No	Imperial Size	Metric Size (mm)	Part No	Imperial Size	Metric Size (mm)
4G / ø2.9mm		nm		6G / ø3.5mm		8G / ø4.2mm		10G / ø4.8mm			12G / ø5.5mm			
82150	4 X 3/8	2.9 X 10	82170	6 X 1/2	3.5 X 13	82210	8 X 3/4	4.2 X 19	82245	10 X 1	4.8 X 25	82278	12 X 1 1/4	5.5 X 32
82155	4 X 1/2	2.9 X 13	82175	6 X 5/8	3.5 X 16	82215	8 X 1	4.2 X 25	82250	10 X 1 1/4	4.8 X 32	82280	12 X 1 1/2	5.5 X 38
82160	4 X 3/4	2.9 X 19	82180	6 X 3/4	3.5 X 19	82220	8 X 1 1/4	4.2 X 32	82255	10 X 1 1/2	4.8 X 38	82285	12 X 2	5.5 X 50
82165	4 X 1	2.9 X 25	82185	6 X 1	3.5 X 25	82225	8 X 1 1/2	4.2 X 38	82260	10 X 1 3/4	4.8 X 44	82290	12 X 2 1/2	5.5 X 64
			82190	6 X 1 1/4	3.5 X 32	82230	8 X 1 3/4	4.2 X 44	82265	10 X 2	4.8 X 50	82295	12 X 3	5.5 X 76
		82195	6 X 1 1/2	3.5 X 38	82235	8 X 2	4.2 X 50	82270	10 X 2 1/2	4.8 X 64				
		82200	6 X 2	3.5 X 50	82240	8 x 2 1/2	4.2 X 64	82275	10 X 3	4.8 X 76				

Brass Round Head Slotted Woodscrews



Part No	Imperial Size	Metric Size (mm)	Part No	Imperial Size	Metric Size (mm)	Part No	Imperial Size	Metric Size (mm)	Part No	Imperial Size	Metric Size (mm)	Part No	Imperial Size	Metric Size (mm)
	4G / ø2.9mm			6G / ø3.5mm		8G / ø4.2mm		10G / ø4.8mm			12G / ø5.5mm			
82310	4 X 1/2	2.9 X 13	82325	6 X 1/2	3.5 X 13	82340	8 X 3/4	4.2 X 19	82362	10 X 1 1/4	4.8 X 32	82366	12 X 1 1/4	5.5 X 32
82315	4 X 3/4	2.9 X 19	82330	6 X 3/4	3.5 X 19	82345	8 X 1	4.2 X 25	82364	10 X 2 1/2	4.8 X 60	82370	12 X 2	5.5 X 50
82320	4 X 1	2.9 X 25	82335	6 X 1	3.5 X 25	82350	8 X 1 1/4	4.2 X 32						
						82355	8 X 1 1/2	4.2 X 38						
						82358	8 X 1 3/4	4.2 X 45						
						82360	8 X 2	4.2 X 50						

Brass Screw Cups



Brass Screw Cups						
Part No	Size					
82560	4g - 5g					
82562	6g					
82564	7g - 8g					
82566	9g - 10g					
82568	12g					

Brass Turned Cups



Brass Turned Pattern Cups						
Part No	Size					
82572	5g					
82574	6g					
82576	8g					
82578	10g					
82580	12g					

Brass Panel Pins



Part No	Thickness X Length	Quantity Per Kilo (Approx)
82850	1.4 X 12mm (1/2")	5662
82852	1.4 X 16mm (5/8")	5400
82854	1.4 X 19mm (3/4")	3600
82858	1.6 X 25mm (1")	2480
82860	1.6 X 32mm (1 1/4")	1679
82862	1.6 X 38mm (1 1/2")	1392

Brass Split Pins



Part No	Imperial Size	Metric Size
82790	1/16 X 1	1.6 X 25mm
82795	3/32 X 1	2.4 X 25mm
82800	1/8 X 1	3.2 X 25mm
82805	1/8 X 1 1/2	3.2 X 38mm
82806	1/8 X 2	3.2 X 50mm
82815	5/32 X 1 1/2	4 X 38mm
82802	3/16 X 1	4.8 X 25mm
82825	3/16 X 2	4.8 X 50mm

Fastenings Bronze

Silicon Bronze Slotted **Countersunk Woodscrews**



Part No	Imperial Size	Metric Size (mm)	Part No	Imperial Size	Metric Size (mm)	Pai No		nperial Size	Metric Size (mm)	Pa N		Imperial Size	S	etric ize nm)	Part No		perial Size	Metric Size (mm)
4G / ø2.9mm Thickness 5.3mm Head Size 6.5mm Head Size			80	8G / ø4.2mm Thickness 7.88mm Head Size			10	10G / ø4.8mm Thickness 9.25mm Head Size					12G / ø5.5mm Thickness 10.28mm Head Size					
82900	4 X 1/2	2.9 X 13	82904	6 X 1/2	3.5 X 13	8 29	12 8	3 X 3/4	4.2 X 19	829	26	10 X 3/4	4.8	X 19	82942	1:	2 X 1	5.5 X 25
82901	4 X 3/4	2.9 X 19	82906	6 X 3/4	3.5 X 19	829	14	8 X 1	4.2 X 25	829	28	10 X 1	4.8	X 25	82944	12 2	X 1 1/4	5.5 X 32
82902	4 X 1	2.9 X 25	82908	6 X 1	3.5 X 2	5 829	16 8	X 1 1/4	4.2 X 32	829	30	10 X 1 1/4	4.8	X 32	82946	12 2	X 1 1/2	5.5 X 38
			82910	6 X 1 1/4	3.5 X 3	2 829	18 8	X 1 1/2	4.2 X 38	829	32	10 X 1 1/2	4.8	X 38	82948	12 2	X 1 3/4	5.5 X 44
			82911	6 X 1 1/2	3.5 X 3	8292	20 8	X 1 3/4	4.2 X 44	829	34	10 X 1 3/4	4.8	X 44	82950	1:	2 X 2	5.5 X 50
						8292	22	8 X 2	4.2 X 50	829	36	10 X 2	4.8	X 50	82952	12 2	X 2 1/4	5.5 X 57
Part No	Imperial Size	Metric Size (mm)				8292	24 8	X 2 1/2	4.2 X 64	829 829		10 X 2 1/2 10 X 3		X 64 X 76	82954 82956		X 2 1/2 2 X 3	5.5 X 64 5.5 X 76
	/ ø6.3mm TI .08mm Hea		Part No	Imperia Size	al s	etric ize nm)									82958 82960		X 3 1/2 2 X 4	5.5 X 89 5.5 X 102
82962	14 X 1	6.3 X 25	16	G / ø7.1mm	` Thickne	,									02900	1.4	2 / 4	3.3 X 102
32964	14 X 1 1/4	6.3 X 32		12.98mm H			Part	Imperi	ial M	etric	Pai	rt Impe	rial	Metri	c Pa	ut	Imperia	al Metric
82966	14 X 1 1/2	6.3 X 38	8297	8 16 X 1	1/2 7.1	X 38	No	Size		ize nm)	No			Size (mm)	N		Size	Size (m
82968	14 X 1 3/4	6.3 X 44	8297	9 16 X 1 3	3/4 7.1	X 44	18G	/ ø7.9mn	,	,	20	0G / ø8.3m	m Th	, ,		24G /	ø9.3mn	n Thickness
82970	14 X 2	6.3 X 50	8298	16 X 2	7.1	X 50	14	4.89mm l	lead Siz	е		15.35mm	Head	l Size		18.	.25mm F	lead Size
82971	14 X 2 1/4	6.3 X 57	8298	2 16 X 2 1	7.1	X 57	82992	18 X	2 7.9	X 50	830	01 20 X	(2	8.3 X 5	830	13	24 X 3	9.3 X 7
82972	14 X 2 1/2	6.3 X 63	8298	4 16 X 2 1	7.1	X 64	82994	18 X 2	1/2 7.9	X 64	830	02 20 X 2	2 1/2	8.3 X 6	830	12	24 X 3 1	/2 9.3 X 8
82974	14 X 3	6.3 X 76	8298	6 16 X 3	7.1	X 75	82996	18 X	3 7.9	X 76	830	04 20 X	(3	8.3 X 7	⁷⁶ 830	11	24 X 4	9.3 X 1
82976	14 X 3 1/2	6.3 X 89	8298	8 16 X 3 1	7.1	X 89	82998	18 X 3	1/2 7.9	X 89	830	06 20 X 3	3 1/2	8.3 X 8	830	10	24 X 6	9.3 X 1
82977	14 X 4	6.3 X 102	2 8299	16 X 4	7.1	X 102	83000	18 X	4 7.9	X 102	830	08 20 X	(4	8.3 X 1	02			

Silicon Bronze Pozi

Countersunk Woodscrews



Part No	Imperial Size	Metric Size (mm)					
	6G / ø3.5mm Thickness 6.5mm Head Size						
83015	6 X 3/4	3.5 X 19					
83016	6 X 1	3.5 X 25					

Part No	Imperial Size	Metric Size (mm)	Part No	Imperial Size	Metric Size (mm)		
	ø4.2mm Thi .88mm Head		10G / ø4.8mm Thickness 9.25mm Head Size				
83017	8 X 3/4	4.2 X 19	83021	10 X 1	4.8 X 25		
83018	8 X 1	4.2 X 25	83022	10 X 1 1/4	4.8 X 32		
83019	8 X 1 1/4	4.2 X 32	83023	10 X 1 1/2	4.8 X 38		
83020	8 X 1 1/2	4.2 X 38	83024	10 X 2	4.8 X 50		

Silicon Bronze Decorative **Screw Cups**



Part No	Description
84550	6G Screw Cup Silicon Bronze
84552	8G Screw Cup Silicon Bronze
84554	10G Screw Cup Silicon Bronze
84556	12G Screw Cup Silicon Bronze
84558	14G Screw Cup Silicon Bronze

Silicon Bronze Woodscrews = 20% standard discount & 30% when you buy 100 or more.

Fastenings Bronze

Silicon Bronze Slotted Raised Head Countersunk Woodscrews





Also known as Oval Head.

Part No	Imperial Size	Metric Size (mm)	Part No	Imperial Size	Metric Size (mm)	Part No	Imperial Size	Metric Size (mm)	Part No	Imperial Size	Metric Size (mm)	Part No	Imperial Size	Metric Size (mm)
	6G / ø3.5mm Thickness 6.5mm Head Size		8G / ø4.2mm Thickness 7.88mm Head Size		10G / ø4.8mm Thickness 9.25mm Head Size		12G / ø5.5mm Thickness 10.28mm Head Size			14G / ø6.3mm Thickness 12.08mm Head Size				
83149	6 X 1/2	3.5 X 13	83154	8 X 1/2	4.2 X 13	83161	10 X 3/4	4.8 X 19	83167	12 X 1	5.5 X 25	83171	14 X 1 1/2	6.3 X 38
83150	6 X 3/4	3.5 X 19	83155	8 X 3/4	4.2 X 19	83162	10 X 1	4.8 X 25	83168	12 X 1 1/4	5.5 X 32	83172	14 X 2	6.3 X 50
83151	6 X 1	3.5 X 25	83156	8 X 1	4.2 X 25	83163	10 X 1 1/4	4.8 X 32	83169	12 X 1 1/2	5.5 X 38	83174	14 X 3	6.3 X 76
83152	6 X 1 1/4	3.5 X 32	83157	8 X 1 1/4	4.2 X 32	83164	10 X 1 1/2	4.8 X 38	83170	12 X 2	5.5 X 50			
83153	6 X 1 1/2	3.5 X 38	83158	8 X 1 1/2	4.2 X 38	83165	10 X 1 3/4	4.8 X 44						
			83159	8 X 1 3/4	4.2 X 44	83166	10 X 2	4.8 X 50						
			83160	8 X 2	4.2 X 50									

Silicon Bronze Slotted Round Head Woodscrews



Metric Metric Metric Metric Part Imperial Part Imperial Part Imperial Part Imperial Size Size Size Size No Size No Size No Size No Size (mm) (mm) (mm) (mm) 4G / ø2.9mm Thickness 6G / ø3.5mm Thickness 8G / ø4.2mm Thickness 10G / ø4.8mm Thickness 5.3mm Head Size 6.5mm Head Size 7.88mm Head Size 9.25mm Head Size 6 X 1/2 3.5 X 13 10 X 3/4 4.8 X 19 83201 4 X 1/2 2.9 X 13 83204 83211 8 X 1/2 4.2 X 13 83222 6 X 3/4 3.5 X 19 10 X 1 4.8 X 25 83202 4 X 3/4 2.9 X 19 83205 83212 8 X 3/4 4.2 X 19 83223 3.5 X 25 83203 4 X 1 2.9 X 25 83206 6 X 1 83213 83224 10 X 1 1/4 4.8 X 32 8 X 1 4.2 X 25 83207 6 X 1 1/4 3.5 X 32 83214 8 X 1 1/4 4.2 X 32 83225 10 X 1 1/2 4.8 X 38 83208 6 X 1 1/2 3.5 X 38 83215 8 X 1 1/2 4.2 X 38 83226 10 X 1 3/4 4.8 X 44 83209 6 X 1 3/4 3.5 X 44 83216 8 X 1 3/4 4.2 X 44 83227 10 X 2 4.8 X 50 3.5 X 50 83210 6 X 2 83217 8 X 2 4.2 X 50 **83237** 14 X 2 6.3 X 50

Part No	Imperial Size	Metric Size (mm)		
	ickness Size			
83230	12 X 1	5.5 X 25		
83231	12 X 1 1/4	5.5 X 32		
83232	12 X 1 1/2	5.5 X 38		
83233	12 X 2	5.5 X 50		
Part No	Imperial Size	Metric Size (mm)		
No 14G		Size (mm) ickness		
No 14G	Size / ø6.3mm Th	Size (mm) ickness		
No 14G	Size / ø6.3mm Th .08mm Head	Size (mm) ickness		
No 14G 12 83234	Size / ø6.3mm Th .08mm Head 14 X 1	Size (mm) ickness Size 6.3 X 25		

Silicon Bronze Slotted Countersunk Machine Screws



Part No	Imperial Size	Part No	Imperial Size	Part No	Imperial Size	
	3/16		1/4	5/16		
84280	3/16 X 1	84293	1/4 X 1	84324	5/16 X 1 1/2	
84282	3/16 X 1 1/4	84296	1/4 X 1 1/2	84326	5/16 X 2	
84284	3/16 X 1 1/2	84300	1/4 X 2	84328	5/16 X 2 1/2	
84286	3/16 X 2	84302	1/4 X 2 1/2	84330	5/16 X 3	
84288	3/16 X 2 1/2	84304	1/4 X 3	84332	5/16 X 3 1/2	
84292	3/16 X 3	84305	1/4 X 3 1/2	84334	5/16 X 4	
		84307	1/4 X 4			

Part No	Imperial Size				
3/8					
84354	3/8 X 1 1/2				
84356	3/8 X 2				
84358	3/8 X 2 1/2				
84360	3/8 X 3				
84362	3/8 X 3 1/2				
84364	3/8 X 4				
84365	3/8 X 4 1/2				
84366	3/8 X 5				
84368	3/8 X 6				
84370	3/8 X 7				
84374	3/8 X 8				

Part No	Imperial Size
	1/2
84391	1/2 X 4
84395	1/2 X 6
84397	1/2 X 7
84399	1/2 X 8
84409	1/2 X 12

Silicon Bronze Slotted Round Head Machine Screws



3/16					
3/16					
83270 3/16 X	1				
83271 3/16 X 1	1/4				
83272 3/16 X 1	1/2				
83274 3/16 X	2				

Part No	Imperial Size	Part No	Imperial Size
	1/4		5/16
83277	1/4 X 1	83289	5/16 X 1 1/2
83279	1/4 X 1 1/2	83291	5/16 X 2
83281	1/4 X 2	83293	5/16 X 2 1/2
83283	1/4 X 2 1/2	83295	5/16 X 3
83285	1/4 X 3		

Part

No

83062

83064

83066

83068

83070

83072

83074 83076

83078

3/8 X 6

3/8 83297 3/8 X 1 1/2
83297 3/8 X 1 1/2
83298 3/8 X 2
83300 3/8 X 2 1/2
83302 3/8 X 3

Silicon Bronze Hex Setscrews



Most are threaded all of the way.

Part No	Imperial Size			
1/4				
83030	1/4 X 1			
83032	1/4 X 1 1/2			
83034	1/4 X 2			
83036	1/4 X 2 1/2			
83038	1/4 X 3			
83040	1/4 X 3 1/2			
83042	1/4 X 4			

Part No	Imperial Size		
5/16			
83044	5/16 X 1 1/2		
83046	5/16 X 2		
83048	5/16 X 2 1/2		
83050	5/16 X 3		
83052	5/16 X 3 1/2		
83054	5/16 X 4		
83056	5/16 X 4 1/2		
83058	5/16 X 5		
83060	5/16 X 6		

Imperial Size	Part No	Imperial Size
3/8		1/2
3/8 X 1 1/2	83080	1/2 X 2
3/8 X 2	83082	1/2 X 2 1/2
3/8 X 2 1/2	83084	1/2 X 3
3/8 X 3	83086	1/2 X 3 1/2
3/8 X 3 1/2	83088	1/2 X 4
3/8 X 4	83090	1/2 X 4 1/2
3/8 X 4 1/2	83092	1/2 X 5
3/8 X 5	83094	1/2 X 6
0/0 V C		

Silicon Bronze Cup Square Bolts



Also known as Carriage Bolts.

Part No	Imperial Size	Part No	Imperial Size		
	1/4		5/16		
84036	1/4 X 2	84066	5/16 X 2		
84038	1/4 X 2 1/2	84068	5/16 X 2 1/2		
84040	1/4 X 3	84070	5/16 X 3		
84042	1/4 X 3 1/2	84072	5/16 X 3 1/2		
84044	1/4 X 4	84074	5/16 X 4		
84046	1/4 X 4 1/2	84076	5/16 X 4 1/2		
84050	1/4 X 5	84078	5/16 X 5		
84052	1/4 X 5 1/2	84080	5/16 X 5 1/2		
84054	1/4 X 6	84082	5/16 X 6		
84056	1/4 X 6 1/2	84084	5/16 X 6 1/2		
84058	1/4 X 7	84086	5/16 X 7		
84060	1/4 X 8	84088	5/16 X 8		
		84092	5/16 X 10		
		84096	5/16 X 12		

Part No	Imperial Size	Part No	Imperial Size
	3/8		1/2
84098	3/8 X 2	84134	1/2 X 2 1/2
84100	3/8 X 2 1/2	84136	1/2 X 3
84102	3/8 X 3	84138	1/2 X 3 1/2
84104	3/8 X 3 1/2	84140	1/2 X 4
84106	3/8 X 4	84142	1/2 X 4 1/2
84108	3/8 X 4 1/2	84144	1/2 X 5
84110	3/8 X 5	84146	1/2 X 5 1/2
84112	3/8 X 5 1/2	84148	1/2 X 6
84114	3/8 X 6	84150	1/2 X 6 1/2
84116	3/8 X 6 1/2	84152	1/2 X 7
84118	3/8 X 7	84154	1/2 X 7 1/2
84120	3/8 X 7 1/2	84156	1/2 X 8
84122	3/8 X 8	84158	1/2 X 9
84124	3/8 X 9	84160	1/2 X 10
84126	3/8 X 10	84162	1/2 X 11
84128	3/8 X 11	84164	1/2 X 12
84130	3/8 X 12		

Fastenings Bronze

Silicon Bronze Hex Head Coach Screws



Also known as Lag Bolts.

Part No	Imperial Size	Part No	Imperial Size	Part No	Imperial Size	Part No	Imperial Size
	1/4		5/16		3/8		1/2
84180	1/4 X 1	84213	5/16 X 1	84230	3/8 X 1 1/2	84252	1/2 X 3
84184	1/4 X 1 1/2	84215	5/16 X 1 1/2	84232	3/8 X 2	84256	1/2 X 4
84185	1/4 X 1 3/4	84216	5/16 X 2	84234	3/8 X 2 1/2	84258	1/2 X 4 1/2
84186	1/4 X 2	84218	5/16 X 2 1/2	84236	3/8 X 3	84260	1/2 X 5
84188	1/4 X 2 1/2	84220	5/16 X 3	84238	3/8 X 3 1/2	84262	1/2 X 6
84190	1/4 X 3	84222	5/16 X 3 1/2	84240	3/8 X 4		
		84224	5/16 X 4	84242	3/8 X 4 1/2		
		84225	5/16 X 4 1/2	84244	3/8 X 5		
		84226	5/16 X 5	84246	3/8 X 6		
		84228	5/16 X 6				

Silicon Bronze Gripfast Nails



A COUNTY COMPANY	COLUMN TO MAKE BY A SAME OF	M 1 1 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	ELISATE REPRESENTA		
Part No	Imperial Size	Metric Size (mm)	Nails Per Kilo (Approx)		
14G / ø2.06mm Thickness 4.5mm Head Size					
85568	14 X 3/4	2.06 X 19	1736		
85572	14 X 1	2.06 X 25	1342		
85574	14 X 1 1/4	2.06 X 32	962		
		mm Thickness n Head Size	5		
85576	12 X 3/4	2.9 X 19	968		
85580	12 X 1	2.9 X 25	750		
85582	12 X 1 1/4	2.9 X 32	593		
85584	12 X 1 1/2	2.9 X 38	506		
85586	12 X 1 3/4	2.9 X 45	438		
85588	12 X 2	2.9 X 50	383		
85590	12 X 2 1/2	2.9 X 62	300		
		mm Thickness n Head Size	5		
85592	10 X 1	3.5 X 25	464		
85594	10 X 1 1/4	3.5 X 32	385		
85596	10 X 1 1/2	3.5 X 38	327		
85598	10 X 1 3/4	3.5 X 45	261		
85600	10 X 2	3.5 X 50	242		
85602	10 X 2 1/2	3.5 X 62	197		
85604	10 X 3	3.5 X 75	165		
		nm Thickness n Head Size			
85608	8 X 2	4.2 X 50	166		
85612	8 X 2 1/2	4.2 X 62	132		
85614	8 X 3	4.2 X 75	110		
85616	8 X 4	4.2 x 102	90		

Silicon Bronze UNC Nuts & Washers



Full Nuts

Part No	Size
84530	3/16
84532	1/4
84534	5/16
84536	3/8
84538	1/2
84540	5/8
84542	3/4
84544	7/8
84546	1



Flat Washers

Part No	Size	Outside Diameter mm
84510	3/16	11mm
84512	1/4	14.28mm
84514	5/16	19.15mm
84516	3/8	22.18mm
84518	1/2	31.73mm
84520	5/8	38.08mm
84522	3/4	47.55mm
84524	7/8	57.10mm
84526	1	63.36mm

Silicon Bronze Studding 3ft lengths



Part No	Size
84410	1/4" X 3'
84412	5/16" X 3'
84414	3/8" X 3'
84416	1/2" X 3'
84418	5/8" X 3'
84420	3/4" X 3'

Fastenings Copper

Copper Boat Nails

Copper Nails, Copper Roves and Copper Tacks are sold by weight (grams and kilos). It is useful therefore to use the approximate quantity per kilo column to work out how many pieces you get per kilo or 1000 grams.



Part No	Nail Gauge x Length	Metric Size (mm)	Approximate Quantity Per 1 KG (1000 grams)		
		s1.63mm Thickne 5mm Head Size	ss		
85432	16 X 5/8	1.63 X 16	2645		
85434	16 X 3/4	1.63 X 19	2200		
85436	16 X 1	1.63 X 25	1507		
	14G / ø2.03mm Thickness 5.44mm Head Size				
85438	14 X 1	2.03 X 25	1055		
85440	14 X 1 1/4	2.03 X 32	845		
85442	14 X 1 1/2	2.03 X 38	705		
85444	14 X 1 3/4	2.03 X 44	600		
85446	14 X 2	2.03 X 51	510		
	13G / ø2.34mm Thickness 6.16mm Head Size				
85448	13 X 1	2.34 X 25	775		
85450	13 X 1 1/4	2.34 X 32	590		
85452	13 X 1 1/2	2.34 X 38	505		
85454	13 X 1 3/4	2.34 X 44	440		
	12G / ø2.64mm Thickness 6.41mm Head Size				
85456	12 X 1	2.64 X 25	675		
85460	12 X 1 1/4	2.64 X 32	475		
85462	12 X 1 1/2	2.64 X 38	400		
85464	12 X 1 3/4	2.64 X 44	350		
85466	12 X 2	2.64 X 51	300		
85468	12 X 2 1/2	2.64 X 64	265		

Part No	Nail Gauge x Length	Metric Size (mm)	Approximate Quantity Per 1 KG (1000 grams)	
		/ ø3.25mm Thickne .58mm Head Size	ess	
85470	10 X 1 1/4	3.25 X 32	250	
85472	10 X 1 1/2	3.25 X 38	220	
85474	10 X 2	3.25 X 51	200	
85476	10 X 2 1/2	3.25 X 64	180	
85478	10 X 3	3.25 X 76	140	
85480	10 X 3 1/2	3.25 X 89	120	
85482	10 X 4	3.25 X 102	105	
	9G / ø3.66mm Thickness 8.82mm Head Size			
85484	9 X 2 1/2	3.66 X 64	125	
85486	9 X 3	3.66 X 76	115	
	8G / ø4.06mm Thickness 9.94mm Head Size			
85488	8 X 2	4.06 X 51	133	
85490	8 X 2 1/2	4.06 X 64	95	
85492	8 X 3	4.06 X 76	80	
85494	8 X 4	4.06 X 102	65	
85495	8 X 5	4.06 X 125		
		ø4.88mm Thickne 11mm Head Size	ss	
85496	6 X 4	4.88 X 102	50	
85497	6 X 4 1/2	4.88 X 112	45	
85498	6 X 5	4.88 X 127	40	
85500	6 X 6	4.88 X 152	35	
		Coppor Ta	cks	

Copper Roves 500 gram boxes



Part No	Diameter	Gauge	Approximate Quantity Per 1 KG (1000 grams)
85520	5/16 (8mm)	14g (2.03mm)	2325
85522	3/8 (10mm)	13g (2.03mm)	1450
85524	7/16 (11mm)	12g (2.64mm)	950
85526	1/2 (13mm)	10g (3.25mm)	700
85528	9/16 (14mm)	9g (3.66mm)	525
85530	5/8 (16mm)	8g (4.06mm)	400
85532	3/4 (19mm)	6g (4.88mm)	225

Copper Tacks



Sold by Weight

Part No	Size	Approximate Quantity Per 1 KG (1000 grams)
82880	1/2" (13mm)	1966
82882	5/8" (16mm)	1929
82884	3/4" (19mm)	1611
82886	1" (25mm)	1295

Fastenings Galvanised

All of our Galvanised fittings are hot dipped and are galvanised to: BS EN ISO 1461:1999

Galvanised Hex Head Bolts



Part No	Metric Size	
М8		
84576	M8 X 30	
84580	M8 X 40	
84582	M8 X 45	
84584	M8 X 50	
84586	M8 X 55	
84588	M8 X 60	
84590	M8 X 65	
84592	M8 X 70	
84594	M8 X 75	
84596	M8 X 80	
84598	M8 X 90	
84600	M8 X 100	

Part No	Metric Size	Part No	Metric Size	Part No	Metric Size	Part No	Metric Size
	M10		M12		M16		M20
84602	M10 X 30	84646	M12 X 30	84694	M16 X 50	84734	M20 X 50
84604	M10 X 35	84650	M12 X 40	84696	M16 X 55	84736	M20 X 60
84606	M10 X 40	84652	M12 X 45	84698	M16 X 60	84738	M20 X 75
84608	M10 X 45	84654	M12 X 50	84700	M16 X 65	84740	M20 X 100
84610	M10 X 50	84656	M12 X 55	84702	M16 X 70	84742	M20 X 120
84612	M10 X 55	84658	M12 X 60	84704	M16 X 75	84744	M20 X 130
84614	M10 X 60	84660	M12 X 65	84706	M16 X 80	84746	M20 X 150
84616	M10 X 65	84662	M12 X 70	84708	M16 X 90	84748	M20 X 160
84618	M10 X 70	84664	M12 X 75	84710	M16 X 100	84750	M20 X 180
84620	M10 X 75	84666	M12 X 80	84712	M16 X 110	84752	M20 X 200
84622	M10 X 80	84668	M12 X 90	84714	M16 X 120	84754	M20 X 240
84624	M10 X 90	84670	M12 X 100	84716	M16 X 130	84756	M20 X 300
84626	M10 X 100	84672	M12 X 110	84718	M16 X 140		
84628	M10 X 110	84674	M12 X 120	84720	M16 X 150		
84630	M10 X 120	84676	M12 X 130	84722	M16 X 160		
84632	M10 X 130	84678	M12 X 140	84724	M16 X 180		
84634	M10 X 140	84680	M12 X 150	84726	M16 X 200		
84636	M10 X 150	84682	M12 X 160	84728	M16 X 220		
84638	M10 X 160	84684	M12 X 180	84729	M16 X 260		
84640	M10 X 180	84686	M12 X 200	84731	M16 X 280		
84642	M10 X 200	84688	M12 X 220	84730	M16 X 300		
84644	M10 X 220	84690	M12 X 240	84732	M16 X 350		
84645	M10 X 240	84692	M12 X 300				

Size	No	Metric Size
/116		M20
M16 X 50	84734	M20 X 50
M16 X 55	84736	M20 X 60
M16 X 60	84738	M20 X 75
M16 X 65	84740	M20 X 100
M16 X 70	84742	M20 X 120
M16 X 75	84744	M20 X 130
M16 X 80	84746	M20 X 150
M16 X 90	84748	M20 X 160
M16 X 100	84750	M20 X 180
M16 X 110	84752	M20 X 200
M16 X 120	84754	M20 X 240
M16 X 130	84756	M20 X 300
M16 X 140		


Galvanised Full Nuts

Galvanised Nylocs Galvanised Washers





Part No	Size	Part No	Size
85180	M6	85192	M8
85182	M8	85194	M10
85184	M10	85196	M12
85186	M12	85198	M16
85188	M16	85199	M20
85190	M20		



Part No	Size
85168	M8 X 1m
85170	M10 X 1m
85172	M12 X 1m
85174	M16 X 1m
85176	M20 X 1m



Part No	Size	Outside Diameter mm
85210	M6 (1/4")	16mm
85212	M8 (5/16")	16mm
85216	M10 (3/8")	21mm
85218	M12 (1/2")	24mm
85220	M16 (5/8")	30mm
85222	M20 (3/4")	37mm







Part No	Size
85242	M10
85244	M12
85246	M16
85248	M20

Galvanised Square Plate Washers



	Part No	Size
	85230	M8 X 2" (50mm) Square
	85232	M10 X 2" (50mm) Square
	85234	M12 X 2" (50mm) Square
	85236	M16 X 2" (50mm) Square
The state of the s	85238	M20 X 2.5" (64mm) Square

Galvanised **Spring Washers**



Part No	Size		
85150	M6 (1/4")		
85151	M8 (5/16")		
85152	M10 (3/8")		
85153	M12 (1/2")		
85154	M16 (5/8")		
85155	M20 (3/4")		

Fastenings Galvanised

Galvanised Cup Square Bolts



Part No	Metric Size	Part No	Metric Size	Part No	Metric Size	Part No	Metric Size	Part No	Metric Size
	М8		M10		M12	M16			M20
84791	M8 X 25	84834	M10 X 30	84888	M12 X 40	84942	M16 X 40	85002	M20 X 100
84792	M8 X 30	84836	M10 X 40	84892	M12 X 50	84944	M16 X 50	85004	M20 X 110
84796	M8 X 40	84840	M10 X 45	84894	M12 X 55	84946	M16 X 60	85006	M20 X 130
84798	M8 X 45	84842	M10 X 50	84898	M12 X 65	84948	M16 X 65	85008	M20 X 140
84800	M8 X 50	84844	M10 X 55	84902	M12 X 75	84950	M16 X 70	85010	M20 X 150
84802	M8 X 55	84848	M10 X 65	84904	M12 X 80	84952	M16 X 75	85012	M20 X 160
84806	M8 X 65	84850	M10 X 70	84906	M12 X 90	84954	M16 X 80	85014	M20 X 180
84808	M8 X 70	84852	M10 X 75	84908	M12 X 100	84956	M16 X 90	85016	M20 X 200
84810	M8 X 75	84854	M10 X 80	84910	M12 X 110	84958	M16 X 100	85018	M20 X 220
84812	M8 X 80	84856	M10 X 90	84914	M12 X 130	84960	M16 X 110	85020	M20 X 240
84814	M8 X 90	84858	M10 X 100	84915	M12 X 140	84962	M16 X 120	85022	M20 X 260
84816	M8 X 100	84860	M10 X 110	84918	M12 X 150	84963	M16 X 130	85024	M20 X 280
84818	M8 X 110	84864	M10 X 130	84920	M12 X 160	84964	M16 X 140	85026	M20 X 300
84822	M8 X 130	84866	M10 X 140	84922	M12 X 180	84966	M16 X 150	85028	M20 X 350
84824	M8 X 140	84868	M10 X 150	84924	M12 X 200	84968	M16 X 160	85030	M20 X 400
84826	M8 X 150	84870	M10 X 160	84926	M12 X 220	84970	M16 X 180		
84828	M8 X 160	84872	M10 X 180	84928	M12 X 230	84972	M16 X 200		
84830	M8 X 180	84874	M10 X 200	84930	M12 X 240	84974	M16 X 220		
84832	M8 X 200	84876	M10 X 220	84932	M12 X 260	84976	M16 X 240		
ews		84880	M10 X 240	84934	M12 X 280	84978	M16 X 260		
		84882	M10 X 260	84936	M12 X 300	84980	M16 X 280		

84938 M12 X 350 **84982** M16 X 300

84984 M16 X 350 84986 M16 X 400

Galvanised Hex Head Coach Screen



Part No	Metric Size	Part No	Metric Size		Part No	Metric Size
	М8		M10			M12
85364	M8 x 40	85375	M10 x 40	8	85386	M12 x 40
85365	M8 x 50	85376	M10 x 50	8	85387	M12 x 50
85366	M8 x 60	85377	M10 x 65	8	85388	M12 x 60
85367	M8 x 70	85378	M10 x 75	8	85389	M12 x 75
85368	M8 x 75	85379	M10 x 80	8	85390	M12 x 90
85369	M8 x 80	85380	M10 x 90	8	85391	M12 x100
85370	M8 x 90	85381	M10 x 100	8	85392	M12 x 130
85371	M8 x 100	85382	M10 x 120	8	85393	M12 x 150
85372	M8 x 120	85383	M10 x 150	8	85406	M12 x 160
85373	M8 x 130	85384	M10 x 180	8	85394	M12 x 180
85374	M8 x 150	85385	M10 x 200	8	85395	M12 x 200

Part No	Metric Size	Part No	Metric Size
M16			M20
85396	M16 x 75	85402	M20 x 125
85397	M16 x 100	85403	M20 x 150
85398	M16 x 120	85404	M20 x 175
85399	M16 x 150	85405	M20 x 200
85400	M16 x 175		
85401	M16 x 200		

Galvanised Countersunk Slotted Woodscrews



84884 M10 X 280 84886 M10 X 300

Hot dipped galvanized products are steel that are dipped into zinc to give a protective coating. They are typically used in wood construction.

Part No

85266

85268

85270

85274

85276

85278

12G / ø5.5mm

14G / ø6.3mm

12 x 2

12 x 2 1/2

12 x 3

14 x 2

14 x 2 1/2

14 x 3

Part No	Size			
8G /	ø4.2mm			
85250	8 x 1 1/2			
85252	8 x 1 3/4			
85254	8 x 2			
10G / ø4.8mm				
85256	10 x 1			
85258	10 x 1 1/2			
85260	10 x 2			
85262	10 x 2 1/2			
85264	10 x 3			

Galvanised Boat Nails



Sold in grams and kilos. These nails are sold by weight.

Part No	Size Inches	Nails Per Kilo (Approx)
85340	2" (51mm)	106
85342	2 1/2" (64mm)	98
85344	3" (76mm)	60
85346	3 1/2" (89mm)	50
85348	4" (102mm)	48
85350	4 1/2" (114mm)	24
85352	5" (127mm)	22
85354	6" (152mm)	14

Stainless Socket Allen Key Countersunk Machine Screws



A2 (308) Stainless steel is suitable for use above the waterline.

A4 (316) Stainless Steel is suitable for use above and below the waterline.

A2 Grade (308)	Size	A2 Grade (308)	A4 Grade (316)	Size	A2 Grade (308)	A4 Grade (316)	Size
ı	VI3		M4			M5	
86000	M3 X 6	86018	86900	M4 X 10	86034	-	M5 X 10
86002	M3 X 8	86020	86898	M4 X 12	86036	-	M5 X 12
86004	M3 X 10	86022	86899	M4 X 16	86038	-	M5 X 16
86006	M3 X 12	86024	86887	M4 X 20	86040	86823	M5 X 20
86008	M3 X 16	86026	86888	M4 X 25	86042	86824	M5 X 25
86010	M3 X 20	86028	86889	M4 X 30	86044	86825	M5 X 30
86012	M3 X 25	-	86901	M4 X 35	86046	86892	M5 X 35
86014	M3 X 30	86032	86890	M4 X 40	86048	86827	M5 X 40
86015	M3 X 50	86033	86891	M4 X 50	86052	86829	M5 X 50
		-	86896	M4 X 60			

86897 M4 X 70

A2 Grade (308)	A4 Grade (316)	Size						
	M6							
86054	-	M6 X 12						
86056	-	M6 X 16						
86058	86832	M6 X 20						
86060	86833	M6 X 25						
86062	86834	M6 X 30						
86064	86893	M6 X 35						
86066	86836	M6 X 40						
86068	-	M6 X 45						
86070	86839	M6 X 50						
86074	86841	M6 X 60						
86076	-	M6 X 70						
-	86843	M6 X 80						
-	86845	M6 X 100						

A2 Grade (308)	A4 Grade (316)	Size
	М8	
86078	-	M8 X 16
86080	86847	M8 X 20
86082	86848	M8 X 25
86084	86849	M8 X 30
86088	86851	M8 X 40
86100	86853	M8 X 50
86104	86855	M8 X 60
86106	-	M8 X 70
86108	86857	M8 X 80
86110	-	M8 X 90
86112	86860	M8 X 100

A2 Grade (308)	A4 Grade (316)	Size	A2 Grade (308)	A4 Grade (316)	Size
	M10			M12	
86114	86861	M10 X 20	-	86874	M12 X 20
86116	86862	M10 X 25	86140	86875	M12 X 25
86118	86863	M10 X 30	86142	86876	M12 X 30
-	86894	M10 X 35	-	86895	M12 X 35
86122	86865	M10 X 40	86146	86878	M12 X 40
86126	86867	M10 X 50	86150	86880	M12 X 50
86130	86869	M10 X 60	86154	86882	M12 X 60
86132	-	M10 X 70	86156	-	M12 X 70
86134	86871	M10 X 80	86158	86884	M12 X 80
86136	-	M10 X 90	86160	-	M12 X 90
86138	86873	M10 X 100	86162	86886	M12 X 100

Stainless Socket Allen Key Cap Machine Screws



A4 (316) Stainless Steel is suitable for use above and below the waterline.

A4 Grade (316)	Size	A4 Grade (316)	Size	A4 Grade (316)	Size
M3		N	M4		M5
87000	M3 X 12	87011	M4 X 12	87020	M5 X 12
87001	M3 X 16	87012	M4 X 16	87021	M5 X 16
87002	M3 X 20	87013	M4 X 20	87023	M5 X 25
87003	M3 X 25	87014	M4 X 25	87024	M5 X 30
87004	M3 X 40	87015	M4 X 30	87025	M5 X 40
		87016	M4 X 40	87026	M5 X 50
		87017	M4 X 50		

A4 Grade (316)	Size				
M6					
87030	M6 X 12				
87031	M6 X 16				
87032	M6 X 20				
87033	M6 X 25				
87034	M6 X 30				
87038	M6 X 50				
87039	M6 X 60				
87041	M6 X 75				
87043	M6 X 90				
87044	M6 X 100				

Stainless Socket Allen Key Cap Machine Screws



A4 (316) Stainless Steel is suitable for use above and below the waterline.

A4 Grade (316)	Size	A4 Grade (316)	Size	A4 Grade (316)	Size
N	18	M10			M12
87050	M8 X 12	87070	M10 X 16	87090	M12 X 25
87051	M8 X 16	87071	M10 X 20	87091	M12 X 30
87052	M8 X 20	87072	M10 X 25	87092	M12 X 40
87053	M8 X 25	87073	M10 X 30	87093	M12 X 50
87054	M8 X 30	87074	M10 X 40	87094	M12 X 60
87055	M8 X 40	87075	M10 X 50	87096	M12 X 75
87057	M8 X 50	87076	M10 X 60	87097	M12 X 80
87058	M8 X 60	87077	M10 X 70	87098	M12 X 90
87061	M8 X 75	87080	M10 X 100	87099	M12 X 100
87062	M8 X 80	87081	M10 X 110		
87063	M8 X 90	87082	M10 X 120		
87064	M8 X 100				
87065	M8 X 120				

Stainless Socket Button Allen Key Machine Screws



A4 (316) Stainless Steel is suitable for use above and below the waterline.

A4 Grade (316)	Size	A4 Grade (316)	Size	A4 Grade (316)	Size	A4 Grade (316)	Size	A4 Grade (316)	Size	A4 Grade (316)	Size
N	14	M5 M6 M8		М8	M10			M12			
86815	M4 X 10	86818	M5 X 10	86820	M6 X 10	86740	M8 X 12	86748	M10 X 12	86800	M12 X 20
86720	M4 X 12	86726	M5 X 12	86732	M6 X 12	86741	M8 X 20	86749	M10 X 20	86802	M12 X 25
86816	M4 X 16	86819	M5 X 16	86821	M6 X 16	86742	M8 X 25	86750	M10 X 25	86804	M12 X 30
86721	M4 X 20	86727	M5 X 20	86733	M6 X 20	86743	M8 X 30	86751	M10 X 30	86806	M12 X 40
86722	M4 X 25	86728	M5 X 25	86734	M6 X 25	86744	M8 X 40	86752	M10 X 40	86808	M12 X 50
86723	M4 X 30	86729	M5 X 30	86735	M6 X 30	86745	M8 X 50	86753	M10 X 50	86810	M12 X 60
86724	M4 X 40	86730	M5 X 40	86736	M6 X 40	86780	M8 X 60	86790	M10 X 60	86812	M12 X 80
86725	M4 X 50	86731	M5 X 50	86737	M6 X 50	86746	M8 X 75	86754	M10 X 75	86814	M12 X 100
86817	M4 X 60	86760	M5 X 60	86770	M6 X 60	86782	M8 X 80	86792	M10 x 80		
		86762	M5 X 80	86738	M6 X 75	86747	M8 X 100	86755	M10 X 100		
				86772	M6 X 80						
				86739	M6 X 100						

Stainless Cup Square Bolts



A2 (308) Stainless steel is suitable for use above the waterline.

A2 Grade (308)	Size	A2 Grade (308)	Size		A2 Grade (308)	Size	A2 Grade (308)	Size
N	16	N	M8 M10		110	N	/ 112	
86170	M6 X 20	86190	M8 X 20		86212	M10 X 20	86166	M12 X 100
86172	M6 X 25	86192	M8 X 25		86214	M10 X 25	86167	M12 X 130
86174	M6 X 30	86194	M8 X 30		86216	M10 X 30		
86176	M6 X 35	86196	M8 X 35		86218	M10 X 35		
86178	M6 X 40	86198	M8 X 40		86220	M10 X 40		
86182	M6 X 50	86202	M8 X 50		86224	M10 X 50		
86186	M6 X 60	86206	M8 X 60		86228	M10 X 60		
86188	M6 X 70	86208	M8 X 70		86230	M10 X 70		
		86210	M8 X 80		86232	M10 X 80		
		86211	M8 X 100		86233	M10 X 100		

Stainless Coach Screws



A2 (308) Stainless steel is suitable for use above the waterline.

A2 Grade (308)	Size	A2 Grade (308)	Size	A2 Grade (308)	Size	A2 Grade (308)	Size
M6		N	18	N	/ 110	N	/ 112
80940	M6 X 30	80950	M8 X 40	80960	M10 X 50	80970	M12 X 50
80941	M6 X 40	80951	M8 X 50	80961	M10 X 60	80971	M12 X 60
80942	M6 X 50	80952	M8 X 60	80962	M10 X 70	80972	M12 X 70
80943	M6 X 60	80953	M8 X 70	80963	M10 X 80	80973	M12 X 80
80944	M6 X 70	80954	M8 X 80	80964	M10 X 90	80975	M12 X 90
80945	M6 X 80	80955	M8 X 90	80965	M10 X 100	80976	M12 X 100
80946	M6 X 90	80956	M8 X 100	80966	M10 X 120	80977	M12 X 120
80947	M6 X 100					80978	M12 X 150

Countersunk Torx Self Tapper A4



A4 (316) Stainless Steel is suitable for use above and below the waterline.

(316)	Imperial Size	Metric Size (mm)					
4G / ø2.9mm							
86601	4 X 1/2	2.9 X 13mm					
86602	4 X 5/8	2.9 X 16mm					
86603	4 X 3/4	2.9 X 19mm					
86604	4 X 1	2.9 X 25mm					
86605	4 X 1 1/4	2.9 X 32mm					

A4 Grade (316)	Imperial Size	Metric Size (mm)	A4 Grade (316)	Imperial Size	Metric Size (mm)	
6G / ø3.5mm			8G / ø4.2mm			
86608	6 X 3/8	3.5 X 10mm	86617	8 X 3/8	3.9 X 10mm	
86609	6 X 1/2	3.5 X 13mm	86618	8 X 1/2	3.9 X 13mm	
86610	6 X 5/8	3.5 X 16mm	86619	8 X 5/8	3.9 X 16mm	
86611	6 X 3/4	3.5 X 19mm	86620	8 X 3/4	3.9 X 19mm	
86591	6 X 7/8	3.5 X 22mm	86592	8 X 7/8	3.9 X 22mm	
86612	6 X 1	3.5 X 25mm	86621	8 X 1	3.9 X 25mm	
86613	6 X 1 1/4	3.5 X 32mm	86622	8 X 1 1/4	3.9 X 32mm	
86614	6 X 1 1/2	3.5 X 38mm	86623	8 X 1 1/2	3.9 X 38mm	
86615	6 X 1 3/4	3.5 X 45mm	86624	8 X 1 3/4	3.9 X 45mm	
86616	6 X 2	3.5 X 50mm	86625	8 X 2	3.9 X 50mm	

A4 Grade (316)	Imperial Size	Metric Size (mm)					
10G / ø4.8mm							
86626	10 X 3/8	4.8 X 10mm					
86627	10 X 1/2	4.8 X 13mm					
86628	10 X 5/8	4.8 X 16mm					
86629	10 X 3/4	4.8 X 19mm					
86630	10 X 1	4.8 X 25mm					
86631	10 X 1 1/4	4.8 X 32mm					
86632	10 X 1 1/2	4.8 X 38mm					
86633	10 X 1 3/4	4.8 X 45mm					
86634	10 X 2	4.8 X 50mm					

12G / ø5.5mm 86636 12 X 1/2 5.5 X 13mr 86637 12 X 5/8 5.5 X 16mr	e
86637 12 X 5/8 5.5 X 16mr	
	m
40 7 0 4	m
86638 12 X 3/4 5.5 X 19mr	m
86594 12 X 7/8 5.5 X 22mr	m
86639 12 X 1 5.5 X 25mr	m
86640 12 X 1 1/4 5.5 X 32mr	m
86641 12 X 1 1/2 5.5 X 38mr	m
86642 12 X 1 3/4 5.5 X 45mr	m

A4 Grade (316)	Imperial Size	Metric Size (mm)				
14G / ø 6.3mm						
86643	14 X 5/8	6.3 X 16mm				
86644	14 X 3/4	6.3 X 19mm				
86645	14 X 1	6.3 X 25mm				
86646	14 X 1 1/4	6.3 X 32mm				
86647	14 X 1 1/2	6.3 X 38mm				
86648	14 X 1 3/4	6.3 X 45mm				

Pan Head Torx Self Tapper A4



A4 Grade (316)	Imperial Size	Metric Size (mm)	A4 Grade (316)	Imperial Size	Metric Size (mm)	A4 Grade (316)	Imperial Size	Metric Size (mm)
	4G / ø2.9m	m		6G / ø3.5m	m		8G / ø4.2mm	
86650	4 X 3/8	2.9 X 10mm	86657	6 X 3/8	3.5 X 10mm	86665	8 X 3/8	3.9 X 10mm
86651	4 X 1/2	2.9 X 13mm	86658	6 X 1/2	3.5 X 13mm	86666	8 X 1/2	3.9 X 13mm
86652	4 X 5/8	2.9 X 16mm	86659	6 X 5/8	3.5 X 16mm	86667	8 X 5/8	3.9 X 16mm
86653	4 X 3/4	2.9 X 19mm	86660	6 X 3/4	3.5 X 19mm	86668	8 X 3/4	3.9 X 19mm
86654	4 X 1	2.9 X 25mm	86661	6 X 1	3.5 X 25mm	86669	8 X 1	3.9 X 25mm
86655	4 X 1 1/4	2.9 X 32mm	86662	6 X 1 1/4	3.5 X 32mm	86670	8 X 1 1/4	3.9 X 32mm
			86663	6 X 1 1/2	3.5 X 38mm	86671	8 X 1 1/2	3.9 X 38mm
			86664	6 X 1 3/4	3.5 X 45mm	86672	8 X 1 3/4	3.9 X 45mm

A4 Grade (316)	Imperial Size	Metric Size (mm)	A4 Grade (316)	Imperial Size	Metric Size (mm)
	10G / ø4.8m	m		12G / ø5.5m	m
86674	10 X 3/8	4.8 X 10mm	86684	12 X 1/2	5.5 X 13mm
86675	10 X 1/2	4.8 X 13mm	86685	12 X 5/8	5.5 X 16mm
86676	10 X 5/8	4.8 X 16mm	86686	12 X 3/4	5.5 X 19mm
86677	10 X 3/4	4.8 X 19mm	86687	12 X 1	5.5 X 25mm
86678	10 X 1	4.8 X 25mm	86688	12 X 1 1/4	5.5 X 32mm
86679	10 X 1 1/4	4.8 X 32mm	86689	12 X 1 1/2	5.5 X 38mm
86680	10 X 1 1/2	4.8 X 38mm	86690	12 X 1 3/4	5.5 X 45mm
86681	10 X 1 3/4	4.8 X 45mm	86691	12 X 2	5.5 X 50mm
86682	10 X 2	4.8 X 50mm			

A4 Grade (316)	Imperial Size	Metric Size (mm)
	14G / ø6.3m	m
86710	14 X 1/2	6.3 X 13mm
86711	14 X 5/8	6.3 X 16mm
86712	14 X 3/4	6.3 X 19mm
86713	14 X 7/8	6.3 X 22mm
86714	14 X 1	6.3 X 25mm
86715	14 X 1 1/4	6.3 X 32mm
86716	14 X 1 1/2	6.3 X 38mm
86717	14 X 1 3/4	6.3 X 45mm
86718	14 X 2	6.3 X 50mm

Stainless Countersunk Pozi Self Tappers



A2 (308) Stainless steel is suitable for use above the

A4 (316) Stainless Steel is suitable for use above and below the waterline.

A2 Grade (308)	A4 Grade (316)	Imperial Size	Metric Size (mm)
	4G /	ø2.9mm	
81482	81483	4 X 1/4	2.9 X 6
81484	81485	4 X 3/8	2.9 X 10
81486	81487	4 X 1/2	2.9 X 13
81488	81489	4 X 5/8	2.9 X 16
81490	81491	4 X 3/4	2.9 X 19
81494	81495	4 X 1	2.9 X 25

A2 Grade (308)	A4 Grade (316)	Imperial Size	Metric Size (mm)
	6G	ø3.5mm	
81496	81497	6 X 1/4	3.5 X 6
81498	81499	6 X 3/8	3.5 X 10
81500	81501	6 X 1/2	3.5 X 13
81502	81503	6 X 5/8	3.5 X 16
81504	81505	6 X 3/4	3.5 X 19
81508	81509	6 X 1	3.5 X 25
81510	81511	6 X 1 1/4	3.5 X 32
81512	81513	6 X 1 1/2	3.5 X 38

A2 Grade (308)	A4 Grade (316)	Imperial Size	Metric Size (mm)
	8G	ø4.2mm	
81514	81515	8 X 3/8	4.2 X 10
81516	81517	8 X 1/2	4.2 X 13
81518	81519	8 X 5/8	4.2 X 16
81520	81521	8 X 3/4	4.2 X 19
81524	81525	8 X 1	4.2 X 25
81526	81527	8 X 1 1/4	4.2 X 32
81528	81529	8 X 1 1/2	4.2 X 38
81530	81531	8 X 1 3/4	4.2 X 44
81532	81533	8 X 2	4.2 X 50
81534		8 x 2 1/2	4.2 X 64

A2 Grade (308)	A4 Grade (316)	Imperial Size	Metric Size (mm)
	10G	/ ø4.8mm	
81536	-	10 X 3/8	4.8 X 10
81538	81539	10 X 1/2	4.8 X 13
81540	81541	10 X 5/8	4.8 X 16
81542	81543	10 X 3/4	4.8 X 19
81544	81545	10 X 1	4.8 X 25
81546	81547	10 X 1 1/4	4.8 X 32
81548	81549	10 X 1 1/2	4.8 X 38
81550	-	10 X 1 3/4	4.8 X 44
81552	81553	10 X 2	4.8 X 50

A2 Grade (308)	A4 Grade (316)	Imperial Size	Metric Size (mm)
	12G	/ ø5.5mm	
81554	-	12 X 1/2	5.5 X 13
81558	-	12 X 3/4	5.5 X 19
81562	81563	12 X 1	5.5 X 25
81564	81565	12 X 1 1/4	5.5 X 32
81566	81567	12 X 1 1/2	5.5 X 38
81568	-	12 X 1 3/4	5.5 X 44
81570	81571	12 X 2	5.5 X 50

Stainless Countersunk Pozi Pan Head Self Tappers



A2 (308) Stainless steel is suitable for use above the waterline.

A4 (316) Stainless Steel is suitable for use above and below the waterline.

A2 Grade (308)	A4 Grade (316)	Imperial Size	Metric Size (mm)
	4G /	ø2.9mm	
81590	-	4 x 1/4	2.9 X 6
81592	-	4 X 3/8	2.9 X 10
81594	81595	4 X 1/2	2.9 X 13
81596	-	4 X 5/8	2.9 X 16
81598	81599	4 X 3/4	2.9 X 19
81600	81601	4 X 1	2.9 X 25

Α2

(308)

81660

81664

81668

81670

81672

81674

Grade Grade

A2 Grade (308)	A4 Grade (316)	Imperial Size	Metric Size (mm)
	6G	ø3.5mm	
81602	-	6 X 1/4	3.5 X 6
81604	-	6 X 3/8	3.5 X 10
81606	81607	6 X 1/2	3.5 X 13
81608	-	6 X 5/8	3.5 X 16
81610	81611	6 X 3/4	3.5 X 19
81614	81615	6 X 1	3.5 X 25
81616	81617	6 X 1 1/4	3.5 X 32
81618	-	6 X 1 1/2	3.5 X 38

Metric

Size

(mm)

5.5 X 13

5.5 X 19

5.5 X 25

Imperial

Size

12 X 1/2

12 X 3/4

12 X 1

81673 12 X 1 1/2 5.5 X 38

12 X 1 1/4 5.5 X 32

12 X 2 5.5 X 50

12G / ø5.5mm

A2 Grade (308)	A4 Grade (316)	Imperial Size	Metric Size (mm)	A2 Grade (308)	A4 Grade (316)	Imperial Size	Metric Size (mm)		
	8G	ø4.2mm			10G / ø4.8mm				
81620	-	8 X 3/8	4.2 X 10	81642	-	10 X 3/8	4.8 X 10		
81622	81623	8 X 1/2	4.2 X 13	81644	81645	10 X 1/2	4.8 X 13		
81624	-	8 X 5/8	4.2 X 16	81646	-	10 X 5/8	4.8 X 16		
81626	81627	8 X 3/4	4.2 X 19	81648	81649	10 X 3/4	4.8 X 19		
81628	-	8 X 7/8	4.2 X 22	81650	81651	10 X 1	4.8 X 25		
81630	81631	8 X 1	4.2 X 25	81652	81653	10 X 1 1/4	4.8 X 32		
81632	81633	8 X 1 1/4	4.2 X 32	81654	81655	10 X 1 1/2	4.8 X 38		
81634	81635	8 X 1 1/2	4.2 X 38	81656	-	10 X 1 3/4	4.8 X 44		
81636	-	8 X 1 3/4	4.2 X 44	81658	81659	10 X 2	4.8 X 50		
81638	81639	8 X 2	4.2 X 50						
81640	-	8 x 2 1/2	4.2 X 64						

A2 Grade (308)	Imperial Size	Metric Size (mm)
	14G / ø6.3m	ım
81676	14 X 3/4	6.3 X 19
81678	14 X 1	6.3 X 25
81680	14 X 1 1/4	6.3 X 32
81682	14 X 1 1/2	6.3 X 38
81684	14 X 1 3/4	6.3 X 45
81686	14 X 2	6.3 X 50

Stainless Raised Head Pozi Self Tappers



A2 (308) Stainless steel is suitable for use above the waterline.

A2 Grade (308)	Imperial Size	Metric Size (mm)	A2 Grade (308)	Imperial Size	Metric Size (mm)
	10G / ø4.8m	m		12G / ø5.5m	m
81710	10 X 1	4.8 X 25	81720	12 X 1	5.5 X 25
81712	10 X 1 1/4	4.8 X 32	81722	12 X 1 1/4	5.5 X 32
81714	10 X 1 1/2	4.8 X 38	81724	12 X 1 1/2	5.5 X 38
81716	10 X 1 3/4	4.8 X 44			
81718	10 X 2	4.8 X 50			

A2 Grade (308)	Imperial Size	Metric Size (mm)	A2 Grade (308)	Imperial Size	Metric Size (mm)
	6G / ø3.5m	m		8G / ø4.2mi	m
81690	6 X 3/8	3.5 X 10	81700	8 X 5/8	4.2 X 16
81692	6 X 1/2	3.5 X 13	81702	8 X 3/4	4.2 X 19
81694	6 X 5/8	3.5 X 16	81704	8 X 1	4.2 X 25
81696	6 X 3/4	3.5 X 19	81706	8 X 1 1/4	4.2 X 32
81698	6 X 1	3.5 X 25	81708	8 X 1 1/2	4.2 X 38
			81709	8 X 2	4.2 X 50

Stainless Screw Cups



Stainless Fastenings = 30% standard discount & 60% when you buy 100 or more.

Size

6g

7g / 8g

9g / 10g

12g

14g

Stainless Raised Head Slotted Self Tappers



White Plastic Screw Caps



A2 Grade (308)	Imperial Size	Metric Size (mm)												
4	4G / ø2.9mı	m		6G / ø3.5m	m		8G / ø4.2m	m		10G / ø4.8m	ım		12G / ø5.5m	ım
81442	4 x 3/8	2.9 x 10	81444	6 X 3/8	3.5 X 10	81453	8 X 1/2	4.2 X 13	81461	10 X 1/2	4.8 X 13	81470	12 X 1	5.5 X 25
			81446	6 X 1/2	3.5 X 13	81454	8 X 5/8	4.2 X 16	81463	10 X 3/4	4.8 X 19	81472	12 X 1 1/4	5.5 X 32
			81448	6 X 5/8	3.5 X 16	81455	8 X 3/4	4.2 X 19	81462	10 X 1	4.8 X 25	81474	12 X 1 1/2	5.5 X 38
			81450	6 X 3/4	3.5 X 19	81456	8 X 1	4.2 X 25	81464	10 X 1 1/4	4.8 X 32			
			81452	6 X 1	3.5 X 25	81458	8 X 1 1/4	4.2 X 32	81466	10 X 1 1/2	4.8 X 38			
						81460	8 X 1 1/2	4.2 X 38	81468	10 X 2	4.8 X 50			

Stainless Raised Head Slotted Woodscrews



A2 Grade (308)	Imperial Size	Metric Size (mm)
	8G / ø4.2mi	m
81910	8 X 3/4	4.2 X 19
81912	8 X 1	4.2 X 25
81914	8 X 1 1/4	4.2 X 32
81916	8 X 1 1/2	4.2 X 38

A2 Grade (308)	A4 Grade (316)	Imperial Size	Metric Size (mm)
	4G /	ø2.9mm	
81902	85700	4 X 1/2	2.9 X 13
-	85701	4 X 5/8	2.9 X 16
-	85702	4 X 3/4	2.9 X 19
-	85703	4 X 1	2.9 x 25

A2 Grade (308)	Imperial Size	Metric Size (mm)	
10G / ø4.8mm			
81917	10 X 1	4.8 X 25	
81918	10 X 1 1/4	4.8 X 32	
81920	10 X 1 1/2	4.8 X 38	

A2 Grade (308)	A4 Grade (316)	Imperial Size	Metric Size (mm)
	6G /	ø3.5mm	
81904	-	6 X 1/2	3.5 X 13
81906	85710	6 X 3/4	3.5 X 19
-	85711	6 X 1	3.5 X 25
81908	-	6 X 1 1/4	3.5 X 32

Stainless Countersunk Slotted Self Tappers A4

Α4

Grade

(316)

81415

81419

81423

81425

81427

81431



A4 (316) Stainless Steel is suitable for use above and below the waterline.

Metric

Size (mm)

4.8 X 13

4.8 X 16

4.8 X 19

4.8 X 25

4.8 X 32

4.8 X 38

4.8 X 50

Imperial

Size

10G / ø4.8mm

10 X 1/2

10 X 5/8

10 X 3/4

10 X 1

10 X 1 1/4

10 X 1 1/2

10 X 2

A4 Grade (316)	Imperial Size	Metric Size (mm)
	4G / ø2.9m	m
81341	4 X 1/4	2.9 X 6
81343	4 X 3/8	2.9 X 10
81345	4 X 1/2	2.9 X 13
81347	4 X 5/8	2.9 X 16
81349	4 X 3/4	2.9 X 19
81353	4 X 1	2.9 X 25

	81349		4	X 3	/4
	813	53	4	X	1
Impe Siz		S	etri Size nm	-	
12G / ø	5.5mr	n			
12 X	1/2	5.5	X	13	
12 X	3/4	5.5	X	19	
12 X	(1	5.5	X	25	
12 X 1	1/4	5.5	X	32	
12 X 1	1/2	5.5	X	38	
12 X	(2	5.5	X	50	

A4 Grade (316)	Imperial Size	Metric Size (mm)	A4 Grade (316)	Imperial Size	Metric Size (mm)
	6G / ø3.5m	ım		8G / ø4.2m	m
81355	6 X 1/4	3.5 X 6	81375	8 X 3/8	4.2 X 10
81357	6 X 3/8	3.5 X 10	81377	8 X 1/2	4.2 X 13
81359	6 X 1/2	3.5 X 13	81379	8 X 5/8	4.2 X 16
81361	6 X 5/8	3.5 X 16	81381	8 X 3/4	4.2 X 19
81363	6 X 3/4	3.5 X 19	81385	8 X 1	4.2 X 25
81367	6 X 1	3.5 X 25	81387	8 X 1 1/4	4.2 X 32
81369	6 X 1 1/4	3.5 X 32	81389	8 X 1 1/2	4.2 X 38
81371	6 X 1 1/2	3.5 X 38	81393	8 X 2	4.2 X 50

A4 Grade (316)	Imperial Size	Metric Size (mm)	
14G / ø6.3mm			
81439	14 X 1 1/2	6.3 X 38	
81441	14 X 2	6.3 X 50	

Stainless Fastenings = 30% standard discount & 60% when you buy 100 or more.

Grade

(316)

81397

81399

81401

81405

81407

81409

81413

Stainless Pan Head Slotted Self Tappers



A4 (316) Stainless Steel is suitable for use above and below the waterline.

A4 Grade (316)	Imperial Size	Metric Size (mm)	A4 Grade (316)	Imperial Size	Metric Size (mm)	A4 Grade (316)	Imperial Size	Metric Size (mm)
	4G / ø2.9m	m		6G / ø3.5m	m		3G / ø4.2mr	n
81233	4 X 3/8	2.9 X 10	81247	6 X 3/8	3.5 X 10	81263	8 X 3/8	4.2 X 10
81235	4 X 1/2	2.9 X 13	81249	6 X 1/2	3.5 X 13	81265	8 X 1/2	4.2 X 13
81237	4 X 5/8	2.9 X 16	81251	6 X 5/8	3.5 X 16	81267	8 X 5/8	4.2 X 16
81239	4 X 3/4	2.9 X 19	81253	6 X 3/4	3.5 X 19	81269	8 X 3/4	4.2 X 19
81241	4 X 1	2.9 X 25	81257	6 X 1	3.5 X 25	81273	8 X 1	4.2 X 25
			81259	6 X 1 1/4	3.5 X 32	81275	8 X 1 1/4	4.2 X 32
			81261	6 X 1 1/2	3.5 X 38	81277	8 X 1 1/2	4.2 X 38
Motric	Δ4		Motri			81281	8 X 2	4 2 X 50

A4 Grade (316)	Imperial Size	Metric Size (mm)
	10G / ø4.8m	m
81283	10 X 3/8	4.8 X 10
81285	10 X 1/2	4.8 X 13
81287	10 X 5/8	4.8 X 16
81289	10 X 3/4	4.8 X 19
81293	10 X 1	4.8 X 25
81295	10 X 1 1/4	4.8 X 32
81297	10 X 1 1/2	4.8 X 38
81301	10 X 2	4.8 X 50

A4 Grade (316)	Imperial Size	Metric Size (mm)
	12G / ø5.5mr	n
81303	12 X 1/2	5.5 X 13
81305	12 X 5/8	5.5 X 16
81307	12 X 3/4	5.5 X 19
81311	12 X 1	5.5 X 25
81313	12 X 1 1/4	5.5 X 32
81315	12 X 1 1/2	5.5 X 38
81319	12 X 2	5.5 X 50
		25.00

A4 Grade (316)	Imperial Size	Metric Size (mm)					
14G / ø6.3mm							
81325	14 X 1 1/4	6.3 X 32					
81327	14 X 1 1/2	6.3 X 38					
81329	14 X 2	6.3 X 50					

Stainless Countersunk Slotted Woodscrews



A2 Grade (308)	A4 Grade (316)	Imperial Size	Metric Size (mm)												
	4G /	ø2.9mm			6G /	ø3.5mm		8G / ø4.2mm			10G / ø4.8mm				
81730	81731	4 X 1/2	2.9 X 13	81738	-	6 X 1/2	3.5 X 13	81750	-	8 X 1/2	4.2 X 13	81768	81769	10 X 3/4	4.8 X 19
81732	81733	4 X 5/8	2.9 X 16	81740	81741	6 X 5/8	3.5 X 16	81752	-	8 X 3/4	4.2 X 19	81770	81771	10 X 1	4.8 X 25
81734	81735	4 X 3/4	2.9 X 19	81742	81743	6 X 3/4	3.5 X 19	81754	81755	8 X 1	4.2 X 25	81772	81773	10 X 1 1/4	4.8 X 32
81736	81737	4 X 1	2.9 X 25	81744	81745	6 X 1	3.5 X 25	81756	81757	8 X 1 1/4	4.2 X 32	81774	81775	10 X 1 1/2	4.8 X 38
-	81729	4 x 1 1/4	2.9 X 32	81746	81747	6 X 1 1/4	3.5 X 32	81758	81759	8 X 1 1/2	4.2 X 38	81776	-	10 X 1 3/4	4.8 X 44
-	82728	4 X 1 1/2	2.9 x 38	81748	81749	6 X 1 1/2	3.5 X 38	81760	-	8 X 1 3/4	4.2 X 44	81778	81779	10 X 2	4.8 X 50
				-	81751	6 X 1 3/4	3.5 X 45	81762	81763	8 X 2	4.2 X 50	81780	81781	10 X 2 1/2	4.8 X 64
				-	81727	6 x 2	3.5 x 50	81764	-	8 X 2 1/2	4.2 X 64	81782	81783	10 X 3	4.8 X 76
								81766	-	8 X 3	4.2 X 76	81784	-	10 X 3 1/2	4.8 X 89
												81786	-	10 X 4	4.8 X 102

A2 Grade (308)	A4 Grade (316)	Imperial Size	Metric Size (mm)	A2 Grade (308)	A4 Grade (316)	Imperial Size	Metric Size (mm)	A2 Grade (308)	Imperial Size	Metric Size (mm)	A2 Grade (308)	Imperial Size	Metric Size (mm)
	120	G / ø5.5mm		14G / ø6.3mm		16G / ø7.1mm		18G / ø8.0mm					
81788	-	12 X 1	5.5 X 25	81804	-	14 X 1 1/4	6.3 X 32	81816	16 X 2 1/2	7.1 X 64	81822	18 X 2 1/2	8 X 64
81790	81791	12 X 1 1/4	5.5 X 32	81806	81807	14 X 1 1/2	6.3 X 38	81818	16 X 3	7.1 X 76	81824	18 X 3	8 X 76
81792	81793	12 X 1 1/2	5.5 X 38	81808	81809	14 X 2	6.3 X 50	81820	16 X 4	7.1 X 102	81826	18 X 3 1/2	8 X 89
81794	81795	12 X 2	5.5 X 50	81810	81811	14 X 2 1/2	6.3 X 64				81828	18 X 4	8 X 102
81796	81797	12 X 2 1/2	5.5 X 64	81812	81813	14 X 3	6.3 X 76				01020	10 / 4	0 X 102
81798	81799	12 X 3	5.5 X 76	81814	-	14 X 3 1/2	6.3 X 89						
81800	-	12 X 3 1/2	5.5 X 89	81815	-	14 X 4	6.3 X 102						
81802	81803	12 X 4	5.5 X 102										

Stainless Round Head Slotted Woodscrews



A2 Grade (308)	Imperial Size	Metric Size (mm)					
4G / ø2.9mm							
81830	4 X 1/2	2.9 X 13					
81832	4 X 5/8	2.9 X 16					
81834	4 X 3/4	2.9 X 19					
81836	4 X 1	2.9 X 25					

A2 Grade (308)	Imperial Size	Metric Size (mm)					
	6G / ø3.5m						
81838	6 X 1/2	3.5 X 13					
81840	6 X 5/8	3.5 X 16					
81842	6 X 3/4	3.5 X 19					
81844	6 X 1	3.5 X 25					
81846	6 X 1 1/4	3.5 X 32					

A2 Grade (308)	Imperial Size	Metric Size (mm)	A2 Grade (308)	Imperial Size	Metric Size (mm)			
	8G / ø4.2m	m		10G / ø4.8mm				
81847	8 X 1/2	4.2 X 13	81864	10 X 3/4	4.8 X 19			
81848	8 X 3/4	4.2 X 19	81866	10 X 1	4.8 X 25			
81850	8 X 1	4.2 X 25	81868	10 X 1 1/4	4.8 X 32			
81852	8 X 1 1/4	4.2 X 32	81870	10 X 1 1/2	4.8 X 38			
81854	8 X 1 1/2	4.2 X 38	81872	10 X 1 3/4	4.8 X 44			
81856	8 X 1 3/4	4.2 X 44	81874	10 X 2	4.8 X 50			
81858	8 X 2	4.2 X 50	81876	10 X 2 1/2	4.8 X 64			
81860	8 X 2 1/2	4.2 X 64	81878	10 X 3	4.8 X 76			
81862	8 X 3	4.2 X 76	81880	10 X 3 1/2	4.8 X 89			
			81882	10 X 4	4.8 X 102			

A2 Grade (308)	Imperial Size	Metric Size (mm)					
12G / ø5.5mm							
81883	12 X 1	5.5 X 25					
81884	12 X 1 1/4	5.5 X 32					
81886	12 X 1 1/2	5.5 X 38					
81888	12 X 2	5.5 X 50					
81890	12 X 2 1/2	5.5 X 64					
81892	12 X 3	5.5 X 76					

A2 Grade (308)	Imperial Size	Metric Size (mm)					
14G / ø6.3mm							
81894	14 X 1 1/2	6.3 X 38					
81896	14 X 2	6.3 X 50					
81900	14 X 3	6.3 X 76					

Pozi Countersunk Woodscrews A2





A2 Grade (308)	Imperial Size	Metric Size (mm)					
6G / ø3.5mm							
85910	6 X 1/2	3.5 X 13					
85911	6 X 3/4	3.5 X 19					
85912	6 X 1	3.5 X 25					
85914	6 X 1 1/2	3.5 X 38					

A2 Grade (308)	Imperial Size	Metric Size (mm)		
8G / ø4.2mm				
85920	8 X 1/2	4.2 X 13		
85921	8 X 3/4	4.2 X 19		
85922	8 X 1	4.2 X 25		
85923	8 X 1 1/2	4.2 X 38		
85924	8 X 2	4.2 X 50		

A2 Grade (308)	Imperial Size	Metric Size (mm)		
	10G / ø4.8mm			
85930	10 X 3/4	4.8 X 19		
85931	10 X 1	4.8 X 25		
85932	10 X 1 1/2	4.8 X 38		
85933	10 X 2	4.8 X 50		
85934	10 X 3	4.8 X 76		
85935	10 X 4	4.8 X 102		

A2 Grade (308)	Imperial Size	Metric Size (mm)	
12G / ø5.5mm			
85940	12 X 1 1/2	5.5 X 38	
85941	12 X 2	5.5 X 50	
85942	12 X 3	5.5 X 76	
85943	12 X 4	5.5 X 102	

Zinc Plated & Yellow Passivated Chippy Pozi Drive Woodscrews (Sold in boxes of 200)



Part No	Description	Part No	Description	Part No
82371	3.5 X 25mm	82394	4 X 70mm	8238
82372	3.5 X 30mm	82395	5 X 20mm	8238
82373	3.5 X 40mm	82381	5 X 30mm	8238
82374	4 X 20mm	82382	5 X 40mm	8239
82375	4 X 25mm	82383	5 X 50mm	8239
82376	4 X 30mm	82396	5 X 60mm	8239
82377	4 X 35mm	82397	5 X 70mm	8239
82378	4 X 40mm	82384	5 X 80mm	
82379	4 X 50mm	82385	5 X 90mm	
82380	4 X 60mm	82386	5 X 100mm	

A2

Grade

(308)

80048

80050

Grade

(316)

Part No	Description
82387	6 X 40mm
82388	6 X 50mm
82389	6 X 60mm
82390	6 X 70mm
82391	6 X 80mm
82392	6 X 90mm
82393	6 X 100mm

Size

Stainless Hex Head Bolts



A2 (308) Stainless steel is suitable for use above the waterline.

A4 (316) Stainless Steel is suitable for use above and below the waterline.

A2 Grade (308)	A4 Grade (316)	Size
	M5	
80000	-	M5 X 25
80002	80003	M5 X 30
80004	80005	M5 X 35
80006	80007	M5 X 40
80008	80009	M5 X 45
80010	80011	M5 X 50
80012	-	M5 X 55
80014	-	M5 X 60

		M6			M8	
5	80015	-	M6 X 25	80052	80053	M8 X 30
)	80016	80017	M6 X 30	80054	80055	M8 X 35
5	80018	80019	M6 X 35	80056	80057	M8 X 40
)	80020	80021	M6 X 40	80058	80059	M8 X 45
5	80022	80023	M6 X 45	80060	80061	M8 X 50
)	80024	80025	M6 X 50	80062	80063	M8 X 55
5	80026	80027	M6 X 55	80064	80065	M8 X 60
)	80028	80029	M6 X 60	80066	80067	M8 X 65
	-	80031	M6 X 65	80068	80069	M8 X 70
	80032	80033	M6 X 70	80070	80071	M8 X 75
	80034	80035	M6 X 75	80072	80073	M8 X 80
	80036	80037	M6 X 80	80074	80075	M8 X 90
	80038	80039	M6 X 90	80076	80077	M8 X 100
	80040	80041	M6 X 100	80078	80079	M8 X 110
	80044	-	M6 X 120	80080	80081	M8 X 120
	80046	80047	M6 X 130	80082	80083	M8 X 130

A2

Grade

(308)

Grade

(316)

Size

M8 X 140

M8 X 150

A2 Grade (308)	A4 Grade (316)	Size	A2 Grade (308)	A4 Grade (316)	Size	
	M10			M12		
80088	80089	M10 X 35	80122	80123	M12 X 40	
80090	80091	M10 X 40	-	80125	M12 X 45	
80092	80093	M10 X 45	80126	80127	M12 X 50	
80094	80095	M10 X 50	80128	80129	M12 X 55	
80096	80097	M10 X 55	80130	80131	M12 X 60	
80098	80099	M10 X 60	80132	80133	M12 X 65	
	80101	M10 X 65	80136	80137	M12 X 75	
80102	80103	M10 X 70	-	80139	M12 X 80	
80104	80105	M10 X 75	80140	80141	M12 X 90	
80106	80107	M10 X 80	80142	80143	M12 X 100	
80108	80109	M10 X 90	80144	80145	M12 X 110	
80110	80111	M10 X 100	80146	80147	M12 X 120	
80112	80113	M10 X 110	80148	80149	M12 X 130	
80114	80115	M10 X 120	80150	80151	M12 X 140	
80116	80117	M10 X 130	80152	80153	M12 X 150	
80118	80119	M10 X 140	80154	-	M12 X 160	
80120	80121	M10 X 150	80156	80157	M12 X 180	
00123	30.27	10 / 100	80158	80159	M12 X 200	

A2 Grade (308)	A4 Grade (316)	Size	A2 Grade (308)	A4 Grade (316)	Size
	M16			M16	
80160	80161	M16 X 50	80178	-	M16 X 110
-	80163	M16 X 55	80180	80181	M16 X 120
80164	80165	M16 X 60	80182	80183	M16 X 130
-	80169	M16 X 70	80184	80185	M16 X 140
80170	80171	M16 X 75	80186	80187	M16 X 150
80172	80173	M16 X 80	80188	-	M16 X 160
80174	80175	M16 X 90	80190	-	M16 X 180
80176	80177	M16 X 100	80192	-	M16 X 200

M6 X 140

M6 X 150

80084

80086

80087

Stainless Hex Head Setscrews



A2 (308) Stainless steel is suitable for use above the waterline.

A4 (316) Stainless Steel is suitable for use above and below the waterline.

A2 Grade (308)	Size
N	/ 13
80300	M3 X 6
80302	M3 X 8
80304	M3 X 10
80306	M3 X 12
80308	M3 X 16
80310	M3 X 20
80312	M3 X 25
80314	M3 X 30
80316	M3 X 35
80318	M3 X 40

A2 Grade (308)	A4 Grade (316)	Size
	M4	
80320	-	M4 X 6
80322	80323	M4 X 8
80324	80325	M4 X 10
80326	80327	M4 X 12
80328	80329	M4 X 16
80330	80331	M4 X 20
80332	80333	M4 X 25
80334	80335	M4 X 30
80336	80337	M4 X 35
80338	80339	M4 X 40
80340	-	M4 X 45
80342	-	M4 X 50

A2 Grade (308)	A4 Grade (316)	Size
	M5	
-	80345	M5 X 8
80346	80347	M5 X 10
80348	80349	M5 X 12
80350	80351	M5 X 16
80352	80353	M5 X 20
80354	80355	M5 X 25
80356	80357	M5 X 30
80358	80359	M5 X 35
80360	80361	M5 X 40
80362	80363	M5 X 45
80364	80365	M5 X 50
80366	80367	M5 X 55
80368	80369	M5 X 60
-	80536	M5 X 80

A2 Grade (308)	A4 Grade (316)	Size					
	M6						
80370	80371	M6 X 8					
80372	80373	M6 X 10					
80374	80375	M6 X 12					
80376	80377	M6 X 16					
80378	80379	M6 X 20					
80380	80381	M6 X 25					
80382	80383	M6 X 30					
80384	80385	M6 X 35					
80386	80387	M6 X 40					
80388	80389	M6 X 45					
80390	80391	M6 X 50					
80392	80393	M6 X 55					
80394	80395	M6 X 60					
80396	-	M6 X 65					
80398	80399	M6 X 70					
80400	80401	M6 X 75					
80402	80403	M6 X 80					
80404	80405	M6 X 90					
80406	80407	M6 X 100					

A2 Grade (308)	A4 Grade (316)	Size			
M8					
-	80409	M8 X 10			
80410	80411	M8 X 12			
80412	80413	M8 X 16			
80414	80415	M8 X 20			
80416	80417	M8 X 25			
80418	80419	M8 X 30			
80420	80421	M8 X 35			
80422	80423	M8 X 40			
80424	80425	M8 X 45			
80426	80427	M8 X 50			
80428	-	M8 X 55			
80430	80431	M8 X 60			
80432	80433	M8 X 65			
80434	80435	M8 X 70			
80436	80437	M8 X 75			
80438	80439	M8 X 80			
80440	80441	M8 X 90			
80442	80443	M8 X 100			
80444	80445	M8 X 110			
80446	80447	M8 X 120			
80448	80449	M8 X 130			
80450	80451	M8 X 140			
80452	80453	M8 X 150			

A2 Grade (308)	A4 Grade (316)	Size		
M10				
80454	80455	M10 X 12		
80456	80457	M10 X 16		
80458	80459	M10 X 20		
80460	80461	M10 X 25		
80462	80463	M10 X 30		
80464	-	M10 X 35		
80466	80467	M10 X 40		
80468	-	M10 X 45		
80470	80471	M10 X 50		
-	80473	M10 X 55		
80474	80475	M10 X 60		
80476	80477	M10 X 65		
80478	80479	M10 X 70		
80480	80481	M10 X 75		
80482	80483	M10 X 80		
80484	80485	M10 X 90		
80486	80487	M10 X 100		
80488	80489	M10 X 110		
80490	80491	M10 X 120		
80492	-	M10 X 130		
80494	80495	M10 X 140		
80496	80497	M10 X 150		

A2 Grade (308)	A4 Grade (316)	Size					
M12							
80498	80499	M12 X 25					
80500	80501	M12 X 30					
80502	80503	M12 X 35					
80504	80505	M12 X 40					
80506	-	M12 X 45					
80508	80509	M12 X 50					
80512	80513	M12 X 60					
80514	-	M12 X 65					
80518	80519	M12 X 75					
80520	80521	M12 X 80					
80522	80523	M12 X 90					
80524	80525	M12 X 100					
80526	-	M12 X 110					
80528	80529	M12 X 120					
80530	-	M12 X 130					
80532	-	M12 X 140					
80534	80535	M12 X 150					

Stainless Countersunk Slotted Machine Screws

A2 Grade (308)	A4 Grade (316)	Size	A2 Grade (308)	A4 Grade (316)	Size
	М3			M4	
80550	80551	M3 X 6	80570	-	M4 X 6
80552	80553	M3 X 8	80572	80573	M4 X 8
80554	80555	M3 X 10	80574	80575	M4 X 10
80556	80557	M3 X 12	80576	80577	M4 X 12
80558	80559	M3 X 16	80578	80579	M4 X 16
80560	80561	M3 X 20	80580	80581	M4 X 20
80562	80563	M3 X 25	80582	80583	M4 X 25
80564	80565	M3 X 30	80584	80585	M4 X 30
80566	-	M3 X 35	80586	80587	M4 X 35
80568	-	M3 X 40	80588	80589	M4 X 40
			80590	-	M4 X 45
			80592	80593	M4 X 50



A2 (308) Stainless steel is suitable for use above the waterline.

A4 (316) Stainless Steel is suitable for use above and below the waterline.

A2 Grade (308)	A4 Grade (316)	Size	A2 Grade (308)	A4 Grade (316)	Size
	M5			М6	
80594	80595	M5 X 8	80632	80633	M6 X 10
80596	80597	M5 X 10	80634	80635	M6 X 12
80598	80599	M5 X 12	80636	80637	M6 X 16
80600	80601	M5 X 16	80638	80639	M6 X 20
80602	80603	M5 X 20	80640	80641	M6 X 25
80604	80605	M5 X 25	80642	80643	M6 X 30
80606	80607	M5 X 30	80644	80645	M6 X 35
80608	80609	M5 X 35	80646	80647	M6 X 40
80610	80611	M5 X 40	80648	-	M6 X 45
80612	-	M5 X 45	80658	80659	M6 X 50
80614	80615	M5 X 50	80660	-	M6 X 55
80616	-	M5 X 55	80662	80663	M6 X 60
80618	-	M5 X 60	80664	-	M6 X 65
80620	-	M5 X 65	80666	80667	M6 X 70
80622	-	M5 X 70	80668	80669	M6 X 75
80624	80625	M5 X 75	80670	80671	M6 X 80
80626	80627	M5 X 80	80672	80673	M6 X 90
80628	-	M5 X 90	80674	80675	M6 X 100
80630	80631	M5 X 100			

A2 Grade (308)	A4 Grade (316)	Size				
M8						
80676	-	M8 X 12				
80678	80679	M8 X 16				
80680	80681	M8 X 20				
80682	80683	M8 X 25				
80684	80685	M8 X 30				
80686	80687	M8 X 35				
80688	80689	M8 X 40				
80690	80691	M8 X 45				
80692	80693	M8 X 50				
80694	80695	M8 X 60				
80696	-	M8 X 65				
80698	80699	M8 X 70				
80700	80701	M8 X 75				
80702	80703	M8 X 80				
80704	80705	M8 X 90				
80706	80707	M8 X 100				

A2 Grade (308)	A4 Grade (316)	Size	Gi	A2 rade 308)	Size
	M10		M12		
80708	80709	M10 X 20	80	736	M12 X 20
80710	80711	M10 X 25	80	738	M12 X 25
80712	-	M10 X 30	80	740	M12 X 30
80714	-	M10 X 35	80	742	M12 X 35
80716	80717	M10 X 40	80	744	M12 X 40
80718	-	M10 X 45	80	746	M12 X 50
80720	80721	M10 X 50	80	748	M12 X 60
80722	-	M10 X 60	80	749	M12 X 65
80724	-	M10 X 65	80	750	M12 X 70
80726	80727	M10 X 70	80	752	M12 X 80
80728	80729	M10 X 75	80	754	M12 X 90
80730	80731	M10 X 80	80	756	M12 X 100
80732	80733	M10 X 90			
80734	80737	M10 X 100			
80735		M10 X 120			

Stainless Pan Head Slotted Machine Screws

A2 Grade (308)	A4 Grade (316)	Size
	М3	
80760	80761	M3 X 6
80762	80763	M3 X 8
80764	80765	M3 X 10
80766	80767	M3 X 12
80768	80769	M3 X 16
80770	80771	M3 X 20
80772	80773	M3 X 25
80774	80775	M3 X 30

A2 Grade (308)	A4 Grade (316)	Size
	M4	
80776	80777	M4 X 6
80778	80779	M4 X 8
80780	80781	M4 X 10
80782	80783	M4 X 12
80784	80785	M4 X 16
80786	80787	M4 X 20
80788	80789	M4 X 25
80790	80791	M4 X 30
80792	80793	M4 X 35
80794	80795	M4 X 40
80796	-	M4 X 45
80798	-	M4 X 50



A2 (308) Stainless steel is suitable for use above the waterline.

A4 (316) Stainless Steel is suitable for use above and below the waterline.

A2 Grade (308)	A4 Grade (316)	Size									
	М5			М6			M8			M10	
80800	-	M5 X 6	80832	-	M6 X 8	80868	-	M8 X 12	80898	-	M10 X 25
80802	-	M5 X 8	80834	80835	M6 X 10	80870	80871	M8 X 16	80899	-	M10 X 35
80804	80805	M5 X 10	80836	80837	M6 X 12	80872	80873	M8 X 20	80900	80901	M10 X 40
80806	80807	M5 X 12	80838	80839	M6 X 16	80874	80875	M8 X 25	80902	-	M10 X 50
80808	80809	M5 X 16	80840	80841	M6 X 20	80876	80877	M8 X 30	-	80903	M10 X 60
80810	80811	M5 X 20	80842	80843	M6 X 25	80878	80879	M8 X 35	80904	80909	M10 X 75
80812	80813	M5 X 25	80844	80845	M6 X 30	80880	80881	M8 X 40	80905	-	M10 X 80
80814	80815	M5 X 30	80846	80847	M6 X 35	80882	80883	M8 X 50	80906	80907	M10 X 100
80816	80817	M5 X 35	80848	80849	M6 X 40	80884	80885	M8 X 60			
80818	80819	M5 X 40	80850	-	M6 X 45	80886	80887	M8 X 65			
80820	80821	M5 X 45	80852	80853	M6 X 50	80888	-	M8 X 70			
80822	80823	M5 X 50	80854	80855	M6 X 60	80890	80891	M8 X 75			
80824	-	M5 X 60	80856	-	M6 X 65	80892	-	M8 X 80			
80826	-	M5 X 65	80858	-	M6 X 70	80894	-	M8 X 90			
80828	80827	M5 X 75	80860	80861	M6 X 75	80896	80897	M8 X 100			
80829	-	M5 X 80	80862	80863	M6 X 80						
80830	-	M5 X 100	80864	-	M6 X 90						
			80866	80867	M6 X 100						

Stainless Full **Nuts**

Stainless Nyloc Nuts

Stainless Dome Nuts

Stainless Wing Nuts

Stainless Tooth Washers





0		0
	000	
Λ2	Δ4	





A2 Grade (308)	A4 Grade (316)	Size
81070	81071	M3
81072	81073	M4
81074	81075	M5
81076	81077	M6
81078	81079	M8
81080	81081	M10
81082	81083	M12
81084	81085	M16

81086 81087 81088

81089

M20

M24

	of the same	AL SECTION OF			0年20年87月8
A2 Grade (308)	A4 Grade (316)	Size	A2 Grade (308)	A4 Grade (316)	Size
81130	81131	M3	81160	81161	M3
81132	81133	M4	81162	81163	M4
81134	81135	M5	81164	81165	M5
81136	81137	M6	81166	81167	M6
81138	81139	M8	81168	81169	M8
81140	81141	M10	81170	81171	M10
81142	81143	M12	81172	81173	M12
81150	-	M14	81174	81175	M16
81144	81145	M16	-	81176	M20
81146	81147	M20			


Grade Grade Size (308)(316)81180 М3 81182 81183 81184 81185 M5 81186 81187 M6 81189 M8 81188 81190 81191 M10 81192 81193 M12 M16 81194

A2 Grade Grade Size (308)(316)М3 81200 81201 81202 81203 M4 81204 81205 M5 M6 81206 81207 81208 81209 M8 81210 81211 M10 81212 M12 81214 M16

Stainless Form A Washers

M24

81148 81149











A2 Grade (308)	A4 Grade (316)	Outside Diameter mm	Size
81000	81001	7mm	МЗ
81002	81003	9mm	M4
81004	81005	10mm	M5
81006	81007	12mm	M6
81008	81009	16mm	M8
81010	81011	20mm	M10
81012	81013	24mm	M12
81020	-	28mm	M14

30mm

37mm

44mm

M16

M20

M24

81015

81017

81019



A2 Grade (308)	A4 Grade (316)	Outside Diameter mm	Size
-	81029	25mm	M4
81030	81031	25mm	M5
81032	81033	25mm	M6
81034	81035	30mm	M8
81036	81037	35mm	M10
81038	81039	35mm	M12



A4 Grade (316)	Size	Outside Diameter mm
80990	M6	-
80991	M8	21mm
80992	M10	24mm
80993	M12	28mm
80994	M16	34mm



A2 Grade (308)	A4 Grade (316)	Size
81040	81041	M3
81042	81043	M4
81044	81045	M5
81046	81047	M6
81048	81049	M8
81050	81051	M10
81052	81053	M12
81054	81055	M16
81056	81057	M20
81058	81059	M24

Stainless Fastenings = 30% standard discount & 60% when you buy 100 or more.

81014

81016

81018

Stainless Steel Studding



A2 Grade (308)	A4 Grade (316)	Size
80910	80911	M4 X 1m
80912	80913	M5 X 1m
80914	80915	M6 X 1m
80916	80917	M8 X 1m
80918	80919	M10 X 1m
80920	80921	M12 X 1m
81151	-	M14 x 1m
80922	80923	M16 X 1m
80924	80925	M20 X 1m
80926	80927	M24 X 1m

Stainless Steel R Clips



Stainles	Stainless Steel R Clips		
A4 Grade (316)	Description		
33880	2mm X 48mm		
33882	3mm X 70mm		
33883	4mm X 76mm		
33884	5mm X 100mm		
33885	6mm X 125mm		

Stainless Steel Half Nuts



A4 Grade (316)	Size
81110	M4
81111	M5
81112	M6
81113	M8
81114	M10
81115	M12
81116	M16
81117	M20

Monel Pop Rivets



Monel Pop Rivets		
Part No	Description	
86700	4.0 X 10mm	
86701	4.8 X 8mm	
86702	4.8 X 12mm	
86703	4.8 X 18mm	
86704	4.8 X 16mm	
86705	6.4 X 16mm	
86706	6.4 X 19mm	

Stainless Steel Clevis Pins



A4 Grade (316)	Dimensions (mm)	A4 Grade (316)	Dimensions (mm)	A4 Grade (316)	Dimensions (mm)
33905	4.75 X 16mm	33915	7.9 X 19mm	33922	9.5 X 32mm
33907	4.75 X 19mm	33916	7.9 X 25mm	33923	9.5 X 38mm
33908	4.75 X 25mm	33917	7.9 X 32mm	33924	12.7 X 25mm
33910	6.35 X 18.5mm	33918	7.9 X 38mm	33925	12.7 X 31.8mm
33912	6.35 X 25mm	33920	9.5 X 19mm	-	
33913	6.35 X 35mm	33921	9.5 X 25mm	-	

Stainless Steel

Eye Nuts



A4 Grade (316)	Thread	D
34004	M6	16mm
34005	M8	20mm
34010	M10	25mm
34015	M12	30mm
34017	M16	35mm

Nylon Washer



Part No	Size
80980	M4
80981	M5
80982	M6
80983	M8
80984	M10
80986	M12

Stainless Steel Circlip



Stainless Steel Circlips	
A2 Grade (308)	Description
86500	M8
86502	M10
86504	M12
86506	M16
86508	M20

Stainless Steel Split Rings



A2 Grade (308)	Diameter (mm)
33875	10mm
33876	14mm
33877	19mm
33878	28mm

Stainless Grub Screws



A4 Grade (316)	Size x Length
86530	M3 x 5
86532	M4 x 6
86534	M5 x 6
86536	M6 x 8
86538	M8 x 10
86540	M10 x 10

Stainless Steel A4 Inter Screws



Knurled Sides, Smooth Domed Top



Smooth Sides, Slotted Raised Countersunk Top

4 Grade (316)	Size	A4 Grade (316)	Size
86520	M4 X 6	86524	M5 X 1
86521	M4 X 12	86525	M6 X 1
86522	M5 X 6	86526	M8 X 2
86523	M5 X 10		

Stainless Steel A2 (308) Panel Pins



Sold in 100 gram intervals

A2 Grade (308)	Thickness X Length	Quantity Per Kilo (Approx)
82144	1.6mm X 20mm	2985
82145	1.6mm X 25mm	2371
82146	1.6mm X 30mm	2083
82147	1.6mm X 40mm	1470

Stainless Steel A2 (308) Split Pins



A2 Grade (308)	Imperial Size	Metric Size (mm)
	1/32 / 0.8mm	
82044	1/32 X 3/4	0.8 X 19
82046	1/32 X 1	0.8 X 25
	1/16 / 1.6mm	
82059	1/16 X 1/2	1.6 X 13
82058	1/16 X 3/4	1.6 X 19
82060	1/16 X 1	1.6 X 25
82061	1/16 X 1 1/8	1.6 X 29
82062	1/16 X 1 1/4	1.6 X 32
82064	1/16 X 1 1/2	1.6 X 38
82065	1/16 X 1 3/4	1.6 X 44
	3/32 / 2.4mm	
82084	3/32 X 1/2	2.4 X 13
82085	3/32 X 5/8	2.4 X 16
82086	3/32 X 3/4	2.4 X 19
82087	3/32 X 7/8	2.4 X 22
82088	3/32 X 1	2.4 X 25
82090	3/32 X 1 1/4	2.4 X 32
82091	3/32 X 1 1/2	2.4 X 38
82092	3/32 X 1 3/4	2.4 X 44

A2 Grade (308)	Imperial Size	Metric Size (mm)
82093	3/32 X 2	2.4 X 50
82094	3/32 X 2 1/2	2.4 X 64
	1/8 / 3.2mm	
82097	1/8 X 1/2	3.2 X 13
82098	1/8 X 5/8	3.2 X 16
82099	1/8 X 3/4	3.2 X 19
82100	1/8 X 7/8	3.2 X 22
82101	1/8 X 1	3.2 X 25
82102	1/8 X 1 1/4	3.2 X 32
82103	1/8 X 1 1/2	3.2 X 38
82104	1/8 X 1 3/4	3.2 X 44
82105	1/8 X 2	3.2 X 50
82106	1/8 X 2 1/4	3.2 X 57
82107	1/8 X 2 1/2	3.2 X 64
	5/32 / 4.0mm	l
82108	5/32 X 1	4 X 25
82109	5/32 X 1 1/4	4 X 32
82110	5/32 X 2	4 X 50
3/16 / 4.8 mm		
82120	3/16 X 3/4	4 X 19
82121	3/16 X 7/8	4 X 22

A2 Grade (308)	Imperial Size	Metric Size (mm)
82122	3/16 X 1	4 X 25
82123	3/16 X 1 1/8	4 X 29
82124	3/16 X 1 1/4	4 X 32
82125	3/16 X 1 3/8	4 X 35
82126	3/16 X 1 1/2	4 X 38
82128	3/16 X 1 3/4	4 X 44
82130	3/16 X 2	4 X 50
82131	3/16 X 2 1/2	4 X 64
82132	3/16 X 3	4 X 75
	1/4 / 6.4mm	1
82133	1/4 X 1 1/4	6.4 X 32
82135	1/4 X 1 1/2	6.4 X 38
82136	1/4 X 1 3/4	6.4 X 44
82138	1/4 X 2	6.4 X 50
82139	1/4 X 2 1/4	6.4 X 57
82140	1/4 X 2 1/2	6.4 X 64
82141	1/4 X 3	6.4 X 76





Copper Grease 70g

A high performance lead-free anti seize compound which is designed for application to threads of nuts and bolts prior to assembly to ensure easy release without damage, even after long periods in adverse conditions. The product is based on a non-melting grease containing a complex blend of heat resistant solids and low shear metals.

Part No

63074



Tef-Gel Anti Corrosion Gel 28g Syringe

When dismantling equipment for maintenance or repairs, this is the stuff you need. Tef Gel is a PTFE based waterproof lubricant with anti-corrosion and anti-seize properties. Tef Gel does not break down in salt water or detergents.

28 Gram Syringe

60700



Stud 'N Bearing Fit - 270

Loctite Stud 'n' Bearing fit is a fast acting high strength threadlocker and bearing retainer that can be used on metal threads, shafts, housings and bearings.

Part No Description

60643 24_ml



Loctite 248 Threadlocker 19g Stick

LOCTITE 248 is a general purpose threadlocker with medium bond strength. This product is available in a convenient stick format. This threadlocker secures and seals bolts, nuts and studs to prevent loosening due to vibration. The product works on all metals, including passive substrates such as stainless steel, aluminium and plated surfaces. It is proven to be tolerant of minor contamination due to industrial oils, e.g. engine oils, corrosion prevention oils and cutting fluids.

Part No Description

60651 19g Medium Stick



LOCTITE 577 Thread Sealant is designed for the locking and sealing of metal pipes and fittings as well as other threaded assemblies. The product provides an instant, low-pressure seal for metal pipes and fittings. It will not creep, shrink or shred. It has excellent chemical and thermal resistance and offers less migration of liquid product after application.

Part No Description

50ml Thread Sealant 60644



Lock 'NSeal - 243

Fast acting thread and lock sealant. Locks carburettor screws, alternator housings, seals oil pressure switches. Vibration proof.

5ml	10ml	24ml
60637	60650	60638



Teroson Up 620 Gelcoat Filler

TEROSON® UP 620 is a gelcoat unsaturated polyester body filler used for restoring the original surface finish to boat hulls and glass fibre panels. It repairs osmosis blisters and minor surface damage. It can be used on glass fibre and gelcoat finishes. Once set, it is waterproof and may be overpainted if required.

Pot Life: 12 mins

Colour: white

Sandable: 20 to 30 mins

Part No Size

61310 Gelcoat Filler 241g Tin



Teroson Up 610 Marine Filler

TEROSON® UP 610 is the universal unsaturated polyester body filler used for marine applications. It repairs transom/stern damages, stress cracks, keel and rudder surfaces, redundant holes, engine mountings, damaged and pitted propellers, cracks and holes on hulls and superstructures, damages caused by osmosis or crazing, gaps between hull and deck and worn and damaged superstructures.

Pot life: 4 mins

Colour: white

Sandable: 15 to 20 mins

Part No Size

61290 Marine Filler 341g Tin

61300 Marine Filler 787g Tin



Teroson Up 130 Chemical Metal

TEROSON® UP 130 is the original rockhard, multi-purpose, unsaturated polyester body filler paste with resistance to water, salt water, oil, fuel and to most weak acids and chemicals. It can repair gasoline tanks, radiators, concrete, housings and castings and many more. Suitable substrates include steel, aluminum, galvanized surfaces, glass fiber, copper and tin.

Pot life: 4:30 mins

Colour: dark grey

Sandable: 15 to 20 mins High chemical resistance

Part No Size

61210 Chemical Metal 321g Tin

61230 Chemical Metal 739g Tin

Teroson Up 230 Light Weight Filler

TEROSON® UP 230 is an easy-to-

body filler used for repairing dents,

sand, lightweight unsaturated polyester

scratches, pinholes, imperfections and

for reshaping. It can be used on steel,

Teroson Up 230 Light

Weight Filler 535g

aluminium, galvanized surfaces and



Teroson Up 150 Glassfibre Filler

TEROSON® UP 150 is an unsaturated polyester body filler used for bridging and repairing holes. It can be used on steel, aluminium, galvanized surfaces and glass fibre.

Pot life: 6:30 mins

Colour: blue/green

Sandable: 20 to 30 mins

Part No Size

61215 Glassfibre Filler 332g

61320 Glassfibre Filler 743g



Teroson Up 110 Elastic Body Filler

TEROSON® UP 110 is an elastic, unsaturated polyester body filler with outstanding flexibility and adhesive qualities that eliminate cracking and flaking. It can repair dents, scratches, pinholes and imperfections and be used for reshaping. It is suitable for use on substrates such as steel, aluminium, galvanized surfaces and glass fibre.

Pot life: 3 mins Colour: grey/green Sandable: 20 to 30 mins

Part No Size

61250 Elastic Body Filler 329g

61270 Elastic Body Filler 759g

glass fibre.

Part No

61355

Pot life: 4:30 mins

Colour: light green

Sandable: 25 to 30 mins

Size

TEROSON UP 190 spare hardener for fillers and resins.

Part No Description

61352 Spare Hardener 15g









Plastic Filler Card

Plastic universal filler cards used for a wide variety of applications.

Part No Item

61364 Single spreader (plastic)



Anza Wide Filling Knives

Part No Description

62130 Filling Knife 350mm



Osculati Gelcoat Filler 100gram

Single-component gel coat. To be knifed out as a regular filler for a bright white finish that restores the original surface of the chipped or splintered gel coat. It can be coated.

Part No Description

96251 Gelcoat Filler 100gram





Euro Filling Knives

Includes 50, 80, 100 & 120mm (2, 3, 4 & 5") Blades

Designed for small mixing and filling jobs on walls, ceilings and woodwork. Extra flexible carbon steel blades. 50mm, 80mm, 100mm and 120mm wide blades.

Part No

61365 Set of 4 metal spreaders



Osculati Gelcoat Filler 200gram

"4 in 1" high-resistance bicomponent white gelcoat. To be used like a regular filler to be knifed out: the final result is a bright white finish restoring the original chipped, scratched or dented gelcoat surface. It can be coated.

Part No	Description
96250	Gelcoat Filler 200gram

Osculati Epoxy Filler 800gram

Two-component epoxy filler to be knifed out. Excellent to restore broken or missing parts. Good compromise between stiffness and flexibility. Hand or machine processing after 4/5 hours.

Part No	Description
61356	Osculati Epoxy Filler 800Gram



Putty Knife

Rigid steel blade for putty and general glazing work. Soft grip handle for comfortable and professional use and a hole for hanging.

Part No

60280



Filling Trowel

Useful for filling in cracks and other small areas. Soft grip handle for comfortable and professional use and a hole for hanging.

Part No

60290



Epifanes Combi Filler

A traditional one-component knifing filler based on alkyd resins. Suitable for levelling of small irregularities in one-component paint systems for wood or steel above the waterline. Apply in thin layers only (max. 1 mm).

Apply between primer coats or prior to the first finishing topcoat Sandable: After 24 hours at 65°F./18°C. and 1 mm film thickness

Part No	Description
69202	Epifanes Combi Filler Tube 225 Gram
69201	Epifanes Combi Filler Tin 800 Gram



Bondafiller

An easy-to-use filler with good sanding properties that gives a smooth, dense surface. Bonds strongly to metal, GRP and wood. Takes all types of paint.

Part No	Size
64450	0.5Kg
64455	1.5Kg



V11 Reinforced Filler - 1Kg

V11 is filled with chopped strands of glass fibre which give the filler great strength. It can be used to bridge larger gaps and holes than is possible with conventional fillers.

Part No	Size
64460	1.0Kg



Body Light - Soft Sanding Filler 3kg

Body Light has a specific weight some 30 percent less than normal body fillers and is made using specially treated synthetic filling materials. Because of the lighter weight the mixing is easier and quicker. With its soft sanding properties shaping can be made to closer tolerances and needs less sanding to bring it to contour. The soft sanding properties of Body Light also reduces abrasive paper usage. Days after application the Body Light can still be sanded with minimal effort.

Part No	Description
64457	3kg Soft Sanding Filler



Bonda Wood Fill is ideal for filling shallow and deep imperfections on wood as well as for skim coating and grain filling. It can be used to build up damaged edges or splits on windows and doorframes or on any type of wooden furniture which needs repairing. This 2 part filler contains rapid hardening properties enabling it to dry and harden very quickly to form a smooth dense surface. It can be sanded, drilled, filed and machined when hard. After it has dried and has been prepared it can be primed and painted using regular paints.

Part No	Description
64580	Teak 500grams
64581	Mahogany 500grams
64582	Oak 500grams
64583	Pine 500grams
64584	White 500grams
64585	Redwood 500grams
64586	Utile 500grams
64591	Supersoft Woodfill Cream 200grams
64592	Supersoft Woodfill Dark 200grams

3463

LOCTITE 3463 is a versatile, dual component, easy to use, steel-filled epoxy repair putty. It is applied like a putty and when cured it exhibits high compressive strength and good adhesion to most surfaces. This product stops leaks in pipes and tanks, fills oversized bolt holes, smoothes welds, and repairs non-structural defects in castings or holes in tanks. This product is typically used in applications with an operating temperature range of -30 °C to +121 °C.

Part No Description

60645 114Gram Metal Magic Steel Stick



Brummer Stopping - 225 Grams

Exterior Grade woodfiller available in many wood shades. A waterproof filler for exterior use, excellent for filling holes and cracks in exterior woodwork e.g. windowsills, doors and garden furniture and is ideal for a wide variety of marine applications as it will not shrink or crack and is impervious to sea-water. May also be used on concrete, plaster, fibreglass and stonework.

Part No	Shade
64105	White
64110	Teak
64115	Med. Mahogany
64117	Light Oak





Raw Linseed Oil

A traditional completely natural oil from the extract of flax seed which penetrates unsealed wood leaving a natural, water resistant finish with a slightly enhanced colour that darkens slightly with age. For use on oak beams, bean canes, cricket bats, and many woodcraft applications and can be used as a lubricant in French Polishing (not suitable for furniture or flooring).

Part No	Description
61515	Raw 500ml
61510	Raw 5 Litre



Boiled Linseed Oil

A natural linseed oil (from the extract of flax seed) blended with driers to improve drying times. Boiled Linseed penetrates unsealed wood leaving a natural, water resistant finish with a slightly enhanced colour that darkens slightly with age. For oiling many types of bare wood mainly for internal use and Woodcare applications. (Not suitable for Oak, furniture or flooring).

A traditional treatment to seal terracotta tiles and other porous substrates. Can be mixed with burnt sand to form a caulking to fill gaps between timber and masonry.

Part No	Description
61520	Boiled 5 Litre



Caulking Cotton

It is useful for caulking seams on traditional wooden boats.

0.5Kg Ball

60475



Oakum

Oakum steeped in Stockholm Tar. Generally used for caulking below the waterline.

4kg Bale

60478



Red Lead Powder

A bright orange powder with strong preservative properties. When mixed with linseed oil putty, it makes 'red lead putty' for use as stopping in seams below the waterline on wooden craft. Appropriate proportions are 16 parts putty to 1 part red lead powder, with linseed oil added to modify the consistency.

Sold by the kilogram tin.

1 Kg

60490







Linseed Oil Putty

Traditional linseed oil based putty for external single glazing into primed softwood, hardwood frames and steel. Requires a protective paint system. Not recommended for use with micro-porous coating

0.5Kg	1Kg	5Kg
60320	60325	60330



Profair

A light weight two-component, epoxy filler, featuring high adhesion and water resistance and when fully cured is easy to sand. Can be applied to a film thickness up to 25 mm without sagging. As a filler and fairing compound, especially suitable for profiling large areas and detailed fairing where structural strength and flexibility is required. It can be used on most primed rigid substrates, above and below the waterline.

1 Litre

67381



Pro Filler

ProFiller is a two-component, lightweight epoxy filler, featuring high adhesion and water resistance. When fully cured it is easy to sand. Can be applied in coats up to 10-12mm for a uniform smooth finish.

5 Itr

66576



Watertite

Watertite is a quick drying epoxy filler which does not shrink and is extremely water resistant, making it suitable for osmosis damage repairs. Fill up to 20mm without sagging. Use above and below the waterline. High strength and adhesion properties. Simple 1:1 mixing ratio for easy measurement of components. Very fast drying. Super-smooth.

Suitable Thinners: None

Coverage: 0.2m² / Itr

Substrates: GRP, Metals & Wood

250ml 1ltr 68406 68407



Gorilla Epoxy Syringe

The easy-to-use syringe keeps the resin and hardener separate, so it is easy to dispense and won't harden over time. The two-part, gap-filling formula easily bonds steel, aluminium, wood, ceramic, tile and most plastics. Plus, it dries in an ideal, crystal-clear finish that makes projects look spotless. Grip Time: 30 Minutes // Open Time: 5 Minutes Dry Time: 24 Hours // Dry Colour: Clear Full Cure: 24 Hours

Part No	Description
60835	Gorilla Epoxy 25ml



Interfill 830

A lightweight epoxy profiling fairing compound used for profiling above and below the waterline on steel, aluminium and composite. Interfill 830 is the premium choice of profiling fillers for professional applicators. High expectations and stringent industry requirements have made Interfill 830 one of the most popular fairing compounds in the world. Interfill 830 is available in both fast and standard cure applications.

Туре	5ltr
Standard	68623
Fast	68621



Interfill 833

Interfill 833 is a technically advanced, easy sand Epoxy Finishing Fairing Compound for use over Interfill 830 profiling filler, to correct minor surface defects before application of finishing coats. The Interfill 833 is coloured green to contrast with the Interfill 830. This makes it easy to monitor film thickness and sand-through during the application procedure.

Туре	5ltr
Standard	68624
Fast	68625



Marine Epoxy Adhesive - 600grm

A two-part epoxy resin-adhesive with a neutral colour, specifically designed for use with the range of Treadmaster coverings. Gives excellent long term resistance to UV, seawater and continual impact in the harsh marine environment. One pack is sufficient for bonding one sheet of Treadmaster.

Part No

91880

Fillers, Epoxy & Resins

AMPRO™

Easy to use, Low Toxicity, Solvent-free Multi-purpose Epoxy System for Coating, Bonding, Laminating and Filling





THE PROFESSIONALS' CHOICE

Select the right system	AMPRO ™	AMPRO ™ CLR	AMPRO ™ BIO	AMPRO ™ SEAL
Low temperature curing	Х	Х		
Clear coating		Х		
Grain enhancing wood coating	Х		Х	
Bio-based content	<10%		40 - 60%	40 - 60%
Sealing & priming porous surfaces				Х
Filling, Fairing or Bonding	Х	Х	Х	

Select the hardener speed	Fast	Slow	Extra-Slow
Working time with a brush at 20°C	1-2 hours	4-5 hours	5-6 hours
50g pot-life in air at 20°C	1/2 hour	1 hour	1 1/2 hours







Low Temperature Curing Multipurpose System. SP 106 re-engineered. 3: 1 mix ratio by volume.

No surface residue, even at +5°C. For bonding, laminating & filling

Ampro 2 Part Epoxy Systems

	J,	3	5		
Part No	Description	on			
67701	Ampro™	1.33KG	Fast F	Pack	
67702	Ampro™	1.33KG	Slow I	Pack	
67703	Ampro™	4.2KG F	ast Pa	ack	
67704	Ampro™	4.2KG S	Slow P	ack	
67705	Ampro™	10KG R	esin C	nly	
67706	Ampro™	20KG R	esin C	nly	
67707	Ampro™	3KG Fa	st Har	dener Only	
67708	Ampro™	3KG Slo	w Har	dener Only	
67709	Ampro™	6KG Fa	st Har	dener Only	
67710	Ampro™	6KG Slo	w Har	dener Only	
67721	Ampro™	1.33KG	Calibr	ated Pump	Set
67722	Ampro™	4.2KG	Calibra	ted Pump S	et
67723	Ampro™	10 KG (Calibra	ted Pump S	et



Ampro Seal 1.3KG

Eposeal 300 re-engineered. 3:1 mix ratio by volume. No surface residue, even at +5°C. For sealing & priming porous surfaces.

Part No Description 67715 Ampro™ Seal 1.3KG



Ampro Clear 1.3KG

SP 320 re-engineered. 3: 1 mix ratio by volume. No surface residue, even at +5°C. Ideal for clear coating applications. Part No Description

67720 Ampro™ Clear 1.3KG



Ampro Bio Based Epoxy System

Accredited bio-based system. 3: 1 mix ratio by volume. No surface residue, even at +5°C. For bonding, laminating & filling

Part No Description

67716 Ampro™ Bio 1.30KG Fast Pack Ampro™ Bio 1.30KG Slow Pack

67719 Ampro™ Bio 4.1KG Slow Pack

Fillers, Epoxy & Resins





Microfibres: Structural Bonding Opaque, very fine cellulose wood fibres for structural bonding. Suitable for both wood and GRP.

Part No Description

67711 Ampro™ Microfibres 500ml 67605 Ampro™ Microfibres 0.5kg



67625



Microballoons: Wood Filling & Bonding Brown, hollow phenolic resin spheres ideal for wood applications. Easy to profile and sand for filling, filleting and bonding.

Part No Description

67713 Ampro™ Microballoons 500ml

Ampro™ Microballoons 0.3kg





Silica: Waterproof Resin Thickener Fine waterproof, white powder, used to thicken the epoxy system. Can be used with Glass Bubbles, Microballoons and Microfibres.

Part No Description

67712 Ampro™ Colloidal Silica 40g

67615 Ampro™ Colloidal Silica 0.25kg





Glass Bubbles: Waterproof Filling & Bonding White, hollow glass spheres for waterproof filling and bonding. Ideal as a finishing filler for hard wearing edges & surfaces.

Part No Description

67714 Ampro™ Glass Bubbles 500ml

67631 Ampro™ Glass Bubbles 0.3kg

Select the additive (s)	Micro Balloons	Glass Bubbles	Micro Fibres	AMPRO Silica
Easy to sand. Filling and filleting for cosmetic wood applications.	X			X
Water-proof or lowest-cost filler for general applications.		X		X
Hard surface finish filler for hard wearing edges and surfaces.		Х		Х
General bonding of softwood, brown in colour	Х			Х
General bonding of softwood, white in colour		X		Х
Structural bonding of wood or composite, opaque in colour.			Х	Х



Mixing Sticks

Pack of 100 lollipop sticks.

Part No Item

67940 Mixing Sticks (Box 100)



Syringes

Available individually or in a kit that includes both sizes and plastic extension tubes.

Part No	Item
67920	10ml
67921	50ml



S-shaped polypropylene paint stirrer. The s-shape make the mixing stick sturdier. Corrosion -resistant to both paint and thinner.

Part No Size 67941 30cm



Fillers, Epoxy & Resins





Calibrated mixing cups for paint and epoxy products.		
Part No	Size	
67951	400ml cup	
67950	650ml cup	
67955	1300ml cup	
67960	2300ml cup	
67962	6ltr Cup	



Glass Fib	re Mat Packs
Chopped fibre mat.	strand glass
Part No	Pack Size

fibre mat.		
Part No	Pack Size	
64505	1m x 1m	



Glass Fibre	apes
	tape available in e or open weaves.
Part No	Pack Size
64520	Open Weave 2M

Open Weave 50M





Seaware Polyester Resin (Lloyds approved)

A marine grade high quality resin which comes complete with an easy to mix hardener. Mainly used for laminating glassfibre using cloth or matting. Used for repairs, rebuilds and reinforcing.

Part No	Description
64528	Polyester Resin 1kg
64529	Polyester Resin 2.5kg
64530	Polyester Resin 5 kg



64525

Glass Fibre Resin

High strength marine grade polyester resin. Use with glass fibre mat or cloth for permanent repairs or for reinforcing GRP, metal, wood or masonry. Also for fabricating GRP mouldings. Bonda Resin provides rapid 'wet out' of glass fibre. The easy mix Hardener provides a maximum reactive resin system.

Part	Size
64465	250g
64470	500g
64475	1Kg
64480	2.5Kg
64485	5Kg
64490	Spare catalyst for 500g
64495	Spare catalyst for 1Kg



Small Fibreglass Repair Kit

500g general purpose resin 25g catalyst 1/2 m² 300g chopped strand mat 3x 12mm brushes 3x 385ml calibrated mixing 10ml syringe 3x stirring sticks 3 pairs latex glove

	3
Part No	Size
64526	Small



Large Fibreglass Repair Kit

2x 500g general purpose resin 25g catalyst

1 m² 300g chopped strand mat

3x 12mm brushes

3x 25mm Brushes

1x 1400ml calibrated cup

3x 385ml calibrated mixing cups

10ml syringe

6x stirring sticks 6 pairs latex gloves

Part No Size 64527 Large



www.wudcare.co.uk

Wudcare Adhesive Fast Grab 5 minute

A strong polyurethane glue that has a fast initial grab time and will expand slightly to increase bite strength. For interior and exterior use.

Fast Grab 5 minute has an initial grab time of 5 to 10 minutes and a firm bond in 4 hours. Full cure will require 24 hours.

After setting, the bond is very stable resisting 'creep', immersion in salt water and exposure to the elements. Use on damp wood, hardwoods, concrete, metal, brick, tarmac, MDF, polystyrene, cork and fibreglass.

Part No	Description
64612	500gram PU Wood Adhesive
64611	1kg PU Wood Adhesive



Collano Wood Glue - 800 Gram Tube

A unique marine wood glue. Collano Semparoc is one of the most versatile glues available. It is economical to use straight from the bottle with little wastage. Collano Semparoc reacts with moisture thus making it ideal for use in wet conditions - 25% moisture in the wood, even at temperatures as low as 5°C. Collano Semparoc regular allows well over one hour assembly time and cures in 3-4 hours.

Part No	Description
64610	Regular (Open Time 1 Hour / Press Time 3-4 Hours at 20 °C)




Gorilla Glue

Water activated, it expands into materials to form an incredibly strong bond to virtually anything. As your solution for almost any project or repair, Gorilla Glue is 100% waterproof, weatherproof, you-name-itproof. It's safe for indoor and outdoor use and strong enough to stand up to intense heat or cold. Sand it, paint it, stain it. Simply stated, it's the Toughest Glue on Planet Earth.

Grip Time: 1-2 Hours // Open Time: 10-15 Minutes Dry Time: 80% in 1-2 Hours // Dry Colour: Light Tan Full Cure: 24 Hours

60800	Gorilla Glue 115ml
60801	Gorilla Glue 250ml



Gorilla Wood Glue, a PVA glue, offers the benefits of an easy-to use, water-based adhesive, with all the holding power Gorilla is known for. The glue is incredibly water resistant and dries a natural colour that offers an invisible bond line for your projects.

Grip Time: 20-30 Minutes Open Time: 5-10 Minutes Dry Time: 80% in 1-2 Hours Dry Colour: Natural Wood Colour

Full Cure: 24 Hours

60820	Gorilla Wood Glue 118ml
60822	Gorilla Wood Glue 532ml

Cascamite

Cascamite structural wood glue is supplied as a powder, to be mixed with cold water as and when required. Once mixed Cascamite is usable to apply for about 1 hour and sets after 6 hours.

Cascamite is specially formulated for exterior joinery exposed to the weather. The powder system enables extremely good gap filling properties, preventing water penetration into joints and producing stronger bonds; ideal for exterior joinery, windows, doors, boats, gates and bathrooms.

Part No	Size
64420	200gram
64425	500gram
64430	1.5kg
64440	3kg

DYN - 185 - Aerodux Resorcinol Resin Kit - 1.2kg & 6kg pack sizes.

Liquid phenol-resorcinol resin adhesive for wood. A two-part system which provides a waterproof, structural bond.

Aerodux 185 is a 2 Pack resorcinol resin adhesive. Totally waterproof, resorcinol resin is recommended for use not only in structural timber applications but also for demanding and critical applications such as fire doors. Used extensively for bonding difficult timbers and can also be used to bond materials such as expanded polystyrene, plastic laminates, natural rubbers and some sheet metals. Can be used if required in hot pressing applications.

Mixed by weight. Ratio of mix 5 parts resin to 1 part powder.

Part No	Description
64403	1.2kg
64405	6kg











Plexus MA300 Cream

Fast high strength Methacrylate Adhesive. Two-part methacrylate adhesive designed for structural bonding of composite, thermoplastic, and metal assemblies. Plexus MA300 has a working time of 3 to 6 minutes and reaches approximately 500 psi in 12 minutes and 1,000 psi in 15 minutes at 74°F (23°C). Medium open time of 3 - 6 mins Easy to use 1:1 ratio Fast, consistent strength development at room temperature High strength, stiffness and toughened Non-sag thixotropic dispensing

Part No	Description
60413	Plexus MA 300 Cream 400ml Adhesive
60414	Plexus 3592 Nozzle 400ml
60403	Plexus MA 300 50ml Adhesive
60404	Plexus 3590 Nozzle 50ml







Superfast Adhesive

SUPERFAST PLUS provides an exceptionally strong bond between almost all kinds of materials, with the exception of polyethylene, polypropylene and fluorine containing plastic materials.

Materials which can be bonded:

ABS, aluminium, Bakelite, bronze, butyl, celluloid, chloroprene, chrome, Delrin, glass, copper, natural rubber, NBR, neoprene, nitrile, nylon, phenol, polycarbonate, polystyrene, porcelain, hard PVC, stainless steel, steel. For porous materials, use with SUPERFAST PLUS Activator.

Part No	Description
60517	20ml Superfast Adhesive
60518	50ml Superfast Adhesive
60519	150ml Activator





Scotch-Weld 10

Scotch-Weld Contact Cement 10 is a liquid, air -drying, adhesive which bonds immediately and permanently upon application of contact pressure. There is no need for clamping or fixturing.

1 Ltr

63773



Marine Epoxy Adhesive - 600grams

This two pack epoxy adhesive is designed to provide the ultimate in bonding performance. Ideal for use on a wide range of deck materials, it provides a bond which is suitable for the most arduous of conditions. Full instructions are on the can. Coverage Approx. 2 Sheets (1200mm x 900mm)

Part No

91880



Loctite EA 3463 Metal Magic 114g Stick

Structural Bonding - 2-component epoxy. Steel-filled kneadable stick for emergency repair. LOCTITE 3463 is a versatile, dual component, easy to use, steel-filled epoxy repair putty. It is applied like a putty and when cured it exhibits high compressive strength and good adhesion to most surfaces. This product stops leaks in pipes and tanks, fills oversized bolt holes, smoothens welds, and repairs non-structural defects in castings or holes in tanks. This product is typically used in applications with an operating temperature range of -30 °C to +121 °C. For the emergency repair of tanks, pipes and castings. Operating temperature range -55 °C to +120 °C.

Part No

60645



Spray 74 - Foam **Bonding Adhesive**

Ideal for general upholstery foam bonding. Bonds fabric to many surfaces. Non-misting, precise spray control.

500ml Aerosol

63763



Spray 77 - Multi-Purpose Adhesive

A high-tack, high-coverage, fast-drying, transparent adhesive for permanently attaching foils, carpeting, foam, paper, cardboard, felt, cloth etc. to painted or unpainted metals, hardboards and other base materials.

500ml Aerosol

63764



Spray 80 - Neoprene Contact Adhesive

Neoprene contact adhesive, excellent for attaching vinyl, insulation foam, padding and rubber parts to metal and other surfaces.

500ml Aerosol

63765



Spray 90 - High Strength Adhesive

Formulated for bonding rigid materials. High bond strength and one minute dry time. Will adhere polyethylene and polypropylene to wood, metal and many other materials.

500ml Aerosol

63766



Wudcare Heavy Duty Spray Adhesive

A long-lasting, multi purpose spray adhesive designed to produce a high bond between a wide variety of materials. For interior and exterior use. Suitable for most surfaces such as: Carpet, Fabrics, Laminates, Plastics, Insulation, Rubber and Foam.

Part No Description

64613 500ml PU Wudcare Heavy **Duty Spray Adhesive**



Trim - Fix Adhesive

Trim Fix spray adhesive is a multipurpose, high temperature resistant, heavy duty spray adhesive specially designed for the automotive industry. Ideally suitable for use on any trimming applications including panels, headlining and carpets. High temperature resistant – up to 120 degrees. Easy to apply - heavy duty spray adhesive. Dries clear - white spray

Part No Description

Trim Fix Adhesive 500ml Aerosol 64615



Loctite 577

This thread Sealant is designed for the locking and sealing of metal pipes and fittings as well as other threaded assemblies. The product provides an instant, low-pressure seal for metal pipes and fittings. It will not creep, shrink or shred. It has excellent chemical and thermal resistance and offers less migration of liquid product after application.

Part No Description

50ml Thread Sealant 60644



Loctite Hydraulic Seal 542

Medium viscosity For sealing threaded hydraulic and pneumatic parts. Will not clog valves or fine filters and has a thixotropic quality which prevents migration of the sealant. Impervious to all common hydraulic fluids including fire-resistant synthetics. Resistant to Hydraulic Fluids including Synthetics

-55 /+150 °C

Part No	Description
60646	50ml Thread Sealant
60649	10ml Thread Sealant





LOCTITE® 2701 is a green, low viscosity, methacrylate-based threadlocking adhesive with high strength, especially for chromated surfaces. Steel fixture time of 10 min, brass 4 min and stainless steel 25 min. Tolerates slight contaminations of industrial oils. Suitable for all metal fasteners. Fluoresces under UV light.

Part No	Description
60647	50ml Thread Sealant
60648	10ml Thread Sealant



Gorilla Super Glue

Gorilla Super Glue dries in 10-30 seconds and is reinforced with rubber for increased impact resistance. We call it Impact-Tough® because it stands up to wear and tear unlike any other instant glue. Grip Time: 10-30 Seconds // Open Time: Not Repositionable // Dry Time: Light Handling after 1-5 Minutes // Dry Colour: Translucent Full Cure: 24 Hours

Part No	Description
60840	Gorilla Superglue 15 grams



Precision Super Glue

The original 'super glue'. Suitable for a variety of surfaces, including metal, china, rubber, wood, leather and most plastics.

Part No	Description
60629	Liquid 5gm Bottle



Stud 'N Bearing Fit - 270

Loctite Stud 'n' Bearing fit is a fast acting high strength threadlocker and bearing retainer that can be used on metal threads, shafts, housings and bearings.

Part No	Description
60643	24ml



Loctite Power Flex Gel

Universal instant adhesive glue / rubber infused gel formula, strong and flexible / non drip gel.

Ideal for paper/card/porcelain/ china/leather/rubber/wood/metal/ craft/hobby/model making/most

Part No	Description
60630	Gel 3gm Tube



Lock 'NSeal - 243

Fast acting thread and lock sealant. Locks carburettor screws, alternator housings, seals oil pressure switches. Vibration proof.

5ml	10ml	24ml
60637	60650	60638



Instant Gasket

Forms perfect replacement gasket and gasket dressings in minutes. Resistant to water, heat, oil, antifreeze, transmission and brake fluids. 40ml tube.

Part	No

60636



Loctite 248 Threadlocker 19g Stick

LOCTITE 248 is a general purpose threadlocker with medium bond strength. This product is available in a convenient stick format. This threadlocker secures and seals bolts, nuts and studs to prevent loosening due to vibration. The product works on all metals, including passive substrates such as stainless steel, aluminium and plated surfaces. It is proven to be tolerant of minor contamination due to industrial oils, e.g. engine oils, corrosion prevention oils and cutting fluids.

Part No	Description	
60651	19g Medium Stick	



Inflatable Boat Repair Kits

Orange kit for neoprene inflatables containing: 125g glue with catalyser + 2 x 14.5 x 21.5cm neoprene patches + brush + sand paper + user instructions.

White/Grey kit for PVC inflatables containing: 125g glue + PVC cleaning product + 2 x 14.5 x 21.5cm neoprene patches + brush + activator + user instructions.

Part No	Description
96255	Orange Neoprene inflatable repair kit
96256	White PVC inflatable repair kit
96257	Grey PVC inflatable repair kit



C-Tec South West Limited, Unit 1 Willow Tree Court, Brannam Crescent, Roundswell Business Park, Barnstaple, Devon, EX31 3TD



CT1 Sealant & Adhesive 290ml

CT1 is the only product in the market with TRIBRID® Technology, making it 360% stronger than a traditional Hybrid Polymer. With TRIBRID® Technology, it is scientifically proven to have excellent colour retention - white stays white and clear stays clear. CT1 will successfully bond: All metals (including lead), Glass Mirrors, All woods, MDF, Polystyrene, Fiberglass Tiles, Concrete, Most stones (without staining), Most synthetic materials, Plastics (excluding PP, PE and PTFE).

Part No	Colour
60510	Black 290ml
60511	White 290ml
60512	Clear 290ml
60513	Grey 290ml
60514	Brown 290ml



Multisolve Aerosol Degreaser + Cleaner

MultiSolve is a complete new multi-purpose solvent; for the safe removal of adhesives and sealants. Removes adhesives, sealants, oil, grease, silicon, wax, tar, paraffin, printing ink etc. Leaves no oil film. Fast, thorough and safe degreasing and cleaning. Can be used on painted surfaces, vinyl, glass, rubber and plastics. Fast drying.

500ml Aerosol

60516



Arbosil 1096 Black Silicone Sealant 380ml

Arbosil 1096 is a one part Low Modulus Neutral Cure Silicone Sealant which cures on exposure to moisture vapour to form an elastic silicone rubber.

Recommended:

Glass Wall Assemblies Perimeter Seals in Curtain Walls Perimeter Sealing of Polyester Powder **Coated Frames**

Sealing of Windows in Swimming Pools Polycarbonate & Acrylic Sheeting Not recommended:

Overpainting Natural Stone

Part No Colour

60399 Black 380ml



3200 Silicone Sealant 280ml

A mildew resistant non-sagging moisture curing rubber sealant. Remainsflexible with excellent resistance to the marine environment. Adheres to bare/ painted metal, fibreglass, gloss, non-oily woods and many plastics and abraded rubbers.

Part No	Colour	
63739	White 280ml	
63741	Clear 280ml	



Arbomast GP is a one part oil based sealant intended primarily for general pointing and sealing of many joints in traditional forms of construction. It forms a skin, but the bulk of the material remains plastic beneath the skin.

Recommended for: Perimeter sealing of painted timber frames.

Sealing of preformed concrete panels e.g. Garages

Part No	Colour	
60398	380ml Black	



Sabatack® 750 XL Sealant & Adhesive 290ml

Extended skin time of approx. 15 minutes Extended open time of approx. 30 minutes High end strength, fast drying. Adhesion without primer.

UV- stable, high temperature resistance.

Can be painted wet-on-wet, hardly any shrinkage.

No blistering, almost odourless.

Free from solvents, isocyanates and silicones.

Certificates: Germanischer Lloyd (WP 0840006 HH), Wheelmark (164.106/1121/WCL MED0326), ISEGA (in connection with HACCP).

Part No	Description
60465	Sabatack 750XL Teak 290ml (RAL8008)
60466	Sabatack 750XL White 290ml
60467	Sabatack 750XL Black 290ml



Arbomast BR 380ml Grey

One part Butyl Rubber based sealant which only cures on the surface and remains putty like. Can be used as a bedding compound for marine windows and other low movement joints.

Part No	Colour
60397	380ml Grey



BT1 Bathroom Sealant & Adhesive 290ml

BT1 is based on our revolutionary TRIBRID® Technology! We have created a unique product upon which bacteria/microbes cannot survive, making it easier to maintain a more hygienic surface which is free of solvents and isocyanates. No more mould and fungal growth!

BT1 will successfully bond:

Woods

Metals

Brickwork

Concrete

Fibreglass

Glass

Ceramics

uPVC

And most plastics (except PP, PE and PTFE), even in wet conditions.

Part No Colour

60515 White 290ml



4000UV Stay White Adhesive Sealant

Resistant to weathering, saltwater, and stresses caused by joint movement. Seals between mechanically fastened joints on wood, fibreglass, metal and most plastics above and below the waterline. 295ml Tube

Part	No	Colour

63742 White 295ml



Sikaflex 221 - General Purpose Adhesive

A one component, polyurethane based adhesive and sealant. Excellent adhesion to concrete, metals, wood, epoxy, GRP, paints and varnishes. Good permanent flexibility, making it ideal as a general purpose bedding compound and sealant both above and below the waterline. Fast cure rate - it is tack free after about an hour. Can be sanded and painted. 310ml cartridge.

Part No	Colour
60426	Grey 310ml







5200 Adhesive Sealant - 295ml Tube

High performance, one component polyurethane adhesive/sealant with no shrinkage. The seal is extremely strong, retains its strength above or below the waterline. Stays flexible too - allows for structural movement. Stress caused by shock, vibration, swelling or shrinking is effectively absorbed. Easy to apply with manual caulking gun. Remains workable with trowel or spatula for up to 4 hours after application. Standard cure (7 days). (Fast cure version cures in 24hrs)

Part No	Colour
63731	Black 295ml
63728	White 295ml
63732	White Fast Cure 295ml

4200FC Adhesive Sealant - 295ml Tube

A one part general purpose polyurethane adhesive/sealant. Chemically reacts with moisture to deliver flexible bonds with good adhesion to wood, fibreglass, gel coat, plastics and metals. Paintable and sandable. Forms watertight, weather resistant seals on joints and boat hardware above and below the waterline. NOTE: When very high strength or unremovable bonds are required, use 3M 5200 or 5200FC. Not recommended for sealing wood decks because it may be permanently softened by certain teak cleaners or sealers. Cure time: 1 day

Part No	Colour
63734	Black 295ml
63733	White 295ml



Sikaflex 291i - General Purpose Sealant & Adhesive

One component, polyurethane based adhesive and sealant developed specifically for the marine construction industry. Excellent flexibility and will adhere well to most materials.

Sikaflex 291 has very similar characteristics to 221, but has added UV filters.

Colour	70ml Tube	300ml Cartridge
Black	60405	60423
White	60412	60425



Sikaflex® -295UV Marine Plastic Window Glazing Adhesive

It has been specially developed for the marine industry, where it is used to bond and seal plastic glazing materials in boats and ships. Because of its excellent weatherability this product can also be used to seal joints in areas of severe exposure. Suitable substrates are aluminium (bright or anodized), GRP (polyester resin), stainless steel, timber and plastic glazing materials (PC, PMMA).

Part No	Description
60430	Sika 295 UV 300ml Black
60429	Sika 295 UV 400ml White Sausage



Sikaflex 296 Marine Mineral Glass Glazing Adhesive

Sikaflex 296 is ideal for direct glazing of mineral glass which requires a purpose designed adhesive with the right combination of application properties and performance characteristics. This is a fast curing elastic polyurethane that is suitable for all types of mineral glass.

Part No	Description
60428	Sikaflex 296 600ml Black Sausage



Sikaflex 290DC Pro Deck Caulking

Sikaflex 290 DC is a one-part UVresistant polyurethane based joint sealing compound specially formulated for caulking joints in traditional timbermarine decking. The sealing compound cures to form a flexible elastomer which can be sanded.

Excellent resistance to seawater and weathering. 310ml will fill 10m of 5mm X 5mm seam approx.

Colour	300ml Cartridge	600ml Sausage
Black	60445	60446





SIS 440 Teak Deck Caulking

TDS Deck Sealant is a one-part neutral cure system which, when exposed to moisture in the air, reacts to form a tough, flexible, solid rubber compound. The sealant is a thixotropic material, which does not sag during cure, and, when cured, has excellent temperature stability and chemical resistance. It is non-corrosive to all substrates and available in black. No priming is required. White and Grey available to order.

Part No	Description
60500	305ml Tube - Black
60501	592ml Sausage - Black



Saba Deck Tape 4mm x 66M

Bond breaker tape used for deck caulking.

Part No	Description
60502	Saba deck Tape 4mm x 66M



Sikaflex 290DC Primer

This primer is formulated to remove surface contamination and wood oils prior to the application of Sikaflex 290DC. This is critical, especially when dealing with oily woods such as Teak.

Part No	Description
60454	250ml



Sikaflex Marine Multiprimer - 250ml

For use with: Sikaflex 221.291 & 290DC. SIKA Multiprimer Marine is an all purpose and easy to apply primer, for use on most substrates such as wood, metals, plastics and painted substrates. SIKA Multiprimer Marine typically dries in 10 minutes ready for Sikaflex application.

Part No Description

60453 Sika Multiprimer Marine 250ml



Sika Primer 207 100ml

This primer is used to give improved adhesion in adhesive bonding applications on a very broad range of different substrates such as float glass, ceramic-coated glass, plastics, pre coatings, painted surfaces, E-coats and metals. This product is suitable for experienced professional users only.

60431 Sika Primer 207 100ml



Sika Primer 205 250ml A solvent cleaner and conditioner which improves adhesion on non-porous surfaces for Sikaflex adhesives.

Part No	Description
60450	Sika Primer 205 250ml



Sika Primer 206 Glass + Metal

Black UV block primer for mineral glass, to be used in conjunction with Sika Activator, Can Also be used on stainless steel as well and two part epoxy/polyurethane paints.

Part No Description

60455 250ml



Sika Primer 215 250ml Special formulation for use on all GRP, wood and some plastic substrates.

Part No Description

60452 Sika Primer 215 250ml



Caulking Gun

Metal caulking gun fits standard cartridge sizes.

Part No

60470



600ml Professional Caulking Gun

Caulking gun suitable for 400 or 600 ml sausages and 310ml tubes. Aluminium tube 375 mm. Power ratio of 12:1.

Part No

60472



Spare Sikaflex Nozzle

Sold individually will fit sikaflex caulking gun tubes. Handy removable red screw top.

Part No

60473



Spare Caulking Gun Nozzle

Will fit most types of sealant cartridges.

Part No

60471



Spare Sikaflex Witches Hat Nozzle

Part No

60456



Arbo Spares		
Part No	Description	
60457	Empty 400ml Cartridge	
60458	Spare Nozzle	
60459	End Caps	



Corrosion Block Grease

It is an anti-corrosion compound developed exclusively to stop existing corrosion and prevent new. It is unique in that it is designed for use in electrics and electronics as well as metals and structures. This makes this product essential for your day-to-day routine maintenance and as a long-term asset protection for your boat/equipment within the harsh marine environment

the harsh manne chimoninent	
Part No	Item
91731	Grease 454g Tub
91732	340g Aerosol
91733	14oz Cartridge





Morris K99 Stern Tube Grease 500g

This grease has outstanding water resistant qualities and is designed to form a special seal at the water interface. This grade is a high quality lead-free calcium hydroxide stearate grease with special additives to provide extreme pressure properties, improve oxidation resistance and protect against rust and corrosion. Recommended for grease filled stern tubes. Also suitable for plain and anti-friction bearings operating in very wet conditions.

Part	No
9173	30





Aqua Slip Grease 500g

Carlube Aqua Slip Grease provides high resistance to salt water corrosion and water washout in addition to allowing good shear stability over a wide temperature range. It is suitable for a wide range of marine applications including; trailer wheel bearings, stern tubes/propeller shafts, cables and pulleys etc.

Par	t I	N	0

63076



Blakes Seacock Grease 500g

Formulated for marine use with high adhesion properties and resistance to water wash out. Primarily designed to be used with the Blakes Seacocks, this quality grease can be used for many other similar marine applications on board your boat.

Working temperature range -30°C to +70°C (-70°F to +160°F).

Part No.

10673



MPG Universal Marine Grease 500g

MPG is a multi-purpose lithium based grease containing zinc oxide additive to repel moisture, making it particularly suitable for use in marine outboard and inboard engines. Also ideal for use in boat trailer hubs and stern tubes.

Part No	Description
1 411110	Docomption

91761 MPG Grease 500g





Copper Grease 70g

A high performance lead-free anti seize compound which is designed for application to threads of nuts and bolts prior to assembly to ensure easy release without damage, even after long periods in adverse conditions. The product is based on a non-melting grease containing a complex blend of heat resistant solids and low shear metals.

Part No

63074

LOCTITE







Loctite Superlube

Superlube with Syncolon (PTFE) is a multi-purpose synthetic lubricant, safe to use on anything that slides, swivels, rolls or squeaks. It withstands temperatures within a range of -43C to 232C. This lubricant forms a non-toxic, anti-corrosive shield that prevents rust and is impervious to salt water.

Part No	Description
60639	Superlube Aerosol 375ml
60640	Superlube Grease Tube 85g
60642	Superlube Oiler Pen 7g





3-IN-ONE Multipurpose Drip Oil

3-IN-ONE's original drip oil lubricates, cleans and prevents rust. Its precise, easy-to-use drip spout enables precise lubrication, with no overspray or splatter. It can be used on in-line skates, tools, bicycles, wheels, fans and moving parts.

100ml

63062



Tef-Gel Anti Corrosion Gel 28g Syringe

When dismantling equipment for maintenance or repairs, this is the stuff you need. Tef Gel is a PTFE based waterproof lubricant with anti-corrosion and anti-seize properties. Tef Gel does not break down in salt water or detergents.

28 Gram Syringe

60700







Duck Oil

A multi purpose service spray. Lubricates, penetrates, displaces water and inhibits corrosion. It is non-conductive and so can be used on all types of electrical equipment without impairing performance. Insulates electrics due to high dielectric strength. It is versatile and can be used on almost any surface. It is also silicone free and so is compatible for use in paint shops.

Part No	Item
61643	500ml Aerosol
61645	5 Litre Tin
61646	Spray Bottle



WD-40

Stops squeaks, displaces water, cleans and protects, loosens rusted parts and frees stuck mechanisms.

300ml	450ml
61650	61652



Double TT Spray

Penetrates and eases corroded parts. Frees and lubricates locks, hinges etc. Stops squeaks on springs, castors etc. Leaves a protective coating to help prevent rust and corrosion. Removes crayon marks, gum and adhesives. Displaces moisture.

Part No	Size
63050	200ml
63052	400ml
63054	600ml

Multisolve Aerosol Degreaser + Cleaner

MultiSolve is a complete new multi-purpose solvent for the safe removal of adhesives and sealants. Removes adhesives, sealants. oil, grease, silicon, wax, tar, paraffin, printing ink etc. Leaves no oil film. Fast, thorough and safe degreasing and cleaning. Can be used on painted surfaces, vinyl, glass, rubber and plastics. Fast drying.

500ml Aerosol

60516





Jizer

A specially formulated emulsifiable solvent degreaser. Removes mineral oil, grease, tar, bitumen and waxes from most surfaces with a powerful dissolving action. Rinses off completely with water.

500ml	5 Litre Tin
61630	61635













MP3 Sport Semi Synthetic 2 Stroke Outboard Oil

Rock Oil synthetic blend 2 stroke outboard MP3 Sport is a NMMA TCW-3 certified oil, capable of the lean oil to fuel ratios of modern high performance air and liquid cooled two stroke outboard engines. The advanced additives ensure easy starting and clean running even under continuous use. It is perfectly suited to oil injection systems but can be premixed. Its ease of starting and clean running characteristics, also make MP3 Sport an ideal lubricant for other high performance two stroke applications.

Part No	Description
91750	MP3 Sport 1 Litre
91751	MP3 Sport 5 Litre



HLP 32 Hydraulic Oil

Rock Oil HLP32 is a high quality, viscosity grade 32, mineral oil based, hydraulic oil. This oil contains high levels of anti-wear, anti-corrosion, antioxidation and anti-foam additives. This oil is specially suited to hydraulic systems where high levels of anti-wear and protection are required in conjunction with good service life reliability.

Part No	Description
91762	HLP 32 5 Litre



Ultraflex Hydraulic Steering Oil Grade 15 hydraulic oil.

Part No Description

11795 1 Litre Ultraflex Steering Oil

MP + Sport 4 Stroke Semi Synthetic Outboard Oil

Rock Oil MP Plus semi-synthetic engine oil is a specially designed NMMA FC-W accredited lubricant for use in all modern 4 stroke outboards. With all-new modern 4 stroke outboards requiring this specification, it can be used with confidence in all 4 strokes outboard application where NMMA FC-W is required. The product is suitable where SAE 10W30, 10 W 40, 15W40 and 25W40 are recommended. It has been blended from the highest quality base oil with state of the art synthetic additives to withstand the rigours of the marine environment. It provides excellent protection from start-up, even in the lowest temperature, to the high operating temperatures of high revving 4 stroke outboard engines. It is suitable for use in both petrol and diesel outboards.

Part No	Description
91754	MP4 + Sport 1 Litre
91755	MP4 + Sport 5 Litre

MP4 Sport 15W-40 4 Stroke Semi synthetic Inboard Oil

Rock Oil MP4 Sport is a premium grade 4 stroke engine oil designed for standard & high-performance engines. The advanced additive, high detergent formulation ensures maximum engine component protection & superior resistance to deposits and corrosion, resulting in extended engine life & optimum performance under all conditions. Especially suitable for the latest inboard high output marine applications.

Grade: API SL/CI-4, ACEA A3/B4 E5/ E7, Volvo VDS-2, VDS-3

Part No	Description
91752	MP4 Sport 1 Litre
91753	MP4 Sport 5 Litre







Hypoid EP 80W-90 Gear Oil

Rock Oil gear oil is developed from the finest base stocks available combined with state-of-the art extreme pressure (EP) additives for use in hypoid axles and gearbox applications.

Hypoid EP 80W-90 Gear Oil is blended to the requirements of the API specification GL-4 making it especially suitable for automotive applications where EP oils are recommended. The Hypoid EP 80W-90 Gear Oil meets or exceeds the following specifications: API GL-4 ZF TE ML 01 (Manual, Non-Synchro Transmissions) ZF TE ML 08 (Steering Systems) ZF TE ML 17A (Transmissions for Lift Trucks)

Part No	Description
91756	EP 80W90 500ml
91757	EP 80w90 1 Litre
91760	EP 80w90 5 Litre





Super Marine Inhibitor Spray

(Fogging Oil)

Super marine inhibitor spray consists of a light mineral oil blended with sophisticated corrosion inhibitors and oxidation stabilisers. In use, it produces a soft, oily film which coats the unexposed internal surfaces. It is ideal, therefore, for applications such as laying up engines. It may also be used on external surfaces where it yields a water repellent, lubricated surface which also prevents rust formation.

Part No	Description
91758	400ml aerosol







Vetus Marine Diesel Engine Oil 15W-40

It is suitable for all modern marine diesel engines and generator sets. It also meets the very high requirements of turbo-charged engines and engines with modern valve technology. This mineral oil provides low oil consumption, excellent rust and internal corrosion protection and detergents to maintain engine cleanliness. As a result, optimal combustion and low exhaust emission values are

Vetus Marine Diesel Engine Oil 15W-40 exceeds the requirements of: API CI-4, ACEA A3/B3, A3/B4, E7, MB 228.3/229.1, MAN M3275, Volvo VDS-3, Cummins CES 20071/20072 / 20076 / 20077, CAT ECF-1.

Part No	Vetus	Description
56742	VMD151	Diesel Oil Sae 15W-40 1 Litre
56743	VMD154	Diesel Oil Sae 15W-40 4 Litre







Vetus Marine Diesel Synthetic Engine Oil 10W-40

This state of the art engine oil is recommended for the new generation marine diesel engines, ensuring low fuel and oil consumption, optimum protection against wear and tear and corrosion and a long service life. The product is ideal for use in diesel engines with very low exhaust gas emissions, in combination with modern low sulphur fuels. Vetus Marine Diesel Synthetic Engine Oil 10W-40 exceeds the requirements of: API CF/SL; ACEA A3/B4, E4, E7;MB 228.5/229.1; MAN M3277CRT; VW 505.00; Volvo VDS-2

Part No	Vetus	Description
56745	VMD101	Synthetic Engine Oil 10W-40 1 Litre
56746	VMD104	Synthetic Engine Oil 10W-40 4 Litre







Vetus Special Gearbox Oil 80W-90

This is recommended for use in bow thruster drive legs, anchor windlass gearboxes and outboard motor drive legs if compliant with the manufacturer's specifications. This oil contains additives which offer full protection against wear and tear, as well as metal to metal contact which may occur under extreme loadings. It has excellent anti-corrosion properties and resistance to ageing. May be mixed with other API GL4 and GL5 oil

Vetus Special Gearbox Oil exceeds the requirements of: API GL-5, SAE 80W-90

Part No	Vetus	Description
56748	VBT05	Special Gearbox Oil 80W-90 500ml









Vetus Hydraulic Steering Oil HF15

This is a low viscosity oil for hydraulic steering systems with optimum results at all temperatures. This oil has a very low coagulation point and a very high viscosity index. May be mixed with other hydraulic mineral oils.

Specification

Viscosity: 22 cSt at 20° C. Viscosity index: 353

DIN 51524

Colour: green

Part No	Vetus	Description
56752	VHS1	Hydraulic Steering Oil 1 Litre



Vetus hydraulic oil (HLP ISO-VG46).

Hydraulic oil is an oil for all power hydraulic systems. The product has particularly high EP and corrosion resistance properties.

Part No	Vetus	Description
56754	VHT1	Hydraulic Oil 1 Litre



The Economy Oil Absorbent Pillow is an excellent absorber of pooled liquids that can gather in tight spaces behind machinery and work benches. The pillow is hydrophobic (absorbs hydrocarbons and repels water) so it is designed to selectively absorb large volumes of oil.

Dimensions: 300mm x 250mm

Absorbency per pillow: 2.5 litres Part No Description

91300 Oil Absorbent Pillow







Vetus Transmission Oil 80W-90

This is suitable for all types of marine transmissions which specify Automatic Transmission Fluid (ATF) Dextron IID or ATF Suffix A. This oil contains additives which protect the internal metal parts of the transmission against corrosion and wear, even at high operational temperatures. It is also suitable for hydraulic systems, for which this oil quality is specified.

May not be used in applications where API GL4 or GL5 are specified. Vetus Transmission Oil exceeds the requirements of: Dexron IID ZF TE-ML-03D/04D/11A/14A/17C **GM Dexron IID**

Colour: red.

Part No	Vetus	Description
56750	VTF1	Transmission Oil 80W-90 1 Litre



3M™ Maintenance Sorbent Pad (Sold Individually)

High Capacity, 15 in x 20 in.

For use on most non-aggressive liquids. Highly absorbent, low profile design. Perfect for placing in, under, and around machines. This high capacity sorbent has a scrim on one side to increase strength and help eliminate linting. This conveniently sized pad allows the user to quickly spread sorbent on and in the path of a spill.

Part No	Description
64046	3M Oil Absorbent Sheet 40cm X 52cm



Fuel Primer Bulbs		
Part No Description		
11762	8mm Fuel Primer Bulb	
11763	10mm Fuel Primer Bulb	

Passivated Steel Sump Pump

A simple and convenient solution to changing oil, especially on engines with inaccessible drain plugs. Also ideal for transferring diesel between tanks or to fill small day tanks. 15 strokes per litre.

Barrel Dia: 29mm.

Part No Description

74205 Sump Pump





Part No Description

76152 Brass Oil Change Pump 300mm long



The FUELSAFE overcomes the risk of fuel theft simply and cheaply by making it impossible to insert a siphon hose into the tank through the filling hose.

55 x 72 Height x Width (mm)

Internal Hose Diameter (38mm or 51mm)

Part No	Vetus	Description
56326	FUEL SAFE	Fuel Antitheft Device



Marinised Morendo

Diesel 'Bug' Killer & Fuel Treatment additive specifically for marine craft, boats and yachts.

Part No Description 61554 1 Litre



Rectangular motor flusher with hose adaptor. Moulded rubber PVC on 8mm painted steel handle. Helps extend engine life by preventing corrosion by standing sea water, sand and silt. Designed for outboard engines with side water inlets. No tools required.

Part No	Description
76164	Motor Flusher (Soft)

Heavy Duty Motor Flusher

Heavy Duty, Twin Sided, Rectangular motor flusher with hose adaptor. Moulded rubber PVC on 8mm painted steel handle. Helps extend engine life by preventing corrosion by standing sea water, sand and silt. Designed for outboard engines with

side water inlets.

No tools required.

Part No	Description
76154	Motor Flusher (Heavy Duty)









De-ionised Water

De-ionized water is produced by passing feed water over an ionexchange medium, which electrolytically removes charged contaminants and exchanges them for hydrogen ions and hydroxyl ions, which combine to produce water.

Part No	Description
63056	De-Ionised Water 1 Litre
63058	De-Ionised Water 5 Litre





Blue Star Antifreeze based on mono-ethylene glycol, containing corrosion inhibitors designed to give protection down to -36°C to 50% dillution.

When mixed with water the antifreeze can be used as a factory fill or a service "top-up" coolant for suitable engine cooling systems, designed for a life of 2 years.

Part No	Description
63060	Anti Freeze 1 Litre
63061	Anti Freeze 2 Litre



Jerry Can 5L, 10L, 20L

Specially developed for carriage and storage of drinking water

Strong and lightweight

Rectangle shape with carry handle

Part No	Capacity
91510	5 Litres
91505	10 Litres
91500	20 Litres





Red Fuel Jerrycans

Heavy-duty jerrycan for diesel or petrol which includes a swivelling pouring spout. Don't leave close to heat source. In case of very hot temperature, don't fill the tank more than 3/4.

Part No	Capacity
91718	10 Litres
91719	20 Litres



Draper syphon pump

Manufactured from plastic, the pump is a useful item for transferring a wide variety of inert liquids. Inlet pipe 390mm long; outlet pipe 400mm long. Display packed.

Part No		
90558		















Heavy Duty Rugged Jerrycans

Very heavy and rugged tanks. The smart nozzle has the following characteristics: -Lid with kid-safe closure. - Nozzle inside the tank when not in use. - Closure valve to overturn the tank and start delivery only when the nozzle is stuck into the deck plug. - Nozzle with vent for regular and spray-free flow.

Part No	Capacity
91511	5 Litres
91512	10 Litres
91513	20 Litres





Bell Tetra Cans

Robust 5 Litre fuel cans with square-sided design.

Comply with S.I. 1982/630.

Part No	Description
91715	5 Litre Red (Petrol)
91716	5 Litre Green (Unleaded)
91717	5 Litre Black (Diesel)



Brass Butt Hinges (Sold Each)

Part No	Length X Open Width
45300	1 1/2" X 3/4" (38 X 19mm)
45590	1 1/2" X 7/8" (38 X 22mm)
45310	2" X 7/8" (51 X 22mm)
45610	2" X 1 1/8" (51 X 29mm)
45320	2 1/2" X 1 1/8" (64 X 29mm)
45630	2 1/2" X 1 3/8" (64 X 35mm)
45330	3" X 1 3/8" (76 X 35mm)
45640	3" X 1 5/8" (76 X 41mm)
45660	4" X 2 3/8" (102 X 60mm)



Card Table Brass Hinges (Sold Each)

Part No Length X Open Width 1/2" X 3" (13 X 76mm)



Brass Hasp & Staple
(sold each)

Part No	Description
Brass	Length X Width
45000	3" X 1" (76 X 25mm)



Brass Lifting Rings (sold each)

Part No	Description
Brass	Length X Width
45200	1 1/2" X 1 1/8" (38 X 29mm

Brass Fittings



Brass Backflap Hinges (Sold Each)

Hinge is made from solid drawn brass extrusion to BS 249 and are fitted with brass pins and finished joints.

Part No	Length X Open Width	
45350	1 1/4" X 1 7/8" (32 X 48mm)	
45360	1 1/2" X 2 3/8" (38 X 60mm)	
45380	2" X 3" (51 X 76mm)	
45390	2 1/2" X 4" (64 X 102mm)	





Brass Barrel Bolts (sold each)

Part No	Description
Brass	Length x Width
45040	2" X 1" (51 X 25mm)
45060	2 1/2" X 1" (64 X 25mm)
45080	3" X 1" (76 X 25mm)
45100	4" X 1 1/4" (102 X 32mm)
45112	6" X 1 1/4" (152 X 32mm)



Brass Turn Button (sold each)

Part No Description 45037 Brass (38mm X 10mm)



Brass Spring Catch
(sold each)

Part No Description

Brass	Length X Width
45560	2" X 1 1/2" (51 X 38mm)



Brass Pia	no Hinge
-----------	----------

Standard Duty 0.9mm Thick	
Part No	Description
45410	Brass Piano Hinge 25mm x 1.83m
45420	Brass Piano Hinge 32mm x 1.83m
45430	Brass Piano Hinge 38mm x 1.83m





Brass Necked Barrel Bolts (sold each)

`	,
Part No	Description
Brass	LXW
45081	3" X 1" (76 X 25mm)



Brass button on plates	
(sold each)	

Part No	Description
Brass	Diameter
45035	2" (51mm)



50mm Brass Ball Catch

(sold each)

Brass body enclosing sprung steel balls.

Part No	Description
45480	Double Ball Catch



Brass Wardrobe Hooks	
Part No	Description
45195	Single
45196 Double	



Brass Flush Draw Handles		
Part No	Description	
Brass	Length X Width	
45462	3" X 1 7/8" (76 X 48mm)	
45464	3 1/2" X 2" (89 X 51mm)	



Brass Butterfly Vent		
Part No	Description	
Brass	Length X Height	
48020	6" X 3" (152 X 76mm)	
48024	9" X 6" (228 X 152mm)	



Brass Door Handles	
A pull handle which can also be used as a sash handle.	
Part No Length	
45468 5" (127mm)	

Brass Sile	ent Cabin Hooks
Part No	Description
Brass	Length
45120	2 1/2" (64mm)
45140	3" (76mm)
45160	4" (102mm)
45180	6" (152mm)



Brass Louvered Vents		
Part No	Description	
Brass	Length X Height	
48035	6" X 3" (152 X 76mm)	
48037	9" X 3" (229 X 76mm)	
48039	9" X 6" (229 X 152mm)	
48041	12" X 6" (305 X 152mm)	

Chrome Plated Fittings



6" x 3"



9" x 3"



9" x 6"



12" x 6"

Chrome Plated Louvered Vents		
Part No	Description	
Chrome	Length X Height	
48036	6" X 3" (152 X 76mm)	
48038	9" X 3" (229 X 76mm)	
48040	9" X 6" (229 X 152mm)	
48042	12" X 6" (305 X 152mm)	



Chrome Hit & Miss Vents		
Part No	Description	
Chrome	Length X Height	
48021	6" X 3" (152 X 76mm)	
48023	9" X 3" (228 X 76mm)	
48025	9" X 6" (228 X 152mm)	



Chrome Butterfly Vents		
Part No	Description	
Chrome	Diameter	
48016	3 3/4" (95mm)	
48017	5" (127mm)	

Chrome Plated Fittings







(Sold Each)

45382

45392

Hinge is made from solid drawn brass		
extrusion to BS 249 and are fitted with		
Brass pins and finished joints.		
Part No	Length X Open Width	
45362	1 1/2" X 2 3/8" (38 X 60mm)	

2" X 3" (51 X 76mm)

2 1/2" X 4" (64 X 102mm)

/	
11	

Standard Duty 0.9mm Thick		
Part No	Description	
45440	Chrome Piano Hinge 25mm x 1.83m	
45450	Chrome Piano Hinge 32mm x 1.83m	
45460	Chrome Piano Hinge 38mm x 1.83m	



Chrome Plated Brass Piano Hinge





Chrome Plated Barrel Bolt		
Square profile.		
Part No	Description	
76104	51mm Long	
76106	76mm Long	
76108	102mm Long	



· · · · · · · · · · · · · · · · · · ·	
Made of chromed brass; lowered with spring, use for lockers and other uses.	
57mm x 40mm Latch	
18mm x 40mm Latch	

Part No Description 96305 Chromed Brass Flush Latch

Chrome	Plated Butt Hinges (Sold Each)
Part No	Length X Open Width
45302	1 1/2" X 3/4" (38 X 19mm)
45592	1 1/2" X 7/8" (38 X 22mm)
45312	2" X 7/8" (51 X 22mm)
45612	2" X 1 1/8" (51 X 29mm)
45322	2 1/2" X 1 1/8" (64 X 29mm)
45632	2 1/2" X 1 3/8" (64 X 35mm)
45331	3" X 1 3/8" (76 X 35mm)
45642	3" X 1 5/8" (76 X 41mm)
45662	4" X 2 3/8" (102 X 60mm)



Chrome Plated Barrel Bolts (sold each) Part No Description Chrome Length x Width 45050 2" X 1" (51 X 25mm) 2 1/2" X 1" (64 X 25mm) 45070 45090 3" X 1" (76 X 25mm) 4" X 1 1/4" (102 X 32mm) 45110



Cabinet Doorstop		
Made of chromed brass.		
52 x 33mm		
Part No	Description	
96301	Chromed Brass Doorstop	



Chrome Plated Hasp & Staple		
Part No	Description	
Chrome	Length X Width	
45010	3" X 1" (76 X 25mm)	



Chrome Plated Button On Plate (sold each)	
Part No	Description

2" (51mm) Diameter



	6 Owner S.A.
Part No	Description
45470	Chrome Brass Finger Catch

0
Teak Finger Ring

Teak Finger Ring		
Part No	Outside Diameter	Inside Diameter
45471	40mm	30mm

45036



Chrome Plated Spring Catch		
Part No	Description	
Chrome	Length X Width	



Chrome Plated Flush Draw Handles		
Part No Description		
Chrome	Length X Width	
45463	3" X 1 7/8" (76 X 48mm)	
45465	3 1/2" X 2" (89 X 51mm)	



Chrome Plated Lifting Ring		
Part No	Description	
Chrome	Length X Width	
45210	1 1/2" X 1 1/8" (38 X 29mm)	
45230	2" X 1 1/2" (51 X 38mm)	
45250	2 1/2" X 2" (64 X 51mm)	



45580



2" X 1 1/2" (51 X 38mm)



Chrome Plated / Brass			
Traditional Cabin Hook			
Part No		Description	
Brass	Chrome	Length	
45120	45130	2 1/2" (64mm)	
45140	45150	3" (76mm)	
45160	45170	4" (102mm)	
45180	45190	6" (152mm)	



Magnetic Slide Latch		
Door latch & strike with lock. Easily adjustable slide that is actuated when parallel with strike. Suitable for +12mm thick doors. 91mm x 56mm		
Part No		
96559		



Chrome Plated Silent Cabin Hook		
Made of chromed brass, double joint.		
Part No	Description	
96308	60mm Long	
96309	80mm Long	
96310	100mm Long	



Chrome Plated Wardrobe Hook		
Part No		
Chrome	Description	
45194	Single	



Roll Locks Chrome Plated		
2 Parts. Nylon Rollers.		
Part No	Size	
48061	Height 28mm	
48062	Height 36mm	



Push Button Locks			
r don Ba	T don Batton Looke		
Plastic locks for cabinets.			
Suitable for doors 16 - 22 mm thick.			
Chrome	Gold		
48050	48051		



Deluxe doorstep ratchet 49mm 49mm x 8mm Made of chromed brass with stainless steel bearings and springs. Part No Description 96311 Deluxe doorstep ratchet CP





Door Locks Push-button brass. Housing 70x45mm. In brown or white.

Brown	White	Size
48055	48058	13mm
48056	48059	16mm
48057	48060	19mm

Stainless Steel Fittings



45491 2 3/8" X 1 1/8" (60 X 29mm) 45489 2 1/2" X 1 3/4" (64 X 44mm)


45493 3" X 1 1/2" (76 X 38mm) 45490 3" X 2" (76 X 51mm)



(Sold Each)

Special stainless steel extra strength hinges, mirror polished finish, suitable for engine trunks and heavy duty usage.

Part No	Description
96280	130mm Long x 90mm Wide x 2.5mm Thick



Stainless Steel Top Pin Hinge

High quality cast polished AISI 316 stainless steel.

4mm thickness.

Type A

180° opening.

(Sold Each)

Part No Description 96290 Hinge A 180° 66 x 66mm



Stainless Steel Piano Hinge (Sold each)

Heavy Duty 1.2mm Thick

Length 1.83m

_		
	Part No	Description
	45485	25mm x 1.83m
	45486	32mm x 1.83m
	45487	50mm x 1.83m



(Sold Each)

Special stainless steel extra strength hinges, mirror polished finish, suitable for engine trunks and heavy duty usage.


Part No	Description
96283	110mm Long x 45mm Wide x 2.5mm Thick




(Sold Each)

Mirror Polished Stainless Steel Rectangular Hinge 60 x 30mm

Part No Description 96287 60mm Long x 30mm Wide x 1.3mm Thick



Type C





Stainless Steel Underpin Hinge

High quality cast polished AISI 316 stainless steel.

4mm thickness.

Type B

Type B

95° opening.

(Sold Each)

Part No Description 96291 Hinge B 95° 66 x 66mm Stainless Steel Smooth Stud

High quality cast polished AISI 316 stainless steel.


4mm thickness.

Type C

95° opening.

(Sold Each)


Part No	Description
96292	Hinge C 95% 66 x 66mm




Type D



Type A



Type B



Stainless Steel Underpin Hinge

stainless steel.

4mm thickness.

180° opening.

Part No Description

(Sold Each)

Type B

96295

High quality cast polished AISI 316

Stainless Steel Top Pin Stud

High quality cast polished AISI 316 stainless steel.

4mm thickness.

Type D

180° opening

(Sold Each)

Part No Description

96293 Hinge D 180° 66 x 66mm Stainless Steel Top Pin Hinge

High quality cast polished AISI 316 stainless steel.

4mm thickness.


Type A

180° opening


(Sold Each)

Part No Description

96294 Hinge A 180° 76 x 40mm




Type D



Type A



Hinge B 95° 76 x 40mm



High quality cast polished AISI 316 stainless steel

4mm thickness.

Type C

Type C

95° opening.

(Sold Each)

Part No Description

96296 Hinge C 95° 76 x 40mm Stainless Steel Top Pin Stud

High quality cast polished AISI 316 stainless steel.

4mm thickness.

Type D

180° opening.

(Sold Each)

Part No Description

96297 Hinge D 180° 76 x 40mm

Stainless Steel Top Pin Hinge High quality cast polished AISI 316 stainless steel.

4mm thickness.


Type A

180° opening.

(Sold Each)

Part No Description


96298 Hinge A 95° 83 x 65mm



Stainless Steel Top Pin Hinge

High quality cast polished AISI 316 stainless steel.

4mm thickness.



Stainless Steel Top Pin Hinge

High quality cast polished AISI 316 stainless steel.

4mm thickness.

Type C

95° opening.

(Sold Each)

Description Part No

96300 Hinge C 95° 83 x 65mm







Counter Hinge SS AISI 316

Cast mirror-polished AISI316 stainless steel hinges. 5mm Thick.

(Sold Each)

Part No Description

48090 38 x 74mm Counter Hinge



Skylight Hinge SS AISI 316

Cast mirror-polished AISI316 stainless steel hinges. 5mm Thick.

(Sold Each)

45482

Part No Description

48092 38 x 100mm Skylight Hinge

Part No Length X Open Width

38mm X 70mm



Short Side Door Hinge SS AISI 316

Cast mirror-polished AISI316 stainless steel hinges. 5mm Thick.

(Sold Each)

Part No Description

48094 38 x 57mm Short Side Door Hinge



Stainless Steel Backflap Hinges Stainless Steel Removable Pin (Sold Each) Backflap Hinges

> Made in stainless steel, mirror polished, with special grease to guarantee a soft movement.

(Sold Each)

Part No Description 96284 72mm Long x 38.5mm



Wide x 2.5mm Thick



Short Side Door Hinge SS AISI 316


Cast mirror-polished AISI316 stainless steel hinges. 5mm Thick.

(Sold Each)

Part No Description

48096 39 x 74mm Short Side

Door Hinge




Backflap Hinge

Reversed Pin

Made of mirror polished stainless steel. Vibration damping by means of a braked central axle. 2mm Thick.

Part No Description

45494 74 x 37mm



Backflap Hinge

Central Pin

Made of mirror polished stainless steel. Vibration damping by means of a braked central axle. 2mm Thick.

Part No Description

45495 74 x 37mm



Stainless Steel Foldable Hinge

Made in stainless steel mirror polished, useful for tables. Casted central part.

(Sold Each)

Part No Description

96281 76mm long x 38mm Wide



Hidden Hinge

HInges for built-in doors, 180° opening. Satin finish. Can hold up to 10kg.

Part No Description


53mm Hidden Hinge Pack of 2



Stainless Steel Foldable Hinge

Made in stainless steel mirror polished, useful for tables. Casted central part.

Part No Description 96282 84mm long x 30mm Wide



Stainless Steel Hinge

2mm thickness

(sold each)

Part No Description

96286 95mm Long x 39mm Wide



Rounded Stainless Barrel Bolts

These traditional designed, time tested barrel bolts have an anti-rattle bushing included. Stainless Steel AISI 316.

Part No	Description
76324	Length 90mm
76326	Length 110mm
76328	Length 120mm



Stainless Steel Pull Latch

Made of stainless steel, light and sturdy, mirror polished finish. Model fitted with ring return spring to eliminate vibrations.

Part No	Description
96306	SS Pull Latch 55 x 65mm
96307	SS Pull Latch 38 x 40mm



Stainless steel AISI 316 Lifting Ring

Part No Description Size 48053 Lifting Ring 56 x 48mm



Strap Hinge

(sold each)

Part No Description

45483 Strap Hinge SS 129mm x 40mm



Button Plate

Made of AISI 316 stainless steel; designed to fix bottom boards or cabinet doors.

96304 45mmØ Button Plate



Stainless Swivel Hasp

316 Grade Stainless Steel

Made of precision cast AISI 316 stainless steel, mirror polished, fitted with swivelling padlock.

90mm x 26mm

Part No Description 23133 Swivel Hasp



Hatch Handle

Heavy Duty, fitted with handle and return spring

Made of precision cast mirror polished AISI 316 stainless steel.

Part No	Description	Size
48052	Hatch Handle	55 x 77mn



Skylight Hinge

(sold each)

Part No Description

45484 Length 180mm x 40mm Width



Stainless Steel Lifting Ring

Casted 316 Stainless Steel. 38 x 48mm

Part No Description

23135 Stainless Steel Lifting Ring



Heavy Duty Hasp & Staple

Mirror polished stainless steel

Closed 33 x 87mm

Open Length 33 x 107mm

Part No Description

96303 Heavy Duty SS Hasp

& Staple



Fabricated Stainless Steel Door Hooks Stainless Steel (304)

Fabricated Stainless Steel Hand Polished Door Hooks, with a plastic bushing in the eye which prevents accidental unhooking due to vibration. This bushing also absorbs rattling sounds.

Part No	Description
76140	Anti Rattle Door Hook 51mm
76142	Anti Rattle Door Hook 64mm
76144	Anti Rattle Door Hook 84mm
76146	Anti Rattle Door Hook 104mm





Cam Over Centre Latch

316 cast stainless steel. Heavy duty cast construction. Spring loaded. The strike pin has an offset screw hole allowing tension adjustment by 1mm. The new installation Jig allows for accurate installation of the Strike Pin. Length when closed 82mm Width 25mm

Height 15mm

Part No	Description
76400	Compression Latch Smooth
76402	Compression Latch Locking








308 grade stainless		
steel. Supplied with a		
horizontal mount catch		
plate but can be		
supplied with a 90°		
catch plate on request.		

Part No	Part No	Description
Standard	Locking Version	Length
45500	45510	70mm
45520	45530	120mm





Anti Rattle Catch SS AISI 316

Locker latch with padlock ring

Part No	Description	A (mm)	B (mm)	C (mm)	L (mm)
48098	Anti Rattle Catch	50	48	42	110



Coat Hook

316 Stainless Steel, spring loaded coat hook allows for a neat and safe fitting when not in use.

51mm x 29mm x 14mm (closed). Hook protrudes 54mm (open).

Part No	Description
76388	SS 316 Folding Coat Hook



Spring Hatch Stay 350mm

Made of stainless steel, fitted with spring hatch opening system, supports heavy loads, suitable for hatches and bilge peaks.

2 fixing plates size 47x47 mm

Part No Description

96063 Stainless Steel 350mm Stay



Door Stop & Catch

This is the answer to all swinging door probles. This attractive 316 Stainless Steel latch has an automatic latch feature and rubber bumper stop. Latch hinge welded closed and polished for that elegant look. 2 1/2".

Part No	Description
96555	Door Stop & Catch




Spring Hatch Stay

Useful for holding locker lids, hatches and doors. Length: 222 mm.

Part No Description

48054 Stainless Steel 222mm Stay





Compression Lift and turn flush latch External Ø 60mm

Bulkhead hole Ø 51mm

Bulkhead thickness 8 - 30mm


Stop stroke 37 - 97mm

Part No

76350 51mm Non Locking

76352 51mm Locking





Compression Lift and turn flush latch External Ø 90mm

Bulkhead hole Ø 76mm

Bulkhead thickness 10 - 34mm

Stop stroke 39 - 100mm

Part No

76358 76mm Non Locking

76360 76mm Locking



Standard Flush Pull Latch


AISI 316

For thickness 5-12mm External Ø 62mm recess Ø 50mm

Part No

76354 50mm Non Locking

76356 50mm Locking







Eclipse MK2 75mm Flush Latch

External Ø 75mm. Bore Ø 60mm. Bulkhead thickness 5-36mm . Adjustable stop lever 30-101mm. Featuring a very comfortable grip, it offers all the best characteristics in a single flush deck design model. Flush design. Large ergonomic handle. 360° rotation. Handle can be lowered every 90°. Open/close indicator. Ergonomic nut for easy calibration. Ergonomic nut for emergency exit. Straight cam suitable for sliding doors and having two different positions. Two-position cam. Plastic spacer with marks for customized cut.

Part No Description

96407 75mm Flush Latch Locker Latch

Made of stainless steel, fitted with spring button and padlock ring hole plate.

Part No 96080

Standard Flush Pull Latch


AISI 316

For thickness 7-19mm External Ø 75mm recess Ø 63mm

Part No

76344 63mm Non Locking

76346 63mm Locking



Stainless Steel Hit & Miss Vents

Made of polished stainless steel.

Part No	Description
48018	152mm x 76mm Hit & Miss Vent
48019	229mm x 76mm Hit & Miss Vent



Stainless Steel Butterfly Vents

Made of polished stainless steel, fitted with rotating locking system.

Part No	Description
48012	4"
48010	5"
48008	6"





Shell Vents

Stamped stainless steel shell (midget)

304 Stainless Steel

JUT Claimic 33 ClcCi	
Part No	Size
76196	41mm x 41mm
76198	57mm x 54mm
76200	25mm H x 90mm Width x 93mm L









Stainless Steel Louvered Vents Oval style Made with polished stainless steel Part No Description


48027 116mm x 128mm 48028 235mm x 118mm



Stainless Steel 304 Round Vents	
Part No	Description
76158	102mm SS Round Vent
76160	127mm SS Round Vent







Stainless Steel Louvered Vents
Rectangular style
Made with polished stainless stee

Part No	Description
48030	SS Louvered Vent 67mm x 127mm
48031	SS Louvered Vent 115mm x 127mm
48032	SS Louvered Vent 118mm x 232mm
48033	SS Louvered Vent 127mm x 232mm



ABS White Louvered Vent	
Part No	Description
96554	201 x 101mm white vent



White Nylon Butt Hinges (Sold Each) Part No Length X Open Width

2 1/2" X 1 5/8" (64 X 41mm) 45685 45686 3" X 1 7/8" (76 X 48mm)



Nylon Fittings

Nylon Backflap Hinges (Sold Each) Made of reinforced nylon.

White Hinge.

Part No	Description
96285	54mm Long x 38mm Wide



Nylon Counter Hinges (Sold Each) Made of reinforced nylon.

White Hinge.

Part No	Description
96336	65 x 40mm
96337	98 x 65mm

Lighting



SERIES 20 (12V)



Port Light - 1nm Part No: 70210



Part No: 70200



Starboard - 1nm





Dimensions in: mm / inch







Dimensions in: mm / inch



Spare Bulb 12V 5W

All Round White Anchor Pole Mount Light (1M)- 2nm


70191 Part No:



Stern Light Transom Mount - 1nm

Masthead Steaming Light - 2nm

Part No: 70230





Aquasignal Series 20 All Round White Plug in 42"

Part No: 70192




Part No: 70240



All Round White Anchor Pedestal Mount Light - 2nm

Part No: 70190



Dimensions in: mm / inch



SERIES 25 (12V)

[12M / 39FT Boat Length]



Masthead Light - 2nm 70010 Part No:



Stern Light - 1nm Part No: 70020



Port Light - 1nm Part No: 70030




Starboard Light - 1nm Part No: 70040




Bi-Colour Light -1nm

Part No:	Casing
70045	White

70050 Black







New Type

Spare Bulb 12V 10W: 70451 Spare Bulb 24V 10W: 70441



Series 25 Festoon Led Bulb 44mm Part No: 70454



All Round Red Light - 2nm




All Round Green Light - 2nm




All Round White Light - 2nm

70060

Part No:



Dimensions in: mm / inch









Combined Mast / Steaming Deck Light - 2nm

70061 Part No:









12/24V Masthead Deck LED Light

225° navigation LED light and deck LED light fitted with 4 x 1W HD LEDs. Techno polymer body with flexible wings that match any kind of mast. Suitable for boats up to 20m in length.

96042 12/24V Masthead/Deck Light LED



SERIES 40 (12V/24V)

[20M / 65FT Boat Length]



Masthead Light - 3nm Part No: 70070 (12V) Part No: 70465 (24V)



Stern Light - 2nm Part No: 70080 (12V) Part No: 70466 (24V)



Bi-Colour Light - 2nm Part No:70090 (12V)


Part No: 70467 (24V)





Port Light - 2nm Part No:70100 (12V) Part No: 70468 (24V)



Starboard Light - 2nm Part No: 70110 (12V) Part No: 70469 (24V)









Tri-colour Standard Fit - 2nm Part No: 70120 (12V) Part No:70470 (24V)



Part No: 70170 (12V) Part No: 70475 (24V)

Quick Fit - 2nm



All Round White Hoist Light - 2nm



Light - 2nm



12V 10W: 70400 24V 10W: 70410 12V 25W: 70380 24V 25W: 70390




Tri-colour Anchor Quick Fit - 2nm

Part No: 70180 (12V) Part No: 70476 (24V)



All Round Green Hoist Light - 2nm

Part No: 70137 (12V)



Tri-colour Anchor Standard Fit - 2nm Part No: 70130 (12V)

Part No: 70471 (24V)



SERIES 40 (12V/24V)

[20M / 65FT Boat Length]



All Round Red Light - 2nm Part No: 70140 (12V)

Part No: 70472 (24V)



All Round Green Light - 2nm

Part No: 70150 (12V)


Part No: 70473 (24V)



All Round White Light - 2nm

Part No: 70160 (12V)

Part No: 70474 (24V)



Series 40/41 LED Tricolour Bulb




Series 40/41 LED Bi-Colour Bulb




Series 40/41

Series 40/41 LED Port Bulb








Part No 70455






Part No 70456



LED Starboard Bulb





Part No 70459

Part No 70457

Part No 70458



Bulb Holder

Replacement lamp holder.

Part No: 70321 (12V/24V)



Bulb Holder

Corresponding locking nut.

Part No: 70320



Series 40 Pulpit Bracket

Part No: 70290



Series 40 Mast Bracket

Part No: 70300

Lighting



SERIES 41 (12V)

[20M / 65FT Boat Length]



Masthead Light - 3nm Part No: 70181 (12V)



Stern Light - 2nm Part No:70182 (12V)



Bi-Colour Light - 2nm Part No:70183 (12V)



Starboard Light - 2nm Part No: 70184 (12V)



Port Light - 2nm Part No:70185 (12V)




Series 41 Pulpit Bracket Part No: 70186



Series 41 Mast Bracket Part No: 70187



Series 41 Universal **Deck Bracket** Part No: 70188



3/0.12 38 32 **50** 1.97 92 / 3.6

Dimensions in mm / inch

Series 40/41 LED Tricolour Bulb




Series 40/41 LED Bi-Colour Bulb










Part No 70455





Part No 70456

Series 40/41 LED White Bulb





Series 40/41 LED Starboard Bulb

70457


12V 10W: 70400 24V 10W: 70410 12V 25W: 70380 24V 25W: 70390


Spare Bulbs











Part No 70458



SERIES 55 (12V/24V)

[20M - 50M Boat Length]



Starboard Light - 2nm Part No: 70251



Port Light - 2nm

Part No: 70252



Masthead Light - 5nm

Part No: 70253



Stern Light - 2nm

Part No: 70254



Halyard Hook Bracket

Part No: 70259



All Round White Light - 2nm Part No: 70255

All Round Red Light - 2nm Part No: 70256



All Round Green Light - 2nm Part No: 70257



120 / 4.7 152 / 5.98

Dimensions in: mm / inch



SERIES 30 LED POLE

[20M / 65ft Boat Length]







Description - All-round white pole light pedestal Pedestal Mt / Fold Down / Plug In Ship size < 20 m / < 65 ft Voltage 12 V

Wattage 1.5 W Visibility 2 nm

Description	Part No
S30 LED All Round White Pedestal 4"	70333
S30 LED All Round White Fold Down 15"	70334
S30 LED All Round White Fold Down 27"	70335
S30 LED All Round White Plug In 43"	70336





Part No	Description
70480	S43 Nav Light & Deck Flood Combi Black
70481	S43 Nav Light & Deck Flood Combi White

LED navigation light and deck light combination.

The series 43 LED navigation lights with LED deck lights have a modern design and an optimized size for sport boats and yachts up to 20 m (65 ft.) in length. The navigation lights fulfil all requirements of the "International Regulations for Preventing Collision at Sea 1972 (COLREG)", published by the international Maritime Organization (IMO) and local rules.



SERIES 34 LED

[50M / 164ft Boat Length] [20M / 65ft Boat Length]




Port Light Part No:70341



Starboard Light Part No: 70342



Stern Light Part No:70343





All Round White Part No: 70344



All Round Red Part No:70345



All Round Green Part No: 70346



Bi-Colour Part No:70347



Spare Quick Fit Base

Position of holes for fixing Dimensions in: mm / inch

57.3






Masthead Part No:70348



Tricolour Part No:70349




43 1.69 Cable entry max Ø10 max Ø5 max Ø 0.2




Masthead with **Anchor Light** Part No:70350




Tri Colour with Anchor Light Part No:70351









Discovery LED Stern Navigation Light

135°

12/24V


1W

Visibility 2 NM

COLREG72-certified for vessels up to 20-m long.

Part No: 96020





Discovery LED Bi-Colour Navigation Light

112.5° left + 112.5° right

12/24V

1W

Visibility 2 NM

COLREG72-certified for vessels up to 20-m long.

Part No: 96021



Discovery LED All Round White Navigation Light

360° mast head. 12/24 Volts. 1.8 Watts. Visibility NM 2

COLREG72-certified for vessels up to 20-m long.

Part No: 96022



Discovery LED Tri-Colour + Anchor Navigation Light

360° mast head + three colours

12/24V

4.8W

Visibility 2 NM

COLREG72-certified for vessels up to 20-m long.

Part No: 96023

LED Lights [12M Boat Length]

RINA (No. ELE112414CS) type-tested for hulls up to 12m.







Part No	Description
96000	Compact LED Light Port
96001	Compact LED Light Starboard
96002	Compact LED Light Stern
96003	Replacement LED Bulb Port
96004	Replacement LED Bulb Starboard & Stern

12V

Part No: 96006





LED SS

Pull-out angular version with stainless steel base

60CM long

12V

Part No: 96008



360 Degree Mooring LED Light

12V

COLREG72- and ABYC-A16-certified for vessels < 20-m long. 100-mm overall height.

Part No: 96007





Port & Starboard SS LED Light

112.5° left + 112.5° right

12V

Part No: 96005


Stern SS LED Light 135° stern and flat mounting

Ø 76,1

RINA and NMMA USA type-tested for vessels up to 12 m in compliance with COLREG '72. ELE 357413CS type-testing.

LED Lights [20M Boat Length]





Sphera II LED Port Navigation Light

COLREG72-certified for vessels up to 20-m long. 100% watertight.


112.5° left

12V/24V

0.6W

Part No: 96009





Sphera II LED Starboard **Navigation Light**

COLREG72-certified for vessels up to 20-m long. 100% watertight.


112.5° right

12V/24V

0.7W

Part No: 96010





Sphera II LED Bow **Navigation Light**

COLREG72-certified for vessels up to 20-m long. 100% watertight.

Bow 225°

12V/24V

2W

Part No: 96011



Sphera II LED Stern Navigation Light

COLREG72-certified for vessels up to 20-m long. 100% watertight.

Stern 135°

12V/24V

2W

Part No: 96012



Sphera II LED Bi Colour **Navigation Light**

COLREG72-certified for vessels up to 20-m long. 100% watertight.

112,5° + 112,5° bicolor

12V/24V

2W

Part No: 96013



Classic 360° Mast Head SS Led Light

Ø 64mm


Height 74mm


12/24 V - 1,7 W

Polycarbonate and AISI316 stainless steel light. For vessels < 20-m long.

Part No: 96403







Utility 85 SS/112.5° Red Port Halogen Navigation Light

Lights made of mirror-polished stainless steel. RINA type-approved in compliance with the COLREG72 regulations.


Part No: 96480




Utility 85 SS/112.5° Green Navigation Light

Lights made of mirror-polished stainless steel. RINA type-approved in compliance with the COLREG72 regulations.

Part No:








Utility 85 SS/White Stern Navigation Light

Lights made of mirror-polished stainless steel. RINA type-approved in compliance with the COLREG72 regulations.

Part No: 96482





12/24V Masthead Deck LED Light

225° navigation LED light and deck LED light fitted with 4 x 1W HD LEDs. Techno polymer body with flexible wings that match any kind of mast. Suitable for boats up to 20m in length.

96042 12/24V Masthead/Deck Light LED





Sealed beam spare light bulb. Available in 12 & 24V. Suitable for Aquasignal Hamburg or Kiel Lights.

Aquasignal Kiel Decklight		
Black casing.		
Part No	Description	
70477	Kiel Decklight	
70478	Kiel Light Bulb 12V 50W	
70479	Kiel Light Bulb 24V 50W	



Navisafe 360 Degree All Round White

The Navilight 360° 2NM - US Coast Guard approved for 2 nautical miles it is the most versatile light of Navisafes range of battery operated portable navigation lights and includes a 360° All-round light, 225° Masthead light, 135° Sternlight, Flashing light, Anchoring light and a Cabin light. It uses super bright LED light, is water proof, floats and attaches almost anywhere through its double magnetic mounting system.

Part No	Description
70355	Navisafe 360 Degree All Round White



Navisafe Tri Colour Light

The Navilight Tricolor 2NM - US Coast Guard approved for 2 nautical miles it includes a green light to be shown at the starboard side and a red light to be shown at the port side. In addition, it includes the white Sternlight, to be used at the stern. It is battery operated, uses super bright LED light, is water proof, floats and attaches almost anywhere through its double magnetic mounting system. The green as well as the red lights show an unbroken light over an arc of the horizon of 112,5 degrees. The white Sternlight shows an unbroken light over an arc of the horizon of 135 degrees. All lights work independently, in a combination of all three or red/green together

Part No	Description
70356	Navisafe Tri Colour Light



Designed to allow secure mounting of the Navi lights with magnetic base to the bow pulpit or stern rail.

Part No	Description
I all INO	Description

70357 Navisafe Clamp On Rail Mount







12V Roll Bar Flood Light

White ABS plastic.

Fitted with dual filament watertight sealed beam.

287 Lumens

60° LED beam angle

High beam light + extended lights 65 + 45W

Overall dimensions 180 x 110 x 125mm

Mounting Base 140 x 46mm

Part No Description

96026 12V Roll Bar Light



Adjustable A Frame Flood Light 9-33V (IP66)

They generate two concentric light beams: a narrow (10°) and very bright internal one (SPOT) and a wide (45°) but less bright external one (FLOOD). Aluminium body, polished stainless steel bracket, vacuum reflector.

13.8W Output.

650 Lumens.

5000-6500K.

7° Led beam angle.

6 x 3W HD LED.

122 x 63 x 115mm.

Part No Description

96027 9-33V Adjustable A Frame Flood Light

Bremen Handheld Halogen Search Light




Watertight, portable searchlight with Morse capability. 12V 50W. On/ off switch, 3 metre cable (2 x 0.75mm²). Sealed beam is included.

Part No

70258

Bremen LED Handheld Search Light





EMC SOLAS P68 LED 3

Bremen LED Search Light IP68

A high-quality, watertight, hand-held search light with morse capability and on/off switch. Comes LED bulbs suitable for 12v or 24v power supply. Housing: High quality, impact & shock resistant rubber. Non-corrosive. Non-magnetic Electrical: 3m pigtail cable included (2 x 0.75mm²)

Part No

70488

All Weather Submergible & Rechargeable LED Spotlight





Weatherproof LED Spotlight

700 Lumens - 500m beam

IP67 waterproof, floatable & submergible to 1m

Built in adjustable stand

Safety lock switch to prevent unwanted ON/OFF activation

Everlasting LED - no replacement bulbs needed

Lightweight 406g

Rechargeable self contained Li-ion battery

Duration 2.5 hours high 6 hours medium & 15 hours low beam

USB charging lead & wrist strap supplied

Part No

70500



Handheld USB Rechargeable LED Torch

300m beam - 500 Lumens

High & low power mode

Duration 2.5 hours on high & 6 hours on low beam

Everlasting LED - no replacement bulbs needed

Rechargeable li-ion battery supplied

Fully adjustable from spot to flood

Made from high grade aluminium

USB charging lead supplied

Part No

70501



Super Cob Work Light

400 lumens

Work light & torch in 1

High & low beam including emergency flash mode.

Red emergency flash mode ideal for signalling

Strong magnetic base & belt clip

High grade aluminium body

Water & impact resistant

3 x AA batteries supplied

Part No

70503





Focus2Go Headlight Rechargeable

580 Lumens - 150m beam

Multi battery option rechargeable battery supplied (B33)

Will run from AAA batteries for backup power (not sup-

plied)

Red side light - Vertically adjustable

Slim compact design - just 95g

LED indicator shows battery capacity and charging sta-

IP64 dust and water resistant

Duration 2.5 hours continuous on high

Direct plug to recharge by micro USB

Part No

70502



WL8 Mini Portable Work/Flood Light Rechargeable

Portable & Rechargeable Work/Flood Light giving a brilliant surround light.

The super bright 10 watt work light can be easily directed where it is needed by rotating the 180° degree handle. It also has a magnetic base allowing hands free use. Ideal for working where there is no mains power or a great back up lighting during power cuts. Giving a lighting time of up to 4 hours per charge. It also has the added benefit of a power bank function to charge your phone or tablet whilst on the go.

Lumens: 700

Area of Illumination: 10 metre surround beam

Battery: Li-ion rechargeable Charger: USB lead included

LED: 10w Cob LED

Duration: 2 hours on high - 4 hours on low

Charging time: 4 - 5 hours


Part No

70504






LED Lights



Description	Part No
Apus White LED Light	96030
Apus Blue LED Light	96031

Chromed brass with clear polycarbonate diffuser. Pressure installation. IP65






Description	Part No
Alcor Red LED Light 12/24V	96029
Alcor White LED Light 12/24V	96409
Alcor Blue LED Light 12/24V	96033

Machined stainless steel body. Snap mounting. IP67 AISI 316








Description	Part No
Tilly LED Light White	96034
Tilly LED Light Blue	96035
Tilly LED Light White 180 degree	96036
Tilly LED Light Blue 180 degree	96037

White plastic body, mirror-polished stainless steel front panel. Snap mounting. IP67







Precision cast mirror polished stainless steel. Polycarbonate diffuser. IP65 AISI 316



Description	Part No
Precision LED Ceiling Light 65mm \varnothing	96040
Precision LED Ceiling Light 86mm∅	96045

Stainless steel body. Hidden screw mounting. It comes with 2 front diffusers giving 2 different degrees of transparency. IP45 AISI 304 Flush Mount



168 Lumens. K 3050-3800. LED Beam Angle 120°. No of LEDs 42 LED SMD. White Light.

Description	Part No
130 Ultra Flat Chromed LED Light	96025
12/24V 3W	



Stainless Steel Domed Switched Light

Stainless steel switched lights with clear lens.

12v DC 15w

Lens dia. 127mm - 171mm O/D

Part No Description

76410 127mm SS Switched Light



Traditional Dome Ceiling Light - Halogen **Dotted Glass Diffuser**

Part No	Description
96046	Ceiling Light 140mm Dome
96047	Ceiling Light 175mm Dome



12V White + Red Flexible Chart Light


1.3W / Switched light


6 LED SMD

330mm Arm length


Part No	Description
96028	12V Flexible Chart Light











12V 0.6 Watt

60 Lumens

3000K

18 LEDS

USB port on side, ideal for powering devices especially if used as a berth light.

Part No Description

96049 USB LED Spotlight Chrome

White plastic body LED spotlight.

Made of ABS with chromed brass articulation. Rotation 300°. Up/down 90°.

Part No Description

96041 LED Spotlight Chrome





Brass & Chrome Berth Lights

Stylish interior lights of brass construction. 12v DC. All come with a 75mm dia. shade and a 90mm dia. base.

Part No	Description
76074	Brass Berth Light 12V 10W
76076	Chromed Brass Berth Light 12V 10W



LED Light Bulb

High-power SMD LED version. Screw G4. 12V. 1.6W. 18W Equivalent. 150 Lumens. 3000K

10 x 38mm

Part No Description 70361 12V G4 Light Bulb 360° 1.6W





Laguna articulated spotlight

Chromed brass.

Turned brass body, satin-finish glass diffuser.

12/24V

3 W

88 Lumens

3000K

LED beam angle 60°

White light

Part No Description
96423 Laguna Articulated

Spotlight





Flexible LED Strip Light

Warm White

3000K

2m long

The profile is sold in bars and consists of a base to be fixed to the wall and a translucent methacrylate covering. LED strips not exceeding 12-mm width can be placed inside. The bars can be aligned to get any length or cut to measure.

Part No	Description
96470	LED Strip 12V 10W
96471	LED Strip 12V 12W
96472	LED Strip 24V 10W
96473	LED Strip Light Diffuser 1M



LED SMD-HD high-efficiency light source. Flat base version, ideal for engine compartments, bathrooms, kitchens, under boom on sailing boats, etc.

Part No	Description
96051	Free Standing Led Light 230 X 24 X 11MM
96052	Free Standing Led Light 310 X 40 X11.5MM + Switch



Linear Overhead LED Light

14 LED SMD-HD high-efficiency light source. Light alloy base with polycarbonate opal lens. Round switches with built-in blue/red LED.

12V

5.2W

228 Lumens

3000K

120° LED beam angle

345x33x12 (H)

Part No Description

96048 Overhead Strip Light



Turnstripe 8-LED track light, rotating version

High intensity LED light and built-in switch; anodized aluminium body, opaline front glass.

12/24V

1W

50Lumen

4000K

LED beam angle 120°

Length 260mm

Part No Description

96414 Turnstripe 8 LED Track Light





We are distributors of the Vetus range of marine equipment. Please contact us if you would like an up to date Vetus Catalogue. Up to date prices can be found once logged into our trade website.



Epifanes Multi Marine Primer "All-in-one-primer"

A one-part multi purpose tie-coat or sanding and adhesion primer for above the waterline combining all characteristics of separate substrate primers in one.

Suitable Thinners:

Brush - Epifanes Brush Thinner Spray - Epifanes Spray Thinner

Coverage: 8 -10m² / Litre

Substrates: Wood, fibreglass, steel, stainless steel, aluminium, galvanized metal, copper and most other bare or painted substrates.

Part No	Description
69310	Multi-Marine Primer White 750ml
69311	Multi-Marine Primer White 2 Litre
69312	Multi-Marine Primer Grey 750ml
69313	Multi-Marine Primer Grey 2 Litre
69314	Multi-Marine Primer Red brown 750ml
69315	Multi-Marine Primer Red brown 2 Litre



Epifanes Undercoat

A one-component primer and undercoat based on a urethane/alkyd resin. For use in a one-component paint system above the waterline. Suitable for interior and exterior use. Recoatable with all Epifanes onecomponent products.

Suitable Thinners:

Brush - Epifanes Brushthinner Spray - Epifanes Spraythinner

Coverage: 8 -10m² / Litre

Substrates: Fibreglass/ GRP, wood, steel & aluminium

Part No	Description
69320	Undercoat White 750ml
69321	Undercoat White 2 Litre
69322	Undercoat Grey 750ml
69323	Undercoat Grey 2 Litre



Epifanes Woodprimer

A traditional one-component primer based on alkyd resins. For use on bare wood, with good filling, building and covering properties. The appropriate primer for wood in one-component paint systems above the waterline. Recoatable with all Epifanes one-

component paints.

Application

Wood: bonding primer on bare wood in a one-component paint system above the waterline.

Suitable Thinners:

Brush - Epifanes Brush Thinner Spray - Epifanes Spray Thinner

Coverage: 8 -10m² / Litre

Substrates: Wood

Part No	Description			
69325	Woodprimer White 750ml			
69326	Woodprimer White 2 Litre			
69327	Woodprimer Grey 750ml			
69328	Woodprimer Grey 2 Litre			



Epifanes Washprimer AQ

A water-based adhesion primer. For interior and exterior use above and below the waterline. Can be overcoated with all Epifanes one-and two-component products. Apply one thin coat. Avoid curtains. May be used on degreased and sanded existing aluminium prior to coating with Epifanes Multi Marine Primer. Coverage: 16m² / Litre

Thinner: Do not thin. Cleaning tools: water Recoatability: After 2 hours at 65°F./18°C

Colour: Off white, dries fully transparent

Substrates: Aluminium, zinc coated and galvanized steel surfaces, non-ferrous metals, glass and ceramics.

Part No	Description
69316	Washprimer AQ 500ml
69317	Washprimer AQ 1 Litre



Epifanes HB Coat

High Build Epoxy Primer

Two component high-build epoxy coating based on epoxy resins, used for the maintenance and protection of de-rusted steel, aluminium, wood and properly cleaned and degreased fibreglass.

Suitable Thinners: Epoxythinner D-601

Coverage: 9m² / Litre

Substrates: Fibreglass/GRP, steel, plywood, alu-

minium.

Part No Description

69338 High Build Epoxy Light Grey Primer 750ml



Epifanes Polyurethane Primer

A hard two-part semi gloss poly-urethane undercoat. Provides an extremely smooth, pinhole-free surface prior to topcoating with Epifanes high gloss polyurethane. Good flowing properties, very quick drying, medium filling and easy sanding.

Suitable Thinners:

Brush - Epifanes Polyurethane Brush Thinner Spray - Epifanes Polyurethane Spray Thinner

Coverage: 9m²/ Litre Substrates: Fibreglass

Part No Description

69339 Polyurethane White Primer 750ml





Epifanes Nautiforte Yacht Paint

A high gloss one-component finish based on siliconized alkyd resins. This finish provides outstanding weather durability, long lasting gloss retention, rapid wet film drying, minimal dirt retention and is non-yellowing.

Suitable Thinners:

Brush - Epifanes Brush Thinner Spray - Epifanes Spray Thinner

Coverage: 14m² / Litre

Substrates: Fibreglass, steel, wood & aluminium:

Part No	Description
69300	Nautiforte White 750ml
69301	Nautiforte White 2 Litre
69302	Nautiforte 24 Light Oyster 750ml
69303	Nautiforte 25 Alpine White 750ml

Epifanes Yacht Enamel

A high gloss, one-component, alkyd-based, traditional marine finish. This enamel has very good flowing and covering properties and provides long lasting gloss retention and excellent weather durability.

Suitable Thinners:

Brush - Epifanes Brushthinner Spray - Epifanes Spraythinner

Coverage: 1 Litre = 15m²

Substrates: Fibreglass/GRP, steel, wood and aluminium.

750ml	Colour	750ml	Colour	750ml	Colour	750ml	Colour
69250	White	69263	16 Bright Red	69275	31 Turkish Blue	69287	210 Antique Ivory
69251	White (2 Litre)	69264	18 Light Grey	69276	33 Light Brown	69288	212 Grey
69252	1 Cream	69265	19 Black	69277	34 Chocolate Brown	69289	213 French Grey
69253	2 Beige	69266	21 Orange	69278	35 Red Brown	69290	214 Dark Grey
69254	3 Wheat	69267	23 Deep Red	69279	37 Yellow	69291	215 Sky Blue
69255	4 Dark Buff	69268	24 Light Oyster	69280	40 Off White	69292	216 Pearl Grey
69256	6 Tropic Green	69269	25 Alpine White	69281	48 Light Green	69293	217 Light Blue
69257	7 Bright Blue	69270	26 Buff	69282	62 Atlantic Green	69294	218 Jade Grey
69258	8 Dark Blue	69271	27 Grey Mist	69283	65 Deep Green	69295	24 Light Oyster (2 Litre)
69259	9 Sea Green	69272	28 Water Blue	69284	72 Dark Green		
69260	11 Dado Brown	69273	29 Ocean Blue	69285	205 Deep Blue		
69262	14 Mahogany	69274	30 Teal Green	69286	206 Blue Grey		



Epifanes Mono-urethane Yacht Paint

A hard, one-component, air-drying, high gloss finish paint based on urethane/alkyd resins. Provides superior covering and filling, long lasting weather durability and high gloss retention. Offers rapid initial curing.

Suitable Thinners:

Brush - Epifanes Brushthinner Spray - Epifanes Spraythinner

Coverage: 1 Litre = 15m²

Substrates: Fibreglass/GRP, steel, wood & aluminium.

	•		
750ml	Colour	750ml	Colour
69220	White	69232	3165 Deep Green
69221	3101 Cream	69233	3168 Green
69222	3107 Bright Blue	69234	3172 Dark Green
69223	3108 Dark Blue	69235	3201 Whale Grey
69224	3116 Bright Red	69236	3210 Dark Blue
69225	3119 Black	69237	3212 Grey
69226	3124 Light Oyster	69238	3221 Mouse Grey
69227	3125 Alpine White	69239	3233 Burgundy
69228	3126 Buff	69240	3242 Dark Beige
69229	3129 Deep Blue	69241	3243 Medium Beige
69230	3137 Bold Yellow	69242	3248 Off White
69231	3140 Matterhorn White	69243	3253 Light Beige



Epifanes Polyurethane Yacht Coating

A high gloss, two-component, polyester saturated, aliphatic urethane coating. Scratch resistant, excellent outdoor durability and weather resistance. The finish provides a perfect flow and easy application by brush, roller or spray.

Suitable Thinners:

Brush - Epifanes Polyurethane Brush Thinner Spray - Epifanes Polyurethane Spray Thinner

Coverage: 10m²/ Litre

Substrates: Fibreglass/GRP, steel, wood &

aluminium.

Part No Description

Polyurethane 800 White 750ml



Epifanes PP Varnish Extra UV

A professional, quick drying, high gloss build up varnish for all types of wood, based on alkyd resin and isocyanate. Recommended sealer for oily wood such as teak and iroco. Resistant to water, alcohol and various household chemicals. Excellent flow and abrasion resistance, superior grain filling and rapid build up. Offers sufficient flexibility for application on working wood (masts). The varnish contains a high quality UV filter, however for exterior use it is advised to overcoat with 2-3 coats Epifanes Polyurethane clear gloss or Epifanes clear gloss varnish for extra UV protection.

Suitable Thinners:

Brush - Epifanes Thinner for PP Varnish Extra or Epifanes PU Brushthinner Spray - Epifanes Thinner for PP Varnish Extra

Coverage: 1 Litre = 14m²

Substrates: Wood

Part No Description 69180 Epifanes PP Varnish Extra 10 Litres 69181 Epifanes PP Varnish Extra 2 Litres



Epifanes Clear Varnish UV

A clear, high gloss, traditional yacht varnish based on tung oil, phenol and alkyd resin. Unique flow characteristics, high build capacity and excellent outdoor durability. Contains an extra UV filter protecting the wood against discolouration. Its flexibility prevents cracking on working wood. This varnish is famous for its high gloss retention and long lasting properties, even in tropical climates.

Suitable Thinners:

Brush - Epifanes Brushthinner Spray - Epifanes Spraythinner

Coverage: 1 Litre = 14m²

Substrates Wood.

Part No	Description
69198	Epifanes High Gloss Clear Varnish 250ml
69199	Epifanes High Gloss Clear Varnish 500ml
69200	Epifanes High Gloss Clear Varnish 1 Litre



Epifanes Woodfinish Matte UV

A clear, satin finish, based on urethane/ alkyd resin and tung oil. Provides a beautiful, rich, matte finish for all fine woodworks, like teak and iroco, giving years of protection against alcohol and other aggressive household chemicals,

Suitable Thinners:

Brush - Epifanes Brushthinner Spray - Epifanes Spraythinner

Coverage: 1 Litre = 12m²

Substrates Wood.

Part No Description

69196 Woodfinish Gloss Matte 1 Litre



Epifanes Rubbed Effect Varnish

A quick drying, clear interior satin finish, based on urethane/alkyd resin. The interior finish gives superior protection against alcohol and other aggressive household chemicals. Apply as a finish coat over several build-up coats of Epifanes clear gloss varnish or woodfinish gloss.

Suitable Thinners:

Brush - Epifanes Brushthinner Spray - Epifanes Spraythinner

Coverage: 1 Litre = 13m²

Substrates: Wood

Part No	Description
69192	Epifanes Rubbed Effect Varnish 500ml
69193	Epifanes Rubbed Effect Varnish 1 Litre



Epifanes Woodfinish Gloss UV

A clear, high gloss varnish-like finish, based on alkyd and phenolic resins. Excellent adhesion to degreased and sanded new teak and other exotic woods. For use where a glossy, varnished look is desired. Its microscopic porosity allows the wood to breathe. The UV filter protects the wood against discoloration. Water and weather resistant and excellent outdoor durability. Sanding between coats is not required if the next coat is applied within 72 hours.

Suitable Thinners:

Brush - Epifanes Brushthinner Spray - Epifanes Spraythinner

Coverage: 1 Litre = 12m²

Substrates Wood.

Part No	Description
69197	Woodfinish Gloss 1 Litre



Epifanes Rapidclear Semigloss/Matt Varnish

A UV semi-gloss or matte wood finish based on modified alkyd/ urethane resins. The answer for a quick and easy alternative to conventional varnish. For long term protection and enhancement of all interior and exterior marine and household woods above the waterline. It bonds extremely well to teak and other oily woods, preventing discoloration and emphasizes the natural grain of the wood. Quick drying, excellent breathing properties, flexibility, maximum durability and longevity.

Suitable Thinners:

Brush - Epifanes Brushthinner Spray - Epifanes Spraythinner

Coverage: 750ml = 10m²

Substrates Wood.

Part No Description

Rapidclear Matt 750ml 69189

69190 Rapidclear Semigloss750ml



Epifanes Teak Oil Sealer

A traditional impregnating oil, based on linseed oil and alkyd resin. Protects teakwood from discoloration caused by weather or pollutants. Ideal for the maintenance of teak decks. May be applied wet on wet. Degrease wood with Epifanes spraythinner for paint & varnish or denatured alcohol and allow to evaporate. Apply with a wide brush, polybrush or lint free cloth until surface is saturated. Remove excess material.

Attention: due to the possible risk of self ignition, after use always keep cloths soaked in water.

Suitable Thinners: Do not thin.

Coverage: 1 Litre = 7m² Substrates Teak Wood.

Part No Description

69195 Teak Oil Sealer 1 Litre



Epifanes Polyurethane Clear Gloss UV

A high gloss, two-component polyester saturated, aliphatic urethane finish with excellent outdoor durability. Resistant to weathering, chemicals, scratching and loss of gloss. Outstanding flow characteristics for both brush and spray applications. The UV filter protects the wood from discoloration. Mixing ratio by weight 2 parts component A to 1 part component B. Allow to activate for 10-15mins before use.

Suitable Thinners:

Brush - Epifanes Polyurethane Brushthinner Spray - Epifanes Polyurethane Spraythinner

Coverage: 750ml = 10m²

Substrates Wood.

Part No Description

Polyurethane Clear Gloss 750ml



Epifanes Classic Mahogany Stain

Epifanes Classic Mahogany Stain is a quick drying, impregnating stain formulated specifically for bare mahogany and other marine woods. This stain provides a warm, rich, red/brown mahogany colour. Depending on desired degree of intensity, a maximum of 3 coats may be applied on bare wood. Recoatable with all Epifanes one component and two-component varnishes.

Suitable Thinners: Do not thin.

Coverage: 4-7m² depending on surface

Substrates: Wood

Part No Description

69182 Mahogany Stain 500ml





Epifanes Brush thinner for Paint & Varnish

A high quality thinner for brushing or rolling most one-component primers, paints and varnishes. The double distillation of this thinner provides maximum purity.

Part No	Description
69205	Brush Thinner Single Pack 500ml
69206	Brush Thinner Single Pack 1 Litre



Epifanes Spray thinner for Paint & Varnish

Thinner for spray applications of onecomponent primers, paints and varnishes. Also highly suited for degreasing wood and existing paint and varnish layers.

Part No	Description
69207	Spray Thinner Single Pack 1 Litre



Epifanes Poly-urethane Brush thinner

A slow evaporating thinner for brushing and rolling Epifanes Poly-urethane Yacht coatings

oodingo.		
Part No	Description	
69208	Polyurethane Brushthinner 500ml	
69209	Polyurethane Brushthinner 1 Litre	



Epifanes Poly-urethane Spray thinner

Fast evaporating thinner for spray applications of Epifanes Polyurethane Yacht coatings.

•	
Part No	Description
69210	Polyurethane Spraythinner 500ml
69211	Polyurethane Spraythinner 1 Litre



Epifanes Thinner for PP Varnish Extra

Fast evaporating thinner for Epifanes PP Varnish Extra. Also suited for degreasing teak wood.

Part No	Description
69212	PP Varnish Extra Thinners 1 Litre



Epifanes Accelerator for Paint & Varnish

A resin based additive for use in traditional one-component, half-synthetic paints and varnishes to speed up the curing process. For interior use, e.g., on chairs, tables, etc., this product can be added up to 50% to Epifanes Clear Gloss Varnish for a harder, more scratch-resistant finish. Do not use with Epifanes Monourethane and Epifanes Nautiforte.

Part No	Description
69213	Epifanes Accelerator 500ml
69214	Epifanes Accelerator 1 Litre







Acrylic Spray Paint

Acrylic spray paints for AIFO/FPT inboard engines.

Part No	Description
91765	400ml Acrylic Spray Paint Red
91766	400ml Acrylic Spray Paint Grey
91767	400ml Acrylic Spray Paint Black



S-shaped polypropylene paint stirrer. The s-shape make the mixing stick sturdier. Corrosion -resistant to both paint and thinner.

Part No	Size
67941	30cm



Mirka Mixing Cups- Sold Individually Calibrated mixing cups for paint and epoxy products.

Part No	Size
67951	400ml cup
67950	650ml cup
67955	1300ml cup
67960	2300ml cup
67962	6ltr Cup



Primer Undercoat - Single Part Primer

A single component primer for all substrates (including steel) above the waterline and an undercoat for Brilliant Gloss/ Multicoat/Non Slip Deck Coating. A quick-drying, high-opacity primer and undercoat, that gives excellent durability and surface stability ready for overcoating with single component topcoats.

Suitable Thinners: No. 1 (811)

Coverage: 12m² / L

Colour	750ml	2.5L
Mid Grey	65955	65960
White	66025	66030



Light Primer - Two Part Epoxy Primer

A two component high performance epoxy primer and undercoat for use both above and below the waterline. Use on glass fibre, wood, steel and aluminium. Superb corrosion, impact and water resistance. Use before Ocean Gloss/ Brilliant Gloss topcoat for a long lasting solution. Can also be used for osmosis protection when application is required at low temperatures.

Suitable Thinners: No. 5 (845)

Coverage: 8.2m² / L

Colour	375ml	750ml	2.25L
Off-white	66568	66566	66567
Grey	-	66570	66575



Prop Primer

Aerosol Primer for propellers and outdrives.

Coverage: 3.5m²/L

500ml Colour Prop Primer Stone Grey 65474



Underwater Primer - Antifouling Primer

Use as part of a single component system below the waterline, including keels; and as a tiecoat before antifouling. Can be applied directly onto the hull or primed surface, and between an existing antifouling and a new antifouling. Fast-drying with excellent waterproofing. For use on all substrates.

Suitable Thinners: No. 1 (811) Brush

Coverage: 7.8m² / L

Colour 750ml 2.5L Grey 66322 66323



Hempel's Sealer 599

A two component epoxy-polyamide with low viscosity and good penetration ability. For saturation of glass fibre laminate, when gel coat has been removed (repair of osmosis damage). For priming of ferrocement boats and boats made of wood that can absorb the sealer.

Suitable Thinners: No 5 (845)

Coverage: 10m² / L

750ml 66452



High Protect II

High build, solvent free epoxy coating for the treatment of, and protection against, osmosis. Available in two shades for overcoating accuracy.

Suitable Thinners: No. 5 (845)

Coverage: 6.6m² / L

Colour 750ml 2.5L 66545 Grey 66540 66550 66555 Cream



Hempel Mille NCT (DIY)

This antifoul is the new replacement for Hempel Ocean Performer. Mille NCT is a high performance self-polishing antifouling based on Hempel's patented binder technology, where the self-polishing is controlled by sea waters interaction with the binder. The powerful bioactive mixture and self-renewing effect results in a sustained antifouling protection. So it is ideal for areas with high fouling. Suitable for use on all substrates except aluminium.

Suitable thinners: Thinners No. 3

Coverage: 13m² / L

Colour	2.5 Litre
White	67410
Grey	67412
Black	67414
True Blue	67416
Souvenirs	67418
Red	67420



Hard Racing

Hard, high strength antifouling which gives a smooth racing finish, offering all round competitive performance. Formulated especially for power boats, racing yachts and vessels which are mud berthed. It may also be used on vessels that are dry sailed. Suitable for all substrates except aluminium. Maximum launch time 3 months.

HSE: 7385, HSE (white) 6969 Suitable thinners: Thinners No. 3

Coverage: 13.5m² / L

Colour	2.5 Litre
White	65010
Red	65025
Black	65040
Dark Blue	65045
True Blue	65085
Grey	65086



Mille NCT Professional Use Only

Mille NCT is a high performance self-polishing antifouling based on Hempel's patented binder technology where the self -polishing is controlled by sea waters interaction with the binder. The powerful bioactive mixture and self-renewing effect results in a sustained antifouling protection. Mille NCT is compatible with virtually all other antifouling systems. Excellent colour retention. Mille NCT is ideal for all type of boats providing an excellent performance for a whole season.

Suitable for boats made of glass fibre, wood, plywood, steel, aluminium, light-alloy metal and Ferro cement.

Suitable thinners: Thinners No. 3

Coverage: 12.3m² / L

Colour	5 Litre
White	67391
Black	67393
Dark Blue	67395
Red	67404



Hard Racing TEC CEL Professional Use Only

Hempel's Hard Racing TecCel is a high performance hard matrix antifouling, providing exceptional protection all season. Includes TecCel to reduce friction to increase speed. As an antifouling for boats of glass fibre, wood, plywood and steel. Do not use on aluminium or other light-alloy metals. Risk of corrosion in case of direct contact. For cold and temperate waters. Part of European Yacht assortment.

For Professional use only.

Suitable thinners: Thinners No. 3

Coverage: 12.3m² / L

Colour	5L
White	67387
True Blue	67388
Dark Blue	67389
Black	67390



Hard Racing Boottop

Strong scrubable antifouling for boottops which gives bright colours on the waterline. It is suitable for all substrates, including aluminium, once suitably primed. Maximum launch time 3 months. HSF: 8636

Suitable thinners: Thinners No. 3 Coverage: 13.8m² / L

Colour	375ml
Black	67370
Dark Blue	67372
Red	67373
White	67374



Tiger Xtra

Self polishing, erodible antifouling. Suitable for both power and sail boats and just 1 coat can last the season. Applying a second coat for year round protection gives excellent and consistent long term performance, under all conditions. It is suitable for use on all substrates except aluminium. Maximum launch time 3 months. HSE:7514 HSE: (white) 7505

Suitable Thinners: Thinners No.3

Coverage: 13.5m² / L

Colour	2.5L	5L
Grey	65416	
Souvenirs	65418	
True Blue	65420	65413
Black	65422	65414
Red	65424	65412
White	65426	
Dark Blue	65427	
Green	65428	



Cruising Performer

Self polishing, erodible antifouling with the very latest eroding technology which reduces the build up of paint, maximizing cruising capability in all areas, whilst ensuring fouling is kept to a minimum. An excellent coverage rate and colour stability ensures cruising Performer offers you the very best in value. Suitable for use on all substrates except aluminium. Maximum launch time 3 months. Suitable thinners: Thinners No. 3 Coverage: 12.5m² / L

Colour	2.5L
Souvenirs	65435
True Blue	65437
Black	65439
Red	65441



Broads

Medium strength copper based antifouling specifically designed to reduce paint build up and give a good performance on fresh, salt and brackish waters. It is suitable for all substrates except aluminium. The maximum launch time is 1 month. HSE:7345

Suitable thinners: Thinners No. 3 Coverage: 12.8m² / L

Colour	2.5ltr
True Blue	65508
Green	65509
Red/Brown	65511
Black	65513





Ecopower Prop Aerosol

Biocide free spray paint that keeps propellers, outdrives and sterngear free from fouling and making it very easy to clean.

An advanced binder technology controls the self-renewing effect throughout the season.

Coverage: 1.3m² / L

500ml	Colour
65474	Prop Primer Stone Grey
65475	Ecopower Penta Grey
65480	Ecopower Black





Globic 6000 Rusty Red

A high solids chemically hydrolysing SPC antifouling based on Nano Acrylate Technology. Globic 6000 offers low friction, self-smoothing, and a best-in class instant activation of polishing and performance for optimal performance from day one. The patented microfibres give Globic 6000 a best-in-class mechanical strength to avoid cracking and peeling. For both new builds and maintenance of underwater hull and boottop for up to a 60 months drydocking interval.

Suitable thinners: Thinners No. 08080

Coverage: 5.8m² / L

Colour	20L
Rusty Red	67398



Classic Antifouling - 76110

Hempel's Antifouling Classic 76110 is an antifouling of the "soluble matrix" type.

Use as an antifouling from keel to light load line on ships trading mainly in cold and temperate waters with short idle periods.

Suitable thinners: Thinners No. 08080 Coverage: 11.2m² / L

Colour	5L	20L
Rusty Red	67399	67400



Olympic Antifouling

Olympic 86951 is a high solid, tin-free, self-polishing antifouling. Polishing is based on an ion exchange, resulting in a hydrolysable activated layer. An inorganic fibre content ensures polishing control and mechanical strength.

Use as an economical antifouling for bottom and boottop on deep-sea operating vessels operating at medium to high speed and high activity with short idle periods, and with dry-docking interval of up to 36 months.

Suitable thinners: Thinners No. 08080 Coverage: 11.2m² / L

Colour + Size	Part no
Rusty Red 20 Litre	67396



Silic One Tiecoat

Silic One Tiecoat is a high solid silicone based tiecoat for Silic One 77450. Also use as a touch-up and repair of damaged areas. Ensures adhesion between Light Primer 45551 and Silic One.

Suitable Thinners: No. 3

(cleaner for tools only)

Coverage: 10m2 / L

Shelf Life: 1 year depending on

storage conditions.

Pot life: 1 hour after opening the

can

Part No Description

65445 Silic One Tiecoat 750ml



Silic One (silicone based antifoul)

Hempel's Silic One is a biocide free, high solid, fouling release coating. Based on silicone, a hydro gel micro layer provides a smooth, low friction surface which prevents organisms attaching to the hull and propellers. Service life of Silic One on the hull is 2 years.

Suitable Thinners: No. 3

(cleaner for tools only)

Coverage: 6m2 / L

Shelf Life: 1 year depending on storage condi-

tions.

Pot life: 1 hour after opening the can

Part Description

No

65447 Hempel's Silic One Red 750ml

Hempel's Silic One Black 750ml



Silic One Propeller Kit - 750ml

Self cleaning even at low speed, can be applied on top of old antifouling if in good condition.

Silic One Propeller Kit contains the following products: Silic One 77450, Silic One Tiecoat 27450

Part No

65450



Brilliant Gloss

Brilliant Gloss is a high gloss alkyd topcoat with excellent colour retention. Flexible and resistant to salt water and pollutants. Easy application ensures an exceptional finish. For exterior and interior use above the waterline.

Suitable Thinners: No. 1 Coverage: 11m²/L

Colour	750ml	Colour	750ml
Matterhorn White	67256	Cream	67276
Town Grey	67258	Britannia Blue	67278
Pure White 375ml	67260	Souvenirs Blue	67280
Pure White 750ml	67262	Cobalt Blue	67282
Pure White 2.5ltr	67264	Flag Blue	67284
Off White	67266	Ice Blue	67286
Polar White	67268	Marine Green	67288
Pale Grey	67270	Survival Orange	67290
Smoke Grey	67272	Bordeaux Red	67292
Black	67274	Radiant Red	67294



MultiCoat

A single component semi-gloss topcoat and primer. Ideal for all areas above the waterline requiring a semi-gloss durable topcoat. Can be applied directly to most surfaces. Provides excellent durability with good resistance to water and oil. Can also be used as a complete coating system on new or bare wood: 1st coat thinned 20%, 2nd Coat thinned 5-10%, further coats undiluted. Add Anti-Slip granules for a non-slip finish. Suitable Thinners: No. 1

Coverage: 12m² / L

Colour	750ml	2.5ltr	Colour	750ml
White	66084	66085	Pale Cream	66092
Mid Grey	66086	-	Navy Blue	66093
Light Grey	66088	-	Light Blue	66097
Black	66090	66091	Pillarbox Red	66102



Anti-Slip Pearls 50g Sachet

Anti-Slip Pearls can be added to all types of paint where a non-slip surface is required. Mix with Hempel's topcoats and varnishes to obtain non-slip finishes on decks and surfaces where required.

66250



Polygloss

Polygloss 55530 is a high-gloss, two-component polyurethane enamel especially suited for application by brush. It has excellent gloss and colour retention. Resistant to water, wear and marine atmosphere.

Suitable Thinners: No. 2 Coverage: 11m² / L

Colour	750ml
Cobalt Blue	66705
Survival Orange	66831
Off White	66830
Pure White	66835
Black	66850



Non-Slip Deck Coating

Durable coating for deck areas. Contains fine granules for a non slip finish (product contains Antislip Pearls). Easy to apply straight onto substrate.

Suitable Thinners: No. 3 Coverage: 11m² / L

Colour	750ml
White	67300
Mid Grey	67302
Light Grey	67304
Pale Cream	67306
Navy Blue	67308



Bilge & Locker Paint

A single component high opacity satin topcoat providing excellent durability with good water and oil resistance for bilges and lockers. Not suitable for permanent immersion

Suitable Thinners: No. 1 Coverage: 12m² / L

Colour	750ml	2.5L
White	66265	66268
Mid Grey	66270	66275
Light Grey	66280	66285



Classic Varnish

A single component traditional varnish produced from the highest quality materials, including tung oil. Use inside and outside above the waterline. Excellent flow at application, a flexible finish and long term UV filters ensure an uncompromising finish that will last for a long time.

Suitable Thinners: Thinners No. 1 Coverage: 18m² / L

HEMPE

750ml	2.5L
66538	66539



Favourite Varnish

A single component alkyd based, full bodied, high gloss varnish. For use above the waterline, both inside and outside. Especially easy to use, giving a tough, durable, long lasting finish, with depth of gloss. Ideal for areas where structural flexibility of the wood is needed.

Suitable Thinners: Thinners No. 1 Coverage: 16m² / L

750ml	2.5L
66489	66494



Dura-Gloss Varnish

A single component, urethane modified alkyd with excellent resistance to alcohol and cleaning materials. For inside and outside areas above the waterline requiring a beautiful durable finish. Quick drying to an extremely hard and durable high gloss surface, highly resistant to wear and abrasion within hours of application.

Suitable Thinners: Thinners No. 1 Coverage: 17m² / L

750ml

66511



Dura-Satin Varnish

A single component, urethane modified alkyd with excellent resistance to alcohol and cleaning materials. For inside and outside areas above the waterline requiring a beautiful durable finish. Quick drying to an extremely hard and durable high satin surface, highly resistant to wear and abrasion within hours of application.

Suitable Thinners: Thinners No. 1 Coverage: 17m² / L

750ml

66536



Diamond Varnish

A two component polyurethane varnish. Use inside and outside above the waterline. Use where a hard, extremely durable and long lasting finish is required. Highly resistant to abrasion and chemicals, for the ultimate finish in durability and beauty. For professional use only.

Suitable Thinners: No. 2(Brush),

No. 6 (Spray) Coverage: 12.m² / L

750ml

66521



Teak Oil - 750ml

Unpigmented teak oil with good penetration to protect wood and make it easier to clean. Helps wood resist both water and dirt, and underlines its original structure. Use to overcoat Teak Colour Restorer on areas of high usage. Not suitable for use on painted or varnished surfaces.

Part No

66373



Teak Cleaner - 750ml

A powder for cleaning all teak areas. Especially good for large areas such as decks, and for wood that's turned dark grey. Removes dirt and marks giving a clean surface ready for you to apply Teak Oil.

Part No

66374



Hempel Anti Slint

Hempel's Anti-Slint 67500 is flame dried silica sand of which the average particle size is approximately 0.5 millimetres. To obtain anti-skid properties on decks and other areas where a skid-proof surface is required.

66251



Hempinol Black Tar Varnish

Narrow Boat Blacking

Hempinol is a physically drying, high-build, bituminous coating and is flexible, water resistant and rust preventing. An economical corrosion protection of interior and exterior steel and concrete substrates in moderately corrosive environments, not exposed to direct sunlight. Well suited for steel and concrete surfaces buried in subsoil conditions.

4L Black Tar Varnish

66430



Hempalin Enamel 52140 is a glossy alkyd enamel which forms a weather resistant coating. It is flexible and resistant to salt water and spillage of mineral oil and other aliphatic hydrocarbons.

A general purpose finishing coat in alkyd systems on exterior and interior steel and woodwork in mildly to moderately corrosive environments. Use as a finishing coat in engine rooms including tank tops, main engines and auxiliary machinery.

Colour	5 L
RAL Colours	67297



Hempathane HS 55810

Hempathane HS 55810 is a two-component polyurethane topcoat, cured with aliphatic isocyanate, with very good gloss and colour retention.

Use as a low VOC finishing coat for protection of structural steel in severely corrosive atmospheric environments.

Suitable thinners: Thinners No. 08080 Coverage: 16.3m² / L

Colour **RAL Colours** 67402



Hempadur 45143 is a two-component, polyamide adduct cured epoxy paint with good wetting properties and low water permeability. It is selfpriming and forms a hard and tough coating which has good resistance against abrasion and impact as well as to seawater, mineral oils, aliphatic hydrocarbons and splashes from petrol and related products. Harmless to grain cargoes. 1. As a high build primer, intermediate and/or finishing coat in (heavy duty) paint systems according to specification. (As a finishing coat where a cosmetic appearance is of less importance).2. For repair and maintenance work at application temperatures above -10°C/15°F on hatch covers, decks, in cargo holds, etc. 3. As a ballast tank coating. Hempadur 45143 is intended for use in cold/temperate climates, Hempadur 45141 is used for warmer climates.

Colour	5L
Black	67403
White	67422
Grey	67423



Hempel's Tool Cleaner 99610

A blend of strong solvents for cleaning of tools that have been used for mixing or application of twocomponent epoxy products. It has better cleaning properties than epoxy thinners. Does not contain chlorinated solvent.

For cleaning of brushes, paint rollers, spray equipment, and other tools which have been used for mixing or application of Hempadur products.

Do not use as thinner for any paint.

Colour	5L
Clear	67401



Hempel's Thinners 08080

Hempel paint is produced and supplied in such a way that thinning is normally not necessary, provided the paint is properly mixed/stirred. However, if the paint is to be applied in a low film thickness (for instance as a "sealer coat") or if the paint has become too thick, e.g. in cold weather, the correct Hempel thinner may be added. As a general rule, thinning should be kept at a minimum as the quality of the paint work will suffer from too liberal thinning. However, if application is to take place at high temperatures (air and/or steel), thinning may even beyond the limits mentioned on the data sheets exceptionally be necessary in order to avoid dry-spray and poor film formation.

Colour	5L
Clear	67397



Hempaspeed TF is a high performance, hard, thin-film coating. Forms an ultra-smooth surface that minimizes growth and reduces drag. For use as an antifouling for boats of glass fibre, steel and aluminium. Suitable for pleasure boats and racing / regatta boats. Ideal for both fresh and salt water use.

hempelyacht.com













Paint can be thinned to improve its flow characteristics and to increase its ability to be absorbed. Care should be taken not to exceed the maximum ratio of thinners as this can adversely affect the product you are applying. When paint is thinned, the spreading rate will increase and the paint will be easier to work with. On the other hand, the dry film thickness will be thinner when the solvents have evaporated and it may be necessary to apply another coat to obtain the required film thickness.

It is important that the correct thinner is used for each application - failure to do so will result in a ruined job.

- No 1 Single component primers, topcoats and varnishes
- No 2 Brush application. Two component polyurethane paint and varnish.
- No 3 Antifouling, non slip deck coating and spray thinner for topcoat.
- No 5 Light Primer

No 6 - Spray application. Two component polyurethane paint and varnish.

Thinner	750ml	5 L
Thinners No. 1	66960	66970
Thinners No. 2	66980	66990
Thinners No. 3	67000	67010
Thinners No. 5	67020	67030
Thinners No. 6	67035	67040





Degreaser - 750ml

A blend of strong solvents for the cleaning of tools that have been used for mixing or application of two component epoxy products. It has better cleaning properties than epoxy thinners. Recommended use: for cleaning of brushes, paint rollers, spray equipment and other tools which have been used for the mixing or application of Hempel products.

Part No

67050

Paint:International

NEW for 2022



One Up Primer Pre Kote

Replaces Yacht Primer and Pre-Kote whilst still delivering the same levels of adhesion and protection

One UP is a single pack primer/undercoat for use above the waterline with International one-pack finishes and deck paints. Simple yet effective, making painting easier for DIY customers without compromising on aesthetic appearance or substrate protection.

Suitable Thinners: No. 1 Coverage: 10m2/L

Substrates: Aluminium, GRP/FRP, Steel, Wood &

Carbon Fibre

Colour	375ml	750ml	2.5L
White	68320	68321	68322
Blue/Grev	_	68323	-



Primocon

Conventional one-part primer for use below water. Quick drying, with anticorrosive properties. Can be used under all major antifouling or as a conversion coat over incompatible or unknown antifouling.

Suitable Thinners: No. 3 Coverage: 8.33m² / L

Substrates: Aluminium, GRP/FRP, Lead, Steel, Wood, Carbon Fibre & Cast Iron.

Colour	750ml	2.5L
Grey	68381	68382



VC-Tar2

Osmosis defence for GRP and anticorrosion barrier for metal. Advanced self-levelling formulation requires no sanding between coats. Smooth surface - ideal primer base for antifoulings.

Suitable Thinners: VC General

Thinners

Coverage: 12.6m² / L

Substrates: Aluminium, GRP/FRP, Lead, Steel, Carbon Fibre & Cast

Iron.

Colour	1L	2.5L
Black	68545	68546
Off White	68547	-



Interprotect

Quick drying, easy to apply, two part epoxy primer. Offers excellent anti-corrosive protection. Can be used as an antifouling tie-coat over existing epoxy primers.

Suitable Thinners: No. 7

Coverage: 9.1m² / L

Substrates: Aluminium, Steel &

Wood

Colour	750ml	2.5L
White	68390	68391
Grey	68392	68393



Perfection Undercoat

High performance two-part polyurethane undercoat. Provides an excellent base for a long lasting gloss finish. Easy application, fast drying and easy sanding. Semi-gloss appearance.

Suitable Thinners: No. 9

Coverage: 13.3m² / L

Substrates: Aluminium, GRP/FRP, Steel, Wood & Carbon Fibre

Part No	Description
68195	White 750ml
68705	White 2.5 Litre
68707	Blue 2.5 Litre

Paint:International



Interprime 820

High performance 2-component epoxy primer containing inert pigments and extenders. Excellent anticorrosive properties. Easy Sanding. Two colours for overcoating Identification.

Thinners: 910 Coverage: 3.6m² / L

Substrates: Aluminium & Steel

Colour	5L	20L
White	68604	68606
Grev	68608	68610



Gelshield 200

A quick drying, easy to apply, epoxy primer for protection of GRP against osmosis. Provides protection against osmosis in five coats (250 µm). Usable down to 5°C. Fast drying allows multiple coat application in a single day.

Suitable Thinners: No. 1 Coverage: 9.1m²/L Substrates: GRP/FRP

Colour	750ml	2.5L
Grey	68412	68413
Green	68414	68415



Gelshield Plus

A high build, solventless epoxy primer. Available in two colours to aid self-on-self application. Contains no harmful solvents to migrate into the hull and cause reblistering.

Colour	2.25 L
Green	68630
Blue	68631



Clear Wood Sealer Fast

Fast-drying, high-build, clear, surface primer. Use under International 1 and 2 part varnishes and finishes. Apply up to 4 coats per day, reducing overall project time. Low viscosity, chemically cured 2-part product; penetrates deep into the wood. Fills the woodgrain, sealing the surface. Provides a perfectly smooth, impact, scratch and wear-resistant surface, ready for overcoating. Crystal clear polyurethane formulation. Increases scheme durability and improves final aesthetics.1:1 mix ratio. Easy to measure and mix.

Suitable Thinners: No. 10 Coverage: 11m2/L Substrates: Wood

10L 68615



Intertuf 203 (20 Litre Tins)

A one pack, tar free vinyl anticorrosive which can be used at temperatures down to -5°C (23°F). As an anticorrosive for both above and below the waterline and also as a sealer coat over Tributyltin (TBT) antifoulings. Suitable for use with controlled cathodic protection. For use at Newbuilding, Maintenance & Repair or On Board Maintenance.

Colour	Part No
Tinted	68617
Aluminium	68618
Black	68619



Intergard 269

A quick drying two pack epoxy holding primer / tie coat which is suitable for overcoating after extended periods of weathering.

Size	Part No
5 Litre	68601
20 Litre	68602



Interstores Primer

A hard wearing, surface tolerant, two pack epoxy primer/finish.

Size	Part No
5 Litre	68685
20 Litre	68686

X.International.





Micron 350

Micron 350 is a premium antifouling, offering outstanding 2-year protection in all conditions. A new formulation ensures truer colours, while self-polishing copolymer technology delivers consistent performance.

Suitable Thinners: No. 3

Coverage: 9m2/L

Substrates: GRP, Wood, Steel/Iron & Lead.

Colour	750ml	2.5L	5L	20L
Black	68000	68001	68002	68003
Navy	68004	68005	68006	68007
Blue	68008	68009	68010	-
Green	-	68012	-	-
Dark Grey	-	68013	-	-
Dover White	68014	68015	68016	-
Red	68017	68018	68019	68020



Ultra 300

Ultra 300 is our ultimate hard antifouling, providing 1 year protection ideal for powerboats or any streamlined yacht, even in the harshest fouling conditions.

Suitable Thinners: No. 3

Coverage: 9m²/L

Substrates: GRP, Wood, Steel/Iron & Lead

Colour	750ml	2.5L	5L
Black	68021	68022	68023
Navy	68024	68025	68026
Blue	68027	68028	-
Green	-	68029	-
Dark Grey	-	68030	-
Dover White	68031	68032	68033
Red	68034	68035	-



Cruiser 250

Cruiser 250 is a polishing antifouling providing quality year-long protection. Quick-drying and convenient, it can also help you get back on the water sooner.

Suitable Thinners: No. 3

Coverage: 9m²/L

Substrates: GRP, Wood, Steel/Iron & Lead.

Colour	750ml	3L
Dover White	68041	68042
Red	68043	68044
Blue	68045	68046
Navy	68047	68048
Black	68049	68050



Trilux 33

Slow polishing, avoids seasonal paint build up. For all substrates including aluminium; recommended for propellers and boottops. Effective fouling protection for up to 18 months.

Suitable Thinners: No. 3

Coverage: 10.5m² / L

Substrates: Aluminium, GRP/FRP, Lead, Steel, Wood, Carbon Fibre and Cast Iron.

Colour	5L
White	68750
Red	68752
Black	68756




Boatguard 100

Boatguard 100 is an effective low-cost antifouling, formulated to repel all kinds of fouling organism. It is quick and easy to apply, and provides comprehensive protection for a whole season.

Suitable Thinners: No. 3 Coverage: 9m²/L

Substrates: GRP, Wood, Steel/Iron and Lead.

Colour	2.5L
Dover White	68036
Red	68037
Blue	68038
Navy	68039
Black	68040



Cruiser 200

Cruiser 200 is a quality polishing antifouling that provides comprehensive protection for all substrates, including aluminium. Available in Bright White.

Suitable Thinners: No. 3

Coverage: 9.2m²/L

Substrates: Aluminium, GRP, Wood, Steel/Iron

and Lead.

Colour 2.5L 68051 Bright White

Paint: Antifoul



Uni-Pro 250 (Professional Use Only)

Uni-Pro 250 is designed specifically for professional use, providing quality fouling protection in almost all conditions.

Suitable Thinners: No. 3 Coverage: 8.3m²/L

Substrates: Aluminium, GRP/FRP, Lead, Steel, Wood, Carbon Fibre & Cast Iron.

Colour	5L	20L
Dover White	68052	-
Red	68053	68054
Blue	68055	-
Navy	68057	68058
Black	68059	-





Trilux Prop-O-Drev

Aerosol application for difficult to reach areas. For propellers, outboards and sterngear. For aluminium, stainless steel and alloy. Biolux® technology for sustained antifouling protection.

Suitable Thinners: No. 3

Coverage: 8.5m²/L

Substrates: Aluminium, Stainless Steel & Alloy

Part No	Colour
68540	Grey 500ml
68542	Black 500ml
68544	Red Propeller Primer 250ml (brush on)



VC Offshore EU

Suitable for salt and freshwater. A hard, smooth finish can be burnished to a very low profile. For racing, sailing and power boats.

Suitable Thinners: No. 3 Coverage: 11.76m²/L

Substrates: GRP/FRP, Lead, Steel, Wood, Carbon fire and Cast Iron.

Colour	750ml	2L
White	-	68442
Red	68443	68444
Blue	68445	68446
Black	-	68448



VC17m Extra

Extra strong thin film antifouling for racing sailboats and powerboats. With a fluoro micro additive for a low friction surface. Hard, smooth surface. Quick drying for fast re-launch.

Suitable Thinners: VC General

Coverage: 11m²/L

Substrates: GRP/FRP, Lead, Steel, Wood, Carbon fibre and Cast Iron.

Colour	750ml	2L
Graphite	68548	68549



Interspeed Professional Antifouling

TBT free, controlled depletion polymer (CDP) self polishing antifouling system.

Thinners: GTA007 (exceptional

circumstances)

Coverage: 3.7m²/L

Substrates:

Colour	20L
Red 6200	69080
Blue 6400	69083

Paint: Antifoul



Interthane 990

A two component, high gloss, polyurethane finish, Interthane 990 provides excellent durability and flexible application. With an over 20 years' global track record, Interthane 990 is a trusted solution providing extended recoat windows, long term protection and aesthetics retention in new construction and maintenance.

Size	Part No
5 Litre	69075
20 Litre	69076



Intergard 740

Intergard 740 is a two pack epoxy cosmetic finish and is particularly useful for areas that experience high abrasion or chemical exposure. Intergard 740 is used as a cosmetic finish in above water areas for newbuilding, maintenance & repair or on board maintenance projects. Intergard 740 is available in a wide range of colours from the Chromascan tinting system.

Size	Part No
5 Litre	69077
20 Litre	69078



Interlac 665

A one pack alkyd finish with good flow properties. Easy to apply with brush/roller or spray. For use as an easily maintained cosmetic finish coat above the waterline. Suitable for use as a bilge coating. Interlac 665 is stocked in a range of popular colours for fast delivery, or to special order in any RAL or BS Colour shade. Some International 'House' colours are available such as Oxford and Mauritius Blue. Please allow up to 3 days additional shipping time for custom colours. Fire resistance: - Surface spread of Flame (WFR) - (IMO Resolution A653 (16)).

Description	5 L	20 L
Interlac 665	69020	69021
Interlac Undercoat	69070	69071



Interior Finish 750 - 5 Litre

Use Interior Finish 750 on all interiors to create a tough, durable and opaque finish, that offers great chemical resistance. When used with Interior Primer 860, it holds a Surface Spread of Flame certificate.

Two-pack polyurethane high gloss finish that's easy to clean.

Specially formulated for interiors of all types of construction.

Reduced surface preparation requirements and fast walk on time speeds.

Part No	Colour
68696	5 Litre White (RAL9003)
68697	5 Litre White (RAL9010) MTO
68698	5 Litre Light Grey (RAL7035) MTO
68699	5 Litre Grey (RAL7038)



Interior Primer 860

Interior Primer 860: is a high build, multipurpose, low VOC epoxy primer, specifically formulated for use in the interiors of all types of construction. Reduced surface preparation requirements, fast walk on time and low odour speed the application process and lowers the impact on other trades. Interior Primer 860: provides excellent anticorrosive protection and holds a Surface Spread of Flame Certificate.

Part No	Colour
68700	5 Litre White (RAL9010)
68701	20 Litre White (RAL9010)
68702	5 Litre Grey (RAL7035)
68703	20 Litre Grey (RAL7035)

Paint:Primer



Super Gloss HS

Formulated using high solid resin technology, Super Gloss HS is a low VOC high gloss finish optimised for roller application, minimising the effort required to achieve an outstanding finish with great durability. Easy to apply even at low temperatures, this high solid formulation delivers full opacity in just 1-2 coats.

Thinner / Cleaner: No 1

Number of coats: 1-2 coats; opacity may vary depending on paint colour and colour of paint/substrate being over coated.

Practical Coverage 12m²/ L

Application method: Roller, Brush

750ml	Description	750ml	Description
68810	White 100	68820	Lighthouse Red 233
68812	Arctic White 248	68822	Thames Green 239
68814	Pearl White 253	68824	Ocean Blue 210
68816	Bahama Beige 243	68826	Atlantic Blue 269
68818	Whale Grey 201	68828	Black 190



Non-Slip Additive

For addition to Yacht enamel, Toplac or Perfection to provide a non-slip surface. Non-slip additive is effectively colourless when mixed into paint, so no change in shade should be observed.

20g

68340







NEW for 2022

Toplac Plus (New for 2022)

Toplac Plus is a silicone alkyd premium gloss yacht enamel for all substrates above the waterline. It is easy to apply by roller without the need for tipping. Toplac Plus contains UV filters for increased durability.

Suitable Thinners: No. 1 Coverage: 13.33m² / L

Substrates: Aluminium, GRP/FRP, Lead, Steel, Wood,

Carbon Fibre and Cast Iron.

Colour	750ml	Colour	750ml
Med White 545	68201	Platinum	68207
Med White 2.5ltr	68202	Bondi Blue 016	68240
Snow White 001	68219	Donegal Green 077	68242
Snow White 2.5 ltr	68220	Yellow 101	68243
Ivory 812	68222	Cream 027	68197
Bounty 350	68223	Fire Red 504	68199
Rochelle Red 011	68226	Rescue Orange 265	68200
Rustic Red 501	68228	Sapphire Blue 830	68203
Jet Black 051	68232	Oyster White 195	68210
Atlantic Grey 289	68234	Matterhorn White 199	68211
Oxford Blue 105	68245	Flag Blue 992	68212
Mauritius Blue 018	68236		
Lauderdale Blue 936	68238		

Perfection

A 2-pack high performance polyurethane topcoat, providing an extremely durable gloss that will last for up to 5 years. Use with perfection undercoat or UCP. 2.25 litre tins are available in the International Professional range.

Suitable Thinners. No. 9

Coverage: 9.3m²/L

Substrates: GRP/FRP, Lead, Steel, Wood & Cast Iron.

Colour	750ml	Colour	750ml
Platinum 183	68246	Mauritius Blue 991	68254
Med White 184	68247	Flag Blue 990	68255
Off White 192	68249	Fighting Lady Yellow	68256
Royal Blue 216	68250	Cream 070	68257
Snow White 750ml	68251	Jet Black 750ml	68259
Snow White 2.25 Litre	68646	Chilli Red 294	68260
Lauderdale Blue 936	68252	Rochelle Red 299	68258
Jade Mist Green 663	68253		

Paint: Antifoul



Interdeck

Slip resistant polyurethane deck paint. Contains a fine mineral additive for a hard wearing, non-slip surface. Low sheen finish prevents sunlight dazzle. Apply straight from the can with a brush or a roller.

Suitable Thinners. No. 1 Coverage: 10.8m² / L

Substrates: Aluminium, GRP/FRP, Steel & Wood

Colour	750ml
White 001	68330
Cream 027	68331
Grey 289	68332
Squall Blue 923	68337
Beige 090	68338



Thinner	500ml	1 L
Thinners No. 1 (single pack, general purpose)	68449	68450
Thinners No. 3 (antifoul & primocon)	68457	68451
Thinners No. 7 (two part epoxy paints)	-	68452
Thinners No. 9 (helps slow down two part polyurethane paints)	-	68453
Thinners No. 10 (910) (two part polyurethane paints)	-	68455
VC General Thinner	-	68550

Thinner	5 L	25 L
Thinner No. 1	68766	68767
Thinner No. 3	68769	68770
Thinner No. 7	68771	68772
Thinner No. 910 (fast)	1ltr	68455
Thinner No. 910 (fast)	5ltr	68773
Thinner No. 920 (slow spray)	5ltr	68774



Danboline

Hard wearing coating for bilges, lockers and bulkheads. Chemical resistance to fumes, fuel and oil. High opacity for thorough coverage. Cleans easily for reduced maintenance.

Suitable Thinners. No. 1

Coverage: 12.3m² / L

Substrates: Aluminium, GRP/FRP, Steel &

Wood

Colour	750ml	2.5 L
White	68420	68419
Grey	68422	68423





Matting Additives

Matting additives can be added to both International finishes and varnishes and ,depending on the mix ratio between the product and the additive, a variety of gloss, satin or matt effects can be achieved. International produces two types of matting additive, suitable for use with either the two-part or one-part products in the range.

Single Pack 750ml Two Pack 750ml 68342 68695





Thinner No. 100

This has been specially formulated for thinning Perfection® and Perfection Pro. Making it easier to apply the product using a brush at elevated temperatures.

1 Litre

68460

Thinner GTA713

Suitable for thinning paints and equipment cleaning from International Paints.

5 Litre	25 Litre
68778	68779

Paint: Varnish



Original Varnish

Traditional, general purpose gloss varnish. Good flow, flexibility and gloss retention. High clarity finish for light colour woods. Use on interior, exterior and over existing varnish.

Suitable Thinners: No. 1

Coverage: 13m²/L Substrates: Wood

375ml 750ml 2.5L 68355 68356 68357



Woodskin

This is a flexible wood oil/varnish hybrid that acts like a skin for your wood. Microporous properties allow woodskin to breath with your wood; tiny holes let the paint film expand and contract but are small enough to repel water the cause of mould and mildew. Woodskin is very easy to apply; no need to thin or sand between coats. With good flow and levelling, Woodskin dries to a subtle, translucent sheen. Woodskin penetrates deep into your wood, leaving a thin surface film that will not crack or flake. Minimal maintenance requirements - simply clean and reapply season after season. The Natural Teak colour of Woodskin will showcase the beauty of any wood. Woodskin is suitable for use on all types of wood, including oily woods such as teak and iroko.

Suitable Thinners: No. 1 Coverage: 10m2/L

750ml 68309



Schooner

Schooner is a traditional tung-oil based gloss yacht varnish for classic yachts, suitable for all internal and external wood. It contains UV filters to screen the sun's damaging rays for remarkable durability. Easy application. Deep, rich gloss. Warm golden colour. Excellent UV protection. For interior and exterior use. Schooner has excellent water resistance, silky application and superior self-levelling properties.

Suitable Thinners: No. 1 Coverage: 14m²/L Substrates: Wood

375ml	750ml	2.5L
68345	68346	68347



Perfection Plus Varnish

Ultimate performance, clear, two-part polyurethane varnish. Chemical cure for the hardest finish & highest abrasion resistance. Superior gloss lasts four times longer than conventional one-part varnishes.

Professional-quality results made easy. 2:1 mix ratio: Easy to measure and mix.

Suitable Thinners: No. 9

Coverage: 13.3m² / L

Substrates: Wood

750ml 2.5L 68366 68367



Compass Varnish

Tough, durable polyurethane finish; resistant to scratches and surface abrasion, oil, mild acid/alkali and alcohol spills. Fast-dry formulation; minimises dust contamination. Reduces work time: apply 2 coats per day, sanding only after every 2nd or 3rd coat. Contains HALS and UV absorbers; protecting your wood from sunlight degradation and increasing the lifespan of the coating. Superior flow and application characteristics ensure a smooth, professional finish. Light amber colour. Suitable for all internal and external woods; including oily timbers such as Teak and Iroko.

Suitable Thinners: No. 1 Coverage: 14.3m²/L Substrates: Wood

375ml 750ml 2.5 L 68351 68352 68353



Goldspar Satin Varnish

A satin finish polyurethane varnish for interior use. Resistant to hot water, mild acids and alkalis. Fast-dry formulation minimises dust contamination.

Suitable Thinners: No. 1 Coverage: 11.5m²/L Substrates: Wood

375ml	750ml	2.5 L
68360	68361	68359



Paint:Primer



Bonda Marine G4

G4 is a highly effective primer and sealer for wood, metal or concrete. It forms a non-porous plastic coating which is tough and flexible. It has excellent adhesion to most materials including GRP.

Part No	Item
64534	500g
64535	1 Kg
64536	2.5 Kg
64537	5 Kg
64538	G4 Thinners 1 Litre




Bonda Rust Primer

A resin based zinc anti-rust coating. It forms a tough skin with a bonded in anti-rust system for long term action. It has excellent adhesion to most metals and leaves a primed surface ready for coating with all types of paint.

Part No	Item
64555	250ml
64560	500ml
64565	1 Litre
64570	2.5 Litre

Loctite Rust Remedy



90ml	
60635	





Prymax Marine Primer Sealer

Prymax GRP Primer is used to obtain a strong waterproof bond onto wood, concrete and metal before applying a GRP laminate.

Coverage 200 grams per square metre

Part No	Description
64531	Prymax Marine Primer Sealer 1kg
64532	Prymax Marine Primer Sealer 2.5kg
64533	Prymax Marine Primer Sealer 5kg




Bonda Marine Wood Seal

Wood seal is formulated from high performance moisture curing resins to provide a non-porous seal with excellent non-yellowing properties. Wood Seal has good gloss retention and forms a tough, flexible coating which is resistant to oil and fuel.

500ml		
64575		







This is a durable, single component polyurethane sealer/ surface hardener which, when applied to soft or rotten woods, will cure to a hard and non-porous finish. Ideal when needing to screw into damp or rotting wood.

500ml		
64541		

Galvafroid

Zinc rich cold galvanising paint for rust protection on all ferrous metals. Prevents rust creep. Suitable for use as a primer or self finish. Mid grey matt finish.

Part No	Item
61103	400ml
61104	800ml

Owatrol Paint Conditioner & Rust Inhibitor

Improves finish, eases application and beats paint drag when added to any oil based paints, varnishes or stains. Reduces brush marks and improves coverage. Fortifies the paint - increasing penetration and adhesion.

A longer lasting finish that resists flaking and peeling. Combats rust by filling rust pores with oil.

Coverage (when used neat) 5 - 8m² per litre for wood and 8 -12m² per litre for rusted surface.

Overnight drying time for wood and 24 hours for metal.

Part No	Description
60591	500ml Owatrol Paint Conditioner & Rust Inhibitor
60592	1 L Owatrol Paint Conditioner & Rust Inhibitor





Paint:Primer







Deks Olje D1 is a saturating wood oil which feeds the wood to replace lost oils. It drives out any moisture and air present in the wood and fills the pores with oil.

Part No	Description
60594	Deks OLJE D1 Saturating Oil 1 L
60595	Deks OLJE D1 Saturating Oil 2.5 L

Deks Olje D2 is a gloss varnish-like, tough, flexible and durable finish that enhances the natural beauty of both interior and exterior wood. Before using Deks Olje D2, all wood surfaces should be treated and protected with Deks Olje D1 saturating wood oil.

Part No	Description
60596	Deks OLJE D2 Saturating Oil 1 L
60597	Deks OLJE D2 Saturating Oil 2.5 L





Bonda 15 Year White is a one component, high gloss, white coating for metal, wood, aluminium and G.R.P. Formulated from premium quality moisture cured polyurethane with light fast pigments 15 Year White has exceptional stability against U. V. light with outstanding non-yellowing and non-chalking qualities. The coating has a combination of hardness and flexibility plus toughness as well as abrasion resistance and resistance to most usual chemicals.

Part No	Description
64539	Bonda 15 Year White High Gloss 1 L

Rustins Advanced

Wood Preserver

Advanced Wood Preserver is a low odour, non-flammable product based on micro emulsion nanotechnology. The ultra-fine particle size allows deep penetration of the preserver to take place so the performance of the product is much greater than standard wood preservation products. It is quick drying and can be applied to wet or dry timbers. For use against wood rotting fungi within domestic, commercial, institutional and industrial premises.

5 L

61124

Paint:Primer





White Spirit

White Spirit is a highly refined solvent meeting the requirements of BS245. Suitable for general cleaning purposes, brush cleaning and paint thinning. It is more suitable for paint thinning than other solvents as it will not affect the drying time of oil based paints.

750ml	2 L
61505	61500



Methylated Spirit

Industrial alcohol for general purpose cleaning and thinning of some spirit based paints and French Polish/knotting products.

50	0	m
\circ	0	

63042



Pure Turpentine

It is generally used by artists and professional decorators for thinning oil based paints and varnishes.

500ml

61497



Cellulose Thinners

Thinners for cellulose based paint. Also use for cleaning brushes and removing unwanted spots of cellulose paint.

500ml

62999






Turpentine Substitute

A high quality turps substitute which is commonly used for thinning oil based paints and cleaning brushes, or as an organic solvent in other applications.

25 L

61495



A specially engineered marine product for use on all types of propellers and stern gear. Propshield Propeller (& Stern Gear) Antifouling Grease Is suitable for: Propellers, prop shafts, rudders, P brackets, trim tabs, outdrives, saildrives, outboards etc. Bronze, stainless steel, aluminium and painted surfaces (plus all other metals & Kiwi Props).

Part No	Description
90583	175g Tub
90584	375g Tub



Jotun Penguard HB Epoxy Primer

This is a two component, polyamide cured, high molecular weight epoxy coating. Designed as a high build, all purpose coating for new construction. Can be used as primer, mid coat, finish coat or as single coat system in atmospheric and immersed environments. Suitable for properly prepared carbon steel, stainless steel, aluminium, concrete, galvanised steel, shop primed steel and thermally sprayed zinc substrates.

5 Litre

67430



Seajet Pellerclean is a foul release propeller coating for propellers, stern gear and trim tabs. This foul release product is environmental friendly, biocide free and provides long term protection. Seajet Pellerclean is suitable for motorboats and sailing yachts up to 30 knots and is available in golden brown.

Includes primer, hardener, topcoat & 3 mixing sticks.

Maximum speed 30 knots

Coverage rate $0.7 \, m^2 / L$

Part No Description 90586 325ml Pack

Paint:Removal



Owatrol Marine Strip

Solvent free - Non-flammable - No toxic fumes - Is easily removed with water. Marine Strip is safe on all surfaces except aluminium. Does not harm plastic. Is safe on G.R.P. Very efficient - Will remove up to 8 coats of paint in one operation. Will not affect 2 component or baked-on paints, polyurethane paint and varnishes. Does not evaporate - Long active work time. Easy to apply Gel - With prolonged stripping action. Does not run.

Part No	Item
60590	1 L



Strypit Paint & Varnish Remover

Rustins new formula Strypit is a non-caustic dichloromethane-free gel suitable for removing multiple coats of paints and varnishes applied to wood, metal, glass, stone and masonry surfaces. Strypit works best when applied liberally and allowed to penetrate after two applications. The gel consistency permits effective use on vertical surfaces. Strips paint, varnish, polyurethane, emulsion, french polish & lacquer. For use on wood, metal, glass & plaster.

Item	Part No
1 Litre	64620
2.5 Litre	64621



Peelaway Marine Anti Fouling Remover

Peelaway Marine is specially formulated to safely remove multiple layers of anti-foul coatings with one application without damaging gel coat. Its patented poultice system allows the product to remain active and work without rapidly drying out. The special poultice blanket supplied also helps collect stripped paint and reduces boatyard contamination risk. Peelaway Marine is a light paste consistency and is easy to apply to vertical surfaces and difficult shapes. It can be applied with a brush or trowel and for larger areas, an airless sprayer can be used.

Suitable for most hull types including GRP, wood, metal & concrete. Always test a small inconspicuous area before applying generally.

Part No	Description
60580	4kg Peelaway
60585	10kg Peelaway



Hempels Paint Stripper - 2.5 L

Highly effective solvent based paint remover, making it easier to remove old paint and antifouling.

Part No

67051



Interstrip AF

A paint stripper especially formulated for removal of antifoulings. Interstrip AF is not aggressive and will not damage gelcoats.

1 L	2.5 L
68435	68436

Paint:Fillers



Interfill 830

A lightweight epoxy profiling fairing compound used for profiling above and below the waterline on steel, aluminium and composite. Interfill 830 is the premium choice of profiling fillers for professional applicators. High expectations and stringent industry requirements have made Interfill 830 one of the most popular fairing compounds in the world. Interfill 830 is available in both fast and standard cure applications.

Туре	5 L
Standard	68623
Fast	68621



Interfill 833

Interfill 833 is a technically advanced, easy sand Epoxy finishing fairing compound for use over Interfill 830 profiling filler, to correct minor surface defects before the application of finishing coats. The Interfill 833 is coloured green to contrast with the Interfill 830. This makes it easy to monitor film thickness and sand-through during the application procedure.

Туре	5 L
Standard	68624
Fast	68625



Pro Filler

ProFiller is a two-component, lightweight epoxy filler, featuring high adhesion and water resistance, When fully cured it is easy to sand. Can be applied in coats up to 10 -12mm for a uniform smooth finish.

JL
66576



Epifanes Combi Filler

mm film thickness

A traditional one-component knifing filler based on alkyd resins. Suitable for levelling of small irregularities in one-component paint systems for wood or steel above the waterline. Apply in thin layers only (max. 1 mm) Sandable: After 24 hours at 65°F./18°C. and 1

Part No	Description
69202	Epifanes Combi Filler Tube 225 Gram
69201	Epifanes Combi Filler Tin 800 Gram



A two component, solvent free, epoxy filler. Use for a variety of filling and fairing jobs both above and below the waterline. Can be applied in thick coats up to approximately 5mm thick without runs or sags. Fair before over coating with relevant primer.

Tool Cleaner: Hempel's Degreaser

130ml

Epoxy Filler

66450



Profair Epoxy Filler

A light weight two-component, epoxy filler, featuring high adhesion and water resistance, which when fully cured is easy to sand. Can be applied to a film thickness up to 25 mm without sagging. As a filler and fairing compound, especially suitable for profiling large areas and detailed fairing where structural strength and flexibility is required. It can be used on most primed rigid substrates, above and below the waterline.

750ml	
67381	



Watertite Epoxy Filler

Watertite is a quick drying epoxy filler which does not shrink and is extremely water resistant, making it suitable for osmosis damage repairs. Fill up to 20mm without sagging. Use above and below the waterline. High strength and adhesion properties. Simple 1:1 mixing ratio for easy measurement of components. Very fast drying. Super-smooth. Suitable Thinners: None Coverage: 0.2m² / ltr

Substrates: GRP, Metals & Wood

250ml 1 L 68406 68407



Primer Paint Brush

Our cheapest basic black bristle brushes. Sold individually or in boxes of 12.

Part No	Size	Box Size
60090	1/2" (12mm)	12
60100	3/4" (19mm)	12
60110	1" (25mm)	12
60120	1 1/2" (38mm)	12
60130	2" (51mm)	12
60140	2 1/2" (63m)	12
60150	3" (76mm)	12
60160	4" (102mm)	12



Laminator Paint Brush

Disposable brush for laminating epoxy and polyester resins. White bristle, plain wood handle. Sold individually or in boxes of 12.

Part No	Size	Box Size
60180	1/2" (12mm)	12
60185	1" (25mm)	12
60190	1 1/2" (38mm)	12
60195	2" (51mm)	12
60200	2 1/2" (63m)	12
60205	3" (76mm)	12
60210	4" (102mm)	12



Topsider Paint Brush

Good quality brush for all finishing work at a reasonable price. Sold individually or in various box sizes.

Part No	Size	Box Size
60010	1/2" (12mm)	24
60020	3/4" (19mm)	24
60030	1" (25mm)	24
60040	1 1/2" (38mm)	18
60050	2" (51mm)	18
60060	2 1/2" (63m)	12
60070	3" (76mm)	12
60080	4" (102mm)	12



Anza Basic Brushes

Basic is a good choice when finish is not of utmost importance. Flat brushes are suitable for painting doors and woodwork. The brushes have synthetic filament heads and basic soft grip handles. Suitable for all paints. Sold individually or in boxes of 10.

Part No	Size	Box Size
61970	35mm	10
61975	50mm	10
61980	70mm	10



Anza Elite Brushes

Elite is a very good choice for the DIY painter who wants to achieve a really good result. Flat brushes are suitable for painting doors and woodwork. The brushes have very high paint pick-up and give great coverage. The synthetic filament heads are of very high quality, developed for all indoor and outdoor paints (both water-based and oil-based). It gives a very good finish and a very good end result.

Part No	Size	Box Size
61930	35mm	10
61935	50mm	10
61940	70mm	10
61945	100mm	10

Hamilton Performance Brush

Sold individually or in boxes of 10.



Anza Platinum Brushes

Platinum is quite simply our best choice, designed for users who demand the highest quality. Flat brushes are suitable for painting doors and woodwork. The brushes are extremely durable and have very high paint pick-up and give excellent coverage, which ultimately means that you save time. The synthetic filament heads are of the highest quality, developed for all indoor and outdoor paints (both water-based and oil-based). It is also developed for precision painting and gives a superior finish and a perfect end result without leaving any marks. Sold individually or in boxes of 10.

Part No	Size	Box Size
61904	25mm	10
61905	35mm	10
61910	50mm	10
61915	70mm	10



HAMILTON®



Natural bristle and synthetic filament blend with good paint pick-up and spreading rates. Sold individually or in various box sizes.

Part No	Size	Box Size
60376	1" (25mm)	12
60377	1 1/2" (38mm)	12
60378	2" (51mm)	12
60379	3" (76mm)	6



Jenny Brushes

These brushes are ideal for applying and laying off high gloss finishes such as enamel or varnish. The finish achieved with these brushes is first class. A foam brush is probably not the ideal brush for applying heavy bodied primers when you may need the stiffness of a good quality bristle brush to manoeuvre and work the paint. Sold individually or in various box sizes.

Part No	Size	Box Size
60215	25mm	48
60216	50mm	48
60217	75mm	36
60218	100mm	24



Hamilton Prestige Pure Synthetic Laying Off Brush

For a great finish when laying off. Thin brush with finely-tipped synthetic filaments designed for finishing not for application. High quality tipped synthetic filaments. Wet the tips and pull through the paint for a flat finish. Easy clean. Sold individually or boxes of 3.

Part No	Size
60380	4" (100mm)



Radiator Brushes

Long handled brush for reaching awkward areas such as bilges. White bristle and plastic handle. Sold individually or in boxes of 10.

Part No	Size	Box Size
60162	1" (25mm)	10
60163	1 1/2" (38mm)	10
60164	2" (51mm)	10



Rota Concave Superfine Foam Roller Refill - 120mm x 35mm

Superfine Foam roller sleeves are suitable for gloss, primers, varnishes and all oil and solvent based paints. For use on smooth or slightly textured surfaces. Sold individually or in boxes of 10.

Part No	
60006	



Felt roller suitable for woodwork, doors and kitchen fittings. Also suitable for marine coatings and other two-component paints. Gives a smooth finish. Fits short and long frames. Sold individually or in boxes of 10.

Part No	Size	Width
62025	Mini	10cm
62030	Mini	15cm



Hamilton Perfection Brushes

Top of the range. High quality brush with natural bristles. Sold individually or in various box sizes.

Straight	Oval	Size	Box Size
Part No	Part No		
60234	-	3/4" (19mm)	6
60235	-	1" (25mm)	6
60236	-	1 1/2" (38mm)	6
60237	60362	2" (51mm)	6
60238	-	2 1/2" (63m)	3
60239	-	3" (76mm)	3



Fluffy General Purpose Roller

A general purpose fluffy roller which fits most frames.

Sold individually or in boxes of 10.

Part No

60005



Foam Roller

A foam roller for topcoat application which fits most frames.

Sold individually or in boxes of 10.

Part No 60003



Epoxy Roller

A foam roller designed for use with epoxy / two-pack products which fits most frames.

Sold individually or in boxes of 10.

Part No 60004



Prestige Felt Mini Roller

4" Wide

Felt fabric for evenness of coating and reduced fibre loss.

Part No

60383



Perfection Short Pile Midi Roller

4" Wide

Excellent paint pick up and finish.

Part No

60382



Prestige Medium Pile Roller

4" Wide

Felt fabric for evenness of coating and reduced fibre loss.

Part No

60384



Performance Foam Mini Roller

4" Wide

High density foam ensures no fibre loss and smooth finish.

Part No

60385



Mini Frame Short

Fits all 4" standard roller heads.

Part No

62065



Performance Short Pile Roller

9" Wide

1 3/4" Core

High density knitted fabric for fast, even coverage.

Part No

60394



Prestige Medium Pile Roller

9" Wide

1 3/4" Core

Continuous fibre fabric for reduced fibre loss and fast, even coverage.


Part No

60395



Roller Frame 9" x 1 3/4"

60007





Anza Felt Midi Rollers

Felt roller suitable for woodwork, doors and kitchen fittings. Also suitable for marine coatings and other two-component paints. Gives a smooth finish.

Fits short & long frames

Part No	Size	Width
62020	Midi	15cm



Anza Plastic Foam Rollers

Foam roller suitable for woodwork, doors and kitchen fittings. Gives a smooth finish. Note! Soft; must not be used with thinners or acetone.

Fits Short & Long frames

Part No	Size	Width
62045	Mini	10cm
62050	Mini	15cm



Anza Felt Rollers

Felt roller suitable for woodwork, doors and kitchen fittings. Also suitable for marine coatings and other two-component paints. Gives a smooth finish.

Fits Anza 18cm frame

Part No	Size	Width
62015	Maxi	18cm



Complete Mini Frame Long

Long handled frame (55cm approx.) complete with general purpose fluffy roller.

Part No

60000



Anza Mini Frame Short

Easy-grip twocomponent handle. Fits Anza extension poles. Frame length 23 cm.

Part No

62066



Anza 18cm x 1 1/2" Roller Frame

For use with Anza maxi felt rollers and Hamilton rollers.

Part No

62055



West Foam Roller Frames

Roller frames to fit West foam rollers.

Part No Size

64329 3" X 1 1/2"



Microfibre Cloths

Pack of 10. Colours may vary. 40 x 40cm

Part No

60360





West Foam Rollers

Foam rollers specifically designed for use with epoxy products.

Part No Size 64334 3" X 1 1/2" 64331 7" X 1 3/4"

10kg Bag of White Rags

Part No

60291

Mixture of rags for cleaning.



Paint Pads

Suitable for applying all coatings, especially top coat finishes.

Part No Item 62095 pad & handle 85 X 85mm 62100 pad & handle 170 X 85mm



30cm Mixing Stick

S-shaped polypropylene paint stirrer. The s-shape make the mixing stick sturdier. Corrosion -resistant to both paint and thinner.

Part No Size 67941 30cm



Mutton Cloth

(Stockinette)

High quality cotton stockinette cloth for general cleaning and polishing tasks.

400gm

60298



Tack Cloths

Cloths for wiping down surfaces prior to painting to ensure a smooth finish. They are slightly tacky and will pick up and hold dust, dirt and sanding residue.

Sold singly or in packs of 10.

Part No

60297

Prep - Heavy Duty Trade Wipes

Safe Guard wipes are tough, fast, safe and convenient wipes designed to remove a wide range of soils such as paint, silicones, mastics, inks, adhesives, oils, greases and general dirt. They are ideal for cleaning the hands, work tools and hard surfaces.

Part No Description

60292 **Heavy Duty Trade Wipes**

(Tub of 80)







Anza Roller Trays

Quality paint trays for use with 18cm rollers. Disposable plastic liners are available.

Part no	Item
62080	Tray for 18cm rollers
62090	Pack of 2 Liners for 18cm





Black Roller Trays

Very sturdy black roller trays available in 3 sizes.

Part No	Tray Size
64337	4" Wide
64336	7" Wide
64338	9" Wide





Enables painting with more manageable quantities. Comes complete with a lid to prevent spillages and enable paint to be kept fresh overnight.

|--|

67963 1 Litre Plastic Paint Kettle and Lid 67964 2.5 Litre Plastic Paint Kettle and Lid



Paint Kettle

Zinc plated. 7" diameter, 3 1/2" deep.

Part No 60299





Paint Strainer/Filter

125 Micron - for sensitive top coats

260 Micron - for solvent top coats

Part No	Description
60317	260 Microns Medium Mesh Orange
60318	125 Microns Fine Mesh Blue



Anza 2 Handed Wire Brush

Two-handed wire brush with extended, curved profile head, for optimal use. Includes ergonomic soft-grip handle.

Part No	Description
62182	Anza 2 Handed Wire Brush
00_	7 11.24 2 1 14.1140 4 11.110 2 14.011
62183	Anza Extension Pole 44-61cm



Pack of 3 Abrasive Brushes

An assorted abrasive brush set. Nylon, brass and wire filing. Suitable for a multitude of cleaning jobs

Part No	Description
60293	Pack of 3



4 Row Wire Brushes

Steel: for removing rust or scale and generally preparing rough exterior surfaces prior to paint-

Brass: for cleaning carvings, mouldings or stone.

Part No	Description
60295	Steel 4 Row Wire Brush
60294	Brass 4 Row Wire

HAMILTON®



Anza Precision Scraper

Ergonomic soft-grip handle. Supplied with a tungsten carbide blade fitted and three blades in the cartridge.

Replacement blades sold separately in a combination pack with 1 pear and 2 triangular shaped blades.

Part No	Description
60390	Scraper, Blades and Holdall
60391	Spare Blades (Pack of 3)



Prestige Heavy Duty Scraper

Reversible tungsten carbide blade that stays sharp and productive up to 100 times longer than conventional blades.

Handle shaped to do the job more efficiently and with ease.

Almost identical to the popular Sandvik scraper.

Part No	Description
60392	Scraper
60393	Spare Blade





Anza Scrapers

High quality scrapers with replaceable blades.

Part No	Item
62140	Scraper 30mm
62145	Scraper 50mm
62150	Scraper 65mm
62160	2 blades 30mm
62165	2 blades 50mm
62170	2 blades 65mm
62155	Tungsten Scraper 50mm
62175	Tungsten Blade 50mm



Flat Scrapers

Used for scraping surfaces or spreading material such as plaster in various construction trades. Soft grip ergonomic handle with a hole for hanging.

3" (75mm)	4" (100mm)
60240	60250



Combination Scraper

Used for stripping paint from flat and curved surfaces. Soft grip ergonomic handle with a hole for hanging.

Part No		
60260		



Triangular Scraper

Used for removing paint and other coatings from awkward areas.

Part No	
60270	



Loctite 577

This thread Sealant is designed for the locking and sealing of metal pipes and fittings as well as other threaded assemblies. The product provides an instant, low-pressure seal for metal pipes and fittings. It will not creep, shrink or shred. It has excellent chemical and thermal resistance and offers less migration of liquid product after application.

Part No Description

60644 50ml Thread Sealant





Loctite Hydraulic Seal 542

Medium viscosity

For sealing threaded hydraulic and pneumatic parts. Will not clog valves or fine filters and has a thixotropic quality which prevents migration of the sealant. Impervious to all common hydraulic fluids including fire-resistant synthetics. Resistant to Hydraulic Fluids including Synthetics

-55 /+150 °C

Part No	Description
60646	50ml Thread Sealant
60649	10ml Thread Sealant





Loctite High Strength 2701

LOCTITE® 2701 is a green, low viscosity, methacrylate-based threadlocking adhesive with high strength, especially for chromated surfaces. Steel fixture time of 10 min, brass 4 min and stainless steel 25 min. Tolerates slight contaminations of industrial oils. Suitable for all metal fasteners. Fluoresces under UV light.

Part No	Description
60647	50ml Thread Sealant
60648	10ml Thread Sealant



PTFE Tape

Thread sealing tape for pipe connection and general on board plumbing. 12mm X 12m

Part No	Colour
93135	White



Leak Stop

For emergency or permanent repair, Leak Stop will repair a pipe leak in under thirty minutes and contain pressure up to 20 bar and temperatures up to 500°F. Quick and easy to use on virtually any material, it is also suitable as corrosion protection and electrical insulation to 16,000 volts.

Part No	Size
93002	50mm x 1.5m
93003	75mm x 2.7m



Silicone Tape

Our Self Fusing Silicone tape provides a reliable solution to leaks in water or exhaust pipes and a multitude of containing and sealing applications. Effective between -50°C and +260°C, it can also insulate to 8000v per upstretched layer. The tensile strength has been tested in excess of 700psi and will effectively seal leaks up to 85Psi (6 bar). It also has good resistance to mild acids, fuels, oils, solvents, salt water, ozone, UV light, and flames. Available Colours: White, Black & Blue

Sizes: 25mm x 3m Roll

Part No	Colour
93401	White
93402	Black
93403	Blue



Clear PVC Hose.

A clear, highly versatile, flexible unreinforced PVC hose

Temperature range: -20°C +55°C

Sold by the metre.

Part No	Hose ID	
90247	3/16" (5mm)	
90248	1/4" (6mm)	
90252	5/16" (8mm)	
90249	3/8" (10mm)	
90251	1/2" (12mm)	



Clear Braided PVC Hose

A soft, flexible PVC hose with polyester yarn reinforcement. Temperature range: 5°C +60°C

Sold by the metre.

Part No	Hose ID
90350	1/4" (6mm)
90360	5/16" (8mm)
90370	3/8" (10mm)
90250	1/2" (12mm)
90260	3/4" (19mm)
90270	1" (25mm)
90280	1 1/4" (32mm)
90290	1 1/2" (38mm)



GREAT VALUE!

Drinking Water Non Toxic

Galvanized steel wire re-enforced clear drinking water hose. For use for suction or delivery of drinking water.

Sold by the metre

Sold by the metre.		
Part No	Hose ID	
89901	13mm	
89902	16mm	
89903	19mm	
89904	25mm	
89907	38mm	
89909	51mm	



Drinking Water Hose DWHOSE

This hose is made of transparent PVC with spiral inlay and is suitable for transportation of drinking water and grey water on board, both suction and pressure.

Temperature proof between -5 and + 65°C

Sold by the metre.

Part No	Hose ID	Max Pressure Bar
56346	10mm	7
56347	12mm	7
56348	16mm	6
56349	20mm	5
56350	25mm	5
56358	28mm	4.5
56352	32mm	4.5
56354	38mm	4
56356	45mm	3
56357	50mm	3



Flexi Bilge Hose

General purpose hose with a white spiral helix embedded in a translucent green super-elastic, flexible PVC. Lightweight, flexible, smooth bore.

Temperature range: -20°C +55°C

Sold by the metre.

Part No	Hose	ID
90210	3/4"	(19mm)
90220	1"	(25mm)
90221	1 1/8"	(28mm) Black
90230	1 1/4"	(32mm)
90240	1 1/2"	(38mm)
90246	2"	(51mm)



Odour Free Waste Hose

Waste hose made from a special formulation of PVC compounds which provide good resistance to odour permeability.

Sold by the metre.

Part I	No F	Hose	ID
9037	5 3	3/4"	(19mm)
9037	6 1	"	(25mm)
9037	8 1	1/2"	(38mm)



Sanitation Rubber Hose

SAHOSE

These hoses are made of SBR rubber with inlays of woven synthetic fabric and stainless steel spiral. Recommended especially for transportation of biological waste from (marine) toilets.

Sold by the metre.

Part No	Hose ID	Max Pressure Bar
56377	16mm	3
56378	19mm	3
56379	25mm	3
56380	38mm	3



GREAT VALUE!

Car Heater Hot Water Hose

Black hot water hose for transporting hot water between -45°C to +120°C. Made from black heat resistant and ozone resistant EDPM rubber. SAE J20 R3.

Sold by the metre.

Part No	Hose ID
89923	13mm
89924	16mm



Calorifier Hose

Type HWHOSE is made of EPDM rubber with an inlay of woven synthetic fabric. Suitable for drinking water and is temperature resistant between -30° and +160°C.

Sold by the metre.

Part No	Hose ID	Max Pressure Bar
56384	13mm	8
56385	16mm	8



GREAT VALUE!

Lloyds Approved Exhaust Hose

Exhaust hose which has rubber lined walls with a galvanized steel reinforcing throughout.

Sold by the metre.

Part No	Hose ID
89922	19mm
89910	25mm
89911	32mm
89912	38mm
89913	45mm
89914	52mm
89918	76mm
89920	102mm



Rubber Exhaust Hose SLANG

Temperature resistant between -30° + 100°C with brief temperatures of 115°C.

Sold by the metre

Part No	Hose ID	Part No	Hose ID
56412	30mm	56419	76mm
56413	40mm	56420	90mm
56414	45mm	56421	102mm
56415	51mm	56422	110mm
56416	57mm	56423	125mm
56417	60mm		
56418	65mm		



SLANG

Type SLANG exhaust hose is the most flexible hose because of the increased spiral reinforcement and the extremely supple rubber. The completely smooth inside of the hose will reduce back pressure in the engine. Exhaust hoses with an internal diameter up to Ø152mm have a bending radius of more than 1.5 X the diameter. Exhaust hoses with an internal diameter of more than Ø152mm have a bending radius of twice the diameter.

30 - 50 = 4 Bar Max Pressure

57 - 75 = 3.3 Bar Max Pressure

90 - 203 = 2 Bar Max Pressure

Type SLANG is Lloyd's Registered and meets the requirements of the SAE J2006 R2 standard.



Cooling Water Hose

MWHOSE

Type MWHOSE is made of EPDM rubber with synthetic fabric and spiralled stainless steel reinforcement. Suitable for cooling water, both suction and pressure (max. 2,5 bar), salt and fresh water.

Temperature resistant between -30° and +120°C.

Sold by the metre

Part No	Hose ID	Max Pressure Bar
56388	19mm	2.5
56389	25mm	2.5
56390	32mm	2.5
56391	38mm	2.5
56392	51mm	2.5



Fuel Hose

For transportation of petrol and diesel fuels. The inside is made of NBR rubber and the outside of CR rubber. Can be used for transportation and as ventilation line. Particularly suitable for use of petrol because of low permeability.

Type FUHOSEA meets the CE standard: ISO 7840 marine fuel A1

Sold by the metre.

Part No	Hose ID	Max Pressure Bar
56360	6mm	10
56361	8mm	10
56362	10mm	10
56363	13mm	10
56364	16mm	10
56365	19mm	10
56366	25mm	10



GREAT VALUE!

Marine Grade Fuel Hose

ISO7840 Black NBR rubber fuel hose. abrasion, ozone and weather resistant. Neoprene rubber which is resistant to flame. -35°C to +100°C.

Sold by the metre.

•		
Part No	Hose ID	Max Pressure Bar
89925	6mm	10
89926	8mm	10
89927	10mm	10
89928	13mm	10
89929	16mm	10
89930	19mm	10
89931	25mm	10
89932	38mm	10

All Hoses are sold by the metre.



Fuel Filling Hose

FFHOSE

Type FFHOSE is made of NBR rubber with spiralled stainless steel inlay. Suitable for petrol and diesel fuels. Resistant to temperatures of -30° and +100°C.

Type FFHOSE meets requirements of SAE J 1527 and the standard ISO 7840 marine fuel A2.

Sold by the metre.

Part No	Hose ID	Max Pressure Bar
56395	38mm	4
56396	51mm	4



Gas Hose		
HP BS3212/2		
Sold by the metre.		

Part No	Hose I.D.
11505	8mm
11506	10mm



Fuel Delivery Hose

This hose is suitable for the medium duty suction and discharge of black fuel oils, gas oils, Kerosene, paraffin, hydraulic oils, mineral based oils, lubricating oils and greases. It is not suitable for benzene, xylol and aromatic solvents.

Sold by the metre.

Part No	Hose ID		
90298	1"	(25mm)	
90300	1 1/2"	(38mm)	
90310	2"	(51mm)	



Copper Tube

- · Annealed soft copper tubing .
- · Manufactured to BS EN 12735-1:2001

Available in 10m coils only.

Part No	OD X Length		
11501	1/4" X 10m		
11502	5/16" X 10m		
11503	3/8" X 10m		



Silicone Hose - ISO13363 type Class B and SAE J 2006 R1 standards.

SIHOSE

Extremely high temperature resistant hose made of high grade silicone rubber with woven synthetic and an encapsulated stainless steel spiral with an external smooth gloss finish. The flexible hose is highly resistant to ageing and suitable for a wide range of applications (exhaust, cooling and waste water

Temperature range of -54° to 177°C. (intermittently up to 250°C.

Sold by the metre.

Part No	Hose ID	Max Pressure Bar
56430	25mm	5.0
56431	32mm	4.5
56432	38mm	4.0
56433	51mm	4.0
56434	63mm	3.5
56435	76mm	3.5
56436	102mm	2.0



Ventilator Hose BLHOSE

Type BLHOSE is made of a woven glass fibre fabric, impregnated with PVC.

Temperature resistant between -20° and +100°C.

Dart Na Cina

Part No	Size
56399	75mm x 10m
56400	103mm x 10m



Ducting Blower Hose

This hose is commonly used for engine room ventilation.

Part No	Size
89940	75mm x 6m
89941	102mm x 6m



Flexible suction/pressure hose


VHOSE	
Part No	Size
56401	152mm
56402	178mm







Extractors, ventilators and bilge blowers can be found on page 113.





Mikalor Stainless steel heavy duty hose clamps

The Supra W4 clamp complies fully with the RoHs directive EU 20032/95/EC dated 1st July 2006. The stainless steel bolt together with the captive nut and spacer system allow you to clamp the most demanding of hose assemblies. Supra W4 is a full stainless steel clamp, destined for demanding applications where high corrosion resistance is vital. This top of the range heavy-duty clamp is ideal for marine applications and the foodstuffs industry, as well as for countless industrial applications where AISI-304 stainless steel is specified.

Stainless Steel Heavy Duty Hose Clamps HCHDS									
Part No	Size	Part No	Size	Part No	Size	Part No	Size	Part No	Size
56618	34-37mm	56624	55-59mm	56630	85-91mm	56636	121-130mm	56642	200-213mm
56619	37-40mm	56625	59-63mm	56631	91-97mm	56637	140-150mm	56643	213-226mm
56620	40-43mm	56626	63-68mm	56632	97-104mm	56638	150-162mm	56644	263 -276mm
56621	43-47mm	56627	68-73mm	56633	104-112mm	56639	162-174mm	56645	316-329mm
56622	47-51mm	56628	73-79mm	56634	130-140mm	56640	174- 187mm		
56623	51-55mm	56629	79-85mm	56635	112-121mm	56641	187-200mm		



JCS Hi-Torque Hose Clips

Available in 304 stainless steel, Hi-Torque hose clamps are specifically designed for use with tough, wire reinforced hoses that require higher sealing pressures, and for when an extra margin of safety and reliability is required.

TYPE HTM - STAINLESS STEEL 304 All parts BS304 - EN 1.4301/1.4576



Part No	Size
90200	30mm
90201	45mm
90202	50mm
90203	65mm

Part No	Size
90204	70mm
90205	90mm
90206	115mm

JCS Hi-Grip general purpose worm drive hose clips are widely regarded for their quality, durability and ability to withstand a great deal of abuse. They are manufactured to exceed BS5315, which has the highest requirements of any of the international standards and tests sealing ability, clamping force and torque. Also has BSI Kitemark and NATO approval, and exceeds all operational requirements of the relevant DIN and SAE standards. 304 STAINLESS STEEL (A2) Hi-Grip stainless steel worm drive hose clips have become the industry standard for demanding applications throughout the world due to their exceptional quality and performance. Made entirely from 18/8 marine quality stainless steel and with Lloyds Register Approval, they are ideal for salt water and other corrosive environments.



Size	To Fit Hose OD (mm)	Part No
12	9.5 - 12	90000
16	11 - 16	90010
20	13 - 20	90020
22	14 - 22	90030
25	17 - 25	90040
30	22 - 30	90050
35	25 - 35	90060
40	30 - 40	90070

Size To Fit Pa Hose OD (mm)	art No
45 35 - 45 90	080
50 35 - 50 90	0090
55 40 - 55 90	100
60 45 - 60 90	110
70 55 - 70 90	120
80 60 - 80 90	130
90 70 - 90 90	140
100 80 - 100 90	150



JCS Hose clips discount = 20% below 10 / 50% over 10 (10 in a box)

Flexible Drive Screwdriver

Screw driver with a hexagon socket head specifically designed to fit JCS hose clips. This tool has a flexible shaft to aid access to awkwardly positioned hose clips.

Part No	Description
90155	Flexible Drive Screwdriver



JCS Multi-Torque 1m Coil

By simply cutting off the required length from a continuous banding roll and engaging one end of the band into each housing of the MULTI-TORQUE connector a hose clamp is made. This kit contains one connector and a 1m coil.

Part No

90151

JCS P Clip Stainless Hose Clips

P-Clips For Pipes, Cables And Hoses

JCS rubber-lined P-Clips are tough and durable, providing a simple and secure fixing solution for even the most challenging of environments. Available in two accurately sized ranges for 6mm and 10mm bolts in both Zinc plated Mild Steel and 304 Stainless Steel. TPE liners are available for both standard and high temperature applications. The standard P clip is supplied with a TPE rubber liner which prevents chafing or damage to the surface of the item being clamped.



To Fit Hose OD (mm)	Part No	To Fit Hose OD (mm)	Part No
5	90178	16	90185
6	90179	19	90186
8	90180	21	90187
9	90181	22	90188
10	90182	25	90189
12	90183	28	90190
13	90184	29	90191

Part No
90192
90193
90194
90195
90196



Nylon Fixing Clips 1001 uses on the boat, the caravan or in the home.


Part No	To Fit Hose OD
90170	1/2" (12mm)
90171	5/8" (16mm)
90172	3/4" (19mm)
90173	1" (25mm)
90174	1 1/4" (32mm)
90175	1 1/2" (38mm)



Strong White Tube Clip Spring clips, suitable for holding poles, oars, boat awnings, boat hooks, fishing rods, etc

Part No	Description
96321	16/18mm
96322	19/20mm
96323	22/24mm
96324	25/26mm
96325	28/30mm





Nylon P clips for fixing cables, conduits et			nduits etc.
Part No	A (height)	B (hole size)	C (width)
70740	3.2mm	5.2mm	13.2mm
70741	4.5mm	5.2mm	9.7mm
70742	6.3mm	5.2mm	9.7mm
70743	7.6mm	4.8mm	9.7mm
70744	9.3mm	4.8mm	9.7mm
70745	12.6mm	5.2mm	12.8mm
70755	15.8mm	4.6mm	12.0mm
70756	19mm	5.3mm	12.0mm
70757	25.4mm	4.6mm	12.0mm
70758	28.6mm	4.6mm	12.7mm



Black Cable Ties Manufactured in nylon MIL standard specification M20693B. Tensile strength to MIL standard specification S23190E and flammability to UL94V2

Sold each or in bags of 100

	·	
Part No	Width	Length
69550	2.5mm	80mm
69551	2.5mm	100mm
69552	3.6mm	140mm
69553	3.6mm	200mm
69554	3.6mm	300mm
69555	4.8mm	120mm
69556	4.8mm	160mm
69557	4.8mm	200mm
69558	4.8mm	300mm
69559	4.8mm	370mm
69560	7.6mm	200mm
69561	7.6mm	300mm
69562	7.6mm	368mm
69563	9mm	430mm
69564	9mm	526mm
69565	9mm	780mm



Cable Tie Fixing

2 way and 4 way cable tie mounts with a self adhesive base. Alternatively the mount can be fixed by using a self tapping screw (not inc) through the hole in the centre.

Sold Each or in bags of 100

Part No	Maximum Cable Tie Size (mm)		Fixing Hole Size (mm)
69570	4.8mm	19.0 x 19.0mm	3.5mm
69571	4.8mm	28.0 x 28.0mm	5.7mm



Cable Tie Cradle

Cable tie cradle suitable for the larger ties. The cradle is fixed to a firm surface using a self tapping screw (not inc)

Sold Each or in bags of 100

Part	Maximum	Base Size	Fixing
No	Cable Tie	(mm)	Hole
	Size (mm)		Size
			(mm)
69572	9.0mm	21.9 x 15.9mm	5.0mm



Cable Tie Eyelet

Cable tie eyelet suitable for fixing cable ties securely to a firm surface. This can be fixed using a self tapping screw (not inc).

Sold Each or in bags of 100

Part	Maximum Cable Tie	Base Size	Fixing Hole
No	Size (mm)	(mm)	Size (mm)
69573	5.0mm	20.0 x 10.0mm	4.3mm



Bronze Skin Fitting



Part No	BSP	Part No	BSP
10835	1/2"	10839	1 1/2"
10836	3/4"	10840	2"
10837	1"	10801	2 1/2"
10838	1 1/4"	10841	3"

10842 **Bronze Deck Drain**

BSP

1/2"

3/4"

1"

1 1/4"

Part No

10861

10862

10863

10864

4"

BSP

1 1/2"

2"

3"

4"



Bronze Skin Fitting & Hose Tails



Bsp	thread	х	hose	tail	size
DOD	uncau	$^{\prime}$	11030	tan	0120

	Bop imoda x	nooo tan o	.20
Part No	BSP	Part No	BSP
10843	1/2" X 3/4"	10847	1 1/2" X 1 3/4"
10844	3/4" X 7/8"	10848	2" 2 1/4"
10845	1" X 1 1/4"	10849	3"
10846	1 1/4" X 1/12"	10850	4"

Bronze Scoop Strainer



Part No	BSP	Part No	BSP
10851	1/2"	10854	1 1/4"
10852	3/4"	10855	1 1/2"
10853	1"	10856	2"

Bronze Long Skin Fitting



Part No	BSP	Thread Length
10857	3/4"	120mm
10858	1"	120mm
10859	1 1/4"	120mm
10860	1 1/2"	120mm

Bronze Skin Fitting + anti rotation nib



Part No	BSP	Thread Length
10000	1/2"	2" (51mm)
10010	3/4"	2 1/2" (64mm)
10020	1"	2 3/4" (70mm)
10030	1 1/4"	3" (76mm)
10040	1 1/2"	3" (76mm)
10041	2"	3 1/2" (89mm)

Bronze Ball Valve & Stainless Steel Handle

Part No

10865

10866

10867

10868



Part No	BSP
10976	1/4"
10977	3/8"
10978	1/2"
10979	3/4"
10980	1"
10981	1 1/4"
10982	1 1/2"
10983	2"
10802	2 1/2"
10984	3"
10985	4"

Full Bronze Ball Valve, Bronze Handle + Acetal Ball



Part No	BSP
10060	1/2"
10061	3/4"
10062	1"
10063	1 1/4"
10064	1 1/2"
10065	2"

Full Bronze Flange Ball Valve, **Bronze Handle + Acetal Ball**



Part No	BSP
10042	1/2"
10043	3/4"
10044	1"
10045	1 1/4"
10046	1 1/2"
10047	2"

The brand new Full Bronze Ball Valve is available in sizes from ½" to 2" BSP and features a polymer ball. All other components that are in contact with saltwater are made from Bronze (body, coupling, stem and gland). The handle can be repositioned to invert the direction of movement, solving installation issues. The valve will also be available with position sensors and flange mounting.

Full Bronze Ball Valve, Bronze Handle + Acetal Ball + Position Sensor

Full Bronze Flange Ball Valve, Bronze Handle + Acetal Ball + Position Sensor

CR Brass Ball Valve & Stainless Steel Handle



Part No	BSP
10081	3/4"
10082	1"
10083	1 1/4"
10084	1 1/2"
10085	2"



Part No	BSP
10071	3/4"
10072	1"
10073	1 1/4"
10074	1 1/2"
10075	2"



Part No	BSP
10770	3/8"
10771	1/2"
10772	3/4"
10773	1"
10774	1 1/4"
10775	1 1/2"
10776	2"

ISIS DZR Ball Valve & **Steel Handle (Hattersley Type)**



Part No	BSP
10581	1/4"
10582	3/8"
10583	1/2"
10584	3/4"
10585	1"
10586	1 1/4"
10587	1 1/2"
10588	2"

Bronze Gate Valve



Part No	BSP
10986	1/4"
10987	3/8"
10988	1/2"
10989	3/4"
10990	1"
10991	1 1/4"
10992	1 1/2"
10993	2"
10994	3"
10995	4"

Bronze Hose Connector



Part No	BSP Thread x Hose Size
10966	1/2" x 19mm
10967	3/4" x 19mm
10968	3/4" x 25mm
10969	1" x 25mm
10970	1" x 32mm
10971	1 1/4" x 32mm
10972	1 1/4" x 38mm
10973	1 1/2" x 38mm
10974	1 1/2" x 50mm
10975	2" x 51mm
10803	2 1/2" x 63mm
10997	3" x 75mm

CR Brass Male Hose Tails



Part No	BSP	Part No	BSP	Part No	BSP
10740	1/8" x 5mm	11807	3/8" x 12mm	11823	3/4" x 16mm
10741	1/8" x 6mm	11808	3/8" x 13mm	11842	3/4" x 19mm
10742	1/8" x 8mm	11811	3/8" x 16mm	11824	3/4" x 20mm
10743	1/8 x 10mm	11813	3/8" x 20mm	11844	3/4" x 25mm
11800	1/4" x 6mm	11814	1/2" x 8mm	11846	1" x 25mm
11801	1/4" x 8mm	11815	1/2" x 10mm	11848	1 1/4" x 32mm
11802	1/4" x 10mm	11817	1/2" x 13mm	11850	1 1/2" x 38mm
11803	1/4" x 12mm	11820	1/2" x 16mm	11852	1 1/2" x 40mm
11804	1/4" x 13mm	11840	1/2" x 20mm	11854	2" x 51mm
11805	3/8" x 8mm	11821	3/4" x 10mm		
11806	3/8" x 10mm	11822	3/4" x 13mm		

CR Brass Female Hose Tails



Part No	BSP	Part No	BSP
10750	1/4" x 8mm	10760	3/4" x 25mm
10751	1/4" x 10mm	10761	1" x 25mm
10752	3/8" x 10mm	10762	1" x 30mm
10753	3/8" x 13mm	10763	1 1/4" x 30mm
10754	1/2" x 10mm	10764	1 /14 x 32mm
10755	1/2" x 13mm	10765	1 1/4" x 38mm
10756	1/2" x 16mm	10766	1 1/2" x 38mm
10757	1/2" x 20mm	10767	1 1/2" x 50mm
10758	3/4" x 16mm	10768	2" x 50mm
10759	3/4" x 20mm		

CR Brass 45 degree Female/Female Elbow



Part No	BSP	Part No	BSP
10573	3/8"	10577	1 1/4"
10574	1/2"	10578	1 1/2"
10575	3/4"	10579	2"
10576	1"		

Standard 90 degree **Hose Connector**



Standard type - Cast in
LG2 GM. Threaded parallel
BSP. Thread size equiva-
lent to ID hose size.

BSP	Type
1/2"	90°
3/4"	90°
1"	90°
1 1/4"	90°
1 1/2"	90°
2"	90°
	1/2" 3/4" 1" 1 1/4" 1 1/2"

Standard Straight Connector



Standard type - Cast in LG2 GM. Threaded parallel BSP. Thread size equivalent to ID hose size.

Part No	BSP	Туре
10107	1/4"	Straight
10109	1/2"	Straight
10110	3/4"	Straight
10120	1"	Straight
10130	1 1/4"	Straight
10140	1 1/2"	Straight
10141	2"	Straight

CR Brass Y Connector



Corrosion Resistant Brass Y connector		
Part No Description		
10791	1 1/4 Y connector	

CR Brass 45 degree Male/Female Elbow



Part No	BSP	Part No	BSP
10784	3/8"	10788	1 1/4"
10785	1/2"	10789	1 1/2"
10786	3/4"	10790	2"
10787	1"		

Bronze Elbow Connector M/F



Part No	BSP	Part No	BSP
10887	3/8"	10892	1 1/2"
10888	1/2"	10893	2"
10889	3/4"	10894	3"
10890	1"	10895	4"
10891	1 1/4"		

Bronze Elbow Connector F/F



Part No	BSP	Part No	BSP
10878	3/8"	10883	1 1/2"
10879	1/2"	10884	2"
10880	3/4"	10798	2 1/2"
10881	1"	10885	3"
10882	1 1/4"	10886	4"

Bronze Straight Connector F/F



Part No	BSP	Part No	BSP
10869	3/8"	10874	1 1/2
10870	1/2"	10875	2"
10871	3/4"	10876	3"
10872	1"	10877	4"
10873	1 1/4"		

1/2"

Bronze Female Equal Tee Connector



Part No	BSP	Part No	BSP
10896	3/8"	10901	1 1/2"
10897	1/2"	10902	2"
10898	3/4"	10797	2 1/2"
10899	1"	10903	3"
10900	1 1/4"	10904	4"

Bronze Hex Equal Nipple M/M



Part No	BSP	Part No	BSP
10921	3/8"	10926	1 1/2"
10922	1/2"	10927	2"
10923	3/4"	10928	3"
10924	1"	10929	4"
10925	1 1/4"		

Bronze Reducing Bush M/F



Part No	BSP	Part No	BSP
10730	1/4" x 1/8"	10700	1 1/4" x 1/2"
10731	3/8" x 1/8"	10701	1 1/4 x 3/4"
10732	3/8" x 1/4"	10910	1 1/4" x 1"
10733	1/2" x 1/4"	10702	1 1/2" x 1/2"
10905	1/2" x 3/8"	10703	1 1/2" x 3/4"
10906	3/4" x 3/8"	10704	1 1/2" x 1"
10907	3/4" x 1/2"	10911	1 1/2" x 1 1/4"
10734	1" x 3/8"	10705	2" x 1 1/4"
10908	1" x 1/2"	10912	2" x 1 1/2"
10909	1" x 3/4"	10796	2 1/2" x 2"

CR Bronze Manifold



Part No	BSP
56590	3/4" Manifold 2 x 1/2" Female
56591	3/4" Manifold 3 x 1/2" Female
56592	1" Manifold 2 x 3/4" Female
56593	1" Manifold 3 x 3/4" Female

Bronze Reducing Nipple M/M



Part No	BSP
10913	1/2" x 3/8"
10914	3/4" x 3/8"
10915	3/4" x 1/2"
10710	1" x 3/8"
10916	1" x 1/2"
10917	1" x 3/4"
10918	1 1/4" x 1"
10919	1 1/2" x 1 1/4"
10920	2" x 1 1/2"

Bronze Reducer F/F



Female/Female		
Part No	BSP	
10489	1/2" x 3/8"	
10490	3/4" x 1/2"	
10491	1" x 3/4"	
10492	1" x 1/2"	
10493	1 1/4" x 1"	

Bronze Female Swing Check Valve



Part No	BSP
10590	3/4"
10591	1"
10592	1 1/4"
10593	1 1/2"

Bronze Reducer F/M



Part No	BSP
10930	1/2" x 3/8"
10931	3/4" x 1/2"
10932	1" x 3/4"
10933	1 1/4" x 1"
10711	1 1/2" x 1"
10934	1 1/2" x 1 1/4"
10712	2" x 1"
10935	2" x 1 1/2"

Corrosion Resistant Reducer F/F



Female/Female		
Part No BSP		
10494	1 1/2" x 3/4"	
10495	1 1/2" x 1"	
10496	1 1/2 x 1 1/4"	

Bronze / CR Brass **Blanking Cap**



Part No	BSP
10944	3/8" Bronze
10945	1/2" Bronze
10946	3/4" Bronze
10947	1" Bronze
10948	1 1/4" CR Brass
10949	1 1/2" CR Brass
10950	2" CR Brass

Bronze Blanking Plug



Part No	BSP
10936	1/4"
10937	3/8"
10938	1/2"
10939	3/4"
10940	1"
10941	1 1/4"
10942	1 1/2"
10943	2"

Bronze Solid Male Plug Hexagon Head



Part No	BSP
10735	1/2"
10736	3/4"

Bronze Back Nut



Part No	BSP
10952	1/2"
10953	3/4"
10954	1"
10955	1 1/4"
10956	1 1/2"
10957	2"
10958	3"
10959	4"

Bronze Intake Scoop



Part No	BSP
10960	1"
10961	1 1/4"
10962	1 1/2"
10963	2"
10964	3"
10965	4"

316 SS Skin Fittings



Part No	BSP
76330	3/8"
76332	1/2"
76334	3/4"
76336	1"
76338	1 1/4"
76340	1 1/2"
76342	2"

Stainless Steel 316 Ball Valve



Part No	BSP
56487	3/8"
56488	1/2"
56489	3/4"
56490	1"
56491	1 1/4"
56492	1 1/2"
56493	2"

316 Stainless Steel **Hose Tail**



Part No	BSP
56472	1/2"
56473	3/4"
56474	1"
56475	1 1/4"
56476	1 1/2"
56477	2"

Mini Skin Fitting



10mm Mini Skinfitting
AISI 316
Part No
76505



10mm Mini Deck Drain AISI 316 Part No 76506

Stainless Steel 316 Skinfitting & Hose Tail



Part No	BSP x Hose Tail
76500	1/2" x 18mm
76501	3/4" x 24mm
76502	1" x 30mm
76503	1" x 39mm

Brass Male Female Mini Ball Valve



Part No	BSP
10777	1/4"
10778	3/8"
10779	1/2"

Fuel Primer Bulbs



Fuel Primer Bulbs	
Part No	Description
11762	8mm Fuel Primer Bulb
11763	10mm Fuel Primer Bulb

Fuel Inline Check Valves



Fuel Inline Check Valves		
Part No	Description	
10280	8mm	
10281	10mm	
10282	12mm	

Soft Copper Tube



10 metre lengths		
Part No	OD X Length	
11501	1/4" X 10m	
11502	5/16" X 10m	
11503	3/8" X 10m	

Copper Clips



Part No	Size
11770	1/4"
11771	5/16"
11772	3/8"

Copper Washers

For BSP male thread.



Part No	To Fit BSP
11700	1/4"
11701	3/8"
11702	1/2"

Orange Gas Hose



Gas Hose		
HP BS3212/2		
Sold by the metre.		
Part No	Hose I.D.	
11505	8mm	
11506	10mm	

Part No

11730

11731

11732

11733

Gas Regulators



Part No	Description
11507	Butane Regulator 5/16"
11508	Camping Gaz Regulator

Stop End Coupling

Tube OD

1/4"

5/16"

3/8"

Part No

11747 11748



For rubber hose.

Bulkhead thickness 1/4" max

Bulkhead Nozzle		
Part No	Description	
11784	5/16" x 3/8" Hose	
11785	3/8" x 3/8" Hose	

Flexible	Gas	Hose



Length

36"

36"

36"

36"

11738

11739

11746

Spigot Size

1/4"

5/16"

3/8"

1/2"



Spigot Size	Length	Ν
1/4"	18"	1
5/16"	18"	t L
3/8"	18"	i
		2

Made in high pressure orange hose (not to exceed 17.5 Bar) and fitted with copper extension spigots held by swaged S/S ferrules. RCD and BSS approved up to 1m. S/S metal braided outer for use in installations where hose is subject to movement abrasion.

Compression Fittings



Straight Couplings			
(Equal ar	(Equal and Reducing)		
Part No	Tube OD x Tube OD		
11520	1/4" x 1/4"		
11523	5/16" x 1/4"		
11524	5/16" x 5/16"		
11526	3/8" x 1/4"		
11527	3/8" x 5/16"		
11528	3/8" x 3/8"		
11529	1/2" x 1/4"		
11530	1/2" x 5/16"		
11531	1/2" x 3/8"		



Male Stud Couplings		
Part No	Tube OD x BSP Male	
11540	1/4" x 1/4"	
11541	1/4" x 3/8"	
11542	1/4" x 1/2"	
11544	5/16" x 1/4"	
11545	5/16" x 3/8"	
11546	5/16" x 1/2"	
11547	3/8" x 1/4"	
11548	3/8" x 3/8"	
11549	3/8" x 1/2"	



Elbow Couplings	
Part No	Tube OD x Tube OD
11560	1/4" x1/4"
11561	5/16" x 1/4"
11562	5/16" x 5/16"
11563	3/8" x 3/8"





Male Stud Elbow Couplings		
Part No	Tube OD x BSP Male	
11572	5/16" x 1/4"	

Female Stud Elbow Couplings	
Part No	Tube OD x BSP Female
11565	5/16 " x 1/4"

Compression Fittings



Tee Couplings	
Part No	Tube OD x Tube OD x Tube OD
11592	1/4" x 1/4" x 1/4"
11593	5/16" x 5/16" x 5/16"
11594	3/8" x 3/8" x 3/8"



Female / Female Connectors	
Part No	BSP x BSP
11580	1/4" x 1/4"
11582	3/8" x 1/4"
11583	3/8" x 3/8"
11584	1/2" x 1/4"
11585	1/2" x 3/8"



Female Hose Connectors		
Part No	BSP X Hose ID	
11615	1/4" x 3/8"	
11616	3/8" x 3/8"	



Mini Gas Ball Valve Compression Fitting		
Part No	Tube OD	
11619	5/16" x 5/16"	
11620 3/8" x 3/8"		



Test Point Elbows	
Part No	Tube OD
11611	1/4"
11612	5/16"
11613	3/8"



Test Point Unions	
Part No	Tube OD
11625	5/16"
11626	3/8"
11627	1/2"



Equal Bulkhead Couplings		
Part No	Tube OD x Bulkhead Thickness	
11602	1/4" x 3/8"	
11603	1/4" x 5/8"	
11606	5/16" x 5/8"	
11607	3/8" x 3/8"	
11608	3/8" x 3/4"	
11609	1/2" x 1/2"	
11610	1/2" x 3/4"	



UNF Compression Fitting		
Part No	Thread x Tube OD	
11775	1/2" x 5/16"	
11776	1/2" x 3/8"	



Titan Fuel Hose Assemblies



TITAN FUEL HOSE ASSEMBLIES BS EN ISO 7840 CLASS A1

These hoses completely meet the EC Recreational Craft Directive, which is a rarity being tested by B.S.I. and given an EC type examination certificate by Lloyds register in order to totally comply with the regulation, unlike many marketed. In most cases 'TITAN' greatly exceeded the test requirements.

Specification:

Special nitrile rubber inner metal braided and then sleeved to show specification. The ends have heavy copper extension spigots swaged in brass with hexagon collar for securing when fitting to compression fittings.

Copper Compression Ring

Spare Olives. Sold in packs of 10.

Part No	Tube OD
11790	1/4"
11791	5/16"
11792	3/8"



Part No	Spigot Size	Length
11710	1/4"	12" (305mm)
11712	1/4"	18" (457mm)
11717	5/16"	12" (305mm)
11719	5/16"	18" (457mm)
11724	3/8"	12" (305mm)
11726	3/8"	18" (457mm)





Hinged Rectangular 1 Burner

Made of polished stainless steel, fitted with folding tap, pot holder and tempered glass cover.

Part No	Description
96402	Hinged Rectangular Burner



Spare Tap

For folding sink.

ription

96435	Spare 7	Tap

2 Burner Gas Cooktop Hob

Equipped with thermocouple. Gas hob with pyroceram burners. outside 500x300mm. recess 480x250mm. Power W 1750+3000.

Part No	Description
96420	2 Burner Gas Cooktop Hob
96401	Single Pot Holder
96421	Double Pot Holder



Ceramic Induction Hob

Inductive heating only heats the surface in contact with the saucepan therefore it implies a high energy saving. Stainless steel structure. Touch screen control. 2 Plate. Voltage 220V. Watts 1300 + 2200. outside 500 x 290mm. recess 470 x 260mm.

Part No	Description
96424	Ceramic Induction Hob
96425	Double Pot Holder

Straight Polypropylene Hose Tail



PolyPropylene Hose Tail Adaptors

1 side bsp male thread the other side hose adaptor.

Part No	Description
96200	1/2" x 13mm hose tail
96202	1/2" x 20mm hose tail
96204	3/4" x 20mm hose tail
96206	3/4" x 25mm hose tail
96208	1" x 25mm hose tail
96212	1 1/2" x 38mm hose tail

Plastic Ball Valve



Plastic Female/Female
Ball Valve

Made of polypropylene, fitted with nylon internal sphere: sturdy and safe.


spricio, stardy and saic.				
Part No	BSP			
96190	1/2"			
96192	3/4"			
96194	1"			
96196	1 1/2"			



White Plastic Skinfitting 90 Degree

Made of white plastic, fitted with 90° hose adapter, complies with EC standards only for usage above the waterline

Part No	Туре	Thread Ø mm	Length mm	Hose adaptor mm
96160	1"	33	36	19mm
96161	1"	33	36	25mm
96162	1 1/2"	47	40	38mm



Nylon	thru-hull	fitting	19/20mm

Part No Description 10239 Nylon Bulkhead fitting 19/20mm

Composite Straight Skin Fittings & SS Cap



Straight Skin Fittings moulded in fibre reinforced Acetal with a beautifully polished stainless steel cap that is ultrasonically welded onto the flange. Light weight and highly corrosion resistant.1 1/4" Hull Thickness. (1 7/8" for 11/2" and 2" versions).

Part No	Description
76176	Skin Fitting 5/8"
76178	Skin Fitting 3/4"
76180	Skin Fitting 1"
76182	Skin Fitting 1 1/8"
76184	Skin Fitting 1 1/2"
76175	Skin Fitting 2"


Composite 90 Degree Skin Fittings & SS Cap



90 Degree Skin Fittings moulded in fibre reinforced Acetal with beautifully polished stainless steel cap that is ultrasonically welded onto the flange. Light weight and highly corrosion resistant. 1 1/4" Hull Thickness.

Part No	Description
76168	Skin Fitting 90 degree 3/4"
76170	Skin Fitting 90 degree 1"
76172	Skin Fitting 90 degree 1 1/8"
76174	Skin Fitting 90 degree 1 1/2"





White Plastic Skinfitting Straight

Made of white plastic, fitted with a hose adaptor (complies with EC standards only for usage above the waterline).

Part No	Thread	A mm	B m (Hose Adaptor)	C mm	D mm
96150	1/2"	22	15	75	43
96151	3/4"	26	19	83	51
96152	1"	32	25	94	62
96153	1 1/2"	48	38	104	78
96154	1 1/4"	41	30	94	67
96155	2"	56	51	116	74

Nylon Deck Drain

Composite Deck Drain



To fit 1 1/4" or 1 1/2" Hose Thread length 47mm.

	3
Part No	Description
10238	Nylon Deck Drain



90 Degree Composite Deck Drain

Stainless & Reinforced Nylon Deck Drain

With removable centre piece for easy access. 2 x Mounting Spacers included. 6mm Each, Face 56mm Diameter. Extremely Low Profile (1mm) to prevent sitting water. Length OA 70mm (80mm for 90 Degree unit). To Fit Deck Material 10mm -25mm



25mm Side Sink Drain Made of stainless steel and moplen; includes plug handle. Grating Ø mm 70

Part	Description
No	
96436	25mm 90 degree drain

Part No	Description
96558	1" Composite Deck Drain



Nylon Drain Plug Suitable for Dinghies

Part No Centres 10780 40mm



Nylon Drain Plug / Chrome Body Large drain plug, with base 32mm

Part No Description

76078

Nylon Drain Plug Brass Base



Stainless Oval Bilge Drain Plug

316 Stainless Steel . Flange 43x64mm Hole Ø 32mm

Part No Description

76322 Oval Drain Plug SS 316



Garboard Drain 316 Stainless Steel

Comes with built in security cable.

With manual T opening.

Flange Ø 55mm

Recess bore Ø 29mm

Part No Description

76070 T Bar Opening





Cast Bronze Drain Plugs

Cast in gunmetal unpolished. Fitted with neoprene washer.

Part No	Bore	Cut Out Diameter	Flange Diameter	Hull Thickness
10794	1/2" 12mm	3/4" 19mm	1 5/8" 42mm	5/16" 8mm
10795	3/4" 19mm	1" 25mm	2" 50mm	3/8" 10mm
10800	1" 25mm	1 3/16" 30mm	2 1/8" 54mm	3/8" 10mm



Garboard Drain Screw Open

316 Stainless Steel

Comes with built in security cable. Screwdriver opening.

Flange Ø 55mm

Recess bore Ø 29mm

Part No Description

SS Screw Opening



Flip-Lock Handle Drain Plug Includes a 1" Nylon Skin Fitting with a Stainless Steel cap.

Part No	Description
76398	Flip Lock Handle Drain Plug 1"



76072



Universal Drain Plugs

A universally applicable lens plug that can be turned or plugged in easily in the opening and by switching the handle it expands and thereby seals.

Part No	Description
10781	Universal Drainplug Set 1/2" 5/8" 3/4"
10782	Universal Drainplug 1"
10783	Universal Drainplug 1 1/4"



Softwood Safety Plugs

Different sizes for plugging hull or skin fitting. 8-38 mm. Package: 10 pcs.

Wooden bungs.

Part No 90510



Wooden Drain Plugs/Bungs

Wooden set of drain plugs 5-28mm (Set of 10 pieces).

Part No

90511



Nylon White Fuel /Water Fillers

Flange 88mm

Neck Length 65mm

Neck 50mm

Part No	Description
10242	Fuel Filler Red 2"
10245	Fuel Filler Green 1 1/2"
10250	Water Filler Blue 1 1/2"







Locking Fuel Fillers

316 Stainless Steel, fitted with corrosion resistant, stainless cylinder lock. When locked the threads are disengaged and the cap will rotate freely but cannot be removed.

Part No	Description
76362	Locking Deck Fill Diesel 1 1/2"
76364	Locking Deck Fill Petrol 1 1/2"
76366	Locking Deck Fill Diesel 2"
76368	Locking Deck Fill Petrol 2"





Chrome Plated Filler Caps		
Part No	Vetus	Description
56676	FCAPWATER	Water 38mm
56677	FCAPDF38	Fuel 38mm
56678	FCAPDF50	Fuel 51mm
56679	CAPWC38	WC Waste Extraction 38mm







Vetus Stainless Steel Filler Caps

Stainless steel (AISI 316) deck entries . Cap size 86.5 mm

With high-gloss polished watertight cover.

Deck entry key for slotted deck entries. Also suitable for deck entries with an octagonal recess.

Part No	Vetus	Description
56661	CAPW38S	Water 38mm
56662	CAPG38S	Unleaded Petrol 38mm
56663	CAPF38S	Diesel 38mm
56664	CAPF51S	Diesel 51mm
56665	CAPWC38S	WC Waste Extraction 38mm
56666	KEY1	Key



Overflowing fuel or foam collector.

The fuel splash-stop is connected right under the deck filler plate to ensure that overflowing fuel or foam cannot flood onto the deck. The excess diesel or petrol fuel is collected in a parallel hose which functions as a reservoir, returning the fuel back into the tank. Capacity: 2 ltr p/mtr

Part No	Description	Vetus
56323	51mm x 19mm	FSA5119
56320	38mm x 16mm	FSA3816









Nylon Elbow Connectors		
Colours may vary		
Part No Hose Size		
10805	1/2" (13mm)	
10806	3/4" (19mm)	
10807	1" (25mm)	
10808	1 1/4" (32mm)	
10809	1 1/2" (38mm)	



Tee Connectors		
Colours may vary		
Part No	Hose Size	
10816	3/8" (10mm)	
10817	1/2" (13mm)	
10818	3/4" (19mm)	
10819	1" (25mm)	
10820	1 1/4" (32mm)	
10821	1 1/2" (38mm)	



"Y" nylon joints for water hoses		
Colours may vary		
Part No	Description	
10828	5/16" (8mm)	
10829	3/8 (10mm)	
10830	1/2 (13mm)	
10831	3/4 (19mm)	





Hose Adaptors (Step downs)		
Part No	Description	Vetus
56705	13-38mm	HA1338
56706	30-60mm	HA3060



Universal Hose Adaptors (Step downs) 13/16/19/22/25/28.5/32/38mm Part No Description 56705 13-38mm







Nylon cylindrical water hose joint

Straight connector that can be uncoupled.		
Part No	Description	
96175	12mm Straight Connector	
96177	20mm Straight Connector	
96179	25mm Straight Connector	





Plastic Hose Connectors		Plastic Hose Connectors			
PVC –Straight		PVC - 60 Degree			
Part No	Description	Vetus	Part No	Description	Vetus
56710	40mm Straight	SLVBR40K	56722	40mm (60 Deg)	SLVBG40K
56711	45mm Straight	SLVBR45K	56723	45mm (60 Deg)	SLVBG45K
56712	50mm Straight	SLVBR50K	56724	50mm (60 Deg)	SLVBG50K
56713	60mm Straight	SLVBR60K	56725	60mm (60 Deg)	SLVBG60K
56714	65mm Straight	SLVBR65K	56726	65mm (60 Deg)	SLVBG65K
56715	75mm Straight	SLVBR75K	56727	75mm (60 Deg)	SLVBG75K
56716	90mm Straight	SLVBR90K	56728	90mm (60 Deg)	SLVBG90K
56717	100mm Straight	SLVBR100K	56729	100mm (60 Deg)	SLVBG100K
56718	110mm Straight	SLVBR110K	56730	110mm (60 Deg)	SLVBG110K
56719	125mm Straight	SLVBR125K	56731	125mm (60 Deg)	SLVBG125K
56720	150mm Straight	SLVBR150K	56732	150mm (60 Deg)	SLVBG150K



Stops bilge debris from entering suction hoses and incorporates a non-return valve to prevent drain-back. Available in either top entry or side entry versions. Suitable for 25mm (1") or 38mm (1 1/2") hose.

Strum Boxes

Part No	Description
73031	Top Entry Strum Box
73030	Side Entry Strum Box



Stepped Non Return Valve

One Way Hose Connector made from sturdy polypropylene. A built in rubber flap allows water to flow in one direction only. Each section can be cut down to size of hose barb required.

	•
Part No	Description
76186	1/2 - 3/4 - 1"
76188	1 - 1 1/4 - 1 1/2"



Stepped Y Piece

This is a new Water Manifold which has been carefully designed to reduce the weight and cost associated with traditionally fabricated water system manifolds. The complete Y-Piece operates with hose sizes of 3/4", 1" and 1 1/2" and is designed to simply cut it down to size

	J	. ,
Part No	Description	
76190	Y Piece Wa	ter Manifold 3/4-1-1 1/2"



Non-Return Valve

A simple way to stop flow back in a suction or discharge line. Designed to fit in-line and is suitable for 19mm (3/4"), 25mm (1") and 38mm (1 1/2") hose. Can be used with both electric and manual pumps.

Part No	Description
73038	19mm (3/4") Valve
73034	25 / 38mm (1" / 1 1/2") Valve



Diverter Valve

Allows one pump to draw from two locations. Features smooth Teflon lubricated lever operation and precision machining to prevent seepage and odour problems.

Part No	Description
73033	25mm (1") Valve
73032	38mm (1 1/2") Valve



Plastic Y Connector - Y3C		
Does not c	ome with hose s.	
Part No	Description	
56271	Plastic Y Connector	



Neat plastic one-way valve for use in freshwater systems to help stop flow back. Especially useful with electric pumps. To fit 1/2" (12mm)

Part No	Description
73155	1/2" Non-Return Valve



Plastic in-line non return valve

YNRE

Does not come with hose connectors.

Part No	Description
56272	Plastic Non Return Valve



Plastic Hose Connectors for 3 Way Valve, Plastic Y Connector

& plastic non return valve		
Part No	Description	
56273	19mm pack of 1	
56274	19mm pack of 2	
56275	25mm pack of 1	
56276	25mm pack of 2	
56277	28mm pack of 1	
56278	28mm pack of 2	
56279	32mm pack of 1	
56280	32mm pack of 2	
56281	38mm pack of 1	
56282	38mm pack of 2	


Washdown Bayonet Fitting



When the bayonet fitting connects the washing hose, the device automatically opens and activates the pump.

Part No	Description
96110	Bayonet Washdown Flush Fitting





Plastic 3 Way Valve			
Does not come with hose connectors.			
Part No	Description		
56270	Y3V Plastic three way valve		









Stainless Steel Breather Nipple

The breathing capacity fulfils the CE requirements. Provided with an easily cleaned stainless steel (AISI 316) gauze, which functions as a flame arrester.

Part No	Size	Part No	Size
56448	16mm straight (AB16S)	56452	19mm angled (AB19B)
56449	16mm angled (AB16B)	56453	25mm angled (AB25B)
56450	19mm straight (AB19S)	56454	38mm angled (AB38B)



Suitable for Ø 16 mm internal diameter hose. In stainless steel (AISI 316).

Part No	Description
56457	Stainless Straight 16mm (ST04S)
56458	Stainless Angled 16mm (ST04HS)

Tank Vents

Chrome plated brass tank vents with fitted gauze and back nut.





Part No	Hose Dia	Aperture	Type
10260	5/8" (16mm)	3/4" (19mm)	Straight
10265	1/2" (13mm)	3/4" (19mm)	90°
10270	3/4" (19mm)	1" (25mm)	Straight



Fuel Breather Vents

Mirror polished AISI 316 stainless steel.

Fitted with flame-proof screen, detachable for easy maintenance. Designed in compliance with the requirements of the UNI EN ISO 21487 regulation.

Part No	Description
96463	19mm Vent 90 degree bend.
96464	16mm Vent 90 degree bend.



Part No	Description	
10745	16mm Chrome	
	Plated Breather Vent	



Part No	Description
10303	Chrome Plated Brass Siphon Break Valve 1/2" X 3/8

Anti Syphon







Part No	Description	

10301 Brass Vent Loop 3/4" 10302 Brass Vent Loop 1"

Anti Syphon Vent Loop

Essential for safety when the toilet is mounted under the water level; supplied with vent valve. NB: These water traps are also suitable for onboard generator's cooling systems.

Part No	To Fit Hose Dia
10258	3/4"(19mm)
10259	1 1/2" (38mm)



Airvent	
Part No	Description
57574	Airvent with Valve (AIRVENTV)
57575	Airvent with Hose (AIRVENTH)



Anti Syphon Device			
Part No	Description		
57576	13-32 with valve (ASDV)		
57578	13-32 with valve + Hose (ASDH)		



Anti Syphon Device				
Part No	Part No Description			
57579	With Valve 38mm (ASD38V)			
57580 With Hose (ASD38H)				




Antisiphon device to be used on exhaust lines, seawater connectors and WCs installed under the floating line.

Part No	Description
96105	Anti Syphon device 13 - 32mm

Blakes Toilet Seacock







Part No	To Fit Hose Dia	O.A. Height		Max hull thickness	Flange Diameter
10675	3/4" (19mm)	94mm	147mm	37mm	83mm
10676	1 1/2" (38mm)	118mm	203mm	36mm	95mm

Part No	Description
10678	Handle for 3/4" Blakes seacock
10679	Handle for 1 1/2" Blakes seacock
10677	Fixing strainer plate + bolts for 3/4" Blakes seacock
10674	Fixing plate + bolts for 1 1/2" Blakes seacock





DIMENSIONS					
ar Plus Se	acocks				
3/4" 1 1/2" (19mm) (38mm)					
147	203				
37	36				
94	118				
83	95				
93	116				
22	38				
61	73				
	3/4" (19mm) 147 37 94 83 93				





Blakes Seacock Grinding Paste

A Specifically and critically manufactured silicon carbide and lithium grease based grinding compound.

Part No	Description
10672	Medium 300 grams P120 Grit
10670	Fine 300 grams P220 Grit



Blakes Seacock Grease

Formulated for marine use with high adhesion properties and resistance to water wash out. Primarily designed to be used with the Blakes Seacocks, this quality grease can be used for many other similar marine applications on board your boat. Working temperature range -30°C to +70°C (-70°F to +160°F).

Part No	Description
10673	500g Blakes Grease





Bilge Water/Oil Separator

The filter element is replaceable and has a capacity of 320 grams, which is the average quantity of oil in 8.000 litres of bilge water. It will remove 95% of oil in the bilge water, with a maximum contamination level of 300 mg/l (p.p.m.) The bilge pump to be used in combination may have a maximum capacity of 25 litres/ minute. It has Ø 19 mm hose connections.

Part No	Description	Vetus
56228	Bilge Water/Oil Separator	BISEP19
56229	Replacement element (pack of 15)	BISEP19F2





No Smell Diesel Filter				
Part No	Description (Length x Width x Height)	Vetus		
56334	Small 16mm (107 x 111 x 111mm)	NSF16DS		
56337	Large 16mm (148 x 150 x 162mm)	NSF16D		
56338	Large 19mm (148 x 150 x 162mm)	NSF19D		
56339	Large 25mm (148 x 150 x 162mm)	NSF25D		
56218	Extra Element (pack of 3) Small	NSF16FES		
56224	Extra Element (pack of 4) Large	NSF16FE		





Small .	NIA	Small	Filter
SIIIaii	INO	SHIEII	LIIIGI

Part No	Description (Length x Width x Height)	Vetus
56217	Filter 16mm (107 x 111 x 111mm)	NSF16S
56218	Extra Element (pack of 3)	NSF16FES





No Smell Filters

The NSFCAN is pre-filled with activated carbon and special gel granules. This combination provides a revolutionary odour reduction. This type is used for NSFD and NSF filters.

The NSFCANS is pre-filled with activated carbon and special gel granules. This combination provides a revolutionary odour reduction. The filter is used for type NSF16DS and NSFS

Part No	Description	Vetus
56225	Large Filter	NSFCAN
56226	Small Filter	NSFCANS





Large No Smell Filter			
Part No	Description (Length x Width x Height)	Vetus	
56220	16mm (148 x 150 x 162mm)	NSF16	
56221	19mm (148 x 150 x 162mm)	NSF19	
56222	25mm (148 x 150 x 162mm)	NSF25	
56223	38mm (148 x 150 x 162mm)	NSF38	
56224	Extra Element (pack of 4)	NSF16FE	

Water Strainers



Fishermans Strainer			
Cast in LG2 gunmetal. BSP threaded. Complete with removable filter. Male/Female Connector.			
Part No	BSP		
10142	1/2"		
10143	3/4"		
10144	1"		

1 1/4"

1 1/2"

10145 10146



Fishermans Strainer			
Spare Metal Gauze.			
Part No	BSP		
10147	1/2"		
10148 3/4"			
10149	1"		
10151	1 1/4"		
10151	1 1/2"		



Pisa Water Strainer

CR Brass bracket mounted water strainer 'PISA' with clear cap. Tested under RINA supervision for use on pleasure vessels.

Part No	Description
10832	Pisa Water Strainer 1/2"
10833	Pisa Water Strainer 3/4"



Bracket for bracket mounted
water strainers.

Part No	Description
11835	Bracket 3/4" - 1"
11836	Bracket 1 1/4" - 1 1/2"




Venezia Water Strainer


CR Brass bracket mounted water strainer 'VENEZIA' with clear lid.

Tested under RINA supervision for use on pleasure vessels

Part No	Description
11830	Venezia Water Strainer 3/4"
11831	Venezia Water Strainer 1"
11832	Venezia Water Strainer 1 1/4"
11833	Venezia Water Strainer 1 1/2"







Aquanet Cooling Water Filter

Technopolymer case with transparent screw cap. Stainless steel pull-out filtering unit. With snap support for easy removal.

Part No	Description
96100	13/19/25mm Water Filter (150Ltr/min)
96101	32/38mm Water Filter (300Ltr/min)




Flush Mount Filter 19mm

For bilge pumps and showers

Prevents clogging from hair debris; fitted with clear plastic case for easy inspection; specially suitable for link rod pumps models Par, Fiamma, Flojet, Shurflo etc.

Part No	Description
96170	3/4" Flush Mount Filter





WF13S

Plastic Cage Strainers - FTR140				
Part No	Description	Litres/min	Vetus	
57183	13mm Strainer	23	FTR140/13	
57184	16mm Strainer	35	FTR140/16	
57185	19mm Strainer	51	FTR140/19	
57186	Spare Cover & O Ring		FTR14001	
57182	Spare Cage		FTR41	



Plastic (Plastic Cage Strainers - FTR330		
Part No	Description	Litres/min	Vetus
57189	13mm Strainer	23	FTR330/13
57190	16mm Strainer	35	FTR330/16
57191	19mm Strainer	51	FTR330/19
57192	25mm Strainer	91	FTR330/25
57193	32mm Strainer	143	FTR330/32
57194	38mm Strainer	200	FTR330/38
57197	Spare Cover & O Ring		FTR3301
57188	Spare Cage		FTR05
57195	Spare O Ring		FTR3302





Plastic Cage Strainers - FILTER150			
Part No	Description	Litres/min	Vetus
57187	28.5mm Strainer	114	FILTER150
57181	Spare Cage		WF12
57196	Spare O Ring		WF10
57207	Spare Small O Ring		WF14S



Plastic Cage Strainers - FTR1320			
Part No	Description	Litres/min	Vetus
57198	38mm Strainer	205	FTR132038
57199	50mm Strainer	365	FTR132050
57202	63mm Strainer	570	FTR132063
57200	Spare Cover & O Ring		FTR13201
57201	Spare Cage		SET0187
57204	Spare O Ring		FTR13202

Fuel Filters

Spare Large O Ring



Osculati Fuel Filters

Fitted with conical, self-locking and self-sealing hose adaptor. Comes with two blanks and two 10mm hose connectors. Height: 145mm / Overhang: 110mm / Cartridge 92Ø mm

Flow I/h at pressure - 0.49 PSI = 182

Flow I/h at pressure - 1.47 PSI = 315

Flow I/h at pressure - 2.45 PSI = 404

Part No	Bowl Type	Osculati
11796	Diesel Plastic	17.660.40
11797	Diesel Aluminium	17.660.41
11799	Petrol + Diesel Clear Bowl	17.664.00
11798	Replacement Cartridge	17.660.45

57208

Delphi 296 Fuel Filters

Single fuel filter with metal settling bowl and bleed screw, complete with interchangeable cartridge. For engines up to 3500cc. Capacity: 50 litres per hour.

Thread: M14 X 1.5

Part No	Bowl Type
11750	Metal
11751	Clear Plastic
11752	Replacement Cartridge







11761

10mm



Vetus Water Separator Fuel Filter

SINGLE, 10 MICRON, MAX. 190 L/H

The 330VTEB water separator/fuel filter will take care of an optimum filtration and protects

the engine from damage and excessive wear.

Part No	Description
57210	330VTEB Water Separator Fuel Filter
57209	VT33FB Replacement Filter Flement

Stud Coupling for Fuel Filters. Part No Thread Size Pipe OD 11765 M14 X 1.5 1/4" 11766 M14 X 1.5 5/16" 11767 M14 X 1.5 3/8"

Vetus WS250

A VETUS fuel filter/water separator fitted between the tank and the fuel lift pump will prevent damage to the engine and ensure easy starting and smooth running. Connection for 9/16" - 18 UNF female thread.

Connection nipples for Ø10mm 3/8" (cutting ring or flare type) can be ordered separately.

Weight 2.27Kg. Filter element can be renewed after 500hrs of use, or one a year. Max capacity: 250l/hr. Recommended max input 150l/hr. Complete with heat deflection shield. Capacity of receiver bowl: ca 270cm3. specially developed for marine use.

Part No	Description
57215	WS250 Water Separator Fuel Filter
57216	Connection Kit Pipe Connections
57217	Connection Kit Flare Connections

The WS180 water separator / fuel filter is suitable for both petrol and diesel fuels. Complies with the fire resistance test according to ISO 1008.



Vetus WS750

11756

10mm

WS750: connection: 7/8" - 14 UNF female thread, connection nipples for 15mm diameter tubing (cutting ring or flare type) can be supplied. weight: 5.4kg. Filter element to be renewed after 1000 hours of use, or once a year. Maximum capacity: 750 litres/hour. Recommended maximum input: 450 litres/hour. In the case of a rotating fuel injection pump, e.g. as installed on the Vetus Deutz marine diesel engines the recommended maximum input is increased to 640 litres/hour. Complete with heat deflecting shield capacity of receiver bowl: ca. 800cm³. Specially developed for marine use.


Part No	Description
57223	WS750FE Spare Filter Element

The WS720 is suitable for both petrol and diesel fuels. It needs to be mounted vertically and close as possible to the tank.



Part No	Description
57211	WS180 Water Separator Fuel Filter
57212	WS720 Water Separator Fuel Filter
57213	WS180FE Spare Filter Element for WS180 & WS720







Vetus All Purpose Tanks

Multiple purpose - material ideal for diesel fuel, fresh water and waste water.


These tanks are made of thick walled (5-7mm) high grade polyethylene which is both rust free and less prone to condensation compared with metal tanks. Due to the construction of the tanks, leakage is impossible. Fittings can be installed wherever you choose and can be ordered separately. Tanks are supplied with diesel, fresh water and waste water labels.


Specifications

Tanks are in accordance within the ISO 21487 standard when inspection lid ILY is installed and the supplied diesel sticker is used.

Available in 42, 61, 88, 110, 137, 170, 215, 335 & 390 Litre.

Suitable for diesel (up to 100°C)





Part No	Description	Vetus
56302	42 Litre	ATANK042
56303	61 Litre	ATANK061
56304	88 Litre	ATANK088
56305	110 Litre	ATANK110
56306	137 Litre	ATANK137
56307	170 Litre	ATANK170
56308	215 Litre	ATANK215
56309	335 Litre	ATANK335
56310	390 Litre	ATANK390



Vetus FTANK25

Vetus diesel fuel tanks are made from high-grade linear polythene, which is both rust free and less prone to condensation compared with metal tanks. The construction of the tank is seamless and therefore, can never leak. The fuel level can be seen from the outside.

The FTANK25 is supplied complete with a fitting kit:

Ø 50mm moulded inlet,

Ø 8mm rotating fuel connectors

Ø 19mm rotating breather connector

2 mounting straps

Part No	Description
56300	25ltr Fuel Tank
56301	FTANK25 Spare connection Kit

All-purpose 100 litre tank, suitable for diesel-, waste- or potable water.

Made out of high-grade polyethylene.

Dimensions: 1010 mm x 390 mm x 315 mm

Overall thickness 8 mm.

Large inspection hole to meet ISO21487 requirements.

38 mm connection for interconnection purpose or draining.

ILT-ready.

Flange in ring cap for easy opening.

Part No	Description	Vetus
56316	100 Litre All Purpose Tank	APT100



Fuel Connection Kit

This fuel connection disc will take care of all fuel related connections Ø 38 mm fuel fill connection.

Ø 8 / 10 mm fuel suction connection.

Ø 8 / 10 mm fuel return connection.

Ventilation connection Ø 16 mm.

5 hole SAE flange tank level sensor

Ø 8 mm suction connection for marine diesel heaters.

Connects using the ILT120B inspection port.

Part No	Description	Vetus
56311	Fuel Kit	ILTCONF38



The WTKIT kit includes inspection lid, right angle connection RT38B for filling hose/RT16B for ventilation/RT16B to water pump, 2 mounting straps, T-joint.

Part No	Description	Vetus
56259	Installation Kit	WTKIT



Suction Pipe

Fitted to the top of fixed tanks.

This suction pipe can be fitted to the top of most of the fixed tanks with a maximum depth of 410mm and suitable for ø 13mm fresh water systems.

		•
Part No	Vetus	
56260	WTS44513B	



Waste Connection Kit

Ø 38 mm connection for discharge (ability to make this a suction connector by mounting a standard Ø 40 mm PVC pipe).

Ø 38 mm inlet connection.

Ø 25 mm inlet connection.

Ø 19 mm inlet connection.

Ventilation connection Ø 19 mm.

5 hole SAE flange tank level sensor connection (suitable for SENSORA, SENSORB and WWSENSORA).

Connects using the ILT120B inspection port.

Part No	Description	Vetus
56312	Waste Kit	ILTCONW



Inspection Lid

For (waste) water tanks only!

- Overall diameter ø 156mm

Cut out diameter ø 115mm

- Not suitable for fuel tanks.
- Ideal for metal tanks.

Part No	Description	Vetus
56261	Lid Only	WTK02



Extraction	on Pipe	For	Waste	Ta	nks

Part No	Description	Vetus
56203	780mm Straight	WTS78038S
56206	780mm Right Angle	WTS78038B



Water Connection Kit

Ø 38 mm fresh water fill connection.

Ø 13 mm fresh water suction connection.

Ventilation connection Ø 16.

5 hole SAE flange tank level sensor connection.

Connects using the ILT120B inspection port.


Part No	Description	Vetus
56313	Water Kit	ILTCOND



Vetus 120mm Inspection Port

A large inspection port for (bio) diesel fuel, fresh water and waste water tanks.

Part No	Description	Vetus
56263	120mm Port	ILT120B



Inspection Lid Kit

Complete with gasket, counter flange and fastenings.

Overall diameter ø 156mm


Cut out diameter ø 115mm


Not suitable for fuel tanks.

Part No	Description	Vetus
56262	Lid & Gasket	WTIKIT

Fixed connectors 38 mm for filling and 16 mm for the breather line. Rotating hose and suction connectors 8mm.







Basic tank type WTANKC

With easy screw down inspection lid


in the moulding together with 5 blind bolt holes.

Specifications

- · Tank capacities of 40, 60 and 80 litres
- Hose connectors for filling line Ø38 mm and breather line Ø16 mm
- · Rotating hose connector Ø13 mm with pick-up pipe for water suction
- · Supplied with installed screw down inspection lid










These tanks are made of odour impermeable synthetic see-through material so the content level can be seen from the outside. The tanks are supplied with connectors, a screw down inspection lid and 2 securing straps. The inlet fitting (type RT..B) should be ordered separately matching the inlet hose diameter.

This range of rigid VETUS tanks are made of high-grade polyethylene. The centre point for a SAE flange gauge sender is incorporated together with five blind bolt holes. The gauge sender should be ordered separately . Tanks are in accordance with the ISO 21487 standard.


Part No	Description	Vetus
56267	40 Litre Tank	FTANK40A
56268	60 Litre Tank	FTANK60A


Synthetic Drinking Water Tank			
Part No	Description Vetus		
56255	40L	WTANK40C	
56256	60L	WTANK60C	
56257	80L	WTANK80C	

Waste Water Tank				
Part No	Description	Vetus		
56195	25 Litre	BTANK25C		
56196	40 Litre	BTANK40C		
56197	60 Litre	BTANK60C		
56198	80 Litre	BTANK80C		












Connections


- Suction pipe with angled Ø38 mm hose connector for deck plate connection
- Angled hose connector Ø38 mm for discharge
- Angled hose connector Ø19 mm for tank ventilation

Bulkhead Waste Water Tank				
Part No	Description	Vetus		
56207	25 Litre Horizontal	WW25WH		
56208	25 Litre Vertical	WW25W		
56210	60 Litre Vertical	WW60W		
56211	80 Litre Vertical	WW80W		









Short term waste water storage


These flexible tanks are constructed in the same robust way as the flexible drinking water tanks . However, the material used is suitable to store waste water. These tanks should be pumped and flushed after a day's boating.

Flexible Waste Water Tanks					
Part No	Description	Vetus	Part No	Description	Vetus
56775	55 Litre	TANKV55	56777	100 Litre	TANKV100
56776	70 Litre	TANKV70	56778	160 Litre	TANKV160
56780	Repair Kit	REPSETOT			



Flexible Water Tanks






The VETUS flexible water tanks consists of three layers

- 1. A wear resistant layer
- 2. A reinforcement layer
- 3. A layer suitable for contact with drinking water

Part No	Description	Vetus	Part No	Description	Vetus
56764	55 Litre	TANKW55	56767	160 Litre	TANKW160
56765	70 Litre	TANKW70	56768	220 Litre	TANKW220
56766	100 Litre	TANKW100	56769	100L - Triangular	TANKW1003
56771	Repair Kit	REPSETWT			



Plastic Hose Connectors

Synthetic fittings for VETUS flexible tanks (type FT) or rigid tanks (type RT). The required hole size for flexible tank is ø 42mm and for rigid tanks ø 43mm .

Part No	Description	Vetus	Part No	Description	Vetus
56232	13mm R/A Rigid Tanks	RT13B	56239	13mm R/A Flexible Tanks	FT13B
56233	16mm R/A Rigid Tanks	RT16B	56240	16mm R/A Flexible Tanks	FT16B
56234	19mm R/A Rigid Tanks	RT19B	56241	19mm R/A Flexible Tanks	FT19B
56235	25mm R/A Rigid Tanks	RT25B	56242	25mm R/A Flexible Tanks	FT25B
56237	38mm R/A Rigid Tanks	RT38B	56244	38mm R/A Flexible Tanks	FT38B



Vetus FTLDB

Interconnection kits for two tanks.

The FTLD connection kit links two fuel tanks. The dimensions of the skin fitting are G 3/4. Two brass skin fittings 3/4" and a coupling are supplied to connect the tanks. Includes two lashing straps to secure the tank.

Part No	Description	Vetus
56315	Interconnection Kit	FTLDB





Tank Spares				
Part No	Description	Vetus		
56238	Rubber gasket	RT001		
56264	Drinking Tank O Ring	WTK002		
56265	Large Gasket	WTK05		
56266	Spare Tank Cap	UNICAP		





Vetus Fuel Connection Kits

Hose connection for filling Ø 38 or 51 mm and a 16 mm tank ventilation connection

Fuel suction pipe according to model selected

Ø8 mm, max. tank depth 440 mm

Ø10 mm, max. tank depth 850 mm

Ø15mm, max. tank depth 970 mm

Fuel return for Ø8, 10, 15 mm hose

Mounting flange for tank level sensors (connection is suitable for sensors with a 5-hole SAE flange)

Terminal tag 6.3 mm for ground wire

2 mounting straps to secure tank

Part No	Description	Vetus
56297	Fuel Connection Kit 38mm / 8mm	FTL3808B
56298	Fuel Connection Kit 38mm / 10mm	FTL3810B
56299	Fuel Connection Kit 51mm / 8mm	FTL5108B
58315	FTL001 Expansion Rubber	
58316	FTL021 Expansion Rubber	



Waste Water installation Kit

Consisting of one inspection lid counter-flange and fastenings, two securing straps, and one wrench for angled fittings.

Overall diameter ø 156mm

Cut out diameter ø 115mm

Part No	Description	Vetus
56200	Waste Water Installation Kit	BTKIT



Vacuum Operated Valve 56mm

This valve is an indispensable safety factor for emptying a waste water tank via shore based pump-out station.

Part No	Description	Vetus
56230	Vacuum Operated Valve	VRF56A



The FUELSAFE overcomes the risk of fuel theft simply and cheaply by making it impossible to insert a siphon hose into the tank through the filling hose.

Part No	Description	Vetus
56326	Anti Fuel Theft device	FUELSAFE



Hole Saw 159mm

Hole saw for plastic, G.R.P. or stainless steel tanks with Ø 159 (6 1/4 ")

Part No	Description	Vetus
56314	Hole Saw 159mm	VSAW159




GREAT VALUE!

Exhaust Waterlock Muffler

Made of high density polyethylene. Suitable for exhaust hose 40/45/50 Ø mm. Capacity 6L. Operating pressure max 0,3 BAR. Length 370mm / 440mm with joints. Width 150mm. Height 190mm / 230mm with joints

Part No Description

10271 Exhuast Muffler 40/45/50mm



Gooseneck Downwards Waterlock

40/45/50mm

Siphon with inlet turned downwards. Size 480 x 110mm. Suitable for exhaust hoses 40/45/50mm.

Part No Description

10272 Gooseneck Waterlock

40/45/50mm




GREAT VALUE!

Horizontal Waterlock Muffler


Available in 3 sizes.

Part No	Description
10273	40mm Horizontal Muffler
10274	45mm Horizontal Muffler
10275	50mm Horizontal Muffler









Type WLOCKLP

Suitable for exhaust hose with an internal diameter of 30mm. Provided with a plug for draining during winter time. Capacity 2.3 litres.

WLOCKLP30

Part No	Description
57443	Fixed 30mm

Type WLOCKLR

Waterlock with Rotating Inlet


360° revolving inlet connection which greatly facilitates the installation. Provided with a plug for draining during winter time. Capacity 4.3 litres.

Part No	Description	
57445	40mm (WLOCKL40R)	
57446	45mm (WLOCKL45R)	
57447	50mm (WLOCKL50R)	




Spare Hose Tails			
Part No	Description		
58320	40mm		
58321	45mm		
58322	50mm		









Type WLOCKLS and WLOCKLP

Waterlock for use with long exhaust hoses (4 metres and longer). Provided with a plug for draining during winter time. Capacity 10.5 litres


Part No	Description
57449	50mm Super (WLOCKL50S)
57450	60mm (WLOCKLP60)
57451	75mm (WLOCKLP75)
57452	90mm (WLOCKLP90)

Type LSSA


Waterlock for boats sailing in rough waters. Capacity 5,7 Litres With rotating inlet/outlet for easy installation. Securing strap supplied as standard.

Part No	Description	
57460	40mm (LSS40A)	
57461	45mm (LSS45A)	
57462	50mm (LSS50A)	









Type LSL

Extra large waterlock designed for long, relatively straight exhaust runs. Capacity 16 Litres. With fixed (nonrotating) inlet and outlet connections.


Part No	Description
57456	60mm (LSL60)
57457	75mm (LSL75)
57458	90mm (LSL90)

Type LSG

Extra large waterlock for boats sailing in rough waters. Capacity 17 Litres with no return valve and rotating inlet/outlet for easy installation.

Part No	Description
57465	75mm (LSG75)
57466	90mm (LSG90)

NLP40, 45, 50.







Type NLP

Waterlock/muffler with dual stage construction. Superior silencing of exhaust noise with minimal back pressure. 360° rotatable top chamber and connectors.

Part No	Description	Part No	Description
57434	40mm (NLP40)	57438	60mm (NLP60)
57435	45mm (NLP45)	57439	75mm (NLP75)
57436	50mm (NLP50)	57440	90mm (NLP90)
57437	50mm Super (NLP50S)		

NLPH 40. 45, 50. Capacity 3 Litres.







Type NLPH

Horizontal two chamber waterlock/muffler with rotatable components and hose connections. Simple and time-saving installation.

Part No	Description
57433	40mm (NLPH40)
57424	45mm (NLPH45)
57441	50mm (NLPH50)
57454	75mm (NLPH75)
57453	90mm (NLPH90)



Spare Hose Connector

This is the rotating hose connection for the NLP type waterlocks

Part No	Description
58320	40mm US001
58321	45mm US002
58322	50mm US003
58323	Spare O Ring



Spare Hose Connector

This is the rotating hose connection of the NLP/S-NLP/HD-LSG-LGS waterlocks.

Part No	Description
57420	50mm SET0001
57421	60mm SET0002
57422	75mm SET0003
57423	90mm SET0004





Type MV

Plastic muffler with check valve, developed for fast craft with powerful engines. Achieves tremendous reduction of exhaust noise.


Part No	Description	D (mm)	H (mm)	L (mm)
57400	90mm (MV090) 11.5 Ltr Capacity	90	210	702
57401	100mm (MV100) 11.5 Ltr Capacity	100	210	702
57402	125mm (MV125) 37 Ltr Capacity	125	320	910
57403	150mm (MV150) 37 Ltr Capacity	150	320	910



Type DEMPMP

This muffler creates additional mixing of the water inside the exhaust line which results in even better noise reduction.

Part No	Description	Part No	Description
57470	40mm (DEMPMP40)	57474	75mm (DEMPMP75)
57471	45mm (DEMPMP45)	57475	90mm (DEMPMP90)
57472	50mm (DEMPMP50)	57476	100mm (DEMPMP100)
57473	60mm (DEMPMP60)		






Type NLPG


Combines the functions of a muffler and gooseneck. Saves installation time and space whilst maintaining the essential qualities of a good exhaust system.


Part No	Description
57444	40mm (NLPG40)
57442	50mm (NLPG50)
57501	60mm (NLPG60)
57502	75mm (NLPG75)
57503	90mm (NLPG90)





NLPG60, 75, 90. 10 litres capacity





Type WLOCKLT

Gooseneck for exhaust hose . Raises the exhaust hose above the waterline so that water cannot backfill the exhaust system.


Part No	Description
57479	40mm (WLOCKLT40)
57480	45mm (WLOCKLT45)
57481	50mm (WLOCKLT50)
57482	60mm (WLOCKLT60)

Type LT

Plastic gooseneck for marine exhaust systems with water injection. Supplied with stainless steel fastening brackets.

57484 LT65/65 155 500 235 65 57485 LT65/75 155 500 235 65/75 57486 LT75/75 155 500 235 75 57487 LT90/90 210 525 300 90 57488 LT90/110 210 525 300 90/110 57489 LT110 210 525 300 110 57490 LT102 210 525 300 102 57491 LT127 275 565 380 380	Part No	Description	L (mm)	H (mm)	B (mm)	D (mm)
57486 LT75/75 155 500 235 75 57487 LT90/90 210 525 300 90 57488 LT90/110 210 525 300 90/110 57489 LT110 210 525 300 110 57490 LT102 210 525 300 102	57484	LT65/65	155	500	235	65
57487 LT90/90 210 525 300 90 57488 LT90/110 210 525 300 90/110 57489 LT110 210 525 300 110 57490 LT102 210 525 300 102	57485	LT65/75	155	500	235	65/75
57488 LT90/110 210 525 300 90/110 57489 LT110 210 525 300 110 57490 LT102 210 525 300 102	57486	LT75/75	155	500	235	75
57489 LT110 210 525 300 110 57490 LT102 210 525 300 102	57487	LT90/90	210	525	300	90
57490 LT102 210 525 300 102	57488	LT90/110	210	525	300	90/110
	57489	LT110	210	525	300	110
57491 LT127 275 565 380 380	57490	LT102	210	525	300	102
	57491	LT127	275	565	380	380
57492 LT152 275 565 380 380	57492	LT152	275	565	380	380








Exhaust Temperature
Alarm

Part No	Description
56071	12V Black
56072	24\/ Plook



Exhaust Temperature Alarm		
Part No	Description	
56073	12V White	
56074	24V White	



Exhaust	Sensor			
Part No	Description	Vetus		
56075	Hose Sensor	XHSH		

Silencer Sensor XHSM



Vetus TC125 127mm

56076

The exhaust hose can be fitted directly to this transom connection. Made of reinforced black synthetic material, with decorative stainless steel band.

Part No	Vetus			
57550	TC125			

Rubber Transom Exhaust

Transom exhaust connection in EPDM rubber with high gloss polished stainless steel mounting ring. Can be mounted to the transom easily and flexibly.

Part No	Description
57545	40mm (TRC40R)
57546	45mm (TRC45R)
57547	50mm (TRC50R)
57548	60mm (TRC60R)
57549	75/90mm (TRC7590R)



Plastic Transom & Check Valve

The exhaust hose can be fitted directly to this transom connection. High quality synthetic materials, integrated rubber check valve.

F
Ę
5
5
Ę

Part No	Description
57551	40mm (TRC40PV)
57552	45mm (TRC45PV)
57553	50mm (TRC50PV)
57554	60mm (TRC60PV)
57555	75mm (TRC75PV)
57556	90mm (TRC90PV)

Stainless Steel Transom & **Check Valve**

The exhaust hose can be fitted directly to this transom connection. High quality stainless steel AISI 316 with high gloss polished cover.

Part No	Description
57558	40mm (TRC40SV)
57559	45mm (TRC45SV)
57560	50mm (TRC50SV)
57561	60mm (TRC60SV)
57562	75mm (TRC75SV)
57563	90mm (TRC90SV)



Osculati Bilge Pumps



Osculati 550 Europump 19mm

Non automatic.

CE certified by RINA in compliance with Law 94/25, directive ISO 8846. 12V.

Flow rate = 32 Litre/min - max.

Flow rate = 25 Litre/min with 2m head.

4 Amp current draw.

4.5m Max head

Part No	Description	Osculati	
96450	Europump 550 12V	16.122.02	



Osculati 800 Europump 19mm

Non automatic.

CE certified by RINA in compliance with Law 94/25, directive ISO 8846. 12V.

Flow rate = 51Litre/min - max.

Flow rate = 25 Litre/min with 2m head.

5.5Amp current draw.

4.5m Max head.

Part No	Description	Osculati	
96451	Furonump 800 12V	16 122 05	



Osculati Float Switch 12/24V

Max current draw 12V = 20 Amps.

Max current draw 24V = 10Amps.

Activation level 51mm.

Deactivation level 19mm

Part No	Description	Osculati		
96452	Float Switch 12/24V	16.603.50		





Universal for any pump with floating or electronic switch. Fitted with: Marina dual LED toggle switch, 3 positions (automatic, off, manual with spring return to off to prevent leaving the pump on), safety fuse. 75 x 60mm.

For pumps 12 V. Current draw 25 Amps

For pumps 24 volt. Current draw 15 Amps

Part No	Description	Osculati		
96453	12V Bilge Panel Switch	16.606.12		
96454	24V Bilge Panel Switch	16.606.24		



Osculati Clampshell Automatic Europumps

Very compact, with built-in electronic level sensor. ABS body, stainless steel shaft. Reduced current draw. Removable from plug-in base. CE certified by RINA in compliance with Law 94/25, directive ISO 28846/28849.

Part No	Description	Hose adaptor	Current Draw (Amp)	Flow Ltr/Min	Head (M)	Osculati
96140	G600 12V Europump II	19mm	2.5	38	2.5	16.124.01
96141	G750 12V Europump II	19mm	3	48	3	16.124.03
96142	G750 24V Europump II	19mm	1.6	48	3	16.124.04
96143	G1100 12V Europump II	22mm	4	70	3.2	16.124.05
96144	G1100 24V Europump II	22mm	2	70	3.2	16.124.06



Rule LoPro 12V Manual Bilge Pump

Connections: For 19mm (3/4"), 25mm (1") or 28mm

(1 1/8") bore hose.

Dimensions: 193mm long, 59mm diameter.

Current Draw: 4 Amps

Fuse Size: 7.5 Amps

Output: Up to 56 litres/minute (12.5 gallons/minute).

Max. recommended discharge head 3m.

Fully rotating discharge body for installation flexibility.

Part No	Description	Rule
75225	Rule Lopro 900gph Bilge Pump	LP900D







Rule LoPro Automatic Bilge Pump 900GPH 12V

High water mode: The pump starts when the water level reaches 50mm (2")

Low water mode: Turn the motor cartridge 180° and the sensor is at 33mm (1.3")

Full Electronic model: The pump automatically turns on every 2.5 minutes to check for water,

If water is detected the pump runs until the water is gone.

Dimensions: 237mm long, 59mm diameter.

Part No	Description	Model	Voltage	Current Draw	Litres/Min	Hose Connection
75234	Lopro Auto 900GPH 12V Bilge Pump	LP900S	12V	4 amps	56	19/25/28mm





Part No	Description	Rule
75145	Rule 360 12V + float switch.	24DA-35A
75150	Rule 360 12V	24DA
75155	Rule 500 12V	25DA
75160	Rule 800 12V	20DA
75162	Rule 800 12V Square	20F
75165	Rule 1100 12V	27DA
75170	Rule 1500 12V	02
75175	Rule 1500 24V	03
75180	Rule 2000 12V	10
75185	Rule 2000 24V	12
75190	Rule 3700 12V	14A
75192	Rule 3700 24V	16A
75206	Rule 4000 12V	56D

Rule Non Automatic Bilge Pumps

These pumps are totally submersible and ignition protected to all existing safety standards.

Cool running motors and stainless steel shafts for long life.

Snap lock strainer base for easy installation and removal.

Silent, vibration free running.

No burn-out if run dry.

Model	360	500	800	1100	1500	2000	3700	4000
Voltage	12V	12V	12V	12V	12V/24V	12V/24V	12V/24V	12V
Fuse Size	2.5A	2.5A	5A	6A	9A/4A	15A/10A	20A/12A	25A/15A
Litres Hour Open Flow	1362 Litres	1892 Litres	3027 Litres	4163 Litres	5676 Litres	7569 Litres	14000 Litres	15100 Litres
Hose Connection	19mm (3/4")	19mm (3/4")	19mm (3/4")	28mm (1 1/8")	28mm (1 1/8")	28mm (1 1/8")	38mm (1 1/2")	50mm (2")
Height	90mm	90mm	95mm	110mm	153mm	155mm	180mm	197mm
Diameter	60mm	60mm	60mm	60mm	100mm	105mm	135mm	135mm





Rule Mate Automatic Bilge Pumps

The Rule-Mate series of automated bilge pumps feature a pump and a non-mercury float switch in a single, compact housing. When the float rises, the pump turns on. There is no on/off cycling and, therefore, no power use until the pump comes on. The pump remains on until the float drops and the pump senses no load against the impeller.

Model	500	800	1100 12V	1100 24		
Part No	75196	75197	75198	75200		
Rule No	RM500B	RM800B	RM1100A	RM1100A-24		
Voltage	12V	12V	12V	24V		
Fuse Size	2.5A	2.5A	6A	6A		
Litres Per Hour Open Flow	1892 Litres	2838 Litres	4163 Litres	4163 Litres		
Hose Connection	19mm (3/4")	19mm (3/4")	28mm (1 1/8")	28mm (1 1/8")		
Dimensions	123mm long x100mm high x 55mm wide					



Rule Automatic Bilge Pumps

Electronic operation on the principle of impeller resistance. Float switches are not required. The pump will turn on every 2 1/2 minutes for about one second to sense for water. If water is present, the pump will sense resistance and continue to run until all water is removed. Thereafter, it will check for water every 2 1/2 minutes. Power use in the checking mode is

	4	
9		
1		
4		
V		

Model	500	1100	2000	3700	4000
Part No	75210	75212	75214	75216	75218
Rule no	25SA	27SA	53S	55S	56S
Voltage	12V	12V	12V	12V	12V
Fuse Size	2.5A	6A	15A	25A	25A
Litres Per Hour Open Flow	1892 Litres	4163 Litres	7567 Litres	14000 Litres	15100 Litres
Hose Connection	19mm (3/4")	28mm (1 1/8")	28mm (1 1/8")	38mm (1 1/2")	50mm (2")
Height x Diameter	100 x 60mm	115 x 60mm	197 x 120mm	210 x 135mm	235 x 135mm



Rule-A-Matic Switch (35)

Float Switches

Rule-A-Matic Plus Switch (40)

Superswitch (37)

These sw / off cyclin	· ·	automatic bilge pump con	trol without rapid on
Model	Rule-A-Matic (35)	Rule-A-Matic Plus (40)	Superswitch (37)

Model	Rule-A-Matic (35)	Rule-A-Matic Plus (40)	Superswitch (37)
Part No	75195	75221	75220
Rule No	35A	40A	37A
Voltage	12V / 24V	12V / 24V	12V / 24V
Max Current	14A	20A	20A
Dimensions	115 x 45 x 85mm	120 x 63 x 66mm	125 x 50 x 70mm





Rule Fco Float Switches 12/24V

The Rule ECO-Switch is an ecologically sound automatic bilge pump control switch. Featuring a non-mercury design, the pump operates with simple air pressure. As water rises in the bilge, air rises in the air tube that is attached to the switch. This air pressure activates the switch which controls your pump. There are no moving internal parts, all wiring is out of the water, and there are no submerged electrical connections at all. Offering complete reliability and outstanding performance, the Rule ECO-Switch offers a viable alternative to traditional float switches.

Part No	Description	Rule
75226	Rule Eco-Switch 12V	39
75228	Rule Eco-Switch 24V	39 - 24







Model 45

rule' High Water Bilge Alarm

Model 41

Model 43 & 44

Bilge Pump Switch Panels

These switches are designed for use with automatically controlled pumps. 3 positions: OFF / ON / MANUAL. Failsafe feature prevents pump being left on when used manually.

Rule Model	41	43	44	45
Part No	75194	75191	75199	75193
Voltage	12V	12V	24V	12/24V
Max Current	20A	20A	20A	20A
Dimensions	83 x 50mm	75 x 62mm	75 x 62mm	57 x 50mm

Rule Bilge Alarm

This device consists of a Rule-A-Matic Plus float switch with an alarm module. It warns of high water levels in the bilge using both a visual and an 85dB audible alarm. Max switching current: 20A, Gauge Diameter: 60mm

Part No	Description	Rule
75222	Rule Bilge Alarm 12V	33ALA
75224	Rule Bilge Alarm 24V	32ALA







Automatic Switch with Electric Field Sensor Technology with 30 second time delay. Electric field sensor automatically senses water levels and switches on the bilge pumps. Nylon material withstands high temperatures. Automatically switches on when 51mm (2") of water is sensed and turns off when water drops below 13mm (1/2")

• BE9006 model - built in 30 second off delay for efficient operation, prevents cycle in small sump installations or enables lower drain than 13mm (1/2")

Part No: 75261



Attwood Float Switch 6-32V

With protective cover. For use with pumps drawing less than 10 amps 6-32V.

Part No: 75080



Attwood 3 Way Bilge Switch

3 positions: Auto/ Off/ Manual.

6 - 32V, 10 amp Max.

Part No: 75100



Supersub Manual Non Automatic Submersible Bilge Pumps

Ideal bilge pump for narrow bilges. Fits under engines. Very low power consumption. Easy installation (multi-position mounting), (2 position outlet hose). Easy to clean (snap fit assembly). Leaves the bilge almost dry.

Supersub 500 : maximum overall height 75mm x maximum overall width 54mm x overall length 183mm

Supersub 1100 : maximum overall height 133mm x maximum overall width 54mm x overall length 215mm

Part No	Description	Model	Voltage	Current Draw	Flow Rate Litres/min		Hose Connections
73250	Whale Supersub 500 12V	SS5012	12v	2.4 Amps	40	34	19mm
73252	Whale Supersub1100 12V	SS1012	12v	4.3 Amps	66	47	25/28mm
73253	Whale Supersub 1100 24V	SS1024	24v	2.2 Amps	66	47	25/28mm





Supersub Smart Automatic Submersible Bilge Pumps

Low profile automatic submersible bilge pumps sense bilge water level and switch on and off automatically. Fits deep down in confined bilge areas under engines or cockpit floors.

Sensor senses for the presence of water.

1100 models also have a built in non return valve.

Height: 75mm x Width 54mm x Overall Length 212mm

Part No	Description	Model	Voltage	Current Draw	Litres/min	Litres/min 1m Head	Hose Connections
73251	Whale Supersub 650 Auto 12V	SS5212	12V	3.4 Amps	40	34	19/25mm Stepped Port
73254	Whale Supersub 1100 Auto 12V	SS1212	12V	5 Amps	66	47	25/28mm Stepped Port
73255	Whale Supersub 1100 Auto 24V	SS1224	24V	2.2 Amps	66	47	25/28mm Stepped Port







Sahara Mk 2 Automatic Bilge Pumps

A new and improved version of attwood's famous sahara bilge pump. Patented X-Air™ Impeller ejects trapped air in the pump and pipework. 90° rotatable elbow outlet allows users to install the pump anywhere in a full 360° orientation. SteadySwitch™: Buoyancy control reduces cycling, draining the bilge not the battery.

Part No	Description	Voltage	Fuse Size	Litres Hour w/o Check Valve	Litres Hour with Check Valve	Hose Connections
75050	500 Sahara Mk2 12V	12V	3 Amps	1530	1368	19/25mm Stepped Port
75052	800 Sahara Mk2 12V	12V	5 Amps	2314	2274	19/25mm Stepped Port
75053	800 Sahara Mk2 24V	24V	2 Amps	2314	2274	19/25mm Stepped Port
75054	1200 Sahara Mk2 12V	12V	6 Amps	4140	3000	25/28mm Stepped Port





Attwood Heavy Duty Non Automatic Bilge Pumps

High capacity pumps with durable, rugged construction and 28mm (1 1/8") outlets. Heavy duty motor and pump design assure long life. Large filter area prevents clogging from bilge debris. These pumps include 36" of 16-gauge caulked and tinned copper wire. Backed by a 3 year warranty. 165 x 132mm (6 1/2" X 5 3/16")

Part No	Description	Model	Voltage	Current Draw	Litres/Hour	Litres/Hour 1m Head	Hose Connection
75010	Heavy Duty 1700	1700	12V	6 Amps	6450	4920	28mm Port
75020	Heavy Duty 2000	2000	12V	8 Amps	7600	5867	28mm Port





Orca Non Automatic Bilge Pumps

These tough and compact pumps combine high performance with low current draw. They are also easy to install and maintain. As well as the standard mechanical float switch, there is also an electric field sensor switch available. It is suitable for 12 and 24 volt bilge pumps with up to 20 amp switching capacity. It senses water level and automatically controls the pump. No toxic mercury. No moving parts.

Orca 500 Dimensions: Height 83mm x Width 102mm x Depth 78.5mm

Orca 950 Dimensions: Height 109mm x Width 135mm x Depth 103mm

Orca 1300 Dimensions: Height 129mm x Width 168mm x Depth 121mm

Part No	Description	Model	Voltage	Current Draw	Litres/Min	Litres/Min 1m Head	Hose Connection
75256	Orca 500	BE0500	12V	1.5 amps	32	26	19mm
75257	Orca 950	BE0950	12V	3.5 amps	57	52	19mm
75258	Orca 1300	BE1450	12V	5 amps	82	65	28mm
75259	Orca 1300 24V	BE1454	24V	2.5 amps	82	65	28mm
75260	Orca 2000 12V	BE2002	12V	10 amps	130	70	28mm









Johnson Bilge Pumps

L750 Dimensions: Height 110mm x Width 70mm

L800 Dimensions: Height 105mm x Width 82mm x Length 142mm

L2200 Dimensions: Height 177 x Width 108mm

Part No	Description	Model	Voltage	Current Draw	Litres/Min	Litres/Min 1m Head	Hose Connection
75110	L750 Submersible Bilge Pump	L750	12V	3 Amps	78.8	60	28mm
75111	L800 Ultima Sensing Pump	L800	12V	3 Amps	38	51	19mm
75112	L2200 Heavy Duty Bilge Pump	L2200	24V	12 Amps	130	120	28/32mm





Part No	Description
73059	EF9910 Straight Connector
73060	EF9920 Straight Connector

Universal Automatic Pressure Pumps

Extremely quiet automatic pressure pumps with integral pressure switches. Fully adjustable and flexible feet for universal mounting arrangement and vibration absorption.

3 model ranges with flow rates of 8, 12 and 18 litres. 2 year warranty.

Part No	73040	73042	73043	73044	73045	73046	73047	73048
Model	UF0812	UF0815	UF1212	UF1214	UF1215	UF1225	UF1815	UF1825
Voltage	12V	12V	12V	12V	12V	24V	12V	24V
Max Outlets	2 to 3	2 to 3	3 to 4	3 to 4	3 to 4	3 to 4	4 to 6	4 to 6
Flow Rate	8 ltr / min	8 ltr / min	12 ltr / min	12 ltr / min	12 ltr / min	12 ltr / min	18 ltr / min	18 ltr / min
Cut out pressure	15psi	45psi	15psi	30psi	45psi	45psi	45psi	45psi
Fuse Size	5A	5A	5A	8A	8A	4A	12A	8A
Hose Connections	13mm (1/2")	13mm (1/2")	13mm (1/2")	13mm (1/2")	13mm (1/2")	13mm (1/2")	19mm (3/4")	19mm (3/4")
Max Lift	3m	3m	3m	3m	3m	3m	3m	3m
Max Head	10m	30m	10m	20m	30m	30m	30m	30m





Jabsco Par Max Freshwater Delivery Pumps

Jabsco's updated and improved lineup of freshwater supply pumps are designed to provide years of satisfactory service in applications both large and small.

Standard models provide good performance in an economical footprint. These configurations are available in 1-3 GPM, perfect for vessels with 1-3 outlets. A plastic housing protects the motors on these units from corro-

HD (Heavy Duty) models include a wider diameter motor with a powder coated shell, cast aluminum endbells and lower housing to improve pressure capability and life. Available in configurations up to 6 GPM (23 LPM) and 60 PSI (4.1 BAR), these pumps deliver exceptional performance.


Part No	75280	75281	75282	75283	75286	75287
Model	Par Max 2	Par Max 2	Par Max 3	Par Max 3	Par Max HD4	Par Max HD4
Voltage	12V	24V	12V	24V	12V	24V
Flow Rate	7.6 ltr / min	7.6 ltr / min	11 ltr / min	11 ltr / min	15ltr / min	15 ltr / min
Cut out pressure	35psi	35psi	25psi	25psi	25psi	25psi
Fuse Size	10A	5A	10A	5A	12A	5A
Hose Connections	13mm (1/2")	13mm (1/2")	13mm (1/2")	13mm (1/2")	13mm (1/2")	13mm (1/2")

Submersible Water Pumps

Submersible, self-venting pumps designed to be dropped into a water tank. Simple, compact and low cost. Suitable for use with pressure switches and micro switch systems. Very quiet with low power consumption.

Part No	73096	73097
Whale No	GP1352	GP1652
Model	Premium 881	High Flow 921
Voltage	12V	12V
Fuse Size	5A	5A
Weight	150g	150g
Hose Connections	10mm or 13mm	(3/8" or 1/2")
Ltr/min @ 0m head / Amps	13.2ltr / 3.6A	15.8ltr / 3.8A
Ltr/min @ 1m head / Amps	11.75ltr / 3.3A	14.8ltr / 3.7A

Whale ((



A - 20mm

B - 109mm

C - 36mm

D - 129mm

In-Line Booster Pumps

Simple, compact and low cost pump for boosting pressure in manual or electric pump systems. Fits unsupported into pipework. Low current draw and low noise.

Part No	73099	73098
Whale No	GP1392	GP1692
Model	Premium 991	High Flow 925
Voltage	12V	12V
Fuse Size	5A	5A
Weight	150g	150g
Hose Connections	10mm or 13mm	(3/8" or 1/2")
Ltr/min @ 0m head / Amps	13.2ltr / 3.6A	15.8ltr / 3.8A
Ltr/min @ 1m head / Amps	11.75ltr / 3.3A	14.8ltr / 3.7A



In-line pump

A - 20mm

B - 88mm

C - 36mm

D - 134mm

E - 27mm



Jabsco HotShot 3 Series Marine Washdown Pump

Years of clean decks and satisfaction in the form of robust and reliable high-flow and high-pressure diaphragm pumps. This kit includes a strainer, hose connectors and a trigger nozzle,

12V

3 GPM (11 LPM)

50 PSI (3.4 BAR)

Part No Description 75284 12V Jabsco HotShot 3 Washdown Pump





Washdown Quick Release Connector

Flush mount quick release connector in AISI316 Stainless Steel

Connections: Deck fitting: 13mm (1/2" BSP) female Bayonet: 19mm (3/4" BSP) Male

Dimensions: 73mm diameter, 95mm high

Connects and disconnects under full pressure

Positive lock bayonet connector

For use with HoseCoil Washdown hoses

Part No Description

75250 Quick Release Washdown Connector

Jabsco Self-priming diaphragm pump 12 volt d.c.

Connections for 19mm (3/4") bore hose

Dimensions: 294 mm long, 159mm wide, 132mm high

Fuse Size: 10(amp)

Maximum Current: 8(amps)

Output: up to 16 litres/minute (3.5 gallons/minute). Maxi-

mum recommended total head 6m

Robust, quiet single diaphragm design

No strainer required

Single diaphragm design allows extended dry running

Self-primes up to 3m (9.5ft) vertical lift

Multi-positional ports for easy mounting

Rated for up to 30 minutes continuous running

Part No Description

75249 Self Priming 12V Diaphragm Pump

0.6L Jabsco Accumulator Tank

Connections: for 13mm (1/2") bore hose or

threaded ports.

Dimensions: 214mm long, 119mm wide,

110mm deep.

Output: volume nominal 0.6 litre, working capacity up to approximately 0.3 litres.

Plastic vessel with internal membrane. May be mounted in any attitude. Compact size for small pressure systems (typically 1 - 2 outlets). Supplied with 2 snap-in connectors for 13mm

 $(\frac{1}{2})$ bore hose.

Part No Description

75240 Accumulator Tank 0.6L



2L Jabsco Accumulator Tank

Connections: 1/2" BSP external threaded. Dimensions: 230mm high, 125mm diameter. Output: nominal 2 litres, working capacity up to approximately 1 litre. Enamelled steel vessel with stainless steel flange and internal rubber membrane. For small to medium-sized pressure systems. May be mounted in any attitude. Stainless steel and rubber wetted parts. Maximum Recommended Working Pressure - 4 bar (60psi)

Part No	Description
75243	Accumulator Tank 2L



1L Jabsco Accumulator Tank

Connections for 13mm (1/2") bore hose or threaded ports.

Dimensions: 340mm long, 120mm wide, 110mm

Output: volume nominal 1 litre, working capacity up to approximately 0.5 litres

Plastic vessel with internal membrane. May be mounted in any attitude. Compact size for small pressure systems (typically 1 - 2 outlets). Supplied with 2 snap-in connectors for 13mm (1/2") bore hose

Part No Description 75241 Accumulator Tank 1L



8L Jabsco Accumlator Tank

Connections: - 3/4" BSP external threaded. Dimensions: - 330mm high, 205mm diameter. Output: - nominal 8 litres, working capacity up to approximately 4 litres. Enamelled steel vessel with stainless steel flange and internal rubber membrane. For small to medium-sized pressure systems. May be mounted in any attitude. Stainless steel and rubber wetted parts. Optional bracket kit for mounting on any flat surface. Maximum Recommended Working Pressure - 4 bar (60psi)

Part No	Description
75251	Accumulator Tank 8L



Accumulator Tank Bracket

Fit 2 litre, 5 litre and 8 litre tanks

Part No	Description
75244	Accumulator Bracket Kit



Gulper 220 Service Kit AK1550

6 x screw No.6 x 1/2" (valve plates), 1 x body, 1x inlet valve, 1 x outlet valve, 1 x diaphragm, 1 x nut nylon M5, 1 x screw M5 x 16 (clamping plate), 1 x outlet valve tricuspid, 1 x Inlet valve plate.

Part No	Description
73142	Service Kit AK1550



AK1005 Service Kit Whale Grey Waste Tank Lid Replacement With Sensor.

Part No Description 73076 AK1005 Service Kit Gulper 220 Shower Drain & Waste Water Pump

Specially designed to pump waste water at up to 14 litres per minute with low power consumption and minimal noise. Has a large single diaphragm and virtually unblockable valves. It is self-priming up to 3m, will run dry without damage and will pump a mixture of air and water. Can be mounted almost anywhere and is easy to install in confined places.

Part No	73092	73093
Voltage	12V	24V
Fuse Size	5A	2.5A
Weight	1.75Kg	
Hose Connections	19mm (3/4")	
Max Head	3m	
Max Lift	3m	
Ltr/min @ 0m Lift, 1m Head	13.4 ltr / 3.5 amps	13.4 ltr / 1.75 amps
Ltr/min @ 1m Lift, 1m Head	12.6 ltr / 4 amps	12.6 ltr / 2 amps



Grey Waste Tank

Designed to collect waste water from showers, sinks, ice-makers etc and, in conjunction with a Gulper 220 pump, automatically discharges the water through a single skinfitting. The tank contains a relay protected float switch to activate the pump when it fills with water. 4 inlet spigots each with two different dimensions to enable a variety of different hose sizes to be connected.

Part No	73077
Inlet hose connections	13mm (1/2") x 1, 19mm (3/4") x 3
	25mm (1") x 3, 38mm (1 1/2") x 1
Outlet hose connection	19mm (3/4") x 1
Dimensions	330mm X 250mm X 170mm
Capacity	9 Litres
Float Switch	Max current: 15A. 6 - 32V only



Attwood Sahara Shower Sump Systems

Designed to centralize all drains (showers, sinks, kitchens, bathrooms, etc). Fitted with check valve to prevent bad odours. Quick inspection snap cover.

Part No	Description	Current Draw	Max Flow Litres Min		Dimensions
75090	12V Sump Waste Tank	2.5 Amps	41	3M	330mm x 186mm x 111mm h
75091	24V Sump Waste Tank	1.3 Amps	41	3M	330mm x 186mm x 111mm h



Jabsco Manual Twist n Lock Toilet Compact Bowl (29090-5000)

Connections: for 19mm (3/4") bore inlet hose, 38mm (11/2") bore discharge hose

Dimensions: 455mm wide, 425mm deep, 345mm high (compare with regular size bowl model)

White vitreous china bowl, enameled wooden seat and cover. Reversible pump mounting for left or right-handed installation. Crevice-free contours and smooth moldings for added hygiene. Multi-angled discharge elbow for ease of installation. Corrosion-resistant materials for fresh or salt water service. All fastenings face front or top for ease of maintenance.

Weight: 10.80 Kg

Part No

75233

Jabsco Manual Twist n Lock Toilet Regular Bowl (29120-5000)

Connections: for 19mm (3/4") bore inlet hose, 38mm (11/2") bore discharge hose

Dimensions: 470mm wide, 485mm deep, 345mm high (compare with compact bowl model)

White vitreous china bowl, enameled wooden seat and cover. Reversible pump mounting for left or right-handed installation. Crevicefree contours and smooth moldings for added hygiene. Multi-angled discharge elbow for ease of installation. Corrosion-resistant materials for fresh or salt water service. All fastenings face front or top for ease of maintenance.

Weight: 13 Kg

Part No

75230



Jabsco Toilet Cleaner 1ltr

Part No

61109



Jabsco Joker Valve

29092-1000

Part No

75236

2007-



Jabsco Twist n' Lock' Pump Assembly (29040-3000)

For 29090 & 29120 series toilets. Includes base valve gasket.

Part No

75229





Jabsco Service Kit 1998-2006 (29045-2000)

Service Kit (includes seal & gaskets) For 2000 series toilets and 29090-2 & 29120-2 series toilets

Part No

75235



Jabsco Service Kit 2007 onwards (29045-3000)

Service Kit (includes seal & gaskets) For 3000 'Twist n' Lock' Series Toilets

For 29090-3 & 29120-3 series toilets

Part No

75231



Jabsco Regular Toilet Seat Wood (29127-1000) Includes Hinges

Part No

75232

Jabsco Compact Toilet Seat Wood (29097-1000) Includes Hinges

Part No

75239



Jabsco Hinge Set 29098-1000

Hinge Set - For wooden Seat/Lid Assembly

Part No

75237



Jabsco Hinge Set 29098-2000

Hinge Set - For wooden Seat/Lid Assembly

For current regular size.

Part No

75238



Manual To Electric Toilet Conversion Kit

Used to convert manual Jabsco toilets into electric toilets. Complete support that replaces the manual pump. Inlet/outlet pipes shall not be replaced.

Part No


75255




Gulper Toilet Waste Pumps

Designed to pump toilet waste at up to 18 litres per minute with minimal noise and is virtually unblock able. It is self-priming up to 3m, will run dry without damage, will pump a mixture of air and waste and will also pump unmacerated waste. Can be mounted almost anywhere and is easy to install in confined places. Features a rotatable inlet / outlet body to suit installation needs.

Part No	73094	73095
Whale No	BP2552B	BP2554B
Voltage	12V	24V
Fuse Size	15A	10A
Weight	2.12Kg	
Hose Connections	38mm (1 1/2")	
Max Head	3m	
Max Lift	3m	
Max Lift & Head	3m	









Part No Description 73141 Service Kit AK1557


Gulper 320 High Capacity Waste Water Pump


High capacity pump (24ltr/min) for fast drainage in grey waste systems. The gulper 320 incorporates non-choke valves with the capability to pump an air / water mixture and to run dry without suffering damage. Installation is easy, thanks to a new three foot design and the 'Ezi-clamp' locking ring which allows the head to be quickly twisted into the desired position. There are also new barbed connections for connection to either 1" (25mm) or 3/4" (19mm) hoses.

Part No	73069	73070
Whale No	BP2052	BP2054
Voltage	12V	24V
Fuse Size	10A	5A
Weight	1.59Kg	
Hose Connections	19mm (3/4") & 2	25mm (1")
Ltr/min @ 0m Lift, 1m Head, 19mm hose	22.8 ltr / 7.5 amps	22.8 ltr / 3.25 amps
Ltr/min @ 1m Lift, 1m Head, 19mm hose	20.8ltr / 7.5 amps	12.6 ltr / 3.25amps













Teak Toilet Paper Holder Traditional, stylish and practical. Part No 96415



Square Teak Grating Available in 2 sizes.

Part No	Description
96404	400 x 400mm
96410	800 x 800mm

Whale IC Grey Water Two Way Manifold WM1982B

Two way manifold with Whale Intelligent Control built in. The IC manifold can be used with a Whale Gulper pump to create a grey water disposal system. The manifold accepts two waste inputs and senses water through the wall. This relays information to the Gulper IC pump to turn on and pump the waste water.

This Whale WM1982B IC manifold is supplied with 2 metres of cable and has 19mm ports.

Part No	Description
75262	Whale IC Grey Water Two Way Manifold



Flow capacity 3.7 gpm (14 lpm) Max Pressure 60 psi (4.3 bar) Height 9" (228.6mm) Max Diameter 4" (101.6mm) Depth inc ports 5 1/2" (139.7mm) **Hose Connections** 1/2" (13mm)

Aqua Filta Water Filter

Aqua Filta is an activated carbon water filter that removes chlorine, unpleasant smells, tastes and colours from marine water systems and uses specially silver-impregnated carbon to inhibit bacterial growth in the filter bed. Aqua Filta absorbs dissolved impurities but retains beneficial mineral salts, thus freshening and cleansing water to make it natural tasting, sweet smelling and crystal clear. The filter head is permanently fixed and the replaceable cartridges can be changed quickly and easily. The inlet / outlet ports can be rotated through 180° to allow installation in confined spaces.

Part No	Description
74300	Aqua Filta
74301	Replacement Cartridge



Rapid dissolving effervescent tablets for treating stored water. Each tablet purifies 25 Its of water. Tablets are foil wrapped to remain stable for 5 years or more. The formulation contains dichloroisocyanurate, an organic chlorine donor with superior disinfection capacity. Manufactured to strict specifications to ensure an accurate dose. Convenient, simple to use method of purifying stored water.

Part No	Description
74302	Pack of 32 water purification tablets

Aqua-Source Clean In-Line Filter

An easy to install in-line water filter designed to remove unpleasant tastes and odours. Contains silver to inhibit bacterial growth. The filter is slim, compact and will last one full season or 4500 Litres. Suitable for use with pressures of up to 4 bar (60psi). Available to fit 3/8" hose or 15mm Quick Connect.

Part No	Description
73156	Aquasource Water Filter 12mm
73157	Aquasource Water Filter 15mm





Tuckaway Faucet

Tuckaway and Telescopic Faucets / Taps

Simple, lightweight faucets suitable for use with Whale foot or electric pumps. Not suitable for pressurised water tems.

13mm (1/2") hose connections.

Part No	Description	Whale No
73091	Tuckaway Faucet	FT1268
73090	Telescopic Faucet	FT1152



Telescopic Faucet



Flipper Pump Tap MK 4

A self-priming freshwater pump with swivelling outlet and light 'to and fro' pumping action. Ideal for use with two sinks. Output of 7 litres per minute. 5 year warranty.


Part No	Description	Whale No
73082	Flipper Pump	GP0418
73083	Service Kit MK3/MK4	AK0405



V Pump Tap Mk 6

Vertical, self-priming freshwater and saltwater pump with angled spout and adjustable height. Ideal where space is limited. Narrow base allows installation between two sinks. Delivers a smooth discharge on each stroke.

Part No	Description	Whale No
73080	V Pump Mk 6	GP0650
73081	Service Kit	AK0618







Babyfoot Pump Mk 2

Compact, low-cost, self-priming freshwater foot pump. Easy to install and useful in restricted spaces. Angled foot operation for more comfortable pumping. Can be used to prime Whale in-line booster pumps.

Part No	Description	Whale
73088	Babyfoot Pump Mk 2	GP4618
73089	Service Kit	AK4615



54 mm (2 1/8°)





Gusher Galley Pump Mk 3

Self-priming galley pump with smooth, double action. Multi-directional inlet and outlet nozzles. 16 litres per minute. Can be used to prime Whale in-line booster pumps.

Part No	Description	Whale
73084	Galley Pump Mk 3	GP0550
73085	Service Kit	AK0553







Tip-Toe Pump Mk 4

Self-priming freshwater foot pump designed for neat thru-floor mounting. The plunger locks down flush with the floor when not in use. Comfortable for bare foot use and has an easy, smooth action.


Part No	Description
73086	Tip-Toe Pump Mk 4 GP1309
73087	Service Kit AK1304



Strum Boxes

Stops bilge debris from entering suction hoses and incorporates a non-return valve to prevent drain-back. Available in either top entry or side entry versions. Suitable for 25mm (1") or 38mm (1 1/2")

Part No	Description
73031	Top Entry Strum Box SB5865
73030	Side Entry Strum Box SB4222



This siphon pump easily transfers any liquid (water, diesel, petrol, etc.) from a container to another preventing dirt and fatigue. Place the pump into the container with the liquid and the end of its hose into the transfer container; take care to place the second container at a slightly lower level. Stir the pump in the liquid to let it rise up to the hose gooseneck and make it fall into the other container. Disconnect the pump from the hose to stop the flow. Made of copper and supplied with 1.7-m hose. No electricity required, fast, safe and clean, minimum Ø hose mm 14. Tube Ø 15mm. Flow 10 I/min.

Part No	Description
90559	Manual Siphon Pump



Pipe Connectors

Elbows are designed to fit onto pump spigots to allow a hose to connect to the pump at 90°. The Y connector enables two pumps to discharge through a single line.

Part No	Description
73037	25mm (1") Elbow (EB3364)
73036	38mm (1 1/2") Elbow (EB3488)
73035	38mm (1 1/2") 'Y' Piece (YP6114)



Whale Easy Bailer Pumps

Whale's hand held pump for easy bail out on board small boats. Portable light weight design. Suitable for bilge water or diesel transfer. Easy to use pump action handle. Flexible hose can be easily directed to hard to reach bilge areas.

Part No	Description
73062	Short Pump (470mm) Easy Bailer 35
73063	Long Pump (673mm) Easy Bailer 55
Perform	nance Data

Performance Data			
Lift	Head	45 Strokes / Min	70 Strokes / Min
0m	0.5m	19 ltr	31.4 ltr
1m	0.5m	19 ltr	31 Itr



Vetus Single action plunger pump

Sturdy plunger pump suitable for fresh water, seawater or other fluids normally present in the bilge.

Material: durable plastic (PP). Temperature resistant to max. 60°C

Ergonomically shaped handle. Self priming.

Hose length: 980mm Hose I.D.: 28mm.

Part No	Description
58631	0.5 Litre Stirrup Pump
58632	0.8 Litre Stirrup Pump



Soft Motor Flusher

Rectangular motor flusher with hose adaptor. Moulded rubber PVC on 8mm painted steel handle. Helps extend engine life by preventing corrosion by standing sea water, sand and

Designed for outboard engines with side water inlets. No tools required.

Part No	Description
76164	Motor Flusher (Soft)



Heavy Duty Motor Flusher

Heavy duty, twin sided, Rectangular motor flusher with hose adaptor. Moulded rubber PVC on 8mm painted steel handle. Helps extend engine life by preventing corrosion by standing sea water, sand and silt. Designed for outboard engines with side water inlets. No tools required.

Part No	Description
76154	Motor Flusher (Heavy
	Duty)



Passivated Steel Sump Pump

A simple and convenient solution to changing oil, especially on engines with inaccessible drain plugs. Also ideal for transferring diesel between tanks or to fill small day tanks. 15 strokes per litre.

Barrel Diameter: 29mm.

Part No	Description
74205	Sump Pump



Brass Oil change hand pump
300mm long

Part No	Desc	ription	
70450	_	0.11 0.1	





Rule Hi Speed Dinghy Inflator 12V

Dimensions: 135mm high, 55mm hand grip diameter. Maximum Current: 25(amps). Inflates a 4 man dinghy in less than 2 minutes using a powerful 300w motor. Supplied with nozzles for all major inflatable boats and valve types. Deflates a dinghy flat and ready to pack. One handed operation. Airflow 550L / Minute (20ft/min) 25 Amps Max. Air release valve protects from overinflating and overheating 3m (10ft) cable with battery clins

offi (Tott) cable with battery clips.		
Part No	Description	Rule
75274	Rule Hi Speed Dinghy Inflator 12V	ID20
75276	Rule Inflator Adaptor Kit	ID20K





653-0001-P

Jabsco Neoprene Impeller & Gasket Kit 6 blades, pin drive, shaft diameter 12mm, impeller diameter 51mm, impeller width 22mm.

Replaces Johnson 09-810B Impeller

Part No	Description
75300	653-0001-P



673-0001-P

Jabsco Neoprene Impeller & Gasket Kit 6 blades, pin drive, shaft diameter 12.7mm

impeller diameter 50.8mm impeller width 22mm

Directly replaces Johnson 09-1026B impeller & Volvo 875808 & 804696 impellers

Also Perkins 24880194 Impeller, Vetus IMP00101 Impeller, Lombardini LDW1204M, LDW602M, LDW903 Impellers .

Part No	Description
75302	673-0001-P



920-0001-P

Jabsco Neoprene Flexible Impeller Kit

Includes gasket & impeller lubricant. neoprene impeller, 8 Blades. Splined drive, shaft diameter 16mm (5/8")

This Jabsco Impeller directly replaces the

Johnson 09-1028B impeller, Volvo 801277, 825941, 877061-2 impellers, Perkins 0460024, 24880178 impeller, Cummins 650607 impeller.

Part No	Description
75304	920-0001-P



1210-0001-P

Jabsco Flexible Neoprene Impeller & Gasket Kit

12 blades, splined drive, shaft diameter 5/8" (16mm) impeller diameter impeller diameter 57.1mm, width 31.5mm

This Jabsco impeller directly replaces the following:

Onan 132-0162 impeller Johnson 09-1027B impeller, Volvo impellers 860203, 3856039-7, 875811-2, Perkins 0460038 impeller, Yanmar 129470-42530 impeller

Part No	Description
75306	1210-0001-P



4568-0001-P

Jabsco Neoprene Impeller & Gasket Kit Fits Jabsco 4900 series pump. Key drive, shaft diameter 5/8" (16mm). Overall impeller diameter 57.1mm. Width 31.5mm. This Jabsco impeller directly replaces: Johnson 09-801B impeller,

Volvo 831182, 875575-3 impellers Yanmar 124310-46090 impeller.

Part No	Description
75312	4568-0001-P



21414-0001-P

Jabsco Neoprene Impeller & Gasket Kit 6 blades, single flat drive, Shaft diameter 8mm impeller diameter 32mm Impeller depth 12mm (Fitted To Yanmar 1GM10)

Part No	Description
75318	21414-0001-P



1414-0001-P

Jabsco Neoprene Impeller & Gasket

6 blades, comes with gasket single flat drive, shaft diameter 8mm impeller diameter 32mm impeller depth 12mm

(Not to be used in Yanmar 1GM10)

Part No	Description
75308	1414-0001-P



6303-0003-P

Jabsco Nitrile Flexible Impeller & Gasket Kit

Oil resistant. Single flat drive, plastic insert. Shaft diameter 8mm, diameter 51mm, depth 22mm, Replaces Johnson 09-824P impeller. Fits Jabsco 23680 Water Puppy pump.

Part No	Description
75314	6303-0003-P



18777-0001-P

Jabsco Neoprene Impeller & Gasket Kit Directly replaces 22120-0001 impeller spline drive, 10 blades,

Shaft diameter 16mm, impeller diameter 57mm, impeller depth 51mm.

Part No	Description
75320	18777-0001-P



4528-0001-P

Jabsco Neoprene Flexible Impeller 6 Blades, comes with gasket pin drive, shaft diameter 9.5mm impeller diameter 40mm, blade length 19mm

Fits 22830-2201 Jabsco pump, along with other pumps.

This Jabsco impeller directly replaces: Johnson 09-806B impeller ,Volvo 803729 impeller, Perkins 24990272 impeller.

Onan 132-0859 , Sherwood 9979, Yammar 104211-42070

Part No	Description
75310	4528-0001-P



17937-0001-P

Jabsco Neoprene Flexible impeller Kit Spline drive, c/w spline seal and gasket. Diameter 65mm,10 blades ,Blade length 51mm. Fits most 1" ported pumps Jabsco & Johnson. This Jabsco impeller will replace The following: Yanmar: 127610-42200, Perkins:

0460024 & 24880031Volvo: 801277 & 877061-2 & 825941

Caterpillar: 7C-3286 Sherwood:18200

Part No	Description
75316	17937-0001-P



22405-0001-P

Jabsco Neoprene Impeller & Gasket Kit 6 blades, pin drive, shaft diameter 12mm. Impeller diameter 40mm, Width 19mm. Directly replaces Johnson 09-808 impeller and Volvo 833995 & 875583-7.

Part No	Description
75322	22405-0001-P

Bilge Pumps - Manual



Gusher Urchin


Compact, lightweight bilge / waste water pump for small to medium sized boats. Pumps up to 43 litres per minute. Has dual size nozzles to fit either 1" (25mm) or 1 1/2" (38mm) hose and can be used for diesel transfer when fitted with nitrile rubber internals. Max priming height: 4m, Max head: 3m. Available in three variants to suit your requirements. 5 year warranty.


Part No	Description
73013	On Bulkhead Fixed Handle (BP9005)
73014	On Bulkhead Removable Handle (BP9021)
73015	Thru Deck / Bulkhead (BP9013)



Performance Data				
Lift	Head	60 Strokes / Min	70 Strokes / Min	
1" (25mm) Hose Bore				
1m	0.5m	34L	43L	
2m	0.5m	33L	40L	
1 1/2" (38mm) Hose Bore				
1m	0.5m	50L	55L	
2m	0.5m	48L	53L	







On Bulkhead Removable Handle

Thru Deck / Bulkhead

Gusher Urchin Service Kits

AK9003 Neoprene Contains:



- 1 x Diaphragm
- 1 x Inlet Valve 1 x Outlet Valve
- 2 x Circlips Small
- 2 x Circlips Large

AK9011 Nitrile



AS9061



Contains:

- 1 x Short Fulcrum Pin
- 1 x Fork
- 2 x Circlips Small
- 2 x Circlips Large
- 1 x Long Fulcrum Pin (underdeck)
- 1 x Fulcrum Pin (removable handle)

AS9062



Contains:

- 1 x Clamping Ring
- 1 x Pinching Screw
- 1 x Nut
- 2 x Circlips Small
- 2 x Circlips Large

AS9064



Contains:

- 1 x Underdeck Clamping Ring
- 1 x Pinching Screw
- 4 x Inserts
- 1 x Nut
- 2 x Circlips Small
- 4 x Circlips Large

AS9066



Contains:

- 1 x Clamping Nut Nyloc
- 1 x Inner Clamping Plate
- 1 x Outer Clamping Plate

AS8680



Contains:

1 x Stainless Steel Handle 240mm 1 x Lanyard

AS9060



Contains:

- 1 x Lever Sleeve (Black)
- 1 x Lever
- 1 x Short Fulcrum Pin
- 2 x Circlips Small
- 2 x Circlips Large
- 1 x Fulcrum Pin

1 x Clamping Screw


2 x Circlips Small 2 x Circlips Large

Part No	Whale	Description
73016	AK9003	Service Kit (Neoprene)
73017	AK9011	Service Kit (Nitrile)
73117	AS9061	Fork Assembly
73118	AS9062	Clamping Ring Kit (Std)
73122	AS9064	Clamping Ring Kit (Underdeck)
73120	AS9066	Inner / Outer Clamping Plate Kit
73121	AS8680	Handle Assembly
73139	AS9060	Lever Kit (Std)

Gusher Titan

Easy to install, self-priming and lightweight bilge / waste pump constructed from corrosion resistant materials. Spring assisted outlet valve for easy priming. Max output of 105 L / min. Available in either bulkhead or deck mounting models. Suitable for pumping diesel when fitted with nitrile rubber internals. 5 year warranty. Hose connections: 38mm (1 1/2"). Max priming height: 4m, max head:






Bulkhead Mounting

Part No	Description	Lift	Head	45 Strokes / Min	70 Strokes / Min
73008	Bulkhead Pump (BP4402)	1m	0.5m	67 L	105 L
73009	Thru-Deck Pump (BP4410)	2m	0.5m	65 L	98 L

Gusher Titan Service Kits



Thru-Deck Mounting

AK4400 Neoprene



Contains:

- 4 x Circlips
- 6 x Screws
- 1 x Outlet Valve Spring
- 1 x Clamping Nut
- 1 x Outlet Valve Plate
- 1 x Inlet Valve Plate
- 1 x Outlet Valve
- 1 x Inlet Valve
- 1 x Diaphragm

AK4419 Nitrile



AS4407



Contains:

- 2 x Nuts
- 2 x Screws
- 1 x Top Clamping Ring
- 1 x Bottom Clamping Ring
- 4 x Circlips

AS4406



Contains:

- 4 x Circlips
- 1 x Standard Operating Lever
- 1 x Lever Fulcrum Pin
- 1 x Standard Fulcrum Pin

AS4409



Contains:

- 2 x Nuts
- 4 x Circlips
- 4 x Inserts for Underdeck
- Clamping Ring
- 2 x Screws
- 1 x Underdeck Clamping Ring
- 1 x Top Clamping Ring

AS4412



Contains:

- 1 x Clamping Bolt
- 1 x Clamping Nut
- 1 x Outer Clamping Plate
- 1 x Inner Clamping Plate
- 4 x Circlips



AS4408

Contains:

- 4 x Circlips
- 1 x Underdeck Operating Lever
- 1 x Underdeck Fulcrum Pin
- 1 x Lever Fulcrum Pin

DP8904




The Whale DP8904 deck plate is suitable for use with the following Whale pumps: Gusher Urchin BP9005, Gusher Urchin BP9013, Gusher 10 BP3708, Gusher 10 BP3740, Gusher Titan BP4402 and Gusher Titan BP4410.

Part No	Whale	Description
73011	AK4400	Service Kit (Neoprene)
73012	AK4419	Service Kit (Nitrile)
73007	DP8904	Deck Plate & Cover
73112	AS4406	Lever Kit
73113	AS4407	Clamping Ring Kit
73114	AS4412	Clamping Plate Kit
73115	AS4408	Under Deck Lever Kit
73116	AS4409	Under Deck Clamping Ring


Gusher 10

Robust, self-priming, die cast alloy bilge pump with non-choke valves. Easy to install and maintain. Approved for use in lifeboats and also suitable for diesel transfer when fitted with nitrile rubber internals. Available in either bulkhead / on-deck mounting or thru-deck. Hose connections: 38mm (1 1/2"). Max priming height: 4m, max head: 4m.


Part No	Description
73004	Thru-Deck Mounting (Bulkhead) (BP3740)
73005	Deck / Bulkhead Mounting Pump (BP3708)







Thru-Deck Mounting



Performance Data			
Lift	Head	60 Strokes / Min	70 Strokes / Min
1m	0.5m	74L	85L
2m	0.5m	73L	81L

Part No	Whale	Description
73019	AK3706	Service Kit (Neoprene)
73020	AK3714	Service Kit (Nitrile)
73007	DP8904	Deck Plate
73108	AS3719	Eyebolt & clamping plate
73109	AS3780	Fork Assembly
73110	AS4405	Handle Assembly
73111	AS3723	Outlet Valve Plate
73068	AK3528	Service Kit (Nitrile)

AK3706 Neoprene



Gusher 10 Service Kits

Contains:

- 2 x Valves (Mk. 2 pump only)
- 4 x Screws
- 2 x Bridge Pieces
- 1 x Diaphragm
- 1 x Buffer
- 2 x Valves (Mk.3 pump only)
- 1 x Gasket (Mk. 3 pump only)

AK3714 Nitrile



AS3719



Contains:

- 2 x Clamping Plates
- 1 x Nut
- 1 x Fulcrum Bush
- 1 x Eyebolt
- 1 x Buffer
- 1 x Label

DP8904



The Whale DP8904 deck plate is suitable for use with the following Whale pumps: Gusher Urchin BP9005, Gusher Urchin BP9013, Gusher 10 BP3708, Gusher 10 BP3740, Gusher Titan BP4402 and Gusher Titan BP4410.

AS3780



Contains:

1 x Fork

- 1 x Insert Fork
- 2 x Bolts
- 2 x Fulcrum Sleeves
- 2 x Nylocs

AS4405



Contains:

1 x Handle Assembly 1x 330mm Lanyard

AS3723



Contains:

- 4 x Screws
- 1 x Bridge Piece
- 1 x Valve
- 1 x Valve Plate
- 1 x Gasket

Gusher 30


High capacity, dual-action die-cast alloy bilge pump with a maximum output of over 160 litres per minute. Fitted with nitrile rubber internals to cope with oily bilge water, effluent and diesel. Twin diaphagms ensure the pump continues working if one is damaged. Can be mounted on deck, bulkhead or under-deck. Approved as an emergency fire pump by Lloyds register. 5 year warranty. Hose connections: 38mm (1 1/2"). Max priming height: 4m, max head: 4m.

Part No	Description
73000	Deck Mount Pump (BP3000)
73001	Bulkhead Pump (BP3010)
73002	Thru-Deck Pump (BP3020)
73003	Service Kit (Nitrile) AK3051


Performance Data			
Lift	Head	60 Strokes / Min	70 Strokes / Min
0m	0.5m	141 L	163 L
1m	0.5m	136 L	159 L
2m	0.5m	136 L	159 L



On-Deck Mounting



Thru-Deck Mounting



Bulkhead Mounting

Gusher 30 Service Kits

AK3051 Nitrile



Contains:

- 2 x Screws No. 6 x 1 1/4
- 2 x Diaphragms
- 2 x Inlet valves & Gaskets
- 1 x Outlet Valve
- 2 x Valve Retainers
- 2 x Valve Chamber Gaskets
- 4 x Washers Nylon M10
- 2 x Buffers

AS3015



- Contains: 1 x Fork Insert
- 1 x Lever & Bush
- 2 x Buffers
- 1 x Nyloc M6
- 1 x Nyloc M8
- 2 x Clamping Screws
- 1 x Connecting Rod & Bush
- 1 x Lever Fulcrum Bolt
- 1 x Body Fulcrum Bolt

AS3016



Contains:

- 2 x Nylocs M8
- 2 x Studs
- 2 x Washers Nylon M10
- 2 x Hand Wheel Nuts

AS3020



Contains:

- 4 x Nuts M6
- 4 x Washers M6
- 1 x Lid
- 1 x Deckplate
- 1 x O Ring (Deckplate Lid)
- 4 x Nyloc Nuts M6
- 1 x Gaiter
- 1 x Underdeck Bracket
- 4 x Screws Hex Head M6 x 20
- 4 x Screws M6 x 50

AS3014



Contains:

- 4 x Clamping Plates
- 2 x Clamping Screws
- 2 x Buffers



Contains:

1 x Handle Assembly Stainless Steel 450mm


Part No	Whale	Description
73003	AK3051	Service Kit (Nitrile)
73100	AS3015	Lever Assembly
73101	AS3016	Hand Wheel & Stud
73105	AS3020	Deck Plate Kit
73106	AS3014	Clamping Plate Kit
73107	AS3095	Handle Assembly

MK V Universal Bilge/Water Transfer Pump

Lightweight and robust plastic bodied pump suitable for a number of applications. It has a rotatable body and inlet / outlet to suit hose direction, and it has easy access for inspection / cleaning. Also features a protected diaphragm and inspection port, non-choke valves and odour proof seals. Suitable for pumping diesel and is approved by Lloyds (MSA) and USCG as a lifeboat bilge pump. Can be installed on deck, thru-deck, on bulkhead or thru-bulkhead. 5 year warranty. Hose connections: 38mm (1 1/2"). Max lift: 4.5m, max head: 4.5m

Part No Description

Mk V Pump BP0510 73050



Performance Data			
Lift	Head	60 Strokes / Min	80 Strokes / Min

Mk V Universal Service Kits

AK8050



Contains:

1 x Inlet Valve Plate

1m 0.5m 56 L

- 1 x Inlet Valve
- 2 x Valve Screws Short
- 1 x Top Cover Seal
- 1 x Diaphragm
- 1 x Outlet Valve
- 2 x Valve Screws Long
- 2 x Circlips Small
- 2 x Circlips Large
- 8 x Screws M5 x 25
- 8 x Nuts M5

Whale	Description
AK8050	Service Kit (Nitrile)
DP9906	Deck Plate Kit & Lid
AS0511	Handle Assembly
AS0522	Front Cover
AS0521	Rocker Arm
AS0561	Diaphragm Plate
AS0531	Underdeck Rocker Arm
	AK8050 DP9906 AS0511 AS0522 AS0521 AS0561

AK0522



Contains:

- 1 x Top Cover
- 1 x Front Cover/Body Black
- 1 x Inlet Valve Plate
- 1 x Inlet Valve
- 2 x Valve Screws Short
- 1 x Top Cover Seal
- 8 x Assembly Screws
- 1 x Outlet Valve
- 2 x Valve Screws Long

AK0521





Contains:

75 L

- 1 x Rocker Arm
- 1 x Pivot Arm
- 1 x Rocker Arm Nut
- 1 x Pivot Pin
- 1 x Hinge Pin
- 2 x Circlips Large
- 2 x Circlips Small





Contains:

- 1 x Stainless Steel Handle
- 1 x Lanyard

AK0561



Contains:

- 1 x Pivot Arm
- 2 x Diaphragm Plates
- 1 x Rocker Arm Nut
- 2 x Circlips Small

AK0531



Contains:

- 1 x Pivot Bush
- 1 x Underdeck Rocker Arm
- 1 x Fork Insert
- 1 x Pivot Arm
- 1 x Rocker Arm Nut
- 1 x Hinge Pin
- 2 x Circlips Large
- 2 x Circlips Small
- 1 x Pivot Pin

MK V Double Action Bilge/Water Transfer Pump


Lightweight and robust plastic bodied pump ideal for larger craft where high output is required.

Available in 3 models for mounting on-deck, thru-deck or on-bulkhead. Due to the twin inlet / diaphragm design, two bilge compartments can be emptied simultaneously. Approved by Lloyds (MSA) and USCG as a lifeboat bilge pump. 5 year warranty.


Max output: 150 Litres min approx. Hose connections: 38mm (1 1/2"). Max lift: 4.5m, max head: 4.5m.

Part No	Description
73053	Deck Mount Pump MH5570
73054	Bulkhead Mount Pump MH5550
73055	Thru Deck Pump MH5560

Performance Data			
Lift	Head	60 Strokes / Min	80 Strokes / Min
1m	0.5m	110 ltr approx	150 ltr approx




Thru-Deck Mounting



Deck Mounting





Bulkhead Mounting

AK8060



Contains:

- 2 x Inlet Valve Plates & Valve
- 4 x Valve Screws Short
- 2 x Top Cover Seals
- 2 x Diaphragms
- 2 x Outlet Valves
- 4 x Valve Screws Long
- 2 x Circlips Large
- 4 x Circlips Small

Part No	Whale	Description
73056	AK8060	Service Kit (Nitrile)
73140	AS3725	Kit for Deck Plates
73051	MH9905	Henderson Deck Plate
73102	AK0502	Service Kit Galley Pump MK1 & 2
73129	AS0354	Compac 50 Inlet/Outlet Body Assembly
73108	AS3719	Gusher 10 Eyebolt & Clamping Plate



Vetus Manual Membrane Pump

A high quality membrane pump suitable for pumping/transferring bilge water, seawater or diesel.

3 m (10 ft) of maximum suction lift

4 m (13 ft) of maximum discharge head

Hose diameter 32mm (1 1/4") Ø

Suitable for boats up to 12 m (ISO 15083)

Part No Description

58630 Vetus Membrane Pump


Compac 50 Low Profile Under Deck Bilge Pump

Low profile bilge pump for use underdeck or thrubulkhead where space is limited. Only 119mm (4 3/4") deep and has rotatable inlet and outlet nozzles for flexibility. Easy to fit and maintain and is supplied complete with deck plate.

Suitable for pumping diesel. 5 year warranty. Max output of 49 ltrs / min. Hose connections: 25mm (1"). Max lift: 3m, Max head: 4m.

Part No	Description
73057	Compac 50 Pump BP0350





Performance Data			
Lift	Head	60 Strokes / Min	80 Strokes / Min
1m	0.5m	39 L	49 L

Compac 50 Service Kits

AK8035 Nitrile



Contains:

- 1 x Inlet Valve
- 1 x Outlet Valve
- 1 x Gaiter (Deckplate)
- 4 x Screws 6 x 1/2
- 4 x Circlips
- 1 x Diaphragm

AS0353



Contains:

- 2 x Clamping Rings
- 2 x M6 Nuts
- 2 x Screws M6 x 40

AS0352



Contains:

- 1 x Rocker Arm
- 1 x Inner Clamping Plate
- 1x Outer Clamping Plate
- 1 x Fulcrum Pin (Short)
- 1 x Fulcrum Pin (Long)
- 4 x Circlips
- 1 x Nyloc M8
- 1 x Screw M8 x 20


Part No	Whale	Description
73058	AK8035	Service Kit (Nitrile)
73127	AS0352	Rocker Arm
73128	AS0353	Clamping Plate
73130	AS0355	Handle Assembly
73131	AS0356	Deck Plate


Sanitation Pump


Lightweight and robust plastic bodied pump designed for pumping toilet waste. It can be mounted in various orientations and positions, and has easy access for inspection and cleaning. Also features large, non-choke valves and odour proof seals. Available in bulkhead and under deck versions. 5 year warranty.

Hose connections: 38mm (1 1/2"). Max lift: 4.5m, max head: 4.5m.

Part No	Description
	'
73078	Bulkhead Mount Pump BP0527
70070	
73079	Under deck Mount Pump BP0535
72050	Camilaa Kit AKOOFO
73052	Service Kit AK8050







Thru-Deck Mounting

Perfo	rmance	Data	
Lift	Head	60 Strokes / Min	80 Strokes / Min
1m	0.5m	56 L	75 L

Chimp Service Kits

AK8010 Neoprene MK1



Contains:

- 1 x Adhesive
- 1 x Inlet Valve Plate
- 1 x Outlet Valve Plate
- 1 x Diaphragm
- 1 x Inlet Valve
- 1 x Outlet Valve
- 4 x Nuts
- 4 x Screws M5 x 25
- 4 x Circlips

Part No	Whale	Description
73066	AK8010	Service Kit Mk 1 (Neoprene)
73067	AK8018	Service Kit Mk 1 (Nitrile)
73064	AK8015	Service Kit Mk 2 (Neoprene)
73137	AS0128	Clamp Plate Kit Mk 2

AK8015 Neoprene MK2



Contains:

- 1 x Diaphragm
- 1 x Inlet Valve
- 1 x Outlet Valve
- 4 x Circlips

AS0128 MK2



Contains:

- 1 x Diaphragm Stud
- 2 x Diaphragm Plates
- 1 x Diaphragm Nut
- 4 x Circlips

Gusher 25

AK3528



Contains:

- 1 x Adhesive
- 2 x Buffers
- 2 x Outlet Valves
- 2 x O Rings
- 2 x Nitrile cords
- 2 x Inlet Valves
- 4 x Screws 2BA
- 2 x Small Bridge Pieces
- 2 x Diaphragms (Nitrile)
- 2 x Large Bridge Pieces

Part No	Whale	Description
73068	AK3528	Service Kit (Nitrile)



Disposable Nitrile Gloves

These gloves are chemical resistant, and are blue in colour.

They are powder free, non sterile and ambidextrous.

Sold in boxes of 100

Part No	Size
60356	Medium
60357	Large
60358	Extra Large



Household Rubber Gloves

Medium weight, household 'Marigold' style rubber gloves which have a soft flock lining for added comfort.

Part No	Size (Sold in pairs)
60335	Medium
60336	Large



3M Premium Safety Goggles

Manufactured to EN 166 349-B standard. For protection against medium energy impact hazards, dust, liquid splashes and molten metal spray.

Part No	Description
64034	Premium Safety Googles



Disposable Latex Gloves

General purpose gloves for minimal risks only. Ambidextrous and non-sterile.

Sold in boxes of 100

Part No	Size
60353	Medium (100)
60354	Large (100)
60355	Xtra Large (95)



Nitrile Gripper Gloves

Versatile gloves ideal for light detailed assembly, inspection, light fabrication and small parts handling.

Part No	Size (Sold in pairs)
60350	Medium
60351	Large
60352	Xtra Large



3M 1100 Ear Plugs

Soft polyurethane foam offers maximum wearer comfort

Smooth, dirt-resistant surface

Tapered design fits most ear canals

SNR = 37dB

Part No	Description
64027	Pair of 3M ear plugs



3M Disposable Suits

Protects skin from hazardous dusts and limited liquid splashes

Elasticated hood, ankles, cuffs and waist

2-way zip with storm flap

Breathable fabric with low linting

Part No	Size
60341	Medium
60342	Large
60343	Xtra Large
64035	3XL



Vetus Deck Overshoes

These sturdy shoe covers have a rubberized traction sole and uppers made of heavy duty polyester-lined PVC. Unlike other shoe covers, Pantheren covers will not tear easily, and shed water. These are excellent, re-usable shoe covers for any work requiring repeated entry and exit of homes or boats.

Part No	Description
58310	Vetus Deck Overshoe Pair



3M Ear Defenders H510AGU

Peltor Optime 1

The ear defender is ideal for use in environments with moderate industrial noise such as workshops, sheet-metal shops and printing works.

Part No	Description
64029	Ear Defenders H510AGU



3M Peltor X4 Ear Defenders

The 3M Peltor X4 Ear Defenders can attenuate sound by as much as 33dB whilst maintaining a sleek, low profile, aesthetically pleasing design.

Part No	Description
64030	Peltor X4 Ear Defenders
64031	Hygiene Kit







Swarfega Original Green

Advanced smooth gel rapid hand cleaner, quickly removes ingrained oil grease and many oil based paints.

Part No	Size
61605	500gm
61610	1Kg
61615	4.5kg

Swarfega Orange Gel

Advanced rapid gel hand cleaner with non abrasive micro-polymer granules for deep down cleaning to remove the most stubborn of soiling's without damage to skin.

Part No	Size
61618	500gm
61619	4.5Kg





Loctite 7850 Hand Cleaner

Made from citrus rinds. Biodegradable and contains no synthetic solvents, mineral oil or petroleum distillate. Contains fine pumice for deep cleaning. Leaves hands smelling fresh and natural.

4001111		
60625		





Loctite 7855 Hand Cleaner

Removes paints, resins, enamels, silicones, adhesives and sealants. Contains no harmful solvents. Aloe, Jojoba and vitamin E moisturise the skin and prevent irritation.

400ml	1.75 Ltr
60622	60623

Prep - Heavy Duty Trade Wipes

Safe Guard wipes are tough, fast, safe and convenient wipes designed to remove a wide range of soils such as paint, silicones, mastics, inks, adhesives, oils, greases and general dirt. They are ideal for cleaning the hands, work tools and hard surfaces.

Contains ingredients to moisturise hands and prevent dryness. Enhanced formulation has anti-bacterial action and will remove bacteria from hands and surfaces. Effective against MRSA, Salmonella, Listeria and E-Coli. Tested by an independent laboratory to PrEN:12054 & BS 1276 standards.

Part No	Description
60292	Heavy Duty Trade Wipes (Tub of 80)

100ml

PPE & Workwear



3M AURA 9312 (FFP1)

The 3M™ Aura™ 9300+ Series Disposable Respirator 06910+ provides lightweight, comfortable and effective protection against dust and mist. The convex shape, twin strap design, nose foam and nose clip ensure comfortable wear over a range of face sizes.

Sold each or in boxes of 20.

Part No

63980



3M 8822 Dust/Mist

Respirator With Valve (FFP2)

Valved Particulate Respirator designed with a soft Comfortable inner face-piece, featuring a patented exhalation valve that prevents heat and moisture build-up. Protects against: fine dusts, fibres, oil and water based mist. Approved to EN149:2001 FFP2. Nominal protection factor 12. Assigned protection factor 10. Sold each or in boxes of 10.

Part No

63986



3M 9322 Three-Panel

Dust/Mist Respirator With Valve (FFP2)

Valved Dust/Mist Respirator, for use in hot and humid areas where FFP2 protection is required. The 9322 has a unique 3 panel construction that offers the user increased comfort and is an individually wrapped foldable product. Also features the 3M cool flow valve. Approved to EN149:2001 FFP2. Nominal protection factor 12. Assigned protection factor 10. Sold individually or in packs of 10.

Part No

63989



3M 8825 Dust/Mist/Metal Fumes Respirator (FFP2)

This valved respirator protects against fine dust, oil based mists and particulate metal fumes. Approved to EN149:2001 FFP2D. Nominal protection factor 12. Assigned protection factor 10.

Sold each or in boxes of 5.

Part No

63992

The HIGHER the number, the GREATER the protection.



FFP1 reduces the wearer's exposure to airborne particles by a FACTOR OF 4



FFP2 reduces the wearer's exposure to airborne particles by a **FACTOR OF 10**



FFP3 reduces the wearer's exposure to airborne particles by a FACTOR OF 20

3M 9332 Dust/Mist/Metal Fumes

Respirator With Valve (FFP3)

- · Provides comfort and style without compromising performance
- Extensive European field trials have proved the superiority of this range over more traditional respirators
- · Three-panel design for improved comfort, fit and communication
- Reliable, effective protection against fine particulates
- 3M Cool Flow valve reduces heat build-up to offer comfortable protection, particularly in hot and humid conditions
- Individually packed, foldable design prevent contamination before use and allows easy storage
- Even-tensioned straps relieve pressure for a comfortable and secure fit
- Red colour coded straps denoting FFP3 protection level. Maximum use level: Assigned Protection Factor: 20 x WEL (Nominal Protection Factor 50 x WEL)

Part No

63993





3M 4251 Respirator FFA1P2R D

Re-Usable 4000 Series Half Mask Respirators. These masks are available in two grades and are designed to give protection against fine dusts, oil, water based mists and organic vapours. Bonded carbon allows the gas/vapour filter to be moulded around the face to improve vision and balance. Textured face seal to provide a more comfortable fit. Parabolic exhalation valve gives easier breathing and reduces heat build up.

The 4251 mask is approved to EN 405: 2002 FFA1P2D. Assigned protection factor for Gases & Vapours: 10 or 1000ppm which ever is the lower. Assigned protection factor for Particulates: 10

Part No

63994



3M 4255 Respirator FFA2P3D

Re-Usable 4000 Series Half Mask Respirators. These masks are available in two grades and are designed to give protection against fine dusts, oil, water based mists and organic vapours. Bonded carbon allows the gas/vapour filter to be moulded around the face to improve vision and balance. Textured face seal to provide a more comfortable fit. Parabolic exhalation valve gives easier breathing and reduces heat build up.

The 4255 mask is approved to EN 405: 2002 FFA2P3D. Assigned protection factor for Gases & Vapours: 10 or 5000ppm which ever is the lower. Assigned protection factor for Particulates: 20.

Part No

63995



3M 6000 Half-Mask Respirators

A low-maintenance, comfortable, reusable respirator which can be used with 2000, 5000 and 6000 series cartridges, filters, adaptors and retainers.

These masks are light-weight and feature a soft, contouring face piece. The 6-point head strap system can be easily disassembled and cleaned.

Filters must be purchased separately. (See next page)

Part No	Size
63997	Small Half Mask
63998	Medium Half Mask
63999	Large Half Mask



3M 6000 Soft Fit Half-Mask Respirators

With a Ready-to-Use Respiratory kit you have a safe solution for Painting. This ready to use kit contains a medium size reusable half mask with a set of A2P2 R filters to protect against organic vapours and particulates. Soft silicone face piece for comfort and durability with Cool Flow valve for reduced heat and moisture build up. Low profile, twin filter design half mask for a balanced secure fit.

Part No	Size	
64000	Medium (6782)	
64001	Large (6783)	





A low-maintenance, comfortable, reusable respirator which can be used with 2000, 5000 and 6000 series cartridges, filters, adaptors and retainers.

These masks are light-weight (450g) and feature a soft, contouring hypo-allergenic face-piece.

The polycarbonate lens is scratch and impact resistant to EN166:B and offers a wide field of vision.

Filters must be purchased separately.

· ······		
Part No	Size	
64003	Large (6900)	
64004	Medium (6800)	
63985	Spare Face Shield Cover	

PPE & Workwear



3M 2125 P2 Particulate Filters Pack of 2

Versatility: can be used on all 3M 6000, 7000 and 7500 Series Half Masks and Full Face Masks

Maximum use concentration: 10xWEL

Standard: EN143



3M 6051 A1 Filters Pack of 2

3M 6051 A1 Filters protect against organic gases and vapours.

Filters are specially designed and shaped to give "swept-back" position to enable excellent field of vision and balance, Class 1

Standard: EN14387

Part No

64006



3M 06915 Organic Vapours/ Gas Filters A2 Pack of 2

The 06915 has a filter type of A1 which will protect against organic vapours. Each filter is lightweight for optimal weight distribution, the unique shape gives unobstructed field of vision. Class 2

Part No

64005



3M 6059 ABEK1 Filters Pack of 2

Compatible with 3M 6000 & 7500

Hazard - Organic Vapours, Inorganic,

series full and half face masks

EN Standard - EN141

Acid gases and Ammonia

3M 501

Part No

64013

Filter Retainer Pack of 2

These retainers fit over the 6000 Series gas and vapour filters to provide a combination dust and gas

The 501 Retainer is needed to hold the 5000 series filter on the front of the 6000 series filter

Part No.

64012



Part No 64007



3M 2135 P3 Particulate Filters Pack of 2

Versatility: can be used on all 3M 6000, 7000 and 7500 Series Half Masks and Full Face Masks Maximum use concentration: 20xWEL (half mask) or 40xWEL (full face mask)

Standard: EN143

Part No

64014



3M 6035 (P3)

Pack of 2

Solid top design reduces chance of premature clogging. Unique easy to check seal promotes enhanced respirator fit. High temperature cover protects filter media from heat, sparks or physical damage. Bayonet fitting ensures precise & safer locking

Part No

64015



3M 5925 (P2)

Pack of 2

The 3M[™] 5925 is a soft, lightweight filter pack, which is designed for use with the 6000 series cartridges and the 3M 501 retainer. They provide the user with a high protection from contaminated environments and a wide range of industrial contaminants. With a filter type of P2, it can protect you against solid, liquid particles and gases with effective filtration efficiency.

Part No

64010



3M 5935 (P3)

Pack of 2

3M™ Particulate Filter 5935 offers P3 R protection against solid and liquid particles, they can be used with 6000 series filters for combined gas and particulate protection in conjunction with a 501 filter retainer.

Part No

64011





Maxwell Up/Down Remote Panel

Push button type. AWPanel / P102983

Easy to use, panel-mounted Up/Down switches for remote windlass operation from the helm, fly bridge or cockpit. Suitable for use with dual-directional solenoids. Manufactured from marine-grade materials.

Splash proof

Suitable for 12 and 24 Volt DC use.

Part No	Description

55377 Up/Down Remote Panel



Maxwell Up/Down Anchor Windlass Switch P102938

Easy to use, panel-mounted Up/Down switches for remote windlass operation from the helm, fly bridge or cockpit. Suitable for use with dual-directional solenoids. Manufactured from marinegrade materials.

Splash proof

Suitable for 12 and 24 Volt DC use.

Part No D	escription
-----------	------------

55420 Up/Down Anchor Switch



Maxwell Circuit Breaker / Isolator

Used primarily for windlasses and capstans.

For protection of the main conductor

Allows battery to be isolated when winch is not in use.

Can be used with 12V or 24V systems.

Part No	Description
55421	40 Amp P100789
55422	70 Amp P102903
55423	80 Amp P100790
55424	135 Amp P100791

Vetus Watertight Foot Switch Black or White

New Maxwell Compact up and down Windlass Footswitch with Black cover. Designed for use with a solenoid on 12 or 24v systems. Grey activation button is reversible to denote direction and can be operated by hand with the cover in place, or by foot with the cover flipped open.

Part No	Description
55364	Foot Switch Black P104810
55361	Foot Switch White P104809







Talamex Winch Handle

All-round plastic winch handle with lock-in mechanism and ball bearing-mounted grip. Light in weight and floats! Length 250 mm

Part No	Description
25200	Winch Handle



Talamex Winch Handle Holder

Talamex winch handle holder in white plastic. Equipped with 4 mounting holes on the back. Also 4 openings on the side for attachment by band of max. 25 mm wide.

Hxwxd: 250x90x55mm

Part No Description

25201 Winch Handle Holder



Blue Winch Key 122mm & chain

Part No Description 76166 Blue Winch Key









RC8-6 65TDC 6MM~1/4" 12V (with or without capstan)

Suitable for 6 mm/7 mm (1/4") chain and 12 mm (1/2") nylon rope. The combined stainless steel and chromed bronze RC8 automatic rope/chain anchor winch is Maxwell's mid-range version of the vertical RC Series Windlass range.

Part No	Description	Voltage (V)	Motor (W)	Maxi- mum Pull / Lift (KG)	Static Hold (KG)	Chain Short Link (mm)	Net Weight, Electric (KG)	Rope Size (Nylon) mm	Chain Speed (Anchor Retrieval) (m)	Rope Speed (Anchor Retrieval) (m)
55410	Without Capstan	12V	600	350	1200	6/7	12.5	12	28 m/min	24 m/min
55411	With Capstan	12V	600	350	1200	6/7	12.5	12	28 m/min	24 m/min









RC8-8 65TDC 8MM~5/16" 12V (with or without capstan)

Suitable for 8mm (5/16") chain and 14-16 mm (1/2") nylon rope. The combined stainless steel and chromed bronze RC8 automatic rope/chain anchor winch is Maxwell's mid-range version of the vertical RC Series Windlass range.

Part No	Description	Voltage (V)	Motor (W)	Maxi- mum Pull / Lift (KG)	Static Hold (KG)	Chain Short Link (mm)	Net Weight, Electric (KG)	Rope Size (Nylon) mm	Chain Speed (Anchor Retrieval) (m)	Rope Speed (Anchor Retrieval) (m)
55412	Without Capstan	12V	1000	600	1200	8	16.5	14-16	32 m/min	28 m/min
55413	With Capstan	12V	1000	600	1200	8	16.5	14-16	32 m/min	28 m/min









RC10-8 100TDC 8MM~5/16" 12V 56:1 (with or without capstan)

Suitable for 8mm (5/16") chain and 14-16 mm (1/2") nylon rope. The combined stainless steel and chromed bronze RC10 automatic rope/chain anchor winch is Maxwell's mid-range version of the vertical RC Series Windlass range.

Part No	Description	Voltage (V)	Motor (W)	Maxi- mum Pull / Lift (KG)	Static Hold (KG)	Chain Short Link (mm)	Net Weight, Electric (KG)	Rope Size (Nylon) mm	Chain Speed (Anchor Retrieval) (m)	Rope Speed (Anchor Retrieval) (m)
55414	Without Capstan	12V	1000	700	1500	8	19	14-16	24 m/min	20 m/min
55415	With Capstan	12V	1000	700	1500	8	19	14-16	24 m/min	20 m/min



RC10-10 100TDC 10MM~3/8" 12V 56:1 (with or without capstan)

Suitable for 10mm (3/8") chain and 16 mm (5/8") nylon rope. The combined stainless steel and chromed bronze RC10 automatic rope/chain anchor winch is Maxwell's mid-range version of the vertical RC Series Windlass range.

Part No	Description	Voltage (V)	Motor (W)	Maxi- mum Pull / Lift (KG)	Static Hold (KG)	Chain Short Link (mm)	Net Weight, Electric (KG)	Rope Size (Nylon) mm	Chain Speed (Anchor Retrieval) (m)	Rope Speed (Anchor Retrieval) (m)
55416	Without Capstan	12V	1200	850	1500	10	20	16	24 m/min	20 m/min
55417	With Capstan	12V	1200	850	1500	10	20	16	24 m/min	20 m/min



P100240 55418

Horizontal HRC 10-8 SCW/SD 12V (8mm-5/16")

The HRC10 Horizontal Series windlasses proudly follow in the highly successful footsteps of Maxwell's previous, fully automatic rope/chain anchor winches. The all new HRC10 fully automatic horizontal windlass series is designed to effortlessly retrieve and deploy 8 mm (5/16") and 14 mm (9/16") or 16 mm (5/8") three strand or 8-brait (plait) rope.

Part No	Description	Voltage (V)	Motor (W)	Maxi- mum Pull / Lift (KG)	Static Hold (KG)	Chain Short Link (mm)	Net Weight, Electric (KG)	Rope Size (Nylon) mm	Chain Speed (Anchor Retrieval) (m)	Rope Speed (Anchor Retrieval) (m)
55418	Horizontal 10—8	12	1000	700	1500	8	19	14-16	24	20



P100242 55419

Horizontal HRC 10-10 SCW/SD 12V (10mm-3/8")

The HRC10 Horizontal Series windlasses proudly follow in the highly successful footsteps of Maxwell's previous, fully automatic rope/chain anchor winches. The all new HRC10 fully automatic horizontal windlass series is designed to effortlessly retrieve and deploy 10 mm (3/8") short link chain and 16 mm (5/8") three strand or 8-brait (plait) rope.

Part N	o Description	Voltage (V)	Motor (W)	Maxi- mum Pull / Lift (KG)	Static Hold (KG)	Chain Short Link (mm)	Net Weight, Electric (KG)	Rope Size (Nylon) mm	Chain Speed (Anchor Retrieval) (m)	Rope Speed (Anchor Retrieval) (m)
55419	Horizontal 10—10	12	1200	850	1500	10	20	16	24	20


Anchors



Rocna Anchor

The roll-bar ensures that the anchor always arrives at the ideal angle for penetration, and the setting skids guide the fluke tip which acts as a sharp chisel cutting into the seabed. With a third of the anchor's weight on its fluke tip, an instant reliable set is ensured with every use.

Part No	Weight (Kg)	Length (mm)	Fluke Area cm²
30006	6kg	630	590
30007	10kg	724	795
30008	15kg	830	1030
30009	20ka	864	1140



Trefoil Bruce Anchor

Trefoil® anchor made of hot-galvanized cast steel, With progressive penetration system.

Part No	Weight	A mm	B mm	C mm
30120	10kg	320	583	375



Holdfast/Danforth Anchor

Tests carried out by the Admiralty have shown that the Holdfast anchor has at least double the holding power of other anchors of equivalent weights.

Part No	Weight (Kg)	Length (mm)	Width (mm)
30010	2.5	525	370
30020	4.5	570	430
30030	7	600	540
30040	10	-	-
30050	14	865	620



Folding Grapnel Anchor

A handy anchor for small craft where space is limited.

Part No	Weight (Kg)	Length (mm)	Width (mm)
30000	1.5	310	290
30001	2.5	355	315
30002	3.2	395	330
30003	4.0	445	400
30004	6.0	535	490
30005	8.0	585	545



Plough Anchor

A popular anchor which is easy to handle and stow. Made in best quality malleable iron and hot dip galvanized. Fitted with an eye on the horn for tripping.


Part No	Weight (Kg)	Plough Length (mm)	Plough Width (mm)	Arm Length (mm)
30070	5	330	240	470
30080	7.5	340	260	550
30090	10	390	270	645
30100	12.5	400	280	665
30110	15	445	305	760



Anchor Swivelling Connector AISI 316

Made of precision-cast AISI 316 stainless steel without protrusions, used to connect the chain to the anchor. It lets the anchor chain slide smoothly through the bow roller and avoids entangling of the shackle. New reinforced model with additional finish, exclusively made by Osculati.

Part	Chain	B mm	C mm	G mm	H mm	L mm	P mm
No	Ø mm						
30182	6/8	10	7	21	95	16	9
30183	9/10	12	11	28	120	21	11



Twist Chain/Anchor Swivel Connector

Made of mirror-polished AISI 316 stainless steel. With the latest asymmetric anchors (Bruce, Delta, Trefoil® etc.), when the anchor is raised, it most probably turns the wrong side. The Twist swivelling connector turns the anchor correctly and it reeves into the roller or hawsehole. A shackle connects the fixed eye to the anchor.

Part No	Chain Ø mm	A mm	B mm	C mm
30185	6/8	120	60	28



Chain Stopper

The chain stopper device prevents the anchor chain releasing prematurely while the boat is in use. It also prevents shock/abnormal loading of the windlass while the boat is at anchor. The Chain Stopper can be disengaged with a simple movement.

Part No	Chain Ø mm		Overhang mm
30170	6/8	60 x 50	47
30171	10/12	80 x 70	63




Chain Claw Gripper

Designed to be hooked to the chain link, it relieves tension from the chain, and therefore prevents abnormal loads on the windlass. Made of polished precision-cast AISI 316 stainless steel.

Part No	Chain Ø mm
30172	6/8
30173	10/12






Chain Pipe 90° AISI316						
Part No	For chain-Ø	Diameter	Height (H)	Inside diameter (iD)	Length	
30236	6-8 mm	95mm	110mm	60mm	105mm	
30237	10-13 mm	95mm	110mm	60mm	130mm	

Galvanised Calibrated Short & Mid Link Chain

Hot dipped Galvanised Chain. Not suitable for lifting.





Sold by the metre.									
Part No	Size	Link	Grade	Α	В	С	Service Load	Max Breaking Load	Max Length
30195	6mm (1/4")	Short	30	6mm	18.5mm	8mm	400kg	1.6 Tons	500m
30205	8mm (5/16")	Short	40 EN818-3	8mm	24mm	12mm	1 Tons	4 Tons	350m
30215	10mm (3/8")	Short	40 EN818-3	10mm	30mm	15mm	1.6 Tons	6.4 Tons	250m
30225	12mm (1/2")	Short	30	12mm	36mm	16mm	1.75 Tons	7 Tons	150m
30227	12mm (1/2")	Mid	3	12mm	48mm	22mm	1.25 Tons	5 Tons	175m
30229	16mm (5/8")	Mid	30	16mm	64mm	24mm	2.5 Tons	10 Tons	100m



Long Link Stainless Steel Chain

Stainless Steel 5mm Long Link Chain. Sold by the metre up to a maximum of 50m. A4 316 Marine Grade Din763 standard. Sold by the metre up to a maximum length of 50m.

Part No	Chain Ø mm
30190	5mm




Chain Connector/Rapid Links

AISI 316 Stainless Steel

Part No	Ø mm	Inner Length mm	Inner Width mm	Breaking Load kg
30233	6	21.0	11.0	950
30234	8	24.0	11.8	1360
30235	10	30.5	14.5	2080







Bow Roller

AISI 316 Stainless Steel

Made of satin-finish stainless steel, suitable for mounting over or under the dolphin striker.

Part No	Length mm	Width mm
23127	393	52



Bow Roller

AISI 316 Stainless Steel

210 x 57 mm

Stainless steel, Chromelux® finish, fitted with nylon sheave and upper safety pin.

Part	Length	Width	Height
No	mm	mm	mm
23124	210	57	70



Monel Seizing Wire


Part No	Decription				
33870	0.9mm x 10m Spool				




Forged Hot Dipped Galvanised Mooring Swivel

It is recommended that the swivel be a size larger than the chain.

Part No	Size
30550	12mm (1/2")
30551	16mm (5/8")
30552	19mm (3/4")
30553	22mm (7/8")








Hinged Bow Roller

AISI 316 Stainless Steel

Made of stainless steel, suitable for all anchors up to 14kg. Nylon sheave.

Part	Length	Width	Height
No	mm	mm	mm
23125	320	90	70





Chain rainbow markers

Package of assorted chain rainbow markers to mark a whole length of chain. The kit includes markers in 5 colours (white, blue, yellow, red and green).

Part No	Description
30240	8mm Assorted Chain Markers Pack of 50
30241	10mm Assorted Chain Marker (Pack of 40)
30242	8mm White Pack of 10
30243	8mm Blue Pack of 10
30244	8mm Yellow Pack of 10
30245	8mm Red Pack of 10
30246	8mm Green Pack of 10
30247	10mm White Pack of 8
30248	10mm Blue Pack of 8
30249	10mm Yellow Pack of 8
30250	10mm Red Pack of 8
30251	10mm Green Pack of 8





Bow Roller

AISI 316 Stainless Steel

Mirror-polished stainless steel with thermopolymer sheave.


Part	Length	Width	Height
No	mm	mm	mm
23126	205	45	53



Maxwell Fixed Bow Roller (ARWU-04) P104345

High gloss polished 316 stainless steel.								
Part	Length	В	С	Н	H1			
No	mm	mm	mm	mm	mm			
55150	460	134	75	65	155			







High quality bow rollers cast in 316 stainless steel. One roller is plain and the other incorporates a drop-nose pin.


Part No	Туре	Roller Diameter	Α	В	С
23120	Standard	60mm	200mm	62mm	68mm
23122	Dropnose Pin	60mm	300mm	75mm	68mm



Galvanized alloy steel U.S. fed spec. RR-C-271 screw pin.



Bow Shackles						Dee Shackles					
Part No	Shackle Thickness	Pin Thickness	L	Jaw width	Safe Working Load (Tonnes)	Part No	Shackle Thickness	Pin Thickness	L	Jaw Width	Safe Working Load (Tonnes)
30430	3/16"	-	-	-	-	30350	3/16"	-	-	-	-
30440	1/4"	5/16"	29mm	12mm	0.50T	30360	1/4"	5/16"	23mm	12mm	0.50T
30450	5/16"	3/8"	31mm	13.5mm	0.75T	30370	5/16"	3/8"	27mm	13.5mm	0.75T
30460	3/8"	7/16"	36mm	17mm	1.00T	30380	3/8"	7/16"	31mm	17mm	1.00T
30470	1/2"	5/8"	48mm	21mm	2.00T	30390	1/2"	5/8"	42mm	21mm	2.00T
30480	5/8"	3/4"	61mm	27mm	3.25T	30400	5/8"	3/4"	51mm	27mm	3.25T
30490	3/4"	7/8"	72mm	31mm	4.75T	30410	3/4"	7/8"	59mm	31mm	4.75T
30495	7/8"	1"	83mm	36mm	6.50T	30420	7/8"	1"	72mm	36mm	6.50T



These galvanised green pin shackles are tested and certified in accordance with EN-13889 (Grade 6).

The oversized pin is stamped with the safe working load. Dimensions in mm.




Tested Green Pin Bow Shackles					Tested Green Pin Dee Shackles						
Part No	Shackle Thickness	Pin Thickness		L	Safe Working Load (Tonnes)	Part No	Shackle Thickness	Pin Thickness	Jaw- Width	L	Safe Working Load (Tonnes)
30290	10 (3/8")	11	17	36.5	1.00	30282	10 (3/8")	11	17	31	1.00
30291	13.5 (1/2")	16	22	51	2.00	30283	13.5 (1/2")	16	22	43	2.00
30292	16 (5/8")	19	27	64	3.25	30284	16 (5/8")	19	27	51	3.25
30293	19 (3/4")	22	31	76	4.75	30285	19 (3/4")	22	31	59	4.75
30294	22 (7/8")	25	36	83	6.50	30286	22 (7/8")	25	36	73	6.50
30295	25 (1")	28	43	95	8.50	30287	25 (1")	28	43	85	8.50



	Bow Shackles								
AISI 316 Stainless Steel									
	Part No	Diameter			Minimum Breaking Load (KN)				
	30422	5mm	20mm	10mm	9.1				
	30423	6mm	24mm	12mm	13.2				
	30424	8mm	32mm	16mm	23.7				
	30425	10mm	40mm	20mm	37.3				
	30426	12mm	48mm	24mm	54.9				
	30427	16mm	64mm	32mm	97.7				



Dee Sna	Dee Snackles						
AISI 316	AISI 316 Stainless Steel						
Part No	Diameter	Length	Jaw Width	Minimum Breaking Load (KN)			
30341	5mm	20mm	10mm	9.1			
30342	6mm	24mm	12mm	13.2			
30343	8mm	32mm	16mm	23.7			
30344	10mm	40mm	20mm	37.3			
30345	12mm	48mm	24mm	54.9			
30346	16mm	64mm	32mm	97.7			



Long Dee Shackles
AISI 316 Stainless Steel


Part No	Diameter	Length	Jaw Width	M.B.L (KN)
30522	5mm	40mm	10mm	9.1
30523	6mm	48mm	12mm	13.2
30524	8mm	64mm	16mm	23.7
30525	10mm	80mm	20mm	37.3
30526	12mm	96mm	24mm	54.9



Flat Dee Locking Shackles							
AISI 31	AISI 316 Stainless Steel						
Part No	Diameter	B mm	C mm				
30535	5mm	50	10				
30536	6mm	57	13				
30537	8mm	79	16				



Flat Dee Locking Shackles With Bar					
AISI 316	Stainless S	teel			
Part No	Diameter	Length	Jaw Width	M.B.L (KN)	
30540	5mm	40mm	12mm	9.1	
30541	6mm	48mm	15mm	13.2	
30542	8mm	64mm	20mm	23.7	



Twisted Shackles	
AISI 216 Stainlage	C+


Part No	Diameter	Length	Width	M.B.L (KN)
30528	5mm	30mm	10mm	9.1
30529	6mm	36mm	12mm	13.2
30530	8mm	48mm	16mm	23.7
30531	10mm	60mm	20mm	37.3
30532	12mm	72mm	24mm	54.9



Snap	Snap Shackles Fixed						
AISI 3	AISI 316 Stainless Steel						
Part I	No Over Leng		Bottor Gap	n M.B.L. (KN)			
3086	0 52mr	n 13mr	m 9mm	12.7			
3086	1 66mr	n 16mr	n 12mm	17.6			
3086	2 96mr	n 22mr	n 16mm	32.6			



Snap Shackles Swivelling							
AISI 316	AISI 316 Stainless Steel						
Part No	Overall Length	Top Gap	Bottom Gap	M.B.L. (KN)			
30865	70mm	13mm	12mm	6.4			
30866	87mm	16mm	16mm	8.8			
30867	128mm	22mm	23mm	16.3			




Flat Dee Shackles

AISI 316 Stainless Steel

Part No		Jaw Width		Shackle Thickness	•
30330	4mm	10mm	18mm	1.9mm	800
30331	5mm	12mm	20mm	2mm	900





Flat Long	Flat Long Dee Shackles					
AISI 316	AISI 316 Stainless Steel					
Part No		Jaw Width	Inside Length	Shackle Thickness	U	
30335	4mm	12mm	24mm	4mm	800	






Spring Hook "Surf - Snap"
AISI 316 Stainless Steel

7 110 1 0 1 0 0 1 1 1 1 1 1 1 1 1 1 1 1				
Part No	Width (B)	Inside Diameter (iD)	Length (L)	Width of Opening (C)
30924	24mm	7mm	50mm	10mm
30923	30mm	10mm	70mm	13mm





900

Swivel Eye Bolt Snap
AICL 216 Stainless Stor

30336

5mm

SI 316 Stainless Steel

7.11.0.7.0.7.0.01.11.11.11.11.11.11.11.11.11.11.11.1						
Part No	•			Material Diameter (ø)	Width of Opening (C)	
30925	64mm	10mm	7mm	3mm	7mm	
30926	87mm	16mm	9mm	5mm	9mm	








Carbine Hook + Eye AISI 316 Stainless Steel

	Part No	Diameter	Overall Length	Eyelet	M.B.L . (KN)
В	30850	5mm	50mm	6mm	3.4
	30851	6mm	60mm	7mm	5.1
	30852	8mm	80mm	9mm	7.8
	30853	10mm	100mm	12mm	11.8
	30855	11mm	120mm	14.5mm	13.9
	30854	12mm	140mm	18mm	16.5



Comes with a washer and nut.

AISI 316 Stainless Steel


Aloi 310 Stailliess Steel					
Part No	Thread	Thread Length	Ring Thickness	Ring I.D	M.B.L . (KN)
30838	M6	40	5mm	15mm	8.2
30839	M6	60	5mm	15mm	8.2
30840	M6	80	5mm	15mm	8.2
30836	M8	80	6mm	20mm	14.5
30841	M8	100	6mm	20mm	14.5
30842	M10	100	8mm	25mm	22.6
30837	M10	120	8mm	25mm	22.6
30843	M12	120	10mm	30mm	32.6



Carbine Hook + Eyelet + Screw				
	AISI 31	6 Stainless 9	Steel	
	Part No	Diameter	Overall Length	Eyelet

Part No	Diameter	Overall Length	Eyelet	M.B.L. (KN)
30844	5mm	50mm	6mm	3.4
30845	6mm	60mm	7mm	5.1
30846	8mm	80mm	10mm	7.8
30847	10mm	100mm	13mm	11.8
30848	11mm	120mm	18mm	13.9
30858	12mm	140mm	18mm	1100kg
30859	13mm	160mm	20mm	1300kg





Spring	Spring Hook with Bow					
AISI 31	AISI 316 Stainless Steel					
Part No	Width (B)	Inside Diameter (iD)	Inside Width (iB1)	Length (L)	Width of Opening (C)	Breaking Load KG
30849	97mm	25mm	53mm	165mm	27mm	2820

Ring I.D



Galvanised Eyebolt						
Comes	Comes with a washer and a nut.					
Part No	Thread	Bolt Length	Length of thread	Ring I.D		
30600	M6	65mm	30mm	10mm		
30610	M8	110mm	70mm	12mm		
30620	M10	115mm	75mm	13mm		
30630	M12	135mm	90mm	14mm		



AISI 316 Stainless Steel

Part No

30912

30914



	(FE		
Eye Nuts			
AISI 31	ss Steel		
Part	Thread	Ring	Height






150mm 100mm

25mm

30640 M16

Ring Bolt SS

	Comes with a nut and washer.				
AISI 316 Stainless Steel					
	Part No	Ring Diameter	Ring I.D		
	34035	M6	80mm	6mm	35mm
	34040	M8	60mm	8mm	50mm
	34045	M10	100mm	10mm	50mm
	34050	M12	120mm	12mm	60mm
	34051	M12	60mm	12mm	60mm



Thread Bolt

Length



120mm

25mm

O Miles						
Stainless Stainl	Stainless Steel Studding 1m lengths					
Size	A2 Grade (308)	A4 Grad (316				
M4 x 1m	80910	809				
M5 x 1m	80912	809				

Size	Grade (308)	Grade (316)
M4 x 1m	80910	80911
M5 x 1m	80912	80913
M6 x 1m	80914	80915
M8 x 1m	80916	80917
M10 x 1m	80918	80919
M12 x 1m	80920	80921
M14 x 1m	81151	-
M16 x 1m	80922	80923
M20 x 1m	80924	80925
M24 x 1m	80926	80927



Galvanized Ring Bolt					
Comes	Comes with a nut and washer.				
Part Thread Length Ring ID Ring No Diag					
30650	M6	65mm	40mm	5mm	
30660	M8	110mm	50mm	8mm	
30670	M10	115mm	63mm	10mm	
30680	M12	135mm	63mm	12mm	
30690	M16	150mm	74mm	16mm	



M12

AISI 316 Stainless Steel			
Part No	Length (L1)	Inside Diameter (id)	Material Diameter (ø)
30928	25mm	12mm	3.9mm





U Bolt SS

Comes with a plate plus nuts and washers.

AISI 316 Stainless Steel

Part No	Thread	Overall Length	Centres	Thread Length
34090	M4	60mm	30mm	30mm
34095	M5	80mm	35mm	40mm
34110	M6	90mm	35mm	40mm
34120	M8	80mm	35mm	40mm
34125	M8	100mm	35mm	50mm
34130	M10	90mm	50mm	40mm
34132	M10	102mm	40mm	60mm
34135	M10	130mm	50mm	55mm
34136	M12	120mm	47mm	78mm
34137	M12	150mm	60mm	65mm







Ring Pl	ate SS			
AISI 30	4 Stainless	Steel		
Part	Loop	Base	Base	R


Part	Loop	Base	Base	Ring ID
No	Diameter	Width	Length	
34052	5mm	30mm	35mm	30mm
34053	6mm	35mm	40mm	35mm
34054	8mm	40mm	50mm	45mm



В	A
304 Stai	nloss

Stainless Steel Ring
AISI 304 Stainless Stee

7 (101 00 1 Ctall 11000 Ctool			
Part No	Α	В	
30879	5mm	40mm	
30880	6mm	45mm	
30882	8mm	50mm	
30884	10mm	75mm	



Stainless Steel Dee	,
Rings	

AISI 304 Stainless Steel			
Part No	Α	В	
30930	5mm	35mm	
30935	6mm	45mm	
30940	8mm	55mm	



Plate with ring.


Made of AISI 316 stainless steel.

Base 27x30mm

Size 19mm

Part No Description

96095	Eye	plate	with	ring



Made of high strength polished stainless steel .

0 0 1					
Part No	Description	Ring Section Ø	Breaking Load kg		
96313	Swivelling Half Ring 28 x 54mm	6.8mm	1500		
96314	Swivelling Half Ring 45 x 66mm	9.2mm	2200		





Eye Pad	Eye Pads				
AISI 304	AISI 304				
Part Loop No Thickness		Base Size			
34056	6mm	60 X 20mm			
34057	8mm	80 X 25mm			
34058	9mm	110 X 32mm			



Eye Plat	Eye Plates				
AISI 304					
Part No	Loop Thickness	Base Size			
34020	5mm	30 X 35mm			
34025	6mm	35 X 40mm			
34030	8mm	40 X 50mm			





Round Eye Plates				
AISI 304				
Part No	Base Diameter			
34031	5mm	33mm		
34032	6mm	40mm		
34033	8mm	50mm		



Turnbuckle Rigging Screws Fork & Fork AISI 316 Stainless Steel Machined

Part No	Thread	Pin Diameter	Length	Jaw Width	Breaking Load kg
34140	M5	5mm	135 - 195mm	6.5mm	460
34145	M6	6mm	160 - 230mm	7.5mm	910
34150	M8	8mm	180 - 255mm	11mm	1330
34155	M10	10mm	210 - 300mm	12mm	2180
34160	M12	12mm	270 - 380mm	14mm	2300
34165	M14	14mm	295 - 415mm	17mm	2190
34170	M16	16mm	340 - 480mm	17mm	5310



Swageless Eye Terminal SS AISI 316				
Part No	To fit wire (mm) Eye Diameter (mm			
34180	4mm	8mm		
34182	5mm	10mm		
34184	6mm	12.75mm		
34186	8mm	16mm		



Swageless Fork Terminal SS AISI 316				
Part No	To fit wire (mm)	Pin Diameter (mm)		
34190	4mm	6mm		
34192	5mm	8mm		
34194	6mm	10mm		
34196	8mm	12mm		



Copper Ferrule				
Part No	To fit wire			
33710	1.5mm			
33715	2.0mm			
33720	2.5mm			
33725	3.0mm			
33730	3.5mm			
33735	4,0mm			
33740	4.5mm			
33745	5.0mm			
33750	6.0mm			



Aluminium Ferrule				
Part No	To fit wire			
33760	2.0mm			
33765	3.0mm			
33770	4.0mm			
33775	5.0mm			
33780	6.0mm			





Galvanised Rigging Screws

Quality galvanised rigging screw twin law

Quality garvariised rigging sorew twirr jaw.				
Part No	Thread Diameter	Body Length	Jaw Width	
30740	M10	150mm	10mm	
30750	M12	195mm	13mm	
30760	M16	230mm	18mm	





AISI 316

(Bulldog Grips)

Part No	To fit wire	Thread Size	Grip Height	Grip Width
33845	2mm	M3	9mm	16mm
33850	3mm	МЗ	10mm	21mm
33855	4mm	M4	10mm	21mm
33860	5mm	M5	10mm	23mm
33865	6mm	M6	11mm	26mm



Electro Galvanized Wire Rope Grip

Din 741				
Part No	To fit wire	Thread Size	Grip Height	Grip Width
30500	5mm	M5	10mm	24mm
30505	6mm	M5	11mm	26mm
30510	8mm	M6	15mm	30mm
30515	10mm	M8	19mm	37mm
30520	12mm	M10	23mm	44mm

Stainless Steel Duplex Wire Rope Grips AISI 316

71101010			
Part No	To fit wire (mm)	Length	Width
33820	2mm	30mm	12mm
33825	3mm	36mm	14mm
33830	4mm	40mm	18mm
33835	5mm	50mm	20mm
33840	6mm	60mm	24mm

301

Rigging & Mooring



Stainless Steel Thimble			
AISI 316			
Part No	To fit wire	Length I.D	Width I.D
33790	2mm	12mm	7mm
33795	3mm	17mm	10mm
33800	4mm	18mm	11mm
33805	5mm	20mm	13mm
33810	6mm	26mm	15mm
33812	8mm	33mm	18mm
33814	10mm	43mm	23mm
33815	12mm	48mm	27mm
33816	16mm	57mm	38mm



Galvanised Thimble

B.S.464/1				
Part No	To fit wire	Length I.D	Width I,D	
30770	6mm	27mm	16mm	
30780	8mm	33mm	22mm	
30790	10mm	38mm	25mm	
30800	12mm	44mm	31mm	
30810	16mm	58mm	41mm	
30820	20mm	73mm	50mm	
30830	24mm	108mm	69mm	
30831	29mm	-	-	
30833	36mm	-	-	



Pelican Hook Stainless Steel				
AISI 316				
Part No Length Width				
30920 100mm 40mm				
30922 150mm 49mm				



Lacing	Button	
AISI 31	6 stainless steel.	
Lacing button for tarpaulin.		
Part No	Description	
96073	19mm Head x 12.5mm Length (M4 Hole)	



Wire Eye Strap

AISI 316. Made of stainless steel, forged and polished.

Part No	Description	Length	Centres
23300	5mm Wire Eye	50mm	37mm
23301	6mm Wire Eye	61mm	46mm
23302	8mm Wire Eye	67mm	49mm
23303	10mm Wire Eye	84mm	61mm



Sheet Eye Strap				
AISI 316				
Part No	Centres	Eye Width	Height	Hole Ø mm
23310	28mm	11mm	12mm	4mm
23311	34mm	15mm	14mm	5mm
23312	44mm	20mm	19mm	5mm









Cast Wire Eye Strap

Stainless Steel AISI 316.

Part No	Thickness	Length	Height	Centres
76216	5mm	48mm	15mm	35mm



Eye Strap A2 304 Stainless Steel 16mm Diameter 60mm Overall

Part No	Description	
76162	16mm Eye Strap	

Wire Rope Cleat Stainless steel A4 AISI 316. Width (B): 30mm.

Wire rope diameter (DS-Ø): 8 + 10mm Thread

(GW):M6 Thread

Length (L):110mm

Thickness (S):3mm

Part No Description 33866 8-10mm A4 316






Part No	Description	Hole Pitch	Hole Diameter
20286	Large lacing hook	12.7mm	4mm
20287	Small lacing hook	15.7mm	4mm



Part No	Description	Hole Pitch	Hole Diameter
20288	Long lacing hook	12.7mm	4mm
20289	Heavy duty short lacing hook	12.7mm	4mm







Stainless	Stainless Steel 316 Dropnose Pins				
Made of stainless steel; with spring locking mechanism and safety tooth.					
Part No	Dimensions (mm)	Part No	Dimensions (mm)		
23107	6mm x 50mm	23115	10mm x 50mm		
23108	6mm x 80mm	23116	10mm x 80mm		
23111	8mm x 50mm	23117	10mm x 100mm		
23112 8mm x 80mm 23118 10mm x 120mm					
23113	8mm x 100mm				



A2 Grade (308)	Diameter (mm)
33875	10mm
33876	14mm
33877	19mm
33878	28mm




A4 Grade (316)	Dimensions (mm)	A4 Grade (316)	Dimensions (mm)	A4 Grade (316)	Dimensions (mm)
33905	4.75 X 16mm	33915	7.9 X 19mm	33922	9.5 X 32mm
33907	4.75 X 19mm	33916	7.9 X 25mm	33923	9.5 X 38mm
33908	4.75 X 25mm	33917	7.9 X 32mm	33924	12.7 X 25mm
33910	6.35 X 18.5mm	33918	7.9 X 38mm	33925	12.7 X 31.8mm
33912	6.35 X 25mm	33920	9.5 X 19mm	-	
33913	6.35 X 35mm	33921	9.5 X 25mm	-	



Stainless Steel R Clips		
A4 Grade (316)	Description	
33880	2mm X 48mm	
33882	3mm X 70mm	
33883	4mm X 76mm	
33884	5mm X 100mm	
33885	6mm X 125mm	







LOOP® THIMBLES - Low Friction Rings

KOHLHOFF LOOP® Thimbles are simple thimbles which can be spliced into control lines. They are used to deflect sheets and control lines, or for lashings. KOHLHOFF LOOP® Thimbles are available in 6 different sizes. They are made of high strength aluminium.

Part No	Α	В	С	Max Rope (B)	Weight/	MWL/kg
53800	20mm	12mm	7mm	6mm	2	150kg
53801	24mm	11mm	11mm	8mm	5	1150kg
53802	30mm	12mm	13.5mm	10mm	7	1750kg
53803	40mm	20mm	17.5mm	12mm	12	2500kg
53804	50mm	25mm	22mm	18mm	39	4000kg
53805	60mm	30mm	26mm	24mm	64	5000kg



Mast Beads - Parrel Beads Sold Individually Made from Ash Wood

Part No	Description
20295	35mm mast beads
20296	25mm mast beads







Cam Strap		
Various colours and lengths.		
Part No Description		
53820	1.5M Yellow	
53822	3.5M Orange	
53824 5M Green		





3 slit AISI 304 buckle		
Part No Description		
96319	For straps up to 30mm	
96320	For straps up to 50mm	





Kingfisher Webbing Available in two colours and two widths. Sold by the metre. Width

vvidtri	Diue	DIACK
25mm	37682	37684
50mm	37694	37696



Stainless Steel Flat Eye Strap AlSI316			
Part No	Description	Dimensions	Centres
96317	30mm Flat Eye Strap	48 x 15mm	38mm
96318	50mm Flat Eye Strap	68.5 x 15mm	55mm



White Nylon Eye Strap		
Part No	Description	
96340	30mm Wide	
96341	40mm Wide	
96342	50mm Wide	

These fenders use a specially designed Majoni adaptor to inflate with a bicycle pump or car pump. The recommended pressure is 0.2 bar / 2.p psi which allows you to give a little visible pressure to the fender with your flat hand.



Star Fender White

Easy to inflate by ball-valve. Strong eyes.

Part No	Description	Length	Diameter
34200	Star Fender 1 White	45cm	12cm
34201	Star Fender 2 White	58cm	15cm
34202	Star Fender 3 White	62cm	21cm
34203	Star Fender 4 White	72cm	24cm
34204	Star Fender 5 White	90cm	30cm

Star Fender Socks



- · Pulled over the fender to prevent scratching of the hull.
- · Made of 100% acrylic, washable
- UV resistant
- Suits all Majoni "STAR" and "DROP" fenders.

Part No	Description
34215	Navy Fender Sock Fits Star 1 Navy
34216	Navy Fender Sock Fits Star 2 Navy
34217	Navy Fender Sock Fits Star 3 Navy
34218	Navy Fender Sock Fits Star 4 Navy
34219	Navy Fender Sock Fits Star 5 Navy

Heavy Duty Fender Navy



Extra strong heavy duty fenders with black head and ball valve. Head of the fender is massive so that they can be extra loaded.

Part No	Description	Length	Diameter
34233	Heavy Duty Fender 1 Navy	54cm	13cm
34234	Heavy Duty Fender 2 Navy	65cm	15cm
34235	Heavy Duty Fender 3 Navy	75cm	20cm
34236	Heavy Duty Fender 4 Navy	85cm	25cm



Star Fender Navy

Easy to inflate by ball-valve. Strong eyes.

Part No	Description	Length	Diameter
34209	Star Fender 1 Navy	45cm	12cm
34210	Star Fender 2 Navy	58cm	15cm
34211	Star Fender 3 Navy	62cm	21cm
34212	Star Fender 4 Navy	72cm	24cm
34213	Star Fender 5 Navy	90cm	30cm

Heavy Duty Fender White



Extra strong heavy duty fenders with black head and ball valve. Head of the fender is massive so that they can be extra loaded.

Part No	Description	Length	Diameter
34224	Heavy Duty Fender White	54cm	13cm
34225	Heavy Duty Fender White	65cm	15cm
34226	Heavy Duty Fender White	75cm	20cm
34227	Heavy Duty Fender White	85cm	25cm

Mega Fender



The Talamex Mega Fender by Majoni is a tough, double ended marine fender for vertical or horizontal use in two extra large sizes



Part No	Description	Length	Diameter
34359	Mega Fender White	110cm	35cm
34360	Mega Fender White	140cm	45cm
34361	Mega Fender Blue	110cm	35cm
34362	Mega Fender Blue	140cm	45cm

Pick Up Buoy



Anchor Marine Pick Up Buoy

Well designed mooring buoys, which are easy to grab by hand or with a boathook. The thimbled eye at the bottom ensures a strong line attachment. Signal Orange.

	3 - 3
Part No	Description
34400	8" Signal Orange Pick Up Buoy
34401	12" Signal Orange Pick Up Buoy

Pick Up Fender



Part No	Description	Length	Diameter
34328	Pick Up Fender Orange	35cm	15cm
34329	Pick Up Fender Orange	40cm	18cm

Bow Fender



Part No	Description	Width	Length
34323	Bow Fender White	33cm	34cm
34324	Bow Fender White	52cm	51cm
34325	Bow Fender Navy	33cm	34cm
34326	Bow Fender Navy	52cm	51cm

Stair Fenders



Part No	Description	Width	Diameter	Height
34376	2 Stair Fender White	25cm	12cm	55cm
34379	2 Stair Fender Blue	25cm	12cm	55cm
34377	3 Stair Fender White	25cm	12cm	75cm
34378	3 Stair Fender Blue	25cm	12cm	75cm



Dumpy Fenders



Practical and compact inflatable fender.

Part No	Description	Length	Diameter
34272	Dumpy Fender White	30cm	15cm
34273	Dumpy Fender White	36cm	18cm
34279	Dumpy Fender Navy	30cm	15cm
34280	Dumpy Fender Navy	36cm	18cm

Bow Fender White V Shape



Bow fender specially designed for extra protection at the bow of modern steep bow yachts.

Part No	Description	Width	Length
34327	Bow Fender White V Shape	14cm	60cm

Angled Fenders



Part No	Description
34380	White Angle Fender Diameter 15cm x Length 32cm
34381	Navy Angle Fender Diameter 15cm x Length 32cm

Heavy Duty Marker Buoy Orange



Extra strong heavy duty marker buoys fitted with a ball valve. Head of the fender is solid and also has stainless steel tubing for extra high load.

Part No	Description	Height	Diameter
34307	Heavy Duty Marker Buoy	48cm	35cm
34308	Heavy Duty Marker Buoy	62cm	45cm
34309	Heavy Duty Marker Buoy	73cm	55cm
34310	Heavy Duty Marker Buoy	88cm	65cm
34311	Heavy Duty Marker Buoy	105cm	85cm

Marker Buoy White



Part No	Description	Height	Diameter
34291	Marker Buoy White	48cm	35cm
34292	Marker Buoy White	62cm	45cm
34293	Marker Buoy White	73cm	55cm
34294	Marker Buoy White	88cm	65cm

Marker Buoy Orange



Part No	Description	Height	Diameter
34299	Marker Buoy Orange	48cm	35cm
34300	Marker Buoy Orange	62cm	45cm
34301	Marker Buoy Orange	73cm	55cm
34302	Marker Buoy Orange	88cm	65cm

Marker Buoy Yellow




Part No	Description	Height	Diameter
34303	Marker Buoy Yellow	21cm	15cm
34304	Marker Buoy Yellow	28cm	21cm
34305	Marker Buoy Yellow	36cm	26cm
34306	Marker Buoy Yellow	40cm	35cm

Short Orange Mooring Buoys



Part No	Description	Height	Diameter
34363	Short Orange Mooring Buoy	60cm	30cm
34364	Short Orange Mooring Buoy	80cm	40cm
34365	Short Orange Mooring Buoy	90cm	50cm
34366	Short Orange Mooring Buoy	100cm	60cm

Long Orange Mooring Buoys



Part No	Description	Height	Diameter
34367	Long Orange Mooring Buoy	115cm	40cm
34368	Long Orange Mooring Buoy	140cm	50cm
34369	Long Orange Mooring Buoy	165cm	60cm





Dock Fenders

In strong winds and strong currents safe and secure docking. Inflatable dock fender, UV resistible PVC. 6-screw attachment.

 $W \times H \times D \text{ cm}$ 110 x 24 x 24

Part No	Description
34383	White Dock Fender
34384	Navy Dock Fender



Flat fenders

Dock Corner Fenders Bow

For corners and roundings.

Inflatable, UV resistible PVC.

Description

White Dock Fender

Navy Dock Fender

Bendable till 90°

W x H x D cm

100 x 19 x 19 Part No

34385

34386

3-screw attachment

Made of an EVA 100+PE 30 sandwich (closed cell materials). They are floating and oil-resistant. Very sturdy and elastic, they can be used as emergency cushions or floating aids

Part No	Description
96070	Flat Fender 48 x 18 x 5cm
96071	Flat Fender 65 x 31 x 8cm
96072	Flat Fender 95 x 31 x 8cm



Flexible White Dock Fender

Special fender for swimming and jetties. Inflatable fender is foldable in two positions. Therefore it is also suitable for corners. 8 screw attachment system.

WxHxDcm

100 x 12 x 7

Part No	Description
34382	White Flexible Dock Fender



Rubber Mooring Snubber

Simply run mooring line through the ends and put three or four turns around the snubber to reduce sudden loads on cleats.

Part No	Description

Mooring Snubber for 14mm Rope

Adapter Valve Majoni



Part No	Description
34375	Adapter Valve

Spare Valve Majoni




Part No	Description
34374	Spare Valve

Aluminium Alloy Boathooks

High quality aluminium boathooks available in fixed lengths of 4ft and 6ft and also in a telescopic design with a variable reach from 3ft to 8ft.

Part No	Description
90581	4ft Fixed
90582	6ft Fixed
90580	3 - 8ft Telescopic





Telescopic Type

Aluminium Boat Hooks		
Part No	Description	
90574	Telescopic Anodised aluminium with PVC hook. Floats. 1.2M - 2.2M	
90575	Talamex Telescopic Boathook 1.2 - 2.1M	
90576	1.6M Fixed Anodised aluminium with PVC hook.	
90577	1.8M Fixed Anodised aluminium with PVC hook.	





Wooden Boat Hooks

A conical flagpole in pine

Truck with holes

Finished with special varnish

Part No Type

Plastic Head Wooden Pine Boathook 1.2M 90578

90579 Stainless Steel Head Wooden Pine Boathook 2.4M



8" Stainless Steel Boathook Head

Hook length: 1 3/4" (45mm)

Internal dia. at open end: 1

1/4" (32mm)

Part No 20291



Rubbing Strakes Stainless steel mirror polished (304). 3/4" & 1" Wide Rubbing Strakes, with a hole

Part No	Description	Part No	Description
76390	3/4" X 8"	76062	1" X 12"
76392	3/4" X 12"	76064	1" X 18"
76394	3/4" X 18"	76066	1" X 24"
76396	3/4" X 24"		




Plastic Convex / Keel Band

Tough, grey plastic convex in 10' (3.05m) lengths.

These plastic strips are usually stuck on with adhesive and screwed every 4 inches or so.

,		
Part No	Description	
91060	1" X 1/4" X 10' (25mm X 6mm X 3m)	
91061	1 1/2" X 1/4" X 10' (38mm X 6mm X 3m)	




Brass Convex

Often referred to as half round or keel band

Oiteiri	eleffed to as fiall found of keel band.
Part No	Size (Width x Depth x Length)
90990	6mm x 3mm x 3m
90995	10mm x 5mm x 3m
91010	15mm x 5mm x 3m
91020	3/4" X 3/16" X 10' (19mm X 5mm X 3m)
91030	3/4" X 1/4" X 10' (19mm X 6mm X 3m)
91035	19.05mm x 9.53mm x 3m
91040	1" x 3/16 x 3m

size of 8.



Brass Flat Strip		
Part No	Size	
90974	3/4" X 1/8" X 10' (19mm X 3.2mm X 3m)	
90975	1" X 1/8" X 10' (25mm X 3.2mm X 3m)	
90976	1 1/4" X 1/8" X 10' (32mm X 3.2mm X 3m)	
90980	1 1/2" X 1/8" X 10' (38mm X 3.2mm X 3m)	





	Metal rod			
Available in 3m lengths and in various types of materia			aterial.	
	Size	Brass	Copper	Bronze
	3/16 X 10' (5mm X 3m)	91254	-	-
	1/4" X 10' (6mm X 3m)	91255	91180	91279
	5/16" X 10' (8mm X 3m)	91260	91190	91280
	3/8" X 10' (10mm X 3m)	91265	91200	91282
	1/2" X 10' (12mm X 3m)	91270	91210	91284
	5/8" X 10' (16mm X 3m)	91275	91220	91286
	3/4" X 10' (19mm X 3m)	-	-	91288
	7/8" X 10' (22mm X 3m)	-	-	91290



Sailmakers Palms		
Part No Description		
35203 Left Handed		
35204 Right Hande		





Selma Splicing Set

- Stainless Steel
- For splicing modern rope constructions.
- 4 Needles: Ø: 1 x 4mm, 1 x 5.5mm,

1 x 7.5mm, 1 x 10mm

Part No Description

35202 Selma Splicing Set 4 Needles



Kevlar Scissors

These compact shears are designed to cut Kevlar and other tough materials. With a carbon steel blade, the scissors deliver a strong and precise cut. The compact design ensures excellent handling and control, while giving you the leverage you need for heavy-duty applications. These 6 1/4 inch shears are also ideal for cutting everyday fabrics and materials, and so are a highly versatile tool.

Part No	Description
35205	6 1/4" Kevlar Scissors



Sailmaker Needles

5 different needles per pack:

Upholsterers Leather Sail Tent Carpet Sack

Part No Description

35201 5 Sailmakers Needles



Bungee Cords		
Quality bungee cords available in 5 lengths.		
Part No	Description	
91650	12" (305mm)	
91655	15" (381mm)	
91660	18" (457mm)	
91665	24" (610mm)	
91670 36" (914mm)		



Shockcord

Kingfisher's shockcords have a braided cover and a natural rubber core. The ropes are made to have 100% stretch, have good abrasion resistance and are used for many applications.

Diameter (mm)	White & Blue Fleck	Black	
3	37550	37596	
4	37552	37598	
5	37554	37600	
6	37556	37602	
8	37560	37604	
10	37562	37606	
12	37564	-	



Shockcord Snaphooks

Black plastic hooks that attach cleverly to the end of shockcord or bungee

Part No	Suitable for sizes
91680	5 - 6mm
91682	8mm





Shockcord Ball loops		
Part No Description		
39157	75mm long	
39158	100mm long	
39159	150mm long	



8 Plait Standard Polyester Cord

Standard polyester cord is an ideal mouse line and general purpose rope. Polyester has a specific gravity of 1.38 which means it will not float. Polyester has no strength loss when wet, it is flexible and has good abrasion resistance. Polyester fibres also have good resistance to chemicals and have a melting point of 295°C.

chemicals and have a melting point of 250 O.					
Part No	Description	Min Break Strength (kgs)			
37641	8 Plait White Cord 1.5mm	70			
37642	8 Plait White Cord 2mm	115			
37645	8 Plait White Cord 3mm	185			
37646	8 Plait Black Cord 3mm	185			
37650	8 Plait White Cord 4mm	340			
37651	8 Plait Black Cord 5mm	540			
37652	8 Plait White Cord 5mm	540			



RIG12 Dyneema Core

Rig12 is a 12 strand Dyneema® SK78 single braid with PU Coating for improved protection against abrasion and the elements. This low stretch line is very easy to splice and is ideal for halyards, control lines, lashings and

Diameter (mm)	Black	Breaking Strain (kg)
2	39050	450
2.5	39051	670
3	39052	900
4	39053	1400
5	39054	2400
6	39055	3200
8	39056	5600



Floatline - 8 Plait Polypropylene Rope

Floatline is single 8 plait braided multi-filament Polypropylene rope with no core. This rope is made in bright colours for high visibility, floats and is an ideal safety rope.

Diameter (mm)	Yellow & Red	Breaking Strain (kg)
6	39110	550
8	39111	870
10	39112	1300



3 Strand Polyester

3 Strand Polyester is soft, strong and is an ideal mooring rope, it is also very easy to splice. All our polyester ropes are now heat set to give better balance and lower stretch.

Diameter (mm)	White	Navy	Breaking Strain (kg)
6	39121	-	650
8	39122	39132	1150
10	39123	39133	1850
12	39124	39134	3000
14	39125	39135	3400
16	39126	39136	5000
18	39127	-	6400
20	39128	39138	8400
24	39129	-	11500



Classic Buff 3 Strand Polyester

3 Strand Polyester classic, is produced using Matt Polyester yarns this makes the product feel very traditional. This rope is easy to splice and is very soft and strong and is ideal for rigging on classic sailing yachts.

Diameter (mm)	Classic Beige	Breaking Strain (kg)
6	39140	556
8	39141	1016
10	39142	1426
12	39143	1900
14	39144	2800
16	39145	3450
18	39146	4300
20	39147	5800



3 strand Nylon

This rope is an ideal anchor and mooring rope. It is high strength yet flexible, splices easily and coils neatly.


Diameter (mm)	White	Breaking Strain (kg)
10	39150	2080
12	39151	3800
14	39152	4800
16	39153	5900
18	39154	6800
20	39155	8400
24	39156	12400



White 8 Strand Anchorplait Rope

This rope is made from Nylon and is an ideal anchor and mooring rope. It is high strength yet flexible, splices to chain easily and coils neatly.

Diameter (mm)	White	Breaking Strain (kg)
14	39160	4800
16	39161	5900
18	39162	6800



Kingfisher Webbing

Available in two colours and two widths. Sold by the metre.

Width (mm)	Blue	Black
25	37682	37684
50	37694	37696



Kingfisher Guardrail Netting 1m wide 50mm mesh

Part No	Description		
39179	1m wide		



Kingfisher Pre spliced Navy Dockline

Dockline is a braided mooring line, it has a polyester cover and a braided nylon core. Due to the construction of the rope it has a good abrasion resistance while also being very strong and comfortable to handle.

Part No	Diameter mm	Length M
39180	12mm	5M
39181	12mm	10M
39182	14mm	10M
39183	16mm	10M



ROPES TESTED TO THE LIMIT

All our ropes are tested to the limit. On the water, in some of the world's greatest yacht races, and off the water at the factory where we test all ropes to destruction. We always publish minimum spliced breaking loads as the only loads that are achievable by, and relevant to, the user.

YACHTROPES.CO.UK















Braid on Braid

Kingfisher's heat set Braid on Braid Polyester is an ideal cruising rope. It is good on the hands and easy to splice. Braid on Braid has a low stretch braided Polyester core with an abrasion resistant braided Polyester cover. After braiding, the rope is heat set under load to reduce stretch. It is ideal for sheets, halyards, control lines and many general purpose applications. Sold by the metre.

Diameter (mm)		Blue Fleck	Yellow Fleck	Green Fleck			Solid Beige	Solid Red	Breaking Strain (kg)
6	39000	39004	39008	39012	39016	39020	39024	39028	820
8	39001	39005	39009	39013	39017	39021	39025	39029	1300
10	39002	39006	39010	39014	39018	39022	39026	-	2400
12	39003	39007	-	39015	39019	39023	39027	-	3200



Dyneema Cruise

This rope is made with a HT Polyester braided cover, and a braided Dyneema® core, all lines have intermediate covers to reduce core / cover slippage. This rope has been designed as an upgrade to our 100% Polyester ropes and is lighter with higher strength and lower stretch.

Diameter (mm)	Blue	Red	Green	Black	Breaking Strain (kg)
6	39030	39034	39038	39041	1100
8	39031	39035	39039	39042	2100
10	39032	39036	39040	39043	3400
12	39033	39037	-	-	5200



Evolution Race 78 - Dinghy Dyneema

This rope has a high performance Dyneema® SK78 12 strand coated core that is high strength, low stretch and low creep. It has a hard wearing HT braided Polyester cover and is easy to splice.

Diameter (mm)	Red	Blue	Yellow	Gold	Breaking Strain (kg)
2	39060	39065	39070	39075	200
3	39061	39066	39071	39076	370
4	39062	39067	39072	39077	820
5	39063	39068	39073	39078	1275
6	39064	39069	39074	39079	1885





Evolution Performance - Control Lines/Sheets/Halyards/Dinghies/Small Boats

Evolution Performance has a low stretch Polyester core with hard wearing 16 plait Polyester cover. It is ideal for control lines, sheets and halyards on dinghies and small sailboats. Similar to sprintline.

Diameter (mm)	Red	Blue	White	Black	Purple	Yellow	Orange	Breaking Strain (kg)
3	39080	39084	39088	39092	39096	39100	39104	175
4	39081	39085	39089	39093	39097	39101	39105	365
5	39082	39086	39090	39094	39098	39102	39106	500
6	39083	39087	39091	39095	39099	39103	39107	800



Evolution Performance Mini Spools

Evolution Performance is a low stretch polyester rope with a hardwearing cover.

Diameter (mm)	White	Red	Blue	Yellow	Orange	Purple	Black
3	39166	39167	39168	39169	39170	39171	39172





Braided Whipping Twine
Waxed polyester braided whipping twine.

Diameter (mm)	White	Red	Blue	Black	Classic/ Beige
1	39173	39175	39176	39177	39178
1.4	39174	-	-	-	-



Plastic Body Blocks for 6mm Rope (Plain Bearing)















53300

53301

53303

53304

53305

53306

6mm Plain Bearing RWO Blocks

Series 19 Micro Blocks offer a compact, comprehensive range for small lines everywhere. The bearings ensure longer life, even under arduous seawater sailing conditions

Part No	RWO	Description	Sheave Diameter (mm)	Working Load (kg)	Breaking Load (kg)
53300	R7101	19mm Plain Bearing Looptop Single	19	285	570
53301	R7129	19mm Plain Bearing Looptop Single + Fork	19	285	570
53302	R7102	19mm Plain Bearing Looptop Single +Becket	19	285	570
53303	R7111	19mm Plain Bearing Looptop Double	19	285	570
53304	R7112	19mm Plain Bearing Looptop Double + Becket	19	285	570
53305	R7114	19mm Plain Bearing Looptop Triple	19	285	570
53306	R7115	19mm Plain Bearing Looptop Triple + Becket	19	285	570

Plastic Body Blocks for 6mm Rope (Ball Bearing)















53316

53317

53318

53320 53319

53321

53322

6mm Ball Bearing RWO Blocks

Series 19 Micro Blocks offer a compact, comprehensive range for small lines everywhere. The bearings ensure longer life, even under arduous seawater sailing conditions.

Part No	RWO	Description	Sheave Diameter (mm)	Working Load (kg)	Breaking Load (kg)
53316	R5101	19mm Ball Bearing Looptop Single	19	130	450
53317	R5129	19mm Ball Bearing Single + Fork	19	130	450
53318	R5102	19mm Ball Bearing Looptop Single + Becket	19	130	450
53319	R5111	19mm Ball Bearing Double	19	130	450
53320	R5112	19mm Ball Bearing Double + Becket	19	130	450
53321	R5120	19mm Ball Bearing Triple	19	130	450
53322	R5122	19mm Ball Bearing Triple + Becket	19	130	450



Plastic Body Blocks for 8mm Rope (Plain Bearing)















8mm Plain Bearing RWO Blocks

Series 28 blocks are available in a wide range of configurations and offer the primary demands in design, high performance and strength with a compact design.

Part No	RWO	Description	Sheave Diameter (mm)	Working Load (kg)	Breaking Load (kg)
53331	R7206	28mm Plain Bearing Single Cheek Block	28mm	430	850
53332	R7229	28mm Plain Bearing Single	28mm	430	850
53333	R7230	28mm Plain Bearing Single + Becket	28mm	430	850
53334	R7211	28mm Plain Bearing Double	28mm	430	850
53335	R7214	28mm Plain Bearing Triple	28mm	430	850
53336	R7215	28mm Plain Bearing Triple + Becket	28mm	430	850

Plastic Body Blocks for 8mm Rope (Ball Bearing)















Part No	RWO	Description	Sheave Diameter (mm)	Working Load (kg)	Breaking Load (kg)
53345	R5207	28mm Ball Bearing Single + Swivel	28mm	140	850
53346	R5201	28mm Ball Bearing Looptop Single	28mm	140	850
53347	R5202	28mm Ball Bearing Looptop Single + Becket	28mm	140	850
53348	R5211	28mm Ball Bearing Double	28mm	140	850
53349	R5212	28mm Ball Bearing Double + Becket	28mm	140	850
53350	R5221	28mm Ball Bearing Triple	28mm	140	850
53351	R5222	28mm Ball Bearing Triple + Becket	28mm	140	850



Plastic Body Blocks for 10mm Rope (Plain Bearing)















53361

53362

53363

53364

53365

53366

53367

10mm Plain Baring RWO Blocks

Series 38 Blocks are available in a wide range of configurations and offer the primary demands in design, high performance and strength with a compact size.

Part No	RWO	Description	Sheave Diameter (mm)	Working Load (kg)	Breaking Load (kg)
53361	R7303	38mm Plain Bearing Single	38mm	450	900
53362	R7304	38mm Plain Bearing Single + Becket	38mm	450	900
53363	R7311	38mm Plain Bearing Double	38mm	450	900
53364	R7312	38mm Plain Bearing Double + Becket	38mm	450	900
53365	R7314	38mm Plain Bearing Triple	38mm	450	900
53366	R7315	38mm Plain Bearing Triple + Becket	38mm	450	900
53367	R7307	38mm Plain Bearing Single Swivel	38mm	450	900

Plastic Body Blocks for 10mm Rope (Ball Bearing)







53379



53380



53381



53382



53383

10mm Ball Bearing RWO Blocks

Series 38 Blocks are available in a wide range of configurations and offer the primary demands in design, high performance and strength with a compact size.

Part No	RWO	Description	Sheave Diameter (mm)	Working Load (kg)	Breaking Load (kg)
53378	R5303	38mm Ball Bearing Single + Swivel	38mm	230	900
53379	R5304	38mm Ball Bearing Single + Swivel + Becket	38mm	230	900
53380	R5311	38mm Ball Bearing Double + Swivel	38mm	230	900
53381	R5312	38mm Ball Bearing Double + Swivel + Becket	38mm	230	900
53382	R5321	38mm Ball Bearing Triple + Swivel	38mm	230	900
53383	R5322	38mm Ball Bearing Triple + Swivel + Becket	38mm	230	900



Plastic Body Blocks for 10mm Rope (Plain Bearing)





















10mm P	10mm Plain Bearing RWO Blocks								
Series 4	5 Blocks a	are available in numerous versions including a ma	tching ratchet block.						
Part No	RWO	Description	Sheave Diameter (mm)	Working Load (kg)	Breaking Load (kg)				
53393	R7401	45mm Plain Bearing Looptop Single	45	600	1200				
53394	R7402	45mm Plain Bearing Looptop Single + Becket	45	600	1200				
53395	R7403	45mm Plain Bearing Single + Swivel	45	600	1200				
53396	R7404	45mm Plain Bearing Single + Swivel + Becket	45	600	1200				
53397	R7411	45mm Plain Bearing Double	45	600	1200				
53398	R7413	45mm Plain Bearing Double + Becket	45	600	1200				
53399	R7416	45mm Plain Bearing Triple	45	600	1200				
53400	R7415	45mm Plain Bearing Triple + Becket	45	600	1200				
53401	R7421	45mm Plain Bearing Fiddle + Swivel	45	600	1200				
53402	R6353	Becket For 45mm Fiddle	45	600	1200				

Plastic Body Blocks for 10mm Rope (Ball Bearing)











Part No	RWO	Description	Sheave Diameter (mm)	Working Load (kg)	Breaking Load (kg)
53412	R5403	45mm Ball Bearing Single + Swivel	45	225	900
53413	R5404	45mm Ball Bearing Single + Swivel + Becket	45	225	900
53414	R5411	45mm Ball Bearing Double + Swivel	45	225	900
53415	R5412	45mm Ball Bearing Double + Swivel + Becket	45	225	900
53416	R5421	45mm Ball Bearing Fiddle	45	225	900



Plastic Body Blocks for 12mm Rope (Plain Bearing)

















12mm Plain Bearing RWO Blocks

Series 57 Blocks are available in numerous versions and are useful wherever a powerful compact multitackle is required.

Part No	RWO	Description	Sheave Diameter (mm)	Working Load (kg)	Breaking Load (kg)
53426	R7503	57mm Plain Bearing Single + Swivel	57	850	1700
53427	R7504	57mm Plain Bearing Single + Swivel + Becket	57	850	1700
53428	R7511	57mm Plain Bearing Double + Swivel	57	850	1700
53429	R7512	57mm Plain Bearing Double + Swivel + Becket	57	850	1700
53430	R7514	57mm Plain Bearing Triple + Swivel	57	850	1700
53431	R7515	57mm Plain Bearing Triple + Swivel + Becket	57	850	1700
53432	R7521	57mm Plain Bearing Fiddle + Swivel	57	850	1700
53433	R6390	Becket for 53432	N/A	N/A	N/A

Plastic Body Blocks for 12mm Rope (Ball Bearing)















Part No	RWO	Description	Sheave Diameter (mm)	Working Load (kg)	Breaking Load (kg)
53443	R5500	57mm Ball Bearing Single + Swivel	57	230	900
53444	R5501	57mm Ball Bearing Single + Swivel + Becket	57	230	900
53445	R5511	57mm Ball Bearing Double + Swivel	57	230	900
53446	R5512	57mm Ball Bearing Double + Swivel + Becket	57	230	900
53447	R5514	57mm Ball Bearing Triple + Swivel	57	230	900
53448	R5521	57mm Ball Bearing Fiddle	57	230	900



Plastic Body Blocks for 14mm Rope (Plain Bearing)









53458

53459

53460

53461

14mm Plain Bearing RWO Blocks

Series 76 Plain Bearing Blocks are robust, strong and reliable.

Part No	RWO	Description	Sheave Diameter (mm)	Working Load (kg)	Breaking Load (kg)
53458	R7603	76mm Plain Bearing Single + Swivel	76mm	1500	3000
53459	R7604	76mm Plain Bearing Single + Swivel + Becket	76mm	1500	3000
53460	R7611	76mm Plain Bearing Double + Swivel	76mm	1500	3000
53461	R7612	76mm Plain Bearing Double + Swivel + Becket	76mm	1500	3000

Plastic Body Blocks for 14mm Rope (Ball Bearing)











53471

53472

53473

53474

53475

14mm Ball Bearing RWO Blocks

Series 76 Ball Bearing Blocks are available in many versions and are used wherever a powerful tackle is required.

Part No	RWO	Description	Sheave Diameter (mm)	Working Load (kg)	Breaking Load (kg)
53471	R5600	76mm Ball Bearing Single + Swivel	76mm	365	1450
53472	R5601	76mm Ball Bearing Single + Swivel + Becket	76mm	365	1450
53473	R5611	76mm Ball Bearing Double + Swivel	76mm	365	1450
53474	R5612	76mm Ball Bearing Double + Swivel + Becket	76mm	365	1450
53475	R5614	76mm Ball Bearing Triple + Swivel	76mm	365	1450



Stainless Steel Blocks for 8mm Rope (Plain Bearing)













53490

53491

8mm Stainless Steel Plain Bearing RWO Blocks

Stainless Blocks 25 are for general purpose use. They are economical, reliable and extremely versatile, with a variety of head fixings and mounts; making them ideal for small marine and industrial rope applications.

Part No	RWO	Description	Sheave Diameter	Working Load (kg)	Breaking	Rope
			(mm)	Load (kg)	Load (kg)	Size
53485	R1000	SS Block 25 Plain Bearing Single Open	25	N/A	650	8mm
53486	R1410	SS Block 25 Plain Bearing Single Bullet	25	N/A	650	8mm
53487	R1610	SS Block 25 Single General	25	N/A	650	8mm
53489	R4960	SS Block 25 Single V Jammer	25	N/A	650	8mm
53490	R1080	SS Block 25 Double	25	N/A	650	8mm
53491	R1100	SS Block 25 Triple	25	N/A	650	8mm

Aeroblocks for 8mm Rope (Plain Bearing)







53502



53503



53504

Part No	RWO	Description	Sheave Diameter (mm)	Working Load (kg)	Breaking Load (kg)	Rope Size
53501	R1121	25mm Aeroblock Single Loop	25	N/A	600	8mm
53502	R1122	25mm Aeroblock Single + Becket	25	N/A	600	8mm
53503	R1123	25mm Aeroblock Single + Swivel	25	N/A	600	8mm
53504	R1124	25mm Aeroblock Single + Swivel + Becket	25	N/A	600	8mm



Aeroblocks for 10mm Rope (Plain Bearing)









53514

53515

53516

53517

Part No	RWO	Description	Sheave Diameter (mm)	Working Load (kg)	Breaking Load (kg)	Rope Size
53514	R1131	25mm Aeroblock 10mm Single Looptop	25	N/A	600	10mm
53515	R1132	25mm Aeroblock 10mm Single + Becket	25	N/A	600	10mm
53516	R1133	25mm Aeroblock 10mm Single + Swivel	25	N/A	600	10mm
53517	R1134	25mm Aeroblock 10mm Single + Swivel + Becket	25	N/A	600	10mm

Series 28 Nova for 8mm Rope (Plain Bearing)



R7207 28 Nova Swivel & M4 Screw Shackle RWO Block

Series 28 plain bearing single swivel block, maximum line size 8mm, maximum working load 430kgs.

Part No Description 53573 R7207 8mm Swivel Block



R7216 – 28 Nova Single Rubber Mounted RWO Block

Series 28 plain bearing single 2 hole fixing tang block, maximum line size 8mm, maximum working load 430kgs

Part No Description

53574 R7216 8mm Swivel Block











53531

53532

53533

Servo Camcleats

With their unique cam design that requires only downward pressure to function, The Delrin® cams, which incorporate integral stainless steel inserts, provide maximum holding power. A well proven Olympic cleat that functions well with the new hi-tech ropes such as Spectra, Vectran & Zylon, and the steel grips do not suffer from rope burn.

Part No	RWO	Description	Centres (mm)	Max Load (kg)	Rope Size
53531	SC110	Servo 11 Camcleat	27	100	3-7mm
53532	SC220	Servo 22 Camcleat	38	200	6-12mm
53533	SC330	Servo 33 Camcleat	52	220	10-16mm





53534

53535

Grippit Camcleats

Two sizes are available. The cams are in anodised aluminium alloy with hi-tech 'acetal' axial bearing surfaces, to ensure minimum weight and good operational resilience to corrosion and extreme usage.

Part No	RWO	Description	Centres (mm)	Maximum Working Load (kg)	Rope Size
53534	R3610	Grippit Camcleat Small	27	100	3-7mm
53535	R3640	Grippit Camcleat Medium	38	160	5-12mm









53527

53528

53529

53530

Camcleat Accessories

Maximum use has been made of hi-tech marine grade materials to cater for modern rope line technology.

Part No	Description
53527	Camcleat Varishim 38mm Centres (R3503)
53528	Camcleat Small Wedge 27mm Centres (R3618)
53529	Camcleat Medium Wedge 38mm Centres (R3648)
53530	Camcleat Large Wedge 52mm Centres (SC338)

Servo Fairleads









53537

53538

53539



53540





53542

Part No	RWO	Description
53536	SC114	Servo 11 SS Top Fairlead
53537	R3612	Servo 11 SS Rear Fairlead
53538	SC115	Servo 11 SS Front Fairlead
53539	SC224	Servo 22 SS Top Fairlead
53540	R3642	Servo 22 SS Rear Fairlead
53541	SC225	Servo 22 SS Front Fairlead
53542	SC334	Servo 33 SS Top Fairlead



Ball Stoppers Sold Each

Part No	Description
53550	Ball Stopper Green 4mm
53551	Ball Stopper Green 6mm
53552	Ball Stopper Green 8mm

Part No	Description
53553	Ball Stopper Red 4mm
53554	Ball Stopper Red 6mm
53555	Ball Stopper Red 8mm





Black moulded bullseye with a stainless steel ferrule.

Aperture 6mm.

Hole centre15mm.

Height 14mm

Manufactured from high load bearing acetal resin for use to re-direct lines.

Part No Description

53572 R2934S Bullseye 5mm



14mm Bullseye

Black moulded bullseye with a stainless steel ferrule.

Aperture 14mm.

Hole centre 24mm.

Height 23mm.

Manufactured from high load bearing acetal resin for use to re-direct lines

Part No Description

R2944S Bullseye 14mm 53575



18mm Bullseye

Black moulded bullseye with a stainless steel ferrule.

Aperture 18mm.

Hole centre 33mm.

Height 30mm.

Manufactured from high load bearing acetal resin for use to re-direct lines

Part No Description

R2984S Bullseye 14mm




Mightystik 57-77Cm Telescopic Tiller Extension		
Part No	Description	
53570	RWO R0531ST Tiller Extension 57 - 77CM	

Safety & Security





- 30% smaller (typ) by volume*
- Easily fits in lifejacket
- Retractable Antenna
- 7 Year Battery Life
- 7 year warranty*
- 24+ hour operational life
- High brightness strobe light >1candela
- 66 channel GPS receiver




Wherever you are, at sea, on land, the rescueME PLB1 provides the reassurance that global emergency services can be alerted by the press of a button.

The rescueMe PLB1 can be operated with a single hand in even the most challenging situations. A simple spring loaded flap covers the activation button preventing inadvertent use.

rescueME PLB1 works with the only officially recognised worldwide dedicated search and rescue satellite network (operated by Cospas Sarsat). As this is funded by governments there are NO CHARGES to use this service.

When activated the rescueME PLB1 transmits your position and your ID to a Rescue Coordination Center via satellite link. Rescue services nearest to you are promptly notified of your emergency and regularly advised of your current location to assist prompt rescue.





Part No	Description
90631	EPIRB1 Emergency Position
	Indicating Radio Beacon

30%(typ) smaller

- 10 year battery life
- 48+ hours operational life
- 5 year warranty
- Fast accurate positioning with 66 channel GPS
- Retractable antenna
- Quick release bracket
- Secure lanyard

The rescueME EPIRB1 provides peace of mind with an impressive 10 year battery life. The world's most compact EPIRB can always be on hand, as its small size allows it to be easily retained within its quick release bracket or placed in an emergency grab-bag or life raft.


A simple protective tab over the operating keys prevents inadvertent activation, yet allows for easy operation when required. The rescueME EPIRB1 also features two high brightness strobes to maximise visibility in low light conditions.

The retractable antenna provides maximum protection and a reduced outline for stowage. When required the antenna is easily deployed with a gentle pull.

For longer offshore or ocean passages, the Ocean Signal E100G EPIRB offers an exceptional 96 hour operational life with the option of an automatic release housing (mandatory for vessels approved under SOLAS regulations).


*30% smaller, compared to other products approved to recognised standards (July 2014) † Subject to warranty statement.





The dimensions are 178mm (H with antenna stowed) x 89mm dia [100mm over the lanyard tab)

inflation, sending the first alert within 15 seconds.



Part No	Description
90632	MOB1 Man Over Board Personal Locator

Introducing the world's smallest AIS MOB device with integrated DSC – the rescueME MOB1 from Ocean Signal. The MOB1 is compatible with even the most compact inflatable life-jackets.

The MOB1 is intended to be installed within the life-jacket and will activate automatically on

- Integrated DSC transmitter
- (digital selective calling)
- The integrated strobe light ensures maximum visibility in low light conditions.
- 30% (typ) smaller than competitors

The MOB1 communicates with the vessel you have been separated from and other vessels in the vicinity (up to 5 miles range dependent on conditions). To alert rescue authorities, an alternative product the rescueME PLB1 communicates directly via a dedicated search and rescue satellite network.

Automatic activation

In an emergency rescueME MOB1 provides 2 methods of rapidly communicating your position, accurate to a few metres, back to the vessel, plus providing visual indication via its

Simple lifejacket integration

built in strobe light. The best chance of rapid rescue if you fall overboard comes from your own vessel. Your crew

7 year battery life

needs to be immediately aware of the incident and keep track of your position whilst recovery is carried out. Even in the most moderate of seas it is alarming how quickly a visual sighting of a man overboard can be lost.

24+ hours operational life

Once activated your MOB1 will transmit an alert to all AIS receivers and AIS enabled plotters in the vicinity. The integrated GPS ensures that your precise location is sent to your vessel and any others that may be assisting.

5 year warranty

An additional feature of the MOB1, is its ability to activate the DSC alarm on your vessels VHF, alerting your crew to the situation.



The rescueME EDF1 electronic distress flare offers users a safe and long-lasting solution to visual signalling in an emergency.



The unique lens design combined with the use of advanced LEDs and highly efficient circuit technology ensures a constant level of light output throughout the life of the user replaceable

The light output is a beam of over 30° throughout the full 360° azimuth, providing in excess of 6 times more light coverage than other electronic flares. Light is also distributed throughout the hemisphere above the unit to ensure visibility from the air.

Part Description No 90633 EDF1

Unlike single use pyrotechnic flares the rescueME EDF1 can be used repeatedly in any of its four modes, ensuring continued visibility is maintained over a longer period. The unit is both safe to store and operate while also eliminating any worries associated with disposal.

Flectronic Distress Flare

The compact size and rugged design means the rescueME EDF1 is the perfect safety product for a grab bag, life raft or hiker's backpack.









ALPHA 600 Aerosol Extinguisher (0.6kg)

Compact aerosol factory sealed BC Dry Powder fire extinguishers.

Manufactured in the UK.

BSI certified to BS 6165:2002 and Kitemarked.

5 year warranty.

Easy low cost maintenance.

Suitable for B and C Fire classifications.

Safe for use on electrical equipment.

Aluminium lightweight body.

Controlled discharge.

Alpha - Supplied with durable plastic (Polypropylene) bracket.

Part No Description

92056 Alpha 600 0.6Kg 13B







Compact aerosol factory sealed BC Dry Powder fire extinguishers.

Manufactured in the UK.

BSI certified to BS 6165:2002 and Kitemarked.

5 year warranty.

Easy low cost maintenance.

Suitable for B and C Fire classifications.

Safe for use on electrical equipment.

Aluminium lightweight body.

Controlled discharge.

Beta - Supplied with coated metal spring clip.

Part No Description

92057 BETA BC DRY POWDER 0.95KG EXTINGUISHER

















ABC Powder Extinguisher 'Ships Wheel' (1kg)

Refillable ABC Dry Powder Extinguishers suitable for use in the home, office, vehicles, boats and many commercial and industrial applications.

Certified by DNV to MED 'Ships Wheel' - meets the recommendations of the Royal Yachting Association and British Waterways Joint Boat Safety Scheme.

Accredited to EN3 by BSI and Kitemarked.

Certified by DNV to MED 'Ships Wheel'.

5 year warranty.

Stored pressure - Easy low-cost maintenance.

Suitable for A, B and C Fire classifications.

Safe for use on electrical equipment.

Controlled discharge.

Supplied with powder coated, steel wire bracket.

Part No Description

92060 FBP1 FIRE EXTINGUISHER ABC 8A 55B 1KG





















ABC Powder Extinguisher 'Ships Wheel' (2kg)

Refillable ABC Dry Powder Extinguishers suitable for use in the home, office, vehicles, boats and many commercial and industrial applications.

Certified by DNV to MED 'Ships Wheel' - meets the recommendations of the Royal Yachting Association and British Waterways Joint Boat Safety Scheme.

Accredited to EN3 by BSI and Kitemarked.

Certified by DNV to MED 'Ships Wheel'.

5 year warranty.

Stored pressure - Easy low-cost maintenance.

Suitable for A, B and C Fire classifications.

Safe for use on electrical equipment.

Controlled discharge.

Supplied with powder coated, steel wire bracket.

Part No Description

92061 FBP2 FIRE EXTINGUISHER ABC 13A/70



bay













Automatic Extinguisher - ABC Dry Powder (1kg)

ABC Dry Powder Automatic fire Suppression Units commonly used to protect machinery/plant and where there is a risk of fire such as in boat/vehicle engine compartments.

Compact and economical automatic extinguisher.

5 year warranty.

Stored pressure - Easy low-cost maintenance.

Suitable for A, B and C class fires.

Safe for use on electrical equipment.

Supplied with powder coated, steel wire bracket.

Part No	Description	
92062	FRA-PI FIRE EXTINGUISHER	ABC 13A















Automatic Extinguisher – ABC Dry Powder (2kg)

ABC Dry Powder Automatic fire Suppression Units commonly used to protect machinery/plant and where there is a risk of fire such as in boat/vehicle engine compartments.

Compact and economical automatic extinguisher.

5 year warranty.

Stored pressure - Easy low-cost maintenance.

Suitable for A, B and C class fires.

Safe for use on electrical equipment.

Supplied with powder coated, steel wire bracket.

Part No Description

92063 FBA-P2 FIRE EXTINGUISHER ABC 13A/70B













Automatic Extinguisher - Clean Agent Gas (1kg)

Ozone friendly Automatic fire Suppression Units commonly used to protect machinery/plant and where there is a risk of fire such as in boat/vehicle engine compartments.

Clean agent (Halon replacement).

Zero ozone depletion.

5 year warranty.

Suitable for B and C class fires.

Safe for use on electrical equipment.

Supplied with powder coated, steel wire bracket.

Part No Description

92064 FBA-GI AUTO FIRE EXTINGUISHER BC














Ozone friendly Automatic fire Suppression Units commonly used to protect machinery/plant and where there is a risk of fire such as in boat/vehicle engine compartments.

Clean agent (Halon replacement).

Zero ozone depletion.


5 year warranty.

Suitable for B and C class fires.

Safe for use on electrical equipment.

Supplied with powder coated, steel wire bracket.





92065 FBA-GI.5 AUTO FIRE EXTINGUISHER BC













Automatic Extinguisher - Clean Agent Gas (2kg)

Ozone friendly Automatic fire Suppression Units commonly used to protect machinery/plant and where there is a risk of fire such as in boat/vehicle engine compartments.

Clean agent (Halon replacement).

Zero ozone depletion.

5 year warranty.

Suitable for B and C class fires.

Safe for use on electrical equipment.

Supplied with powder coated, steel wire bracket.

Part No Description

92066 FBA-G2 AUTO FIRE EXTINGUISHER BC





Fire Blanket (100 x 100cm)

A range of glass fibre fire blankets for domestic and light industrial use. Can also be used on fires involving personal clothing. Manufactured in the UK.

BSI certified to BS EN 1869:1997 and Kitemarked.

Supplied in a red hard plastic container for easy surface mounting

Part No

92055



Automatic Extinguisher - Clean Agent Gas (4kg or 6kg)

Ozone friendly Automatic fire Suppression Units commonly used to protect machinery/plant and where there is a risk of fire such as in boat/vehicle engine compartments.

Clean agent (Halon replacement).

Zero ozone depletion.

5 year warranty.

Suitable for B and C class fires.

Safe for use on electrical equipment.

Supplied with powder coated, steel wire bracket.

Part No	Description
96430	FBA-G4 4kg Auto Fire Extinguisher
96431	FBA-G6 6kg Auto Fire Extinguisher



Vetus Fire Port (FIREPORTB)

This fire port permits a fire extinguisher to be discharged into the engine space, or any other enclosed area. In the event of a fire, the extinguisher nozzle can be inserted through the port in complete safety, thus avoiding fuelling the fire by opening the compartment and minimising risk to the crew.

Recommended by CE and ABYC directives

Also suitable for outboard motors

Made of UV and seawater resistant synthetic material Cut-out diameter: Ø 38 mm. Outside dimensions: Ø 76 mm.

Part No

58231





Vetus Gas & Carbon Monoxide Detector 12/24V

The gas detector model GD1000 offers a gas detection system for a range of combustible gases including propane, butane, methane and hydrogen. In addition it will also detect poisonous carbon monoxide.

Maximum relay contact ratings for extractor fan, gas solenoid valve and external alarm: 1A for each function.

Control panel dimensions: 85 x 85mm

Built in depth: 40mm

Sensor 35 x 26 x 62mm

Part No	Vetus	Description
55935	GD1000	12V/24V Detector + Sensor
55936	GSENSOR	Extra Sensor





Vetus Petrol & Carbon Monoxide Detector 12/24V

The gas detector PD1000 detects petrol vapour to prevent the risk of explosion in the engine room, as well as poisonous carbon monoxide (CO).

Maximum relay contact ratings for extractor fan, gas solenoid valve and external alarm: 1A for each function.

Control panel dimensions: 85 x 85mm

Built in depth: 40mm

Sensor 35 x 26 x 62mm

Part No	Vetus	Description
55937	PD1000	12V/24V Detector + Sensor
55938	PSENSOR	Extra Sensor


Granit Padlock













Granit Padlock

ABUS-Plus disk cylinder - highest protection against manipulation. Body and shackle coated for optimum inner and outer corrosion protection. Shackle and body made from hardened steel alloy. The Cylinder can be re-keyed to match an existing key. Keyed Alike locks available to order with a 10% surcharge.


Part No	Width	Abus No	Α	В	С	D	Е
93500	63mm	37/55 S & S	27.5	26	85	11	63

Diskus Padlock












Diskus Padlock


Discus design resists usual attack methods.100% corrosion resistant - body and shackle made from stainless steel and internal components are made from corrosion resistant materials. Keyed Alike locks available to order with a 10% surcharge.

Part No	Width	Abus No	Α	В	С	D	Е
93507	60mm	24IB/60	17.5	13	60	8	60
93509	71mm	24IB/70	19.5	17	71	10	71

Combination Padlock








Combination Padlock

Combination design with 4 digit resettable code. Body made from forged solid brass, shackle from stainless steel and internal parts made from corrosion resistant materials. Precision locking mechanism with special protection against manipulation.

Part No	Width	Abus No	Α	В	С	D	Е
93510	50mm	180IB/50	25	25	75	8	50
93511	63mm	180IB/63	25	63	113	8	63

Aquasafe Padlock








Aquasafe Padlocks

Solid brass body with hardened steel shackle (IB model has stainless shackle) and corrosion proof internals. Sealed lock body with cover seal to protect against water / dirt ingress. Vinyl casing. Keyed Alike locks available to order with a 10% surcharge.

Part No	Width	Abus No	Α	В	С	D	Е
93671	28mm	70/45	20.5	24.5	73	8	28
93673	28mm	70IB/45	20.5	24.5	73	8	28

Submariner Padlock





Submariner Padlock

Abus 83 Series Submariner weatherproof brass body, open shackled, heavy-duty padlock with a rust-free stainless steel shackle. Has a high impact sealed lock body with a keyway protective cover designed to keep dirt out and offering maximum security and durability even in the harshest environment.

Part No	Width	Abus No	Α	В	С	D	E
93580	56.5mm	83WPIB/53C	23.5	27.5	97.5	35.5	56.5

Brass Padlocks Security Tech Germany


Brass Padlock Multi-packs				
Part No	Description			
93548	40mm Twin Pack 65/40			
93563	40mm Twin Pack Stainless Shackle 65IB/40			
93547	40mm Quad Pack Keyed Alike 65/40			
93549	50mm Twin Pack 65/50			

Hardened Shackle Brass Padlocks

Solid brass body with hardened steel shackle. Corrosion proof internals. Precision pin tumbler cylinder. Keyed Alike locks available to order with a 10% surcharge. HB models have long

Part No	Padlock Width	Abus No	Α	В	С	D	Е
93531	20mm	65/20	9.5	11.5	34	3.5	20
93534	25mm	65/25	13.5	13.5	42	4	25
93537	30mm	65/30	16	17.5	50	5	30
93538	50mm	65/50 HB80C					
93543	35mm	65/35	20	19	55	5.5	35
93545	40mm	65/40	22	22.5	62	6.5	40
93550	40mm	65/40 HB40	22	40	77	6	40
93552	40mm	65/40 HB63	22	63	103	6	40
93554	45mm	65/45	25.5	24.5	68	7	45
93556	50mm	65/50	28	29	77	8	50
93558	50mm	65/50 HB80	28	80	129	8	50
93560	60mm	65/60	33	35	91	9.5	60
93562	40mm	65IB/40 SS Shackle	22	22.5	62	6.5	40

Extreme Weatherproof Padlock







Extreme Weatherproof Padlocks

Abus 83WP Extreme weatherproof open & closed shackle. Heavy-duty fully re-keyable through hardened steel alloy padlock, with a ball bearing locking mechanism for extra security. Has a tough through hardened steel alloy shackle as standard with NanoProtect Chrome Plating.

Part N	o Width	Abus No	Α	В	С	D	E
93581	56.5mm	83WP/53C	23.5	27.5	97.5	35.5	56.5
93582	65mm	83WP/63C	25.8	33	109.5	34.5	65
93583	56.5mm	83WPCS/53C	19	25	97.5	34.5	56.5



Heavy Duty Hasp & Staple

Mirror polished stainless steel

Closed 33 x 87mm

Open Length 33 x 107mm

Part No Description

96303 Heavy Duty SS Hasp & Staple

Swivel Hasp



316 Grade Stainless Steel 90mm x 26mm Part No 23133

Hasps & Staples



Part No		Description
Brass	Chrome	Length X Width
45000	45010	3" X 1" (76 X 25mm)







Hasp & Staples

Diskus Hasp & Staple

High security hasp and staple especially recommended for use with Abus Diskus locks to lock gates, hangar doors, containers etc. Hasp and hinge pins are made from stainless steel and the staple is made from hardened steel. Available in two sizes.

Part No	Abus No	Length	Width	Staple Aperture
93659	140/120	140mm	56mm	12.5mm
93660	140/190	190mm	56mm	12.5mm

Basic Hasp & Staple

Corrosion protected steel construction with hidden screws. Suitable for padlocks with shackles up to 12mm.

Part No	Abus No	Length	Width	Staple Aperture
93668	200/115	116mm	47mm	13.5mm

Cobra Loop Cables





Cobra Loop Cables

Flexible steel cables with a plastic sheathing. Excellent for securing bicycles, scooters, general components and

Part No	Abus No	Diameter	Length	Weight
93571	1850/185	8mm	185cm	356g
93570	8/200	8mm	200cm	317g
93565	10/200	10mm	200cm	566g
93566	10/500	10mm	500cm	1249g
93564	10/1000	10mm	1000cm	2324g
93567	12/120	12mm	120cm	416g

Locks the butterfly nut: 1) So the engine cannot plunge

into the water; 2) prevents the outboard engine from being stolen, as the secure lock must be broken. Made of anodized aluminium pipe thickness 4 mm (very sturdy); brass and stainless steel lock with two keys. Tough sturdy look discourages thieves; compact model with stainless steel end-pieces and the inner pipe is made of anti-rattle foam .

Secure Lock Antitheft Device

Part	Description
No	
96315	Antitheft up to 25HP
96316	Antitheft over 25 HP and for all Mercury engines

Outboard Locks



Allpa Outboard Clamp Lock

allpa

Adjustable lock mechanism allows fitment to most outboard motors. Body constructed from 316 stainless steel with a brass lock. Complete with floating key ring.

Dimensions: 303 X 40 X 40mm

Part No 91587

Outboard Motor / Outdrive Leg Bolt Locks

These locks fit over bolts preventing nut removal. Body made from 316 stainless steel with brass lock. Includes PVC protection cover.

Part No	To Fit Bolt Size	Diameter	Length
91589	M10	29mm	55mm
91588	M12	38mm	73mm



Contains:

Pair of oars

Red hand flares

Bailer and 2 sponges

Waterproof torch and whistle

Lifesaving signal cards

Floating knife

Drogue

Repair clamps

Rescue quoit and 30m line

Bellows hand pump



Ocean Safety Life Raft

The Ocean Standard life raft is a practical yet affordable life raft and is the latest addition in the life raft range offered by Ocean Safety. It was introduced to fulfil the requirement for a quality yet practical entry level life raft, which is ideal for coastal and short offshore recreational boating and non-coded craft.

Made with quality rubber

Insulated floor

Highly visible orange canopy

4 x 30 litre water pockets


Zip closure on entrance

Rain water dispenser system and collection system

Automatic light

ORC safety pack

Part No	Description
90625	Ocean Standard 4 Man 650 x 430 x 280mm
90626	Ocean Standard 6 Man 740 x 480 x 290mm



Unique aluminised polythene suit designed with heat sealed seams for maximum protection.

MED Ship's Wheel approved

One size fits all

Protection to -30 degrees C

Part No Description

90620 Thermal Protective Aid - MCA









Kru XF: Automatic + Harness - Navy

A versatile and lightweight lifejacket that is ISO approved, AIS ready and features Wave Barrier technology, the Kru XF is ideal for coastal sailing & general watersports. Wave Barrier technology delivers sub 5 second super-fast turn speed. The wearer is placed on their back keeping airways raised above water and clear. The interlocking bladder blocks the flow of water into the wearers airways, massively reducing the risk of secondary drowning

Easy front donning

Rated 150N with actual buoyancy of 170N

Side adjustment for bespoke fit

Tailored collar for increased comfort

Single crotch strap eliminating ride-up

Harness and non-harness versions available

Stainless steel D-ring for safety harness (harness version only)

Durable outer cover

Approved service network

Part No

90618



Kru Sport ADV

The Ocean Safety Kru Sport ADV Inflatable PFD offers a sprayhood and wave barrier technology, as well as a quick-burst zip and a lifejacket light. It is AIS ready. Sprayhood. Lifejacket light. Scoop back neck design for increased comfort. Side adjustable waist belt.

Crotch strap for additional security

Wave barrier technology helps keep airways clear

170N buoyancy

Wave barrier tech delivers sub-5-second turn speed

The wearer is placed on their back, keeping airways raised above the

Interlocking bladder blocks the flow of water into the wearer's airways, reducing the risk of downing

Part No

90621



The AQ40L is a compact flashing lifejacket light, automatically water activated by its sensor lead or manually. Its unique size and shape, makes the AQ40L ideal for a variety of life jackets.

Ultra bright powerful white flashing LED dome light Manual and automatic water activation by sensor lead Functional and simple design Fixing clip designed for easy attachment Maintenance free five year battery life Tamper-proof

Part No Description

90619 Aquaspec AQ40LM Lifejacket Light

United Moulders Junior Manual Re-Arm Pack- 24G



The United Moulders (UM) lifejacket inflator uses a screw on cartridge and activates when it comes into contact with water. The cartridge mechanism has a compressed high powered spring which is held by a paper element. When the paper element dissolves it releases the spring which allows the firing mechanism to puncture the CO2 cylinder, the CO2 then travels through the manifold and inflates the lifejacket. The Automatic system is backed up by a manual override, which allows the user to pull the toggle and inflate the lifejacket.

90609 24G Manual Junior Re-Arming Pack



United Moulders Gas Cylinder Manual Re-Arm Pack- 33G

The manual re-arming kits are for both United Moulders and Halkey Roberts activated lifejackets.

Part No Description

90611 33G Manual Re-Arming Pack

United Moulders (UM) Automatic Kit UM 33G Automatic Re-Arm Kit



The United Moulders (UM) lifejacket inflator uses a screw on cartridge and activates when it comes into contact with water. The cartridge mechanism has a compressed high powered spring which is held by a paper element. When the paper element dissolves it releases the spring which allows the firing mechanism to puncture the CO2 cylinder, the CO2 then travels through the manifold and inflates the lifejacket. The Automatic system is backed up by a manual override, which allows the user to pull the toggle and inflate the lifejacket.

90610 33G Auto Re-Arm Pack UM



Halkey Roberts (HR) Automatic Kit: HR 33G Automatic Re-Arm Kit

The Halkey Roberts Automatic system activates when a salt water bobbin is in contact with water. The bobbin dissolves and allows the firing mechanism to puncture the CO2 cylinder, the CO2 then travels through the manifold and inflates the lifejacket. The Automatic system is backed up by a manual override pull cord, which allows the user to pull the toggle and inflate the lifejacket.

Part No	Description
raitino	Description

90612 Halkey Roberts 33G Auto Re-Arming Pack



United Moulders Gas Cylinder Only

Replacement gas cylinders only.

Flease note no kit parts are included.		
Part No	Description	
90615	24G Cylinder	
90616	33G Cylinder	
90617	60G Cylinder	



United Moulders MK5 Auto Cartridge (Black)

Part No Description

90608 UM Mk5 automatic cartridge



Halkey Roberts Retaining Clip

Part No Description

Green Halkey Roberts retaining clip 90613



Halkey Roberts Super Bobbin

Part No Description

90614 Yellow Halkey Roberts Super Bobbin






Commander

Luxurious chair with excellent support. The front part can be folded up for steering in a standing or leaning position. Available colours: • White (CHCOMW) • Dark blue (CHCOMB) • Without upholstery (CHCOMU). Supplied without pedestal. Fits pedestals with slide only. Use seat cover CCDS or CCSB to keep the seat clean and protected against UV.

SPECIAL ORDER



Part No	Description	Vetus	D1	D2	H1	H2	W1	W2	ØT	Hole Pattern	Weight (kg)
58400	Commander Seat White	CHCOMW	684	485	715	610	610	415	720	R	15
58401	Commander Seat Dark Blue	CHCOMB	684	485	715	610	610	415	720	R	15
58402	Commander Seat No Upholstery	CHCOMU	684	485	715	610	610	415	720	R	15



Comfortable FLIP-UP boat seat. The front part can be folded up for steering in a standing or leaning position. Available colours: • White (CHFUS) • Dark blue (CHFUSBL) • Without upholstery (CHFUSQU). Supplied without pedestal. Fits pedestals with slide only. Use seat cover CCDS or CCSB to keep the seat clean and protected against UV.

SPECIAL ORDER

Part No	Description	Vetus	D1	D2	H1	H2	W1	W2	ØT	Hole Pattern	Weight (kg)
58403	Queen Seat White	CHFUS	715	490	600	510	560	460	800	R	12
58404	Queen Seat Dark Blue	CHFUSBL	715	490	600	510	560	460	800	R	12
58405	Oueen Seat No Unholstery	CHEUSOU	715	490	600	510	560	460	800	R	12



Comfortable FLIP-UP boat seat. The front part can be folded up for steering in a standing or leaning position. With comfortable head rest. Available colours: • White with dark blue seams (CHFUSW) • Dark blue with white seams (CHFUSB) • Cream with cream seams (CHFUSC) • Without upholstery (CHFUSKU). Supplied without pedestal. Fits pedestals with slide only. Use seat cover CCDS or CCSB to keep the seat clean and protected against UV.


Part No	Description	Vetus	D1	D2	H1	H2	W1	W2	ØT	Hole Pattern	Weight (kg)
58406	King Seat White	CHFUSW	720	490	620	500	570	450	800	R	13
58407	King Seat Dark Blue	CHFUSB	720	490	620	500	570	450	800	R	13
58408	King Seat No Upholstery	CHFUSKU	720	490	620	500	570	450	800	R	13



Master

High quality helm seat with armrests. Stainless steel frame (AISI 304). Available colours: • White (CHFASW) • Dark blue (CHFASB) • Cream (CHFASC) • Without upholstery (CHFASU). Supplied without pedestal. Fits pedestals with slide only. Use seat cover CCMB to keep the seat clean and protected against UV.

SPECIAL ORDER



Part No	Description	Vetus	D1	D2	H1	H2	W1	W2	ØT	Hole Pattern	Weight (kg)
58409	Master Seat Dark Blue	CHFASB	690	500	630	510	595	510	760	R	15
58410	Master Seat White	CHFASW	690	500	630	510	595	510	760	R	15
58411	Master Seat Cream	CHFASC	690	500	630	510	595	510	760	R	15
58412	Master Seat No Upholstery	CHFASU	690	500	630	510	595	510	760	R	15



Sailor

Helm seat with armrests. Anodised aluminium frame. Available colours: • White (CHSAILW) • Dark blue (CHSAILB). Supplied without pedestal. Fits pedestals with slide only. Use seat cover CCDS or CCSB to keep the seat clean and protected against UV.

SPECIAL ORDER

Part No	Description	Vetus	D1	D2	H1	H2	W1	W2	ØT	Hole Pattern	Weight (kg)
58413	Sailor Seat White	CHSAILW	600	440	620	540	585	430	700	R	8.2
58414	Sailor Seat Dark Blue	CHSAILB	600	440	620	540	585	430	700	R	8.2





Classic helm chair with comfortable arm rests. Anodised aluminium frame. Available colours: • White (CHCASW) • Dark blue (CHCASB). Supplied without pedestal. Fits all pedestals. Use seat cover CCDS or CCSB to keep the seat clean and protected against UV.


Part No	Description	Vetus	D1	D2	H1	H2	W1	W2	ØT	Hole Pattern	Weight (kg)
58415	Skipper Seat White	CHCASW	590	420	535	415	595	430	680	R/S	9.5
58416	Skipper Seat Dark Blue	CHCASB	590	420	535	415	595	430	680	R/S	9.5



Lieutenant

Comfortable seat with a foldable front part for steering in standing or leaning positions. Available colours: • White (CHLIEUTW) • Dark blue (CHLIEUTB). Supplied without pedestal. Fits pedestals with slide only. Use seat cover CCDS or CCSB to keep the seat clean and protected against UV.

SPECIAL ORDER



Part No	Description	Vetus	D1	D2	H1	H2	W1	W2	ØT	Hole Pattern	Weight (kg)
58417	Lieutenant Seat Dark Blue	CHLIEUTB	710	510	540	410	585	430	710	R	8
58418	Lieutenant Seat White	CHLIEUTW	710	510	540	410	585	430	710	R	8



Sporty seat with good lateral support. The front part can be folded up for steering in standing or leaning positions.

Available colours: • Black (CHSPORTTB) • White
(CHSPORTW) • White with black (CHSPORTWB) • Without
upholstery (CHSPORTU). Supplied without pedestal. Fits
pedestals with slide only. Use seat cover CCDS or CCSB to keep the seat clean and protected against UV.

SPECIAL ORDER

Part No	Description	Vetus	D1	D2	H1	H2	W1	W2	ØT	Hole Pattern	Weight (kg)
58419	Pilot Seat White	CHSPORTW	670	475	600	510	500	403	720	R	8.7
58420	Pilot Seat Black & White	CHSPORTWB	670	475	600	510	500	403	720	R	8.7
58421	Pilot Seat No Upholstery	CHSPORTU	670	475	600	510	500	403	720	R	8.7



Sporty seat with good lateral support. Modern design. Available colours: • White (CHDRIVEW) • White with black (CHDRIVEWB). Supplied without pedestal. Fits pedestals with slide only. Use seat cover CCDS or CCSB to keep the seat clean and protected against UV.


Part No	Description	Vetus	D1	D2	H1	H2	W1	W2	ØT	Hole Pattern	Weight (kg)
58422	Driver Seat White	CHDRIVEW	640	450	600	510	520	405	670	R	7
58423	Driver Seat Black With White	CHDRIVEB	640	450	600	510	520	405	670	R	7

Seats

Admiral

A sporty and comfortable seat with lateral supports. The front part can be folded up for steering in standing or leaning positions. Available colours: • White (CHADMW) • Dark blue (CHADMB). Supplied without pedestal. Fits pedestals with slide only. Use seat cover CCDS or CCSB to keep the seat clean and protected against UV.

SPECIAL ORDER



Part No	Description	Vetus	D1	D2	H1	H2	W1	W2	ØT	Hole Pattern	Weight (kg)
58424	Admiral Seat White	CHADMW	730	510	620	550	580	430	730	R	8.5
58425	Admiral Seat Dark Blue	CHADMB	730	510	620	550	580	430	730	R	8.5



Major

A comfortable seat with a foldable front part for steering in standing or leaning positions. Available colours: White (CHMAJORW) • Dark blue (CHMAJORB). Supplied without pedestal. Fits pedestals with slide only. Use seat cover CCDS or CCSB to keep the seat clean and protected against UV.


SPECIAL ORDER

Part No	Description	Vetus	D1	D2	H1	H2	W1	W2	ØT	Hole Pattern	Weight (kg)
58426	Major Seat White	CHMAJORW	730	510	660	555	585	400	730	R	9.5
58427	Major Seat Dark Blue	CHMAJORB	730	510	660	555	585	400	730	R	9.5




Crew


Deluxe light weight seat with folding back rest. With or without cushions. Available colours: • Light grey (without upholstery) (CHCS) • White (CHCW) • White with dark blue insert (CHCBWB) • Grey (CHCG). Supplied without pedestal. Only fits pedestals without slide. Use seat cover CCDS or CCSB to keep the seat clean and protected against UV.



Part No	Description	Vetus	D1	D2	H1	H2	W1	W2	ØT	Hole Pattern	Weight (kg)
58429	Crew Ergonomic Seat Light Grey (No Upholstery)	CHCS	482	435	435	405	470	470	630	S	3
58430	Crew Folding Seat White	CHCW	482	435	435	405	470	470	630	S	3
58431	Crew Folding Seat White & Dark Blue	CHCBWB	482	435	435	405	470	470	630	S	3
58432	Crew Folding Seat Grey	CHCG	482	435	435	405	470	470	630	S	3







Reverso White Single Seat + Rotating Backrest RAL

It can be used both forwards and backwards.

Part No	Description	Osculati
96418	Reverso White Single Seat	48.410.04

STOCK ITEM



Fisherman

Classic seat with folding back rest. Anodised aluminium hinges. Available colours: • White with dark blue seams (CHFSWW) • Dark blue with white seams (CHFSBW). Supplied without pedestal. Fits all pedestals. Use seat cover CCDS or CCSB to keep the seat clean and protected against UV.

SPECIAL ORDER


Part No	Description	Vetus	D1	D2	H1	H2	W1	W2	ØT	Hole Pattern	Weight (kg)
58433	Fisherman Seat White With Dark Blue Seams	CHFSWW	480	350	450	360	400	400	575	R/S	3.3
58434	Fisherman Seat Dark Blue With White Seams	CHFSBW	480	350	450	360	400	400	575	R/S	3.3



First Mate

Comfortable deluxe seat with folding back rest. Anodised aluminium hinges. Available colours: • White with blue seams (CHFSW) • Dark blue with white seams (CHFSB) • Light grey with dark grey seams (CHFSL) • Grey with light grey seams (CHFSD). Supplied without pedestal. Fits all pedestals. Use seat cover CCDS or CCSB to keep the seat clean and protected against UV.

STOCK ITEM



Part No	Description	Vetus	D1	D2	H1	H2	W1	W2	ØT	Hole Pattern	Weight (kg)
58435	First Mate Seat White With Blue Seams	CHFSW	480	350	450	360	400	400	575	R/S	3.3
58436	First Mate Seat Dark Blue With White Seams	CHFSB	480	350	450	360	400	400	575	R/S	3.3
58437	First Mate Seat Light Grey With Dark Grey Seams	CHFSL	480	350	450	360	400	400	575	R/S	3.3
58438	First Mate Seat Grey With Light Grey Seams	CHFSD	480	350	450	360	400	400	575	R/S	3.3



First Class

Comfortable deluxe double seat with folding back rest. Anodised aluminium hinges. Available colours: • White with dark blue seams (DCHFSW) • Dark blue with white seams (DCHFSB). Supplied without pedestals. Fits on two pedestals.

SPECIAL ORDER

Part No	Description	Vetus	D1	D2	H1	H2	W1	W2	ØT	Hole Pattern	Weight (kg)
58439	First Class Bench White With Dark Blue Seams	DCHFSW	480	350	450	360	900	900	-	2 x R	13
58440	First Class Bench Dark Blue With White Seams	DCHFSB	480	350	450	360	900	900	-	2 x R	13



Ferry

Seat with moveable double sided backrest. Anodisedaluminium hinges. Available colours: • White with dark blue seams (CHTBSW) • Dark blue with white seams (CHTBSB). Supplied without pedestal. Fits all pedestals. Use seat cover CCDS or CCSB to keep the seat clean and protected against UV.

SPECIAL ORDER

Part No	Description	Vetus	D1	D2	H1	H2	W1	W2	ØT	Hole Pattern	Weight (kg)
58441	Ferry Seat White With Dark Blue Seams	CHTBSW	570	375	460	380	420	420	706	R/S	6
58442	Ferry Seat Dark Blue With White Seams	CHTBSB	570	375	460	380	420	420	706	R/S	6



Ferry Bench

Double seat with moveable double sided backrest.

Anodised aluminium hinges. Available colours:

• White with dark blue seams(DCHTBSW) • Dark blue with white seams (DCHTBSB).

Supplied without pedestals. Fits on two pedestals (with or without slide).

Part No	Description	Vetus	D1	D2	H1	H2	W1	W2	ØT	Hole Pattern	Weight (kg)
58443	Ferry Bench White With Dark Blue Seams	DCHTBSW	570	375	460	380	900	900	-	2 X R 2 X S	15
58444	Ferry Bench Dark Blue With White Seams	DCHTBSB	570	375	460	380	900	900	-	2 X R 2 X S	15

Seats



Part No	Description	Vetus	D	Н	W
58445	Single Seat Cover Silver	CCDS	500	830	640
58446	Single Seat Cover Dark Blue	CCSB	500	830	640
58447	Master Seat Cover Dark Blue	CCMB	580	700	580

Seat cover - weather proof

To keep the seat dry and clean and protected against UV. Made of nylon with PU coating. A drawstring is included. Types CCDS and CCSB fit all single seats except the 'Master' seat.

Available colours:

- · Dark blue
- Silver

SPECIAL ORDER








Total Control	-
	N
TO BE	

-	1	-Varance

Part No	Description	Vetus
58448	White 1.37m x 5m	CHSKAIW
58449	Dark Blue 1.37m x 5m	CHSKAIB
58450	Cream 1.37m x 5m	CHSKAIC



A sample swatch of materials is available upon request.

Seat Material.

The marine grade skai imitation leather is maintenance free, and water and UV resistant. Available in rolls of 1.37 metre width and 5 metres long.

SPECIAL ORDER

Seat pedestals

All pedestals are made of high grade aluminum and have a 360° rotatable swivel on top. Gas adjustable pedestals are operated with a handle. Manually adjustable pedestals have both a lockpin with a locking position every 25 mm and a clamping knob for complete security. The sliding mechanism can be moved through 135 mm in total and locked in one of 7 positions.










Gas adjustable pedestals with slide

For optimum enjoyment of your seat. Gas spring height adjustable aluminum seat pedestal with slide and 360° swivel. Polished base.

Part No	Description	Vetus	Height (H)	Hole pattern	Post Ø (D1 / D2)	Base Ø (D3)	Weight (kg)
58460	Gas Pedestal 30 - 40CM	PCG3040	300 - 400	R/S	73 / 87	228	6
58461	Gas Pedestal 35 - 47CM	PCG3547	350 - 470	R/S	73 / 87	305	7
58462	Gas Pedestal 43 - 60.5CM	PCG4363	435 - 605	R/S	73 / 87	305	7,8









Manually adjustable pedestals with slide

Manually height adjustable aluminum seat pedestal with slide and 360° swivel. Polished base.

SPECIAL ORDER

Part No	Description	Vetus	Height (H)	Hole pattern	Post Ø (D1 / D2)	Base Ø (D3)	Weight (kg)
58463	Manual Pedestal 30 - 40CM	PCMS3040	300 - 400	R/S	73 / 87	228	6
58464	Manual Pedestal 35 - 47CM	PCMS3547	350 - 470	R/S	73 / 87	305	7
58465	Manual Pedestal 43.5 - 60.5CM	PCMS4363	435 - 635	R/S	73 / 87	305	7,8



Manually adjustable pedestals without slide

Manually height adjustable aluminium seat pedestal with 360° swivel only. Anodised base.

SPECIAL ORDER

Part No	Description	Vetus	Height (H)	Hole pattern	Post Ø (D1 / D2)	Base Ø (D3)	Weight (kg)
58466	Manual Pedestal 30 - 40CM	PCM3040	300 - 400	S	60 / 73	228	4
58467	Manual Pedestal 35 - 47CM	PCM3547	350 - 470	S	60 / 73	228	5
58468	Manual Pedestal 43.5 - 63.5CM	PCM4363	435 - 635	S	60 / 73	228	5,8







Fixed height pedestals

With 360° swivel, available with orwithout slide. Anodised base.

Part No	Description	Vetus	Height (H)	Hole pattern	Post Ø (D1 / D2)	Base Ø (D3)	Weight (kg)
58469	Fixed Pedestal & Slide 33CM	PCFS33	330	R/S	73	228	4,2
58470	Fixed Pedestal & Swivel 33CM	PCF33	330	S	73	228	
58471	Fixed Pedestal & Slide 45CM	PCFS45	457	R/S	73	228	4,8
58472	Fixed Pedestal & Swivel 45CM	PCF45	457	S	73	228	



Footrest

Rotatable and foldable footrest for pedestals. Made from a marine grade aluminium with stainless steel fastenings. For extra grip the aluminium base plate has a diamond profile.

SPECIAL ORDER

Part No	Description	Vetus	Post Ø(D2)	Suits pedestal type	Weight (kg)
58476	Footrest For Tube 73MM	FTREST73	72	PCM, PCF	3.5
58477	Footrest For Tube 87MM	FTREST87	87	PCMS, PCG	3.5



Bell shape pedestal

A seat pedestal with a friction lock 360° swivel. The height is manually adjustable. Made from a marine grade aluminium. The large bell shaped base is grey powder coated.

SPECIAL ORDER

Part No	Description	Vetus	Height (H)	Hole pattern	Post Ø (D1)	Base Ø (D3)	Weight (kg)
58478	Manual Bell Shaped Pedestal	PCBELL	330-430	S	60	254	2,3

Base with swivel

Low profile anodised base with 360° swivel.



Part No	Description	Vetus	Height (H)	Hole pattern	Base Ø (D3)	Weight (kg)
58479	Seat Pedestal With Swivel	PC13	134	S	228	2

SPECIAL ORDER

Base with swivel and slide

Low profile anodised base with 360° swivel and slide.



Part No	Description	Vetus	Height (H)	Hole pattern	Base Ø (D3)	Weight (kg)
58480	Seat Pedestal With Slide	PCS15	133	R/S	228	4

SPECIAL ORDER

Swivel with slide

Aluminium 360° swivel with slide with 7 locking positions.

For direct mounting.



-	
-	
THE RANGE	

Part No	Description	Vetus	Height (H)	Hole pattern	Base Ø (D3)	Weight (kg)
58481	Swivel Seat Base	PCBS	70	R/S	S	2,5
58482	Swivel Seat Base 360 Rotatable	PCBSR	70	R/S	S	2,5









Rotatable base with locking position

Aluminium 360° rotatable base with 7 locking positions. For direct mounting.

Part No	Description	Vetus	Height (H)	Hole pattern	Base Ø (D3)	Weight (kg)
58483	Swivel Seat Base	PCBL	51	S	S	2

SPECIAL ORDER

Removable swivel base

Rotatable and removable plastic 360° swivel base for direct mounting.

Part No	Description	Vetus	Height (H)	Hole pattern	Base Ø (D3)	Weight (kg)
58484	Seat Base	PCB	55	S	S	0,7

SPECIAL ORDER

Rotatable stainless steel base

360° Rotatable base for direct mounting. Made from stainless steel AISI 304.

Part No	Description	Vetus	Height (H)	Hole pattern	Base Ø (D3)	Weight (kg)
58485	Rotatable Stainless Steel Base	PCBR	23	S	S	1

SPECIAL ORDER

Seat slide for direct mounting. The sliding mechanism can be moved through 135 mm in total and locked in one of 7 positions.

Part No	Description		Height (H)		Base Ø (D3)	J
58486	Seat Slide	SCU	70	R + S	S	2

SPECIAL ORDER

Removable pedestal (fixed height)

With 360° swivel or slide and recessed anodised base. Base and pedestal fit most commonly used similar systems in the market.





Part No	Description	Vetus	Swivel (hole pattern)	Height (H)	Post Ø (D2)	Base Ø (D3)	Recessed Depth	Hole Ø
58487	Removable Fixed Pedestal Swivel	PCR38	Swivel (S)	380	60	228	70	90
58488	Removable Fixed Pedestal Slide	PCRS38	Slide (R)	380	60	228	70	90

Seats



Removable pedestal

With 360° swivel and recessed anodised base. Base and pedestal fit most commonly used similar systems in the market.

SPECIAL ORDER

Part No	Description	Vetus	Swivel (hole pattern)	Height (H)	Post Ø (D2)	Base Ø (D3)	Recessed Depth	Hole Ø
58489	Removable Fixed Pedestal 330mm	PCRQ33	Quick Position (S)	330	60	228	70	90
58490	Removable Fixed Pedestal 380mm	PCRQ38	Quick Position (S)	380	60	228	70	90



PCRBASE

This (spare) plug-in pedestal base can be used as an extra mounting position or as replacement for existing pedestal bases. The base is made of a marine grade anodized aluminium.

SPECIAL ORDER

Part No	Description	Vetus
58491	PCRBASE (Spare Base)	PCRBASE



We are distributors for Vetus marine products and stock a wide range of their most popular lines. However we can get hold of anything else displayed in the Vetus catalogue except engines.







Part No








LPC GB 230V

64881



Part No 64883

Mirka Delta 663CV 230V Triangular Sander

Part No 64889



Hose 27mm X 4M + Connector

Part No 64882



Dust Bag Fleece For DE1230

Spare Bag for Mirka dust extractor.

Part No 64878



Mirka Spare Mains Lead 230V

Part No 64877



Dust Bag Fleece For DE1025 L (old model)

Spare Bag for Mirka dust extractor.

Part No 64888

Sanding Discs

All of our discs are sold individually.



Basecut 150mm Sanding Discs

Basecut is the economical, high efficiency choice for sanding with paper. There are several productivity and efficiency features, including a high initial, aggressive cut and a long working lifespan.

Part No	Grade	Box Size
64840	P40	50
64842	P60	50
64844	P80	100
64846	P120	100
64848	P150	100
64854	P240	100
64855	P320	100
64856	P400	100

MIRKE



Abranet Ace HD 150mm Discs

Abranet Ace HD is durable and tough with ceramic grains. The strong net structure resists high wear and tear and the product is ideal for heavy-duty applications. The improved woven mesh backing increases the lifetime of the abrasive, and makes the sanding process faster. Abranet Ace HD for dust -free sanding has coarse grits P40 and P60.

Part No	Grade	Box Size
64800	P40	25
64802	P60	25

MIRKE



Autonet 150mm Discs

Mirka Autonet Disc 150mm are a revolutionary new-age surface finishing solution which has been specially developed for the unique demands of the automotive refinishing industry. The patented construction of Mirka Autonet consists of a dense network of polyamide fabric threads onto which the abrasive grit is bonded. 50 per box.

Part No	Grade	Box Size
64832	P80	50
64833	P120	50
64834	P180	50
64835	P240	50
64836	P320	50
64837	P400	50





MIRKE

Abralon 150mm Foam Sanding Discs

Abralon is a unique, multifunctional sanding material developed for tackling both smooth and profiled surfaces. The patented, flexible construction allows it to create a smooth sanding pattern on angled surfaces and edges while minimizing the risk of pressure marks. The flexible weave allows water and air to pass freely, resulting in a cleaner sanding process and a long lasting abrasive. Recommended for fine sanding of profiled surfaces and for finishing prior to polishing. Recommended to use wet.

20 Per Box

Part No	Description	Box size
64798	P600	20
64799	P1000	20
64838	P2000	20
64839	P3000	20



Mirka Autonet 125mm Discs

Mirka Autonet is specially developed for the automotive refinishing industry. Autonet is a new-age surface finishing solution offering speed; efficiency and an amazing dust extraction ability. The patented construction eliminates clogging and pilling and ensures a long lifespan, while other highlights include excellent initial aggressivity, reduced edge wear in finer grits and a versatile range to suit any application.

Part No	Grade	Box Size
64900	P40	50
64902	P60	50
64904	P80	50
64908	P120	50
64912	P180	100
64914	P240	100
64916	P320	100

MIRKE

All of our discs are sold individually.







Abranet 152mm Triangular Discs

The multifunctional and classic Abranet is especially developed for sanding putty, primers, lacquers, composite materials and a wide range of other materials for industrial use. Abranet combines high performance and a long lifespan, making it a cost-effective solution. Designed for dry sanding, by hand or with a machine, the true dustfree sanding characteristics result in a cleaner work environment, as well as a better surface finish.

Part No	Grade	Box Size
64740	P60	10
64741	P80	10
64742	P120	10
64743	P180	10
64744	P240	10
64745	P320	10

3M Scotch Brite

50mm Roloc Surface Conditioning Discs

Sold Each

Part No	Grade & Size
63948	Very Fine Blue
63949	Super Fine Red
63950	Roloc Holder



150mm Hookit Soft Interface Pad

A soft interface pad made from a very flexible foam which attaches to a standard Hookit disc pad to provide excellent full disc contact, even on curved surfaces.

Part No

63597



Backing Pad Net 100x152x152mm Grip 34H Medium

Backing pad suitable for the Mirka® DEOS Delta sander.

Part No 64751



Backing Pad Net 150mm 5/16" Grip 48H Medium

A 150 mm (6") backing pad with a central air inlet. The air channels leading to the centre of the backing pad has an increased air flow and therefore the dust is removed efficiently.

Part No 64884





150mm Hookit Hand Pad

A comfortable pad with an elastic strap that holds the pad onto the hand for scuff sanding flat or contoured surfaces. The Hookit pad face provides easy attachment and removal of Hookit discs.

Part No

63598



Pad Saver 100x152x152mm 32H

These cost effective pad savers, placed between the backing pad and the sanding disc, should be changed regularly.

Part No

64750



Backing Pad Saver 150mm

These cost effective pad savers, placed between the backing pad and the sanding disc, should be changed regularly.

64885



Backing Pad Saver 125mm

These cost effective pad savers, placed between the backing pad and the sanding disc, should be changed regularly.

Part No

64887



Hookit Backing Pads

Specially made for use with Hookit discs. These pads securely hold the disc yet allow for easy change and re-attachment of discs. All pads are lightweight, shock resistant and well balanced. Max speed for ø150mm pads is up to 7000 rpm.

Part No	Size	Туре
63577	150mm	5/16 Standard 15 Hole
63578	150mm	5/16 Soft 15 Hole
63579	150mm	M8, Standard 15 hole
63580	150mm	M8, Soft 15 hole



Hand Blocks

These blocks are designed for use with Hookit abrasive sheets / rolls.

Part No	Type	Dimensions
63587	Hard	70 x 127mm
63588	Soft	70 x 127mm
63589	Hard	70 x 197mm
63590	Hard	70 x 390mm



Sanding Block for 150mm **Grip Discs**

An ergonomic sanding block with grip which is sized to fit the hand. You can use the 150mm orbital sanding for hand sanding with this block.

Part No 64886





3M Twist-Lok Pad Holder

Specially designed for use with 3M hand pads to make clean up jobs faster, easier and safer. Distributes pressure evenly over pad surface for efficient cleaning action and improved pad life. Length: 120mm, Width: 89mm

Part No 64064



Anza Cork Sanding Block

Useful tool for sanding most surfaces.

70 X 120mm

Part No

62180



Hookit Facing Material

Allows conversion of self-made fairing boards to the Hookit attachment system to utilize the high performance Hookit rolls.

Part No Width X Length 63255 115mm X 3.6m

Rigid Fairing Board



3M Dry Coat System

Use to detect surface imperfections such as pinholes in body filler and deep scratches in primer. Requires no masking. Use for wet and dry sanding. Ideal to highlight body lines

Part No	Description
63566	3M Dry Coat Sponge
63567	3M Dry Coat 50grm Cartridge



Tack Cloths

Cloths for wiping down surfaces prior to painting to ensure a smooth finish. They are slightly tacky and will pick up and hold dust, dirt and sanding residue. Sold singly or in packs of 10.

Part No 60297



Fairing Boards

3M Marine Fairing Boards are designed for fairing, shaping, sanding and finishing boats, plugs and moulds. The rigid board can be used for large flat areas such as free board and deck areas. The flexible board is for concave and convex curved areas such as hulls. Both boards are designed for use with Hookit abrasive sheets / rolls.

Dimensions: 115mm X 750mm

Part No	Item
63257	Rigid Fairing Board
63256	Flexible Fairing Board



3M 115mm Red Roll

High performance abrasive sheet supplied in convenient rolls to be cut and used by hand or with self-made boards up to 3 metres long.

Available in 50m reels or cut by the metre.

Part No	Grade
63206	P40
63205	P60
63204	P80
63203	P100
63202	P120
63201	P150
63200	P180



High performance, non cracking aluminium oxide abrasive coated on a heavyweight E paper. This allows for fast cutting capabilities and longer life.

Part No	Grade
64720	P40
64722	P60
64724	P80
64726	P100
64728	P120
64730	P150
64732	P180
64734	P240



MIRKE

Mirka Q.SILVER 115mm x 25M **Fairing Board Roll**

With a backing consisting of a flexible and strong impregnated latex paper, Q-Silver features optimal aggressivity, resulting in fast and efficient stock removal. The high heat endurance of this fully resin bonded abrasive makes it ideal for tough tasks, such as 'down-tometal' sanding operations.

Part No	Grade
64890	P80
64891	P120
64892	P180
64894	P240
64896	P320



3M Wet or Dry Paper

Premium quality silicon carbide paper for wet or dry use with excellent cutting properties and long life. Available by the sheet or in packs of 50. 230 x 280mm

Part No	Grade	Part No	Grade
63300	P80	63310	P400
63301	P100	63311	P500
63302	P120	63312	P600
63303	P150	63313	P800
63304	P180	63314	P1000
63305	P220	63315	P1200
63306	P240	Microfine	
63307	P280	1/2 Sheet	
63308	P320	63316	P1500
63309	P360	63317	P2000





3M Fre-Cut Sheets

Clog-resistant, robust abrasive sheets ideal for dry sanding paints, fairing compounds and primers. Available by the sheet or in packs of 50.

230 x 280mm

Part No	Grade	Part No	Grade
63281	P80	63275	P240
63280	P100	63274	P280
63279	P120	63273	P320
63278	P150	63272	P400
63277	P180	63271	P500
63276	P220		

prep



Prep Abrasive Sanding Blocks

Foam core coated with two grades of abrasive. Suitable for use on wood, metal and plastic.

Part No	Description
63535	Medium-Fine Sanding Block
63536	Medium-Coarse Sanding Block



3M Sanding Sponges

Sanding sponges suitable for sanding edges or contours of wooden surfaces. Hi-Flex or Soft-back types can be used for sanding shaped wooden surfaces where a very high flexibility is required. Hi-Flex sponges are double-sided and the soft-back are single sided with a foam back.

	Part No	
Grade	Hi-Flex	Soft-Back
Medium (P120 - P150)	63539	63530
Fine (P220 - P240)	63538	63531
Superfine (P400 - P500)	-	63532
Ultrafine (P600 - P800)	-	63534
Microfine (P1000 - P1200)	-	63533





Pack of 3





3M Doodlebug System

The 3M Doodlebug cleaning system consists of a swivelling holder to which a selection of cleaning pads attach. The holder features special grippers that hold pads firmly in place and provide for easy attachment and changing of pads. The head incorporates a clamping attachment for a brush handle. There are three different pads available: White for delicate cleaning tasks (e.g. glass, ceramic tiles), blue for medium duty jobs and brown for heavy duty cleaning and stripping.

Part No	Description
64060	Doodlebug Holder
64061	White Pad (Fine)
64062	Blue Pad (Medium)
64063	Brown Pad (Coarse)



3M Scotch-Brite™ Hand Pads

Three grades of tough Scotch-Brite™ pads. The delicate pads are suitable for light scouring including rust removal, the general purpose can replace wire wool and the heavy duty pads can be used instead of scrapers, steel wool and metal sponges. The extra thick pads are 154 X 95mm and the standard thickness general purpose pads are 224 X 158mm.

Heavy Duty

Pa	rt No	Description
64	066	Extra thick delicate pad (White)
64	065	General Purpose Pad (Green)
64	067	Extra thick heavy duty pad (Blue)
64	068	General purpose pads (pack of 3) (Green)



3M Twist-Lok Pad Holder

Specially designed for use with 3M hand pads to make clean up jobs faster, easier and safer. Distributes pressure evenly over pad surface for efficient cleaning action and improved pad life. Length: 120mm, Width: 89mm

Part No		
64064		

Mirka Goldflex Sanding Pads -Tear off the roll

The soft and flexible Goldflex Soft has been developed for sanding profiled surfaces and irregular, difficult-to-reach details by hand. Goldflex Soft is especially useful within the automotive industry and the car repair branch. The foam base is grip friendly and applies pressure evenly, which reduces the risk of sanding through the surface. The special stearate coating prevents clogging. Suitable for both dry and wet sanding.

Part No	Description
63528	P150 Pack of 200
63529	P180 Pack of 200



Mutton Cloth

(Stockinette) 400grams

High quality cotton stockinette cloth for general cleaning and polishing tasks.

Part No 60298



Microfibre Cloths

Pack of 10. Colours may vary. 40 x 40cm

Part No

60360



10kg Bag of White Rags

Mixture of rags for cleaning.

Part No

60291





MIRKA



MIRKE



MIRKA

Lambs' wool pad 6" 150 mm 2-pack	
Part No	Description
64870	Lambs' wool pad 6" 150 mm 2-pack

Twisted	Wool Pad 180mm Double Sided
Part No	Description
64871	Twisted Wool Pad 180mm Double Sided

Adapter M14	
Part No	Description
64872	Adapter



63657

63658







	· · · · · · · · · · · · · · · · · · ·
3M Double Sided Foam Compounding System	
Get easy	changeouts using 3M Hookit™ and Quick Connect attachment systems.
Part No	Description
63660	3M 50708 Blue Quick Connect High Gloss Pad 216mm
63655	3M 50878 Green Quick Connect Compounding Pad 150mm
63656	3M 50874 Green Quick Connect Compounding Pad 216mm

3M 14mm Quick Connector	
3M 3327	1
Part No	Description
63661	Quick Connect Adapter



Compounding Pad

3M 50879 Yellow Quick Connect Polishing Pad 150mm

3M 50875 Yellow Quick Connect Polishing Pad 216mm



Compounding Pad



Polishing Pad



Polishing Pad



Adaptor



Backup Pad

3M Superbuff Polishing & Compounding Pads

Double sided, soft edged pads for use with polishes & rubbing compounds. 200mm diameter.

3M Hookit SBS Polishing & Compounding Pads

Single sided pads for use with 3M Hookit backing pads.200mm Diameter

backing page.20011111 Blameter.	
Part No	Description
63711	Compounding Pad
63712	Polishing Pad
63713	Backup pad 5/8"
63714	Backup pad 14mm



3M™ Perfect-it™ Boat Wash

3M's best product solution to clean a variety of boat surfaces. The product is a professional strength concentrate, making up to 16 gallons. It works safely on surfaces from stem to stern. It works without stripping wax

Part No	Description
63680	Boat Wash 473ml
63681	Roat Wash 946ml



3M™ Perfect-It™ Gelcoat Heavy **Cutting Compound**

This fast-cutting compound removes heavy oxidation, scratches, and other defects. Use 3M™ Perfect-It™ Gelcoat Heavy Cutting Compound for any P800 scratches or finer.

Part No	Description
63704	Heavy Compound 946ml



3M™ Perfect-It™ Gelcoat Medium Cutting Compound + Wax

This compound plus wax combines a fast cutting power, a high gloss finish, and durable wax protection. Use this for any P1000 and finer scratches.

Part No	Description
63682	Medium Compound & Wax 473ml
63683	Medium Compound & Wax 946ml









3M™ Perfect-It™ Gelcoat Light Cutting Polish + Wax

When a brilliant finish and durable protection are needed for P1500 and finer scratches, 3M™ Perfect-It™ Gelcoat Light Cutting Polish + Wax is the perfect solution for light or dark coloured gelcoat.

Part No	Description
63686	Light Compound & Wax 473ml
63687	Light Compound & Wax 946ml

3M™ Perfect-It™ Boat Wax

Our 3M™ Perfect-It™ Boat Wax keeps all sorts of surfaces looking great. It's safe for gelcoat, paint, fibreglass and metals and has a pleasant tropical scent. The pure wax finish protects against the elements.

Part No	Description
63690	3M Perfect - It Boat Wax 473ML
63692	3M Perfect - It Boat Wax 946ML

Finesse-it Finishing Material 473ml

Designed for use on topside paint systems to remove swirl marks after compounding, while leaving a glazed finish. Also suggested as the final stage in acrylic plastic reconditioning.

Part No 63702



3M Extrafine Plus **Compound 1 Litre**

Use 3M™ Perfect-It™ Extra Fine Plus Compound after Fast Cut Plus as a single polish product, for outstanding body shop results.

Part No 63650



3M Fast Cut Plus Extreme 865ml

A fast acting liquid abrasive that removes sanding scratches from refinished or original paintwork and helps achieve a superior high gloss finish. For all paintwork including hard and scratch resistant. Fast cut-rate performance +25% faster cut compared to old 50417 compound.

Part No 63705



3M Ultrafine SE Polish 1 Litre

Perfect-it III Ultrafina SE polish helps eliminate rotary swirl and hologram effects using standard electric or air-powered rotary polishing machines. (1000 - 2500 rpm)

Part No

63654

MIRKE



MIRKA



MIRKE



Polarshine 10 Polishing Compound 1ltr

An ultimate single compound system. Polarshine 10 is a medium coarse polishing compound especially designed for achieving the best result after sanding with Mirka's unique products. Polarshine 10 is suitable for all paint systems and for polishing of scratch resistant clear coats. It is designed to keep the surface temperature low when polishing and it removes marks permanently. Polarshine 10 is silicone-free and can be applied both by machine and by hand.

Part No	Description
64860	Polarshine 10 Polishing Compound 1ltr

Polarshine 20 Polishing Compound

Polarshine 20 is a medium coarse polishing compound for scratch removal and optimised to work on fresh and soft clear coats. This watersoluble polishing compound gives an excellent cut and leaves a very high gloss surface. In order to obtain a hologram free and superior high gloss surface especially on darker colours it is recommended to use Polarshine 5 as the last step in the polishing process.

Part No	Description
64862	Polarshine 20 Polishing
	Compound 1ltr

Polarshine 35 Polishing Compound

Polarshine 35 is a coarse polishing compound developed for demanding Industrial and Marine applications. Polarshine 35 is suitable for materials such as gel coats, high gloss lacquers and composites. This product has a faster and more efficient compound and produces a high surface gloss. By using Polarshine 35 you are able to minimize the sanding steps. This polishing compound has special emulsifying properties, which reduce the risk of drying out or overheating the surface. The viscosity of Polarshine 35 reduces splashing and is easy to use.

Part No	Description
64864	Polarshine 35 Polishing Compound 1ltr

MIRKA



Polarshine 45 Polishing Compound 1ltr

A coarse and fast cutting polishing compound that helps you save time and still achieve a perfect deep gloss finish. Removes sanding scratches from P600 and finer quickly and permanently. Designed for hard surfaces and coatings, especially within the marine sector. Used in both production and restoration processes, Polarshine 45 is ideal for one-step polishing of white and light-coloured gel coat surfaces. For darker colours, we recommend a second step with Polarshine 10 to remove swirl marks.

Part No	Description
64865	Polarshine 45 Polishing Compound 1ltr

115 x 6.0 x 22.23mm









Reca Eco Ceramic Mop Flappy Discs

115 x 22.23mm

Available in 2 grades.

Part No

63462 - P40

63463 - P60

Reca Stainless Steel Cutting Disc

Rapid cutting times in steel and stainless steel. Suitable for universal use. Satisfies the most stringent oSa safety requirements. Fibreglass reinforcement . Disc does not break.

Part No 63460

high removal rate for the toughest operating conditions and high edge strength. Stepped design with Turbo profile. Satisfies the most stringent oSa safety requirements. Certified

Medium-hard Turbo rough grinding disc with

115mm

Mechanical Steering

Easy Connect Steering System Package (Up to 150HP)

(For boats up to 9m outboard + 10.5m inboard.)

Includes Helm, Cable, Bezel Kit and Alpha Wheel. Complete steering system in a box, for OEM and aftermarket. Compact planetary design, 4 turns lock to lock, low back lash. Powder coated helm. Time saving, quick and easy cable connection. Everything you need for new or replacement installation. Comparable to - Teleflex SH5094P, Safe T QC. Ultra-Flex T-71FC and Morse D290.

Part No	Description
49094	10 Feet Easy Connect Steering System
49096	12 Feet Easy Connect Steering System
49098	14 Feet Easy Connect Steering System
49099	15 Feet Easy Connect Steering System
49100	16 Feet Easy Connect Steering System
49102	18 Feet Easy Connect Steering System
49104	20 Feet Easy Connect Steering System

multiflex

Lite 55 Steering System Package (Up to 55HP)

Includes Helm, Cable, Bezel Kit and Alpha Wheel. Complete steering system in a box for OEM and aftermarket. Compact rotary design, 2.5 turns lock to lock, adjustable mounting positions. All die cast aluminium helm cover. Everything you need for new or replacement installation. Comparable to - Teleflex Compac T and SH8050. Morse CO230 and U/Flex T67.

Part No	Description
49121	7 Feet Lite 55 Steering System
49122	8 Feet Lite 55 Steering System
49123	9 Feet Lite 55 Steering System
49124	10 Feet Lite 55 Steering System
49125	11 Feet Lite 55 Steering System
49126	12 Feet Lite 55 Steering System
49127	13 Feet Lite 55 Steering System
49128	14 Feet Lite 55 Steering System
49129	15 Feet Lite 55 Steering System
49130	16 Feet Lite 55 Steering System



115HP Multiflex Hydraulic Steering Kit

Kit includes:

Hydraulic Helm HP-16F. Hydraulic Cylinder OC-115U. 5 meters Hose Kit with Factory Crimped End Connector CT-5.0. Hydraulic Oil 2 litre HO-150.

Volume = 85 CC Port Thread = 9/16-24 UNEF Force = 330 Kgf Stroke = 185 mm

Part No

49140

Hydraulic Steering Systems

Packaged Hydraulic Steering System: Outboard multisteer

175HP Multiflex Hydraulic Steering Kit

Kit includes:

Hydraulic Helm HP-20 Hydraulic Cylinder OC-175 7.5 meters Hose Kit with Factory Crimped End Connector CT-7.5 Hydraulic Oil 2 liters HO-150

Volume = 122 CC Port Thread = 9/16-24 UNEF Force = 422 Kgf Stroke = 203 mm

Part No

49141



MTC30KIT Complete Hydraulic Steering Kit

Includes:

Pump type HTP2010 (white).

Fittings to connect to Ø 8 mm hose.

Cylinder type MTC3008.

Nylon hose Ø 8 mm type HS04N (15 metre roll).

Hydraulic steering oil type VHS1 (1 litre).

All required fittings.

Specifications:

Max. Torque: 294 Nm (30 kgm) (216 ft.lbs).

Wheel turns: 3.4 Stroke 150 mm. Volume 67 cm³.

Length of tiller arm 129 mm.

Pump shaft: Ø 3/4" with 1:12 taper.

Part No Vetus Description

55440 MTC30KIT Complete hydraulic steering kit.



MTC3008 Cylinder

High quality brass bodied cylinder for larger yachts and work boats. Supplied with zinc plated rod end and compression fittings with bleed nipples.

Stroke 150mm


Cylinder Volume 67CM3

Length Of Tiller Arm 129mm

Weight 1.8KG

Max Torque (NM) 294

Part No	Vetus	Description
55442	MTC3008	8mm tubing



MTC5210 Cylinder

High quality brass bodied cylinder for larger yachts and work boats. Supplied with zinc plated rod end and compression fittings with bleed nipples.

Stroke 160mm


Cylinder Volume 104CM3

Length Of Tiller Arm 140mm

Weight 3.4KG

Max Torque (NM) 510

Part No Vetus Description 55443 MTC5210 10mm tubing



MTC7210 Cylinder

High quality brass bodied cylinder for larger yachts and work boats. Supplied with zinc plated rod end and compression fittings with bleed nipples.

Stroke 225mm


Cylinder Volume 146CM3

Length Of Tiller Arm 196mm

Weight 3.8KG

Max Torque (NM) 706

Part No Vetus Description 55444 MTC7210 10mm tubing



MTC12510 Cylinder

High quality brass bodied cylinder for larger yachts and work boats. Supplied with zinc plated rod end and compression fittings with bleed nipples.

Stroke 160mm

Cylinder Volume 253 CM³

Length Of Tiller Arm 140mm

Weight 7.1KG

Max Torque (NM) 1226

Part No	Vetus	Description
55445	MTC12510	10mm tubing



MTC7210SL Cylinder (for transom hung rudders)

High quality brass bodied cylinder for transom hung rudders with protruding ram. Including fitting flange and compression fittings with bleed nipples.

Stroke 225mm

Cylinder Volume 146 CM³

Length Of Tiller Arm 196mm

Part No	Vetus	Description
55447	MTC7210SL	10mm tubing



MTC17510 Cylinder

High quality brass bodied cylinder for larger yachts and work boats. Supplied with zinc plated rod end and compression fittings with bleed nipples.


Stroke 225mm

Cylinder Volume 356CM³ Length Of Tiller Arm 196mm

Weight 8KG

Max Torque (NM) 1717

Part No	Vetus	Description
55446	MTC17510	10mm tubing




HTP2010 White or Black

(with or without non return valves)

A compact helm pump which can be mounted and operated at any angle. Suitable for use with cylinders MTC30-72.

Capacity 19.7cm³/rev Number of pistons 5 Weight without valve 3.3kg Weight with valve 4.1kg 10mm tubing

Part N	o Vetus	Description
55390	HTP2010	HTP White Helm pump
55393	HTP2010B	HTP Black Helm pump
55398	HTP2010R	HTP White Helm pump non return valves
55401	HTP2010RB	HTP Black Helm pump non return valves



HTP3010 White or Black

(with or without non return valves)

A compact helmpump which can be mounted and operated at any angle. Suitable for use with cylinders MTC30-72. Without non return valves.

Capacity 30.0cm³/rev

Number of pistons 5

Weight without valve 3.3kg

Weight with valve 4.1kg

10mm tubing

Part No	Vetus	Description
55391	HTP3010	HTP White Helm pump
55394	HTP3010B	HTP Black Helm pump
55399	HTP3010R	HTP White Helm pump non return valves
55402	HTP3010RB	HTP Black Helm pump non return valves

HTP4210 White or Black

(with or without non return valves)

A compact helmpump which can be mounted and operated at any angle. Suitable for use with cylinders MTC30-72. Without non return valves.

Capacity 42.0cm³/rev

Number of pistons 7

Weight without valve 3.3kg

Weight with valve 4.1kg

10mm tubing

Part No	Vetus	Description
55392	HTP4210	HTP White Helm pump
55395	HTP4210B	HTP Black Helm pump
55400	HTP4210R	HTP White Helm pump non return valves
55403	HTP4210RB	HTP Black Helm pump non return valves



HTPF Adapter Flange

This polished stainless steel flange can be used to fit a pump type HTP to replace an older type MTP pump. It can also be used as a simple embellishment . 38mm Depth

Part No 55385



HTPF2 Adapter Flange

This polished stainless steel flange can be used to fit a pump type HTP to replace an older type MTP pump. It can also be used as a simple embellishment . 78mm Depth

Part No 55386



HTPF3 Waterproof Seal Kit

This can be used for situations where the HTPF or HS1000 wheel adjuster may fill with water. Consists of a rubber seal and a stainless steel trim ring.

Part No 55387



HS1000 Steering Wheel Adjuster

This adjuster unit is fitted onto the steering pump and will greatly enhance the helmsman.™s steering comfort, both seated and standing.

Part No

55384





Vetus	Hydraulic n	ylon steering	hose.
-------	-------------	---------------	-------

3 · · · · · · · · · · · · · · · · · · ·			
Part No	Vetus	Size	Required Connection Parts
55488	HS04N	6mm x 8mm x 15m	HS1011S Sleeve Insert (20 pieces)
55478	HHOSE6015	6mm x 10mm x 15m	HS145S Sleeve Insert (20 pieces)
55479	HHOSE6030	6mm x 10mm x 30m	HS145S Sleeve Insert (20 pieces)
55480	HHOSE6050	6mm x 10mm x 50m	HS145S Sleeve Insert (20 pieces)
55483	HHOSE8015	8mm x 12mm x 15m	HS1031MS Straight/ HS1037MS Angled





HS10131

Vetus Sleeve Inserts + Olives

Sleeve insert Ø 6mm + Olive Ø 8mm for use with HS04N nylon hose.

Pack of 10 pieces.

Part No Vetus 55518 HS10131



HS145S Vetus Sleeve Inserts

Sleeve insert, Ø 6.5mm for use with HH6....

Pack of 20 pieces.

Part No Vetus 55519 HS145S



Vetus Sleeve Inserts

Sleeve insert, Ø 6mm for use with HS04N.

Pack of 20 pieces.

Part No Vetus 55517 HS1011S



By Pass Valve

If a change-over to tiller steering is required an installation of a by-pass valve is necessary.

Part No	Vetus	Description
55502	BYPASS8	For 8mm Tubing
55503	BYPASS10	For 10mm Tubing



HS1031MS

Vetus Straight Hose Connector

For nylon hose Ø 8mm x 12mm (HHose8..)

Pack of 2

Part No Vetus 55520 HS1031MS



HS1037MS

Vetus Right Angle Hose Connector

For nylon hose Ø 8mm x 12mm (HHose8..)

Pack of 2

Part No Vetus

HS1037MS 55521



Vetus 2 Quick Couplings

Set 2 quick couplings for hydraulic cylinders.

Part No Vetus

55457 **HHSET**



Vetus Compression Brass Olives

Part No	Vetus	Description
55514	SET0173	HS894 Brass Olive 10mm x 9.2mm
55516	SET0174	HS897 Brass Olive 10mm x 10.4mm



Replacement Rod Ends

High quality Stainless Steel replacement rod end fitting for standard fit steel versions

Part No	Vetus	Description
55450	HS071	M10 x 1.5 SS 316 (For MTC30)
55452	HS101	M12 x 1.75 SS 316 (For MTC52-72)
55453	HS210	M20 x 1.5 SS 316 (For MTC125-175)

Steering Systems



Hydraulic Fluid Header Tank (HTANK)

This transparent tank can be installed with all Vetus steering pumps up to 89 cm³ per revolution. It is also recommended for electro-hydraulic hatch lifters, when operating more than one cylinder. It has a capacity of about 200 cm³ and is supplied with a large vented screw cap, for easy filling and a mounting bracket. The tank comes complete with 1 metre of Ø 8 mm hose, two matching hose clips, one G 1/4 and one G 3/8 nylon hose

Part No	Vetus
55438	HTANK



Rudder Connection Kit				
Part No	Vetus	Description		
55454	HSET10	M10 for MTC30		
55455	HSET12	M12 for MTC52-72		
55456	HSET20	M20 for MTC125-175		



Vetus Tilting Steering Pump

For both seated and standing steering positions.

Type HTPT has a tilt mechanism which allows the steering wheel to be locked in five different positions with a total tilt range of 48°. The steering wheel shaft is made of stainless steel (AISI316) and all other visible parts are made of black rubber and synthetic mater . These pumps are supplied with built-in non return valves, a pressure relief valve and feature the same specifications as steering type HTPR.

Part No	Vetus	Ø mm Tubing	Capacity cm³/rev	Number of pistons
55407	HTP3010T	10	30.0	5
55408	HTP4210T	10	42.7	7



HELM Aluminium Rudder Arms

Connections made by in 2 bolt clamps and 2 locking grub screws (included). There are 4 attachment points, making it suitable for several steering cylinders.

Part No	Vetus	Description
55460	HELM30	Helm Rudder Arm 30mm Shaft
55461	HELM40	Helm Rudder Arm 40mm Shaft
55462	HELM50	Helm Rudder Arm 50mm Shaft
55463	HELM60	Helm Rudder Arm 60mm Shaft



Ultraflex Hydraulic Steering Oil

Grade 15 hydraulic oil.

Part No Description

11795 1 Litre Ultraflex Steering Oil



Vetus Hydraulic Steering Oil HF15

This is a low viscosity oil for hydraulic steering systems with optimum results at all temperatures. This oil has a very low coagulation point and a very high viscosity index. May be mixed with other hydraulic mineral oils.

Specification

Viscosity: 22 cSt at 20° C.

Viscosity index: 353

DIN 51524 Colour: green

Part No	Vetus	Description
56752	VHS1	Hydraulic Steering Oil 1 Litre

Steering Systems

Type PRO Steering Wheels

The perfect match for traditional and modern boats

Type PRO has 2 models. Type 'T' with a satin-gloss varnished teak rim and type 'P' with a semi-hard polyurethane rim which will keep your hands warm. Both models have substantial spokes and a hub cover made of high-gloss polished stainless steel (AISI 316). The hub itself is made of synthetic material and bored for a Ø $\frac{3}{4}$ " shaft with 1:12 taper which will fit most steering systems. These steering wheels are according to the CE and ABYC directives. Outer rim Ø32 mm

Part No	Vetus	Description	Ø (mm)	Ø Outer rim (mm)
55528	PRO40P	Polyurethane rim steering wheel	400	32
55529	PRO50P	Polyurethane rim steering wheel	500	32
55530	PRO60P	Polyurethane rim steering wheel	600	32
55532	PRO40T	Teak steering wheel	400	32
55533	PRO50T	Teak steering wheel	500	32
55534	PRO60T	Teak steering wheel	600	32









Type SWSPORT



Type SWCRUISER

Cruiser steering wheel

A three-spoke steering wheel finished in silver aluminium accents and a diameter of 350 mm.

Bored for Ø 3/4" shaft, tapered 1:12.

Part No	Vetus	Description	Ø (mm)
55590	SWCRUISER	Three spoke sport steering wheel, black with aluminium inserts	350

Type SWSPORT

Sport steering wheel

A sporty three-spoke steering wheel finished in carbon with a diameter of 350 mm.

Bored for Ø 3/4" shaft, tapered 1:12.

Part No	Vetus	Description	Ø (mm)
55589	SWSPORT	Three spoke sport steering wheel, carbon finish	350

Part No	Vetus	Description
55536	SETPS1	1" Diameter Steering Wheel Boss (Tapered 3 1/2:12)
55551	SETKS1	1" Diameter Steering Wheel Boss (Tapered 3 1/2:12)

PASBUSA Steering Wheel Shaft Adaptor

All VETUS wheels and steering pumps have a Ø 3/4" bore, with a 1:12 taper. The PASBUS is a tapered bushing that can be applied to the 3/4" shaft of a steering pump so that it can receive a wheel with a 1" bore. This allows wheels made by others to be installed on their pumps.

Product ID

55591





Steering Systems



Type KW / KWL

With a mahogany rim

The spokes and hubcap are made of stainless steel (AISI 316). The hub itself is made of aluminium.

• Bored for Ø 3/4" shaft, tapered 1:12

Part No	Vetus	Description	Ø (mm)	Ø shaft (mm)	Tapered
55580	KW38	Steering wheel with mahogany rim	380	19,05	1:12
55581	KW45	Steering wheel with mahogany rim	450	19,05	1:12
55582	KW55	Steering wheel with mahogany rim	550	19,05	1:12
55586	KWL38	Steering wheel with mahogany rim and spokes	380	25,4	31/2:12
55587	KWL45	Steering wheel with mahogany rim and spokes	450	25,4	31/2:12
55588	KWL55	Steering wheel with mahogany rim and spokes	550	25,4	31/2:12

Steering Wheel Hub CAP				
Part No	Description			
55573	SWCAP64B Hub Cap Brass			
55574	SWCAP87B Hub Cap Brass			
55575	SWCAP64S Hub Cap Stainless Steel			
55576	SWCAP87S Hub Cap Stainless Steel			

KS32G

KS32Z







Type KW



Type KWL

Type KS

No more cold hands - steering wheels

Model KS has stainless steel (AISI 316) rims, spokes and a cap. The rims have a layer of semi-hard PU-foam with an integralskin. These soft-feel wheels are resistant to all weather conditions. Type KS38, 45 and 55 are supplied in the colour grey (RAL 704) or black. Bored for Ø 3/4" shaft, tapered 1:12

Part No	Vetus	PU-foam Layer	Ø (mm)	Ø shaft (mm)	Tapered
55540	KS32G	Grey	320	19	1:12
55541	KS32Z	Black	320	19	1:12
55542	KS36G	Grey	360	19	1:12
55543	KS36Z	Black	360	19	1:12
55544	KS38G	Grey	380	19	1:12
55545	KS38Z	Black	380	19	1:12
55546	KS45G	Grey	450	19	1:12
55547	KS45Z	Black	450	19	1:12
55548	KS55G	Grey	550	19	1:12
55549	KS55Z	Black	550	19	1:12







KS55Z





Indasa Precision Gold Masking Tape

Washi rice paper technology for thin, super flat edge line. Ideal for critical paintwork Excellent UV resistance 90 days (indoor) 60 days (outdoor)

Part No	Width x Length
64690	25mm x 50m
64691	50mm x 50m



7 Day Masking Tape

A high performance creped paper tape for interior and exterior masking, as used by the professionals. Removes cleanly up to 7 days.

Part No	Width x Length
93027	25mm x 25m



Standard Masking Tape

A general purpose masking tape, useful for a wide variety of applications.

Part No	Width x Length
60300	19mm x 50m
60305	25mm x 50m
60310	38mm x 50m
60312	50mm x 50m



3M Gold Masking Tape

Designed with a flat paper backing with synthetic adhesive, this tape offers a good solvent and water resistance and a good paint anchorage. Adhesive transfer resistance and sunlight stability. a good temperature resistance (100 ° C). It offers a good paint line, good handling, good paint flaking resistance and clean removal. Helps resist paint bleed through.


Part No	Width x Length
63912	24mm x 50m
63913	48mm x 50m



3M 3434 Masking Tape

Use Scotch High Performance Masking Tape 3434 for a wide variety of applications in auto refinishing. Use in environments up to 110°C and in conditions of high water resistance. Our high performance blue crepe paper masking tape has excellent solvent and water resistance properties

Part No	Width x Length
63931	24mm x 50m
63933	48mm x 50m



3M Scotch Blue 14 Day Tape

Provides UV stability and adhesive transfer resistance for up to 14 days after application. Conformable and smooth for use in various paint and varnish masking applications.

Part No	Width x Length
63917	24mm x 54.8m
63918	48mm x 50m



80°C Masking Tape

A marine and automotive quality creped paper masking tape to achieve a professional finish. Temperature resistant to 80C.

Part No	Width x Length
93030	18mm x 25m
93031	25mm x 25m

Mirka 120°C Blue Line Masking Tape

A high-performing masking tape for professional use in automotive, shipyard and building market. Designed to meet the most demanding masking situations in Aerospace, Automotive, Building, Construction, Decorative and Marine applications and withstands 120°C oven use for 30 minutes. Superior holding power and excellent solvent, water and UV resistance. Highest degree of industrial indoor-outdoor performance. Approved for IR curing process. Excellent paint line and residue-free removal with a removal time of 15 days indoors and 10 days outdoors.

Part No	Width x Length
64940	24mm x 50m
64941	48mm x 50m



PTFE Tape 12mm x 12m

Thread sealing tape for pipe connection and general on board plumbing.

Part No	Colour
93135	White



PSP Fine Line Masking Tape

A high quality masking tape for use when a fine definition line is required. It is flexible and allows precise application, even on curves, without tearing. Being thin (0.11mm), there is little build up of paint at the edges.

Part No	Width x Length
93113	6mm x 33m
93114	12mm x 33m
93115	19mm x 33m
93117	25mm x 33m
93116	25mm x 66m



PVC Electrical Tape 19mm x 20m

PVC to BS 3924 flame retardant standard. Ideal for luff, cringles, spar and mast markings and on-board electrics.

Part No	Colour
93137	White
93138	Black
93139	Red
93140	Blue
93141	Green
93142	Yellow



Saba Deck Tape 4mm x 66M

Bond breaker tape used for deck caulking.

Part No	Description
60502	Saba deck Tape 4mm x 66M



3M Fine Line Tape

Highly conformable polypropylene tape which stretches easily for painting smooth curves.

Part No	Width x Length
63920	3mm x 55m
63921	6mm x 55m
63922	12mm x 55m
63923	19mm x 55m



3M Prespacing Tape

SCPS-100 is a translucent paper tape designed for use with printed graphics produced with Scotchcal™, Controltac™ and Scotchlite™ Films. It has high adhesion on small film formats and delicate film pieces, and can be removed easily after use.

Part No	Width x Length
63935	1.22m x 91.4m



Black Gorilla Tape

Made with double thick adhesive, strong reinforced backing, and a tough all-weather shell, Gorilla Tape is the biggest, strongest, toughest tape yet. It sticks to rough and uneven surfaces, including wood, stone, stucco and brick, that ordinary tapes can't hold.

Part No	Width x Length
60810	48mm x 11m



3M Hand Masking Film MF99

Film is non porous. Resistant to paint penetration. Can be used with lacquers. Flake resistant for multiple coats. Transparent and compacts for easy disposal. Clings to surfaces to protect against overspray.

Coverage: 68.9 sq.mtrs

Part No Size

99" x 90ft 2.51m x 27.4m 63905



3M Taped Masking Film

Ideal for SMART repairs! This plastic film is a great way to quickly mask around areas which require painting. The high quality material ensures that the boat is fully protected against paint spray whilst also preventing paint runs off the film.

Part No	Width x Length
63900	40cm x 25m
63901	60cm x 25m
63902	90cm x 25m
63903	110cm x 25m
63904	180cm x 25m



Gorilla Clear Repair Tape

This tape features the strength of Gorilla Tape in a weatherproof, airtight, crystal-clear tape. Easy to tear by hand, with Gorilla Clear Repair Tape, you can fix, patch, seal, hold and protect almost any surface with a crystal-clear appearance for a perfect fix every time.

Part No	Width x Length
60812	48mm x 8.2m

Tapes



Duck Tape 50mm x 5m

A self adhesive, high quality, waterproof cloth tape suitable for numerous repair jobs on all boats and canoes.

UV version: Resistant to UV light and weather conditions.

Part No	Colour
93004	Light Grey UV Resistant
93072	Clear
93073	White
93074	Black
93075	Red
93076	Blue
93077	Green
93078	Yellow
93079	Silver



Self Amalgamating Tape

A non-adhesive tape with a protective release liner, which bonds to itself and not your fittings. Ideal for rigging screws, terminals on deck electrics and emergency hose repairs.

Size	Black	White
19mm x 5m	93123	93127
25mm x 5m	93124	93128
19mm x 10m	93125	93129
25mm x 10m	93126	93130



Race/Course Cards

A pack of 15 self-adhesive waterproof write on stickers with a removable adhesive. Simply jot down the race course in the club house, remove the sticker from the backing paper and position on dinghy. Win the race then remove cleanly afterwards without leaving any residue.

Part No		
93034		



Vinyl Foam Hatch Tape

Self-adhesive plasticised vinyl foam tape for bedding in windows, deck fittings and engine hatch covers.

Size	Black	Grey	White
19mm x 3mm x 3m	93094	93095	93096
25mm x 6mm x 3m	93097	93098	93099
25mm x 3mm x 3m	93100	-	-



Double Sided Vinyl Foam Tape

A strong, black double-sided adhesive tape for light to medium weight fixtures. The product uses the classic PVC BEAR FOAM, which provides a compressible tape to fill any void between two uneven rigid surfaces, thus preventing vibration or partial contact of the adhesive surfaces.

Part No	Size
93017	19mm x 1mm x 5m
93018	19mm x 3mm x 3m
93019	25mm x 3m x 3m



Double Sided Tape

A strong, self adhesive double sided tape suitable for a range of temporary and permanent repair jobs on board.

Part No	Size
93105	50mm x 5m



Head Lining Tape

A rigid PVC strip backed with a VHB performance adhesive system. DUAL-LOCK, manufactured by 3M™ simply locks to itself. The fastener can be attached to a bulkhead or any smooth surface and will provide an ideal re-closable fastening system for headlinings, cushions etc, securing items in lockers, trim panels and a multitude of other applications.

Part No Size

93007 2x 25mm x 125mm





Anti Chafe Stainless Steel Sheet

Extra flexible stainless steel sheets to protect boat gelcoat and paint against any damage caused by rope chafing. Suitable to protect from chafing caused both by mooring and manoeuvering lines. Made of stainless steel and provided with 3M VHB™ powerful adhesive tape. Gelcoat and paint are preserved

Part No	Description
96485	150 x 50mm 1 sheet
96486	225 x 50mm 1 Sheet



Grip Foam

A strong soft blue or grey foam with a high performance waterproof adhesive. Providing extra grip with added comfort to any flat or profiled surface.

Part No	Colour	Size
93101	Blue	2mm x 95mm x 300mm
93102	Grey	2mm x 95mm x 300mm



3M™ Dual Lock™ Reclosable Fastener SJ355D

This is a general purpose acrylic adhesive on the back of a black, polypropylene reclosable fastener. It is up to 12 times stronger than traditional hook and loop technology. Tough polyolefon mushroom shaped stems snap together to create the tensile strength to replace traditional fasteners. Fast assembly with no drilling. 'Invisible' fixing. High temperature and solvent resistant. Mushroom heads lock together replacing standard hook and loop system.

Part No Size 63895 5m x 25mm



Monster Tape

Monster Tape is extremely strong and is resistant to UV light, salt water and works comfortably at temperatures -40°C to - 85°C. It has a high performance adhesive on one side. The multipurpose tape for repairs on board.

Part No	Size
93410	75mm x 1.5m



Soft Grip Tape

Soft, comfortable, textured rubber tape, coated with a waterproof adhesive that will remove cleanly without leaving any sticky residue. Essential for the dinghy racer, providing extra grip where needed.

Part No	Colour	Size
93000	Black	50mm x 4m
93001	Grey	50mm x 4m



Hook & Loop Fastener Tape

A self adhesive hook and loop fastener tape ideal for sail ties and quick release fixings.

Size	Black	White
25mm x 1m	93147	93149
25mm x 25m	93148	93150



PSP Back to Back

This is an easy to use product for quick release with a hook face and loop reverse. It is particularly useful for use as stowage straps, sail ties, bundling and many other applications, rolls available in black or white.

Part No	Size
93151	White 25mm x 2m
93152	Black 25mm x 2m





Grip Kit

A soft conformable rubber grip tape to coil wrap tillers, windsurf, kite and ski handles. Pack includes self amalgamating tape to secure ande

Cildo.	
Part No	Size
93155	30mm x 1.8m



Spinnaker Repair Tape

Self adhesive rip stop nylon tape ideal for reinforcing batten pockets and carrying out temporary repairs to torn sails. Packed in a hanging sleeve. 50mm x 4.5m

Colour	Part No	Colour	Part No
White	93037	Fluorescent Yellow	93046
Black	93038	Fluorescent Pink	93047
Red	93039	Lilac	93048
Magenta	93040	Orange	93049
Royal Blue	93041	Sea Green	93050
Light Blue	93042	Grey	93051
Mid Green	93043	Fluorescent Green	93052
Yellow	93045	Fluorescent Orange	93053



Dacron Repair Tape

A Dacron cloth tape for adding insignia or making repairs to high load areas of sails and covers. 75mm x 1.5m

Colour	Part No	Colour	Part No
Dark Blue	93009	Blue	93012
White	93010	Red	93013
Black	93011	-	-





Dacron Sail Repair Patch

Two strong sail cloth patches to apply to either side of a sail for the larger repair. Now also in a range of colours for repairs to covers, dodgers and spray hoods, etc.

Size:

24cm x 37cm x 2 sheets

Part No	Colour
93022	White
93023	Red
93024	Royal Blue
93025	Black
93026	Dark Blue



Heavy Duty Sail Repair Tape

A self adhesive polyamide fabric tape for semi-permanent sail repair. Seawater and weather resistant with very high ageing resistance. The tape is supple but exceptionally strong. Available in white only.

Part No	Size
93060	50mm x 2m
93061	100mm x 2m



Mylar Repair Tape

A transparent repair tape for semi-permanent repairs of sail windows and Mylar sails. UV and salt water resistant.

Part No	Size
93084	50mm x 3m
93085	150mm x 3m



Mast Collar Tape

A self bonding waterproof collar which does not require un-stepping the mast when fitting.

Part No	Colour	Size
93119	White	100mm x 1.5m
93120	Black	100mm x 1.5m



Spreader Tape

A soft waterproof tape for capping crosstree ends to reduce chafing of sails. 25mm x 10m

Part No	Colour
93088	White
93089	Silver
93090	Black
93091	Light Grey (UV Resistant)







Kevlar Repair Tape /Patch

Manufactured from Kevlar scrim encapsulated in a Mylar film, then coated with a high coat-weight of UV resistant adhesive. Ideal for repairs to Kevlar and high performance sails.

Part No	Colour	Size
93057	Gold	75mm x 1.5m Tape
93058	Gold	24cm x 37mm (2 sheets) Patch
93054	Black	75mm x 1.5m Tape
93055	Black	24cm x 37mm (2 sheets) Patch

Dacron Wave Tape

A self adhesive Dacron cloth edging, which is designed to be applied to the leech of the mainsail to help reduce flutter and breakdown. The tape becomes waterproof once the adhesive has set, normally within an hour at room temperature.

Part No	Colour	Size
93385	White	75mm x 3m
93386	Black	75mm x 3m
93387	Gold	75mm x 3m



Kite Tape

Anti-Chafe Patch

This tear resistant adhesive rip-stop nylon is available in an extensive range of colours and comes in a roll width of 150mm. It is perfect for the sailor or kitesurfer, who notices a small tear in their kite or sail, which needs to be dealt with as soon as possible. Size: 150mm x 2.5m

Part No	Colour	Part No	Colour
93360	White	93367	Lilac
93361	Black	93368	Mid Green
93362	Red	93369	Sea Green
93363	Pink	93370	Yellow
93364	Magneta	93371	Flo Yellow
93365	Royal Blue	93372	Orange
93366	Light Blue	93373	Grey

Anti-Chafe Patch can be cut to size to use around cleats or fairleads or even be applied to a dinghy or keelboat spinnaker chute for friction free hoists and drops. Vulnerable areas can be protected and as a clear product, it will not detract from the overall visual effect of any surface. The glue has been developed to be waterproof and has a strong adhesion with a good temperature resistance and proven longevity. Each pack contains:

Two clear 125mm x 150mm patches (250 micron) One clear 100mm x 125mm patch

One clear 75mm x 125mm patch (130 micron)

Part No	Colour
93395	Clear (4 sheets)

(130 micron)



Rig Wrap

Stretch and coil wrap the clear/opaque tape around rigging in places where the sails come into contact. Reduce wear on expensive sails and provide a friction free surface to ease the passage of sails on tack and gybe.

Part No	Size
93405	25mm x 5m



Tell Tales

For perfect upwind sail trimming 16 self adhesive discs:

8 x Red thread

8 x Green thread

Part No 93400



Main Tales

Similar to tell tales fitted to genoa luffs the main-tales should be fitted at intervals along the leech of the mainsail so that you can accurately trim the mainsail when sailing upwind or on a reach.

Pack Size:

8 x Dacron discs

8 x Ripstop nylon strips

Part No

93399

Tapes



Exit Tape

Interior application, self-adhesive route marking tape. Photo luminescent properties are designed to charge in natural or artificial light and provide a high intensity initial glow, after which it retains sufficient energy to be seen all night long, conforming to SOLAS regulations for Low Level Lighting.

Suitable for use as a Low Level Lighting System subject to installation to ISO 15370. Available in plain or with exit arrows.

Size: 50mm x 1m rolls

Part No	Description
93390	Plain 50mm x 1m
93391	Arrows 50mm x 1m



Glow Strip

A photo-luminescent safety marking tape, which is designed to be seen all night. It is UV and weather resistant and specially designed for exterior use.

Part No	Size
93380	25mm x 1m (pack of 3)
93381	38mm x 1m (pack of 2)
93382	1m & 20 x 45mm discs



Leak Stop

For emergency or permanent repair, Leak Stop will repair a pipe leak in under thirty minutes and contain pressure up to 20 bar and temperatures up to 500°F. Quick and easy to use on virtually any material, it is also suitable as corrosion protection and electrical insulation to 16,000 volts.

Part No	Size
93002	50mm x 1.5m
93003	75mm x 2.7m



Silicone Tape

Our Self Fusing Silicone tape provides a reliable solution to leaks in water or exhaust pipes and a multitude of containing and sealing applications. Effective between -50°C and +260°C, it can also insulate to 8000v per upstretched layer.

The tensile strength has been tested in excess of 700psi and will effectively seal leaks up to 85Psi (6 bar). It also has good resistance to mild acids, fuels, oils, solvents, salt water, ozone, UV light, and flames.

Part No	Colour	Size
93401	White	25mm x 3m
93402	Black	25mm x 3m
93403	Blue	25mm x 3m





Outdoor Safety Walk Tape

The product consists of large abrasive particles bonded by a tough, durable polymer to a dimensionally stable plastic film. The reverse side is coated with a rubber based pressure sensitive adhesive, covered by a removable protective liner. The product provides a tough, durable, slip resistant surface for heavy duty applications, ladders and ramps.

Primarily for use as a heavy duty, durable, slip resistant surface. For dry, wet, muddy, oily floors in industrial or commercial applications such as: agriculture and forestry, road building, civil engineering and building construction, lorries, tractors, cranes construction vehicles, building machinery, armoured vehicles....

Part No	Size
64054	25mm x 18.3m



Safety Tread Tape

This non-slip surface for decks and companion-ways is easily applied and has a permanent pressure sensitive adhesive.

Size	White	Black	Frosty Clear
25mm x 5m	93226	93228	93230
50mm x 5m	93227	93229	93231



Heavy Duty Safety Tread

A rugged abrasive, self adhesive anti-slip tape. Ideal for most types of craft, pontoons, landing stages etc. Backed with a PVC liner, this product is fully waterproof.

Part No	Colour	Size
93232	Black/Yellow	50mm x 5m



Deck Strip

Safety tread die-cut into ten strips. Suitable for applying to steps etc. 10 strips each

Part No	Colour	Size
93235	White	19mm x 300mm
93234	Black	19mm x 300mm



Retro Reflective Tape

A self-adhesive tape ideal for night time identification. Colours reflect in a beam of light. Ideal for tenders, trailers etc

Colour	25mm x 2.5m 2 Roll Pack	50mm x 2.5m	25mm x 5m	50mm x 5m
White	93158	93159	93160	93161
Red	93164	93165	93166	-
Yellow	93170	93171	-	93173
Green	93176	-	-	-



Reflexite Grid Pattern Sew-On Tape

A dazzling sew-on tape which conforms to BS6629. It is used by the police, fire and ambulance services.

Part No	Colour	Size
93218	White	50mm x 1m
93220	Green	50mm x 1m
93222	Red	50mm x 1m



Solas Retro-Reflective Tape

Internationally approved self adhesive tape for life saving appliances. Enables the appliances to achieve maximum night-time visibility. Withstands intense exposure to sunlight, sub-zero temperatures and continuous immersion in seawater.

Part No	Size
93214	50mm x 1m
93215	50mm x 45m



Spray Stop

Provides a cost effective, flexible and IMO compliant solution to prevent the risk of spray out from pipe flanges. Quick and easy to apply.

Part No	Size
93397	25mm x 1m (pack of 2) Silver
93398	50mm x 1m (pack of 1) Silver

Tapes





Available in all coveline colours. Please specify colour when ordering.

Part No	Description	Part No	Description
93350	D1 21mm x 10m	93355	T1 19mm x 50m
93351	D1 21mm x 50m	93356	T2 44mm x 10m
93352	D3 40mm x 10m	93357	T2 44mm x 50m
93353	D3 40mm x 50m	93358	T3 20mm x 10m
93354	T1 19mm x 10m	93359	T3 20mm x 50m



Boat stripe Tape - Solid Colour

For a smart co-ordinated finish, use Boat Stripe to colour match your coveline. 50mm x 16m

Colour	Part No	Colour	Part No
White	93301	Orange	93309
Black	93302	Yellow	93310
Red	93304	Silver	93311
Dark Blue	93305	Matt Gold	93312
Mid Blue	93306	Turquoise	93314
Light Blue	93307	Burgundy	93315
Green	93308	Charcoal	93316

Light Blue Turquoise





Mid Blue

Coveline Ta	Coveline Tape						
A tough and	weatherproof to	ape to enhance	any coveline.				
Colour	15mm x 15m	19mm x 15m	25mm x 15m	Colour	15mm x 15m	19mm x 15m	25mm x 15m
White	93238	93239	93240	Orange	93262	93263	93264
Black	93241	93242	93243	Yellow	93265	93266	93267
Beige	93244	93245	93246	Silver	93268	93269	93270
Red	93247	93248	93249	Matt Gold	93271	93272	93273
Dark Blue	93250	93251	93252	Turquoise	93280	93281	93282
Mid Blue	93253	93254	93255	Burgundy	93283	93284	93285
Light Blue	93256	93257	93258	Charcoal	93286	93287	93288
Green	93259	93260	93261	-	-	-	-


Dark Blue

Red



Waterline Tape







Go-Fast / Water Line Tape

Go-Fast tape gives a professional finishing touch to power boats. There are three different coloured stripes on each tape with a void between the colours. Waterline tape is similar, but with no gap between the colours. Please specify the colour combination required when ordering. The combinations available are:

Dark Blue / Mid Blue / Light Blue

Dark Blue / Mid Blue / Yellow

Dark Blue / Yellow / Dark Blue

Dark Blue / Silver / Dark Blue

Red / White / Mid Blue

Red / Orange / Yellow

Black / Red / Orange

Black / Red / Silver

Туре	Description	Part No
Go-Fast Tape	V12 12mm x 10m	93324
Go-Fast Tape	V12 12mm x 50m	93325
Go-Fast Tape	V21 21mm x 10m	93326
Go-Fast Tape	V21 21mm x 50m	93327
Go-Fast Tape	V27 27mm x 10m	93328
Go-Fast Tape	V27 27mm x 50m	93329
Go-Fast Tape	V40 40mm x 10m	93330
Go-Fast Tape	V40 40mm x 50m	93331
Waterline Tape	B27 27mm x 10m	93341
Waterline Tape	B27 27mm x 50m	93342
Waterline Tape	B39 39mm x 10m	93343
Waterline Tape	B39 39mm x 50m	93344



Treadcote

It is designed to rejuvenate the appearance of heavily weathered or stained treadmaster Original. This paint is easy to apply, with full surface preparation and application details shown on the can. Coverage: 5-7m²/L

Part No	Description
91883	White Sand
91884	Grey
91885	Blue
91886	Fawn

Tapes

Treadmaster Sheets 1200 x 900mm

1200mm X 900mm sheets of Treadmaster that can be easily cut to shape using a craft / Stanley knife and stuck down using either Treadmaster marine contact adhesive or Treadmaster marine epoxy adhesive.

Colour	Diamond Pattern	Smooth Pattern
Blue	91800	91810
Fawn	91801	91811
Light Blue	91802	91812
Light Grey	91803	91813
Grey	91804	91814
White	91805	91815
Black	91806	

Treadmaster Step Pads 275mm X 135mm

Self adhesive pads sold in packs of two.

Colour	Diamond Pattern	Smooth Pattern
Blue	91821	91851
Fawn	91823	91853
Light Blue	91824	91854
Light Grey	91825	91855
Grey	91822	91852
White	91820	91850

Treadmaster Step Pads 550mm X 135mm

Self adhesive pads sold in packs of two.

Colour	Diamond Pattern	Smooth Pattern
Blue	91831	91861
Fawn	91833	91863
Light Blue	91834	91864
Light Grey	91835	91865
Grey	91832	91862
White	91830	91860

Treadmaster Step Pads 412mm X 203mm

Self adhesive pads sold in packs of two.

Colour	Diamond Pattern	Smooth Pattern
Blue	91841	91871
Fawn	91843	91873
Light Blue	91844	91874
Light Grey	91845	91875
Grey	91842	91872
White	91840	91870

Smooth - Blue



Smooth - Fawn



Smooth - Light Blue



Smooth - Light Grey



Smooth - Grey



Smooth - White



Diamond - Blue



Diamond - Fawn



Diamond - Light Blue



Diamond - Light Grey



Diamond - Grey



Diamond - White



Marine Epoxy Adhesive - 600grams

This two pack epoxy adhesive is designed to provide the ultimate in bonding performance. Ideal for use on a wide range of deck materials, it provides a bond which is suitable for the most arduous of conditions. Full instructions are on the can. Coverage Approx. 2 Sheets (1200mm x 900mm)



91880



Contract

These terms and conditions, together with any other conditions specified in Seaware's website, invoices and price lists, form the entire contract between Seaware (hereinafter referred to as 'the Company') and the Customer and all items supplied by the Company are subject to these terms and conditions. For the avoidance of doubt, the Company shall not be bound by any terms or conditions set out in the Customer's order and these conditions of sale shall supersede and prevail over any other terms and conditions stipulated or referred to by the customer.

Unless otherwise expressly agreed in writing by us, all quotations, prices and conditions are subject to revision without notice. The Company reserves the right to increase prices at any time prior to acceptance of any order placed.

All goods are sent by 1st class post where possible, at a cost of £3.95 + VAT, otherwise they will be sent via Fedex for an overnight delivery (excluding Saturday, Sunday and Bank Holidays). The cost of this service is a flat rate of £8.95 + VAT, for orders up to 20kg. Please note that dangerous goods (eg. paints, resins, liquids etc) cannot be sent by 1st class post. Shipping to areas such as the Scottish Highlands (above Glasgow), Offshore Islands & Overseas will be charged at cost. Please contact us for carriage charges. Free Shipping is applied when goods are purchased at the value of £150 (ex VAT). This free shipping is only applicable to the mainland UK. Orders dispatched by other means at the Customer's request will be charged at cost. Delivery of heavy items (chain, bulk anodes, bulk paint etc) will be charged at cost. Any delivery date is not guaranteed, however delivery shall be made within a reasonable period taking into account all circumstances affecting such delivery. The Company will not be responsible for late delivery beyond our control. Shortages must be notified within three days of arrival. The Company shall not be liable for any damage which occurs to goods in transit, other than in the Company's own transit, and Customers are advised to seek redress with the carriers involved. For the avoidance of any doubt, any insurance risk will pass to the Customer on delivery.

Terms of Payment

Payments by Trade Account Customers shall be made in full to the Company by the 20th of the month following the date of invoice (by Bacs if possible). Failure to pay by this date will result in your account being placed on 'stop' and no further orders will be able to be placed, until it is paid in full. All payments shall be made strictly in accordance with the terms of Contract without deduction and the Customer agrees not to withhold or defer payment of any sums by virtue of any claim made by him against the Company. Credit cards are not acceptable methods of payment for Trade Account Customers. No general property or equitable interest in goods supplied by the Company to the Customer, hereinafter called "the contract goods", shall pass to the Customer until such time as the price of the contract goods and all other monies (if any) due from the Customer to the Company in respect of the contract goods or under any other contract between the Company and the Customer shall have been paid to the Company in full. In the event of payment on any invoice remaining outstanding for more than 30 days, interest shall be charged thereon at a rate of 2% above the base rate of HSBC, per month, or part month, of which the payment remains outstanding. VAT is chargeable on all business EU sales unless a VAT number and two letter country code is provided with the order.

The Company will not accept liability for any claims, howsoever arising, unless it has received written notice of the claim within three days of the Customer receiving the goods. The Company cannot be held responsible for errors in typing, description, illustration or specification which are intended only as a guide.

Returns

Goods may be returned for a full refund within 30 days, at the buyer's expense, accompanied with the original invoice. Items must be in a re-saleable condition, with all packaging intact. In some cases a 15% restocking charge may be made unless otherwise agreed. Damaged goods/packaging cannot be accepted. The Company will, at its option, either repair free of charge, or replace free of charge, any product which is found to the satisfaction of the Company to be defective as a result of faulty design, manufacture or workmanship provided that:

- 1. The products are returned, properly packaged, with a copy of the original invoice, within 30 days from the date of delivery. If we originally delivered the item by van we will collect it (but please ring us to arrange this first), or the Customer can drop it into the office or, if the Customer wishes to post it back, we will refund the postage.
- 2. Where the products are made to the Customer's specification, the defects are not as a result of errors in such specification.
- 3. The products have not been modified in any way by the Customer; and
- 4. The products have not been used for any purpose other than that for which they were designed or otherwise mis-used. Suitability for application is the responsibility of the Customer.

Repaired or replaced goods will be returned free of charge.

Special Orders

Orders for non-stock items must be confirmed in writing by the Customer and are non-cancellable. The Company cannot accept the return of items specially ordered.

Useful Information

Aluminium

LM5 is the principle aluminium alloy used on boats due to its high resistance to corrosion from sea water or marine atmospheres. It is excellent for producing castings required to exhibit and maintain a surface of high polish and is easily anodised.

Name	Designation	Alloy Elements	Uses
-	LM5	Al 95%, Mg 5%	Corrosion resistant castings

Brass

Brasses are alloys of copper and zinc (generally 5 to 40%), and may contain small amounts of other alloying elements. Most are available in a range of forms and can be fabricated by casting, forging, stamping, rolling, extrusion and machining.

They fall into two classes, the alpha alloys with less than 37% zinc which are ductile and can be cold worked and the alpha/ beta or duplex alloys which are harder and stronger with limited cold ductility. Lead can be added as an alloying element resulting in a brass that can be rapidly machined and produces minimal tool wear. Additions of aluminium, iron and manganese to brass improve strength, whilst silicon additions improve wear resistance. Additions of tin or aluminium to either alpha or duplex brasses improves corrosion resistance in sea and brackish waters for applications such as propellers.

Name	Designation	Alloy Elements	Uses
Common Brass	CZ108	Cu 63%, Zn 37%	Interior fittings, screws
Naval Brass	CZ112	Cu 62%, Zn 37%, Sn 1%	Pre-war boat fittings
High Tensile Brass	CZ114	Cu 46.2%, Zn 37%, Mn 2%, Al 1.5%, Fe 1%, Pb 1.5%, Sn 0.8%	Snap shackles, propellers, winches
DZR Brass	CZ132	Cu 61%, Pb 2.8%, As 0.1%	Hull valves and skin fittings

Bronze

The term bronze originally described alloys with Tin as the only or principal alloying element. Modern day bronzes tend to be Copper alloys in which the major alloying element is not Nickel or Zinc.

The usual alloy for fasteners is silicon bronze. It has a very long working life (30 - 50 years in marine environment) due its superb resistance to corrosion.

Name	Designation	Alloy Elements	Uses
Aluminium Bronze	CA104	Cu 80%, Al 10%, Ni, 5% Fe 5%	High strength fittings
Phosphor Bronze	PB102	Cu 95%, Sn 5%, P 0.2%	Fabricated / wrought fittings
Silicon Bronze	CS101	Cu 96%, Si 3%, Mn 1%	Fastenings
Gunmetal	LG2	Cu 85%, Sn 5%, Pb 5%, Zn 5%	Cast hardware

Stainless Steel

Grade 304 is the standard "18/8" stainless; it is the most versatile and most widely used stainless steel, available in a wider range of products, forms and finishes than any other. It has excellent forming and welding characteristics. Grade 316 is the standard molybdenum-bearing grade, second in importance to 304 amongst the austenitic stainless steels. The molybdenum gives 316 better overall corrosion resistant properties than Grade 304, particularly higher resistance to pitting and crevice corrosion in chloride environments. 316 is usually regarded as the standard "marine grade stainless steel".

Name	Designation	Alloy Elements	Uses
'Standard'	304, A2	Fe, <0.8% C, 17.5-20% Cr, 8-11% Ni, <2% Mn, <1% Si, <0.045% P, <0.03% S	General Purpose
'Marine Grade'	316, A4	Fe, <0.03% C, 16-18.5% Cr, 10-14% Ni, 2-3% Mo, <2% Mn, <1% Si, <0.045% P, <0.03% S	Marine fittings & fastenings

Useful Information

Bronze Pipework Range

In recent years there has been a campaign to highlight the dangers of using inferior metals for skinfittings and associated equipment. Confusion exists over various types of metals including brass, gunmetal, bronze, DZR copper alloy, chromed nickel, DZR brass, and what is and is not approved by various authorities. Bronze is therefore one of, if not the best material to use for marine plumbing.

Manufactured to the European standard CC491K

One added benefit is that the bronze ball valves come with stainless steel handles, generally the first thing to corrode on more inferior products.

Corrosion Resistant Brass

The so-called dezincification resistant (DZR or DR) brasses, sometimes referred to as CR (corrosion resistant) brasses, are used where there is a large corrosion risk and where normal brasses do not meet the standards. Applications with high water temperatures, chlorides present, or deviating water qualities (soft water) play a role. DZR-brass is excellent in water boiler systems. This brass alloy must be produced with great care, with special attention placed on a balanced composition and proper production temperatures and parameters to avoid long-term failures.

Galvanic Corrosion

Galvanic corrosion is an electrochemical action of two dissimilar metals in the presence of an electrolyte and an electron conductive path. It occurs when dissimilar metals are in contact.

The natural differences in metal potentials produce galvanic differences, such as the galvanic series in sea water. If electrical contact is made between any two of these materials in the presence of an electrolyte, current must flow between them. The farther apart the metals are in the galvanic series, the greater the galvanic corrosion effect or rate will be. Metals or alloys at the upper end are noble while those at the lower end are active. The more active metal is the anode or the one that will corrode.

Control of galvanic corrosion is achieved by using metals closer to each other in the galvanic series or by electrically isolating metals from each other. Cathodic protection can also be used to control galvanic corrosion effects, the use of zinc anodes being a good example.

Galvanic Series in Seawater
Noble (least active) → Anodic (Most Active)
18-8-3 Stainless steel, type 316 (passive)
Monel
18-8 Stainless steel, type 304 (passive)
Titanium
Silicon bronze
Copper
Aluminum bronze
Naval brass
18-8-3 Stainless steel, type 316 (active)
18-8 Stainless steel, type 304 (active)
Cast iron
Galvanized steel
Zinc
Magnesium

Fasteners for Fittings				
Fitting	Suitable	Unsuitable		
Material	Fastenings	Fastenings		
Galvanised	Galvanised or Stainless	Brass or Bronze		
Aluminium	Stainless	Galvanised, Brass or Bronze		
Brass	Brass or Bronze	Stainless		
Bronze	Bronze or Stainless	Brass		
Stainless	Stainless or Monel	Galvanised or brass		

3M Masks and Filters	286-288	Bilge Pump Float Switches	262
Abrasive Pads	352	Bilge Pumps	260-265, 276
Abrasives	348-355	Blakes Seacock	246
Accumulator Tanks	268	Blocks	314-321
Acetone	27	Blowers	112-113
Acoustic Materials	118	Boarding Ladders	45
Adhesive Cleaner	27, 153	Boat Cleaning	23-29
Adhesives, Glues and Sealants	151-156	Boat Hooks	308
Aerials	84-90	Boat Nails	121, 123
Aerial Connectors and Accessories	92	Bollards	30
Aerodux Resorcinol Resin Kit	149	Bolts	119, 122, 123, 126, 132
Air Vents	245	Bonda G4	215
Allen Key Machine Screws	124-125	Bonda Topcoat	216
Anchor Swivels	292-293	Bow Rollers	294-295
Anchor Windlasses	290-291	Bow Thruster Anodes	11
Anchors	292	Bow Thrusters	105-107
Anode Backing Pads	4	Brass Convex	308
Anode Fixing Studs	4	Brass Flat Strip	309
Anodes - Aluminium	11, 22	Brass Panel Pins	116
Anodes - Brass	21	Brass Plumbing	233-234, 236, 246
Anodes - Outboard	13-20	Brass Screw and Turn Cups	116
Anodes - Propeller	9-10, 19	Brass Split Pins	116
Anodes - Shaft	8, 22	Brass Woodscrews	116
Anodes - Zinc	5-21	Breathers	114
Antennas	84-90	Bronze Plumbing	232-236
Antenna Accessories	90-94	Buckets	28
Antenna Mounts	93	Bulgin Products	54
Antifoul	200-201, 208-210	Bullseyes	323
Antifoul Removal	218	Bungee Cords	310
Anti-Freeze	163	Bungs	241
Anti Syphon	245, 255	Buoys	306
Anti theft	332	Busbars	55
Aquasignal Navigation Lights	176-182	Butterfly Vents	166, 174
Backing Pads For Anodes	4	Butyl Rubber	154
Bag of Rags	28	Cabin Lights	188-190
Bailer Pumps	273	Cable Ties & Fixings	67, 231
Bailers	29	Cable Glands	68-71
Ball Joints	101	Cable Grommets	102
Ball Loops	310	Cable Ties	67
Ball Stoppers	323	Cam Cleats	322
Ball Valves	232-233, 236, 238-239	Cam Straps	303
Barrel Bolts	165, 167, 172	Canopy Cleaner	24
Batteries and Battery Boxes	65	Carbine Hooks	297
Battery Charger	68	Carbon Monoxide Detectors	79
Battery Switches	66-67	Catches	165, 167, 168, 173
Battery Terminals	65	Caulking	156
Beacons	324	Caulking Cotton	143
Bearings	95-96	Caulking Guns	157
Bilge Blowers	113	Caulking Nozzles	157
Bilge Cleaner	25	Ceiling Lights	188-189
Bilge Panel Alarms and Switches	263	3 3	

Cellular Antennas	94	Delphi Fuel Filter	250
Cellulose Thinners	217	Detectors	79
Chain	293	Diesel Additive	163
Chain Miscellany	293-294	Dinghy Inflator	274
Chippy Woodscrews	132	Disposable Gloves	284
Circlips	137	Disposable Suits	284
Circuit Breakers	62	Distress Flares	325
Clamps	229-230	Diverter Valves	244
Cleats	31	Doodlebug - 3M Abrasive System	352
Cloths/Rags	28	Door Handles	166
Coach Screws	120, 123, 126	Drain Plugs	241
Coat Hooks	173	Drop Nose Pins	302
Coax Cable	92	Dry Coat	350
Cobra Cables	332	Dual Station Units	100
Commoning Posts	53	Duck Oil	159
Compounding Pads	353	Duck Tape	366
Compounding	352-355	Dust Masks	286-287
Connector Blocks	55	Dyneema	310, 313
Contact Adhesive	151, 374	Ear Defenders and Plugs	284, 285
Control Cables	103-104	Electrical Cable Sleeving	55-56
Control Panels	79-80	Electrical Cables	46-49
Convex	308	Electrical Connectors	50
Copper Boat Nails and Roves	121	Electrical Tape	365
Copper Clips	237	Engine Cleaner	159
Copper Grease	139	Engine Control Accessories	101-102
Copper Tacks	121	Engine Control Cables	103-104, 356
Copper Terminals	50	Engine Controls	98-100
Copper Tubing	228, 237	Engine Descaler	23
Copper Washers	237	Engine Mounts	107-108
Cord	310	Epifanes Products	25, 141, 192-197
Corrosion Block	158	Epoxy Fillers, Glues and Resins	144-146
Courtesy Lights	188	Epoxy Primers	217
Cowl Ventilators	32	Escape Hatches	36-38
Crimping Tools	68	Exhaust Alarm	259
Crocodile Clips	53	Exhaust Hose	227-228
Cup Square Bolts	119, 123, 126	Exhaust Hose Clips	229-230
Cutlass Bearings	95	Extraction Ventilators and Hoses	113-114
Cylinders	335, 357-358	Eye Bolts	297
Dashboard Instruments	74-77	Eye Nuts	298
Deck Caulking	156	Eye Plates	299
Deck Drains	232, 240	Eye Straps	301, 303
Deck Fuel and Water Fillers	242	Fairing Boards and Rolls	350-351
Deck Glands	69	Fairleads	31, 43, 323
Deck Lights	177, 181, 185	Fast Cut Compound	354-355
Deck Plates	33-34	Fastenings - Accessories	139
Deck Scrubs	28-29	Fastenings - Brass	116
Deck Speakers	90	Fastenings - Copper	121
Decorative Tapes	372-373	Fastenings - Galvanised	122-123
De-Ionised Water	163	Fastenings - Silicon Bronze	117-120
Deks Olje	216	Fastenings - Stainless Steel	124-138

Faucets / Taps	272
Fender Eyes	299
Fender Steps	305
Fenders Flot	304-305, 307
Fenders Flat	307
Ferrules	300
Fibreblast	23
Fibreglass Repair Kit	147
Fibreglass Tape and Mat	147
Fids - Splicing	309
Fillers	140, 142, 144
Filling Card, Knives and Trowel	141
Filler Caps	242
Filters	247-250
Filters (sea water strainer)	248
Filters (water separator/fuel filter)	
Fine Line Tapes	365
Fire Blankets	328
Fire Extinguishers	326-329
Flags, Flagstaffs, Bases and	43
Flares	325
Flexible Tanks	254
Float Switches	260, 262-263
Flood Lights	186
Foam Brushes	221
Folding Steps	45
Foot Pumps	273
Foot Switches	62
Freshwater Foot Pumps	273
Fuel Splash Stop	242
Fuel Cans	164
Fuel Filters	249-250
Fuel Gauges	76
Fuel Hoses	227-228
Fuel Inline Check Valve	236
Fuel Primer Bulbs	162
Fuel Sender	77-78
Fuel Safe	163
Fuel Tanks	251, 253
Fuel Treatment	163
Funnels	29
Fuses, Holders and Boxes	63-64
Galley Equipment	239
Galvafroid	215
Galvanised Boat Nails	123
Galvanised Coach Screws	123
Galvanised Cup Square Bolts	123
Galvanised Hex Bolts/Setscrews	122
Galvanised Nuts and Washers	122
Galvanised Spray	20

0 1 1 101 111	100
Galvanised Studding	122
Galvanised Woodscrews Gas Detector	123 79
Gas Fittings	237-238
Gas Hose	228, 237
Gas Regulators	237
Gas Struts	35
Gasket - Instant	152
Gate Valve	233
Gauges	74-77
Gear Oil	160
Glass Cleaner	25
Gloves	284
Glues, Sealants and Adhesives	148-157
Goggles	284
Goosenecks	256, 258-259
Grab Handles	42
Grease	97, 158
Grey Water Tanks	251, 253-254 120
Gripfast Nails Grub Screws	138
	311
Guardrail Netting Hand Cleaners	
Handrails	285 42
	331-332
Hasps and Staples Hatch Handles	
	37
Hatch Latches	35
Hatch Stays	35
Hatch Tape	34
Hatches	33-38
HDTV Antennas	94
Heat Shrink Sleeving	56 51-52
Heat Shrink Terminals	
Hempel Products	198-205, 218, 219
Hex Bolts Hinges	122, 132 165-175
Hook & Loop Tape	367
Horns	73
Hose Clamps and Clips	229-230
Hose Connectors and Tails	233-234, 236, 238-239,
Hoses	226-228
Hydraulic Oils	160, 162
Impellers	274-275
Inflatable Boat Cleaner	25
Inflatable Boat Repairer	152
Inspection Hatches	33-34
Inspection Lids	252
Inspection Ports	252
Instrument Dials and Gauges	74-79
Interior Lights	188-190

International Products	206-214
Inter Screws	138
Jenny Brushes	221
Jerrycans	164
Jizer/ Degreaser	159
Jugs	28
Junction Boxes	68
Keel Band	308
Kevlar Scissors	309
Lacing Hooks and Buttons	301-302
Ladders and Steps	45
Latches	165-175
Latex Gloves	284
LED Flood Light	186
LED Light Bulbs	179-180
LED Lights	182-190
Level Sensors	77-78
Life Jackets and Accessories	334-335
Life Raft	333
Lifting Rings	165-175
Linseed Oil	143
Locker Catches	165-175
Locker Doors and Service Kits	33
Loctite 577/ Thread Sealants	139
Loctite Glues	152
Louvered Vents	166, 175
Low Friction Rings	303
Lubricants	158-159
Lugs / Electrical Connectors	50
Machine Screws	118, 124-125, 134 -135
Main Tails	369
Manual Bilge Pumps	276-280
Marker Buoys	306
Mooring Buoys	306
Masking Tape	364-365
Mast Beads	303
Metal Polish	27
Metal Rod	309
Methylated Spirit	217
Mixing Cups and Sticks	146-147
Mixing Pots	147
Monel Pop Rivets	137
Monel Seizing Wire	294
Mooring Snubber	307
Mooring Swivels	294
Mould Remover	29
Mousing Line	310
Mufflers	256-258
Multiflex Multiflex Steering	100-104, 356 356
Multiflex Steering	550

MultiSolve	29
Mushroom Ventilators	110
Mutton Cloth	28
Navigation Lights (Battery)	185
Navigation Lights	176-185
Nitrile Gloves	284
No Smell Filters	247
Non Return Valves	244
Non Slip Sheets	374
Non Slip Tape	371
Nozzles	157
Nuts and Washers	120, 122, 136-137
Nylon Washers	137
Oakum	143
Oars	44
Oil	159-162
Oil Absorbent Pads	162
Oil Containers	164
Outboard Locks	332
Outboard Steering Systems	356
Overshoes	284
Owatrol	215-216, 218
Oxalic Acid	24
P Clips	68, 230
P.P.E.	284-288
Packing	97
Pad Eyes	299
Paddles	44
Padlock Cobra Cables	332
Padlocks	330-331
Paint Brushes	220-221
Paint Fillers	219
Paint Filters	223
Paint Kettles	223
Paint Pad	223
Paint Primer	216-217
Paint Removal	218
Paint Rollers	221-223
Paint Scrapers	224
Paint Stripper	218
Paint Trays	223
Panel Pins	116, 138
Panel Wipes	27
Parrel Beads	303
Pelican Hook	301
Personal Safety	324-325
Pick Up Buoys	305
Pipe Clips	230
Plastic Hose Connectors	243
Plastic Screw Cups	129
Plumbing	225-229

Plumbing Tapes	225
Polishing	26-27, 354-355
Polishing Pads	353
Polyester Resin	147
Portholes	38-41
Pozi Self Tappers	127-128
Pozi Woodscrews	117, 131-132
Pressure Pumps	266
Primers	156-157, 192-193, 198, 200, 202, 206-207, 210- 212, 215, 217
Proflush	23
Prop Protector	96
Propeller Shaft Anodes	8, 22
Propshield	217
Protective Workwear	284-288
PTFE Tape	225
Pulpit Netting	311
Pumps	260-283
Pump Service Kits	277-283
Push Button Locks	168
Putty and Putty Knives	141-143
R Clips	137
Rags	223
Rail Mounts	42-43
Ratchet Mounts	93
Re Arming Kits	335
Rechargeable LED Lights	186-187
Red Lead Powder	143
Red Roll - Abrasives	351
Reflective Tapes	370-371
Relays	56
Repair Tape	365, 368-369
Resins	146
Resorcinol Glue	149
Respirators and Filters	286-288
Rigging Screws and Terminals	300
Rings, Ring Plates and Ring Bolts	298-299
Rocker Switches	58-59
Rod	309
Roller Frames	222-223
Roller Trays	223
Rope	310-313
Rope Cutter	196
Rowlocks	44
Rubbing Strake	308
Rust Primer	215
Sabatak	154
Safety Goggles	284
Safety Tread Tape	370-371
Sail Cleaner	24

Sail Repair	368
Sailmaker Needles	309
Sailmaker Palms	309
Sampson Post Sand Paper	348-352
Sanders and Accessories	347
Sanding Blocks	350-351
Sanding Discs	348-350
Sanding Rolls	351
Sanding Sponges	352
Sanitation Hose	226, 228
Scoop Strainer	232, 236
Scotch Brite	352, 349
Scrapers	224
Screw Cups	116-117, 128
Screw Eyes	298
Scrubbing Brushes	28-29
Sealants, Adhesives and Glues	151-156
Sealers	148-157
Search Lights	186, 215
Seat Covers	342
Seat Pedestals and Accessories	342-346
Seats	336-341
Self Tapper Screws	126-130
Selma Splicing Set	309
Senders	77-78
Service Kits	33, 277-283
Setscrews	119, 133
Shackles	295-297
Shell Vents	110-111
Shockcord	310
Shore Power	57
Shower Sumps and Pumps	269-270
Sikaflex Primer/Glue/Sealants	155-157
Silent Cabin Hooks	
Silic One	166, 168 201
Silicon Bronze Coach Screws	120
Silicon Bronze Cup Square Bolts	119
Silicon Bronze Grip Fast Nails	120
Silicon Bronze Hexbolts/	199
Silicon Bronze Machine Screws	118-119
Silicon Bronze Nuts and Washers	120
Silicon Bronze Screw Cups	117
Silicone Bronze Set Screws	119
Silicon Bronze Woodscrews	117-118
Silicon Bronze woodscrews Silicon Hose	-
	228
Siphon Pumps	273
Skin Fittings	232, 236, 240, 241
01 11 114 11 0	
Slotted Machine Screws Slotted self Tappers	118-119, 134-135 129-130

Slotted Woodscrews	116-118, 123, 129-131	Tack Cloths	350
Snap Hooks	297	Tanks	251, 253
Snap Shackles	296	Tank Spares and Accessories	255
Sound Insulation	109	Tapes	225, 364-375
Speakers	90	Taps	272
Splice Fids and Set	309	TDS	156
Split Pins	116, 138	Teak Cleaners	24, 26
Split Rings	137	Teak Oils	26, 203
Sponge	28	Tef Gel	139, 159
Spray Adhesive	151	Tell Tales	369
Stain Removers	26, 29	Tempature Sensors	259
Stainless Steel Allen Key Machine Screws	124-125	Terminals Crimp/Electrical	50-52, 54, 64, 68
Stainless Steel Clevis Pins and Split Rings	137	Thermal Blankets	333
Stainless Steel Coach Screws	126	Thimbles	301
Stainless Steel Countersunk Machine	134	Thinners	217
Stainless Steel Cup Square Bolts	126	Thread Bar	120, 122, 137
Stainless Steel Grub Screws	138	Three Way Valves	244
Stainless Steel Hex Bolts	132	Throttle Cables	103-104
Stainless Steel Inter Screws	138	Throttle Control	98-99
Stainless Steel Nuts and Washers	136-137	Tiller Extension	323
Stainless Steel Pan Head Machine Screws	135	Tinned Electrical Cables	46-49
Stainless Steel Panel Pins	138	Toggle Fasteners	173
Stainless Steel Pozi Self Tappers	127-128	Toggle Switches	58-59
Stainless Steel Pozi Woodscrews	131-132	Toilets	270
Stainless Steel Screw Cups	128	Toilet Hose	226, 228
Stainless Steel Set Screws	133	Toilet Cleaner	23
Stainless Steel Slotted Self Tappers	129	Topcoats	202, 204, 212
Stainless Steel Split Pins	138	Torches	187
Stainless Steel Torx Self Tappers	126-127	Torx Screws	126-127
Stainless Steel Slotted Woodscrews	129-130	Trade Wipes	27
Stanchions	43	Transom Exhaust	259
Steering Cylinders	357-358	Treadcoter	25
Steering Accessories	358-361	Treadmaster	374-375
Steering Systems	356-361	Turned Cups	116
Steering Wheels	362-363	Turpentine	217
Stern Gland Lubricator	96	TV Antennas	94
Stern Gland Packing	96	U Bolts	299
Strum Boxes	243	Ultrasonic Sensor	78
Studding - Galvanised	122	USB Sockets	57
Studding - Silicon Bronze	120	Varnish	214-215
Studding - Stainless	137	Varnish Removal	218
Suction Pipes	252	Velcro Tape	367
Sump Pumps	163	Vent Loops	245
Superglue	152	Ventilation	110-114, 166, 174, 175
Swarfega	285	Ventilators	32
Switch Panels	59-61	Ventilator Hose	114
Switches	58	VHF Accessories	70, 90, 91
Swivels	102, 292-294, 297, 299	VHF Antennas	84-89
Syphon Pump	29	Vinyl Cleaner	25, 27, 29
Syringes	146	Wardrobe Hooks	166, 168

Wash Cloths/Mitts	28
Washers	120, 122, 136-137, 237
Washing Up Detergent	27
Waste Tanks	251, 253
Waste Water Installation Kit	255
Waste Water Pumps	269, 271 276
Water Filters	248, 272
Water Hose	226-228
Water Pumps	272-273
Water Purification Tablets	272
Water Strainers	248
Water Tanks	251, 254
Waterlocks	256-259
Waterproof Plug and Sockets	53-54
Watertite Filler	144
Wax	25, 26, 354
WD-40	159
Webbing	303
Wet or Dry Paper	351
Whale Service Kits	269, 276-283
Whipping Twine	313
White Spirit	27
Winch Handle and Keys	289
Wind Indicators	84-85
Windex	84-85
Windlasses	290-291
Windscreen Wiper Controls	80
Windscreen Wiper Arms, Blades	81-83
Wire Brushes	224
Wire Rope Cleat and Grips	300-301
Wireless Phone Chargers	71-72
Wood Glues	148-149
Wood Hardener and Preserver	216
Woodscrews	116-118, 123, 129-132
Wooden Bungs	241
Wooden Mast Beads	303
Worklights	187
Zinc Spray	20
Zinc Plated Woodscrews	132